

**Environmental testing - Part 2-65: Tests - Test Fg:
Vibration - Acoustically induced method (IEC 60068-2-
65:2013)**

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 60068-2-65:2013 sisaldab Euroopa standardi EN 60068-2-65:2013 ingliskeelset teksti.	This Estonian standard EVS-EN 60068-2-65:2013 consists of the English text of the European standard EN 60068-2-65:2013.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 03.05.2013.	Date of Availability of the European standard is 03.05.2013.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 19.040, 29.020

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Aru 10, 10317 Tallinn, Eesti; www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:
Aru 10, 10317 Tallinn, Estonia; www.evs.ee; phone 605 5050; e-mail info@evs.ee

English version

**Environmental testing -
Part 2-65: Tests -
Test Fg: Vibration -
Acoustically induced method
(IEC 60068-2-65:2013)**

Essais d'environnement -
Partie 2-65: Essais -
Essai Fg: Vibrations -
Méthode induite acoustiquement
(CEI 60068-2-65:2013)

Umgebungseinflüsse -
Teil 2-65: Prüfverfahren -
Prüfung Fg: Schwingen -
akustisch angeregt
(IEC 60068-2-65:2013)

This European Standard was approved by CENELEC on 2013-03-13. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 104/591/FDIS, future edition 2 of IEC 60068-2-65, prepared by IEC TC 104 "Environmental conditions, classification and methods of test" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 60068-2-65:2013.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2013-12-13
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2016-03-13

This document supersedes EN 60068-2-65:1994.

EN 60068-2-65:2013 includes the following significant technical changes with respect to EN 60068-2-65:1994:

– minor technical and editorial changes were made throughout the document as originally requested by the DE National Committee;

– following comments at the CD stage, particularly from the UK National Committee, significant technical and editorial additions were made to the standard for acoustic testing employing the progressive wave tube technique.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 60068-2-65:2013 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

- | | | |
|-------------|------|---------------------------|
| IEC 60068-1 | NOTE | Harmonized as EN 60068-1. |
| ISO 266 | NOTE | Harmonized as EN ISO 266. |

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 61672-1	-	Electroacoustics - Sound level meters - Part 1: Specifications	EN 61672-1	-
ISO/IEC 17025	2005	General requirements for the competence of testing and calibration laboratories	EN ISO/IEC 17025	2005

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references.....	7
3 Terms, definitions, symbols and abbreviations.....	7
3.1 Terms and definitions	7
3.2 Symbols and abbreviations	11
4 Acoustic environments and requirements for testing.....	11
4.1 Acoustic environment for testing	11
4.1.1 General	11
4.1.2 Reverberant field	13
4.1.3 Progressive wave field	14
4.1.4 Cavity resonance	14
4.1.5 Standing wave	14
4.2 Sound sources.....	14
4.3 Measuring apparatus	14
4.3.1 General	14
4.3.2 Acoustic measurements.....	14
4.3.3 Vibration response measurements	15
4.3.4 Analysis of results.....	15
4.4 Requirements for testing.....	15
4.4.1 Type of facility	15
4.4.2 Mounting.....	15
4.4.3 Specimen instrumentation.....	16
4.4.4 Preparation of test control.....	17
5 Recommended severities.....	18
6 Preconditioning.....	18
7 Initial measurements.....	19
8 Testing	19
8.1 Normal testing	19
8.2 Accelerated testing	19
9 Intermediate measurements.....	19
10 Recovery	19
11 Final measurements	19
12 Information to be given in the relevant specification.....	20
13 Information to be given in the test report	20
Annex A (informative) Guidance for the test requirements.....	22
Bibliography	30
Figure 1 – Third-octave band spectrum for aeronautical applications	12
Figure 2 – Octave band spectra for fans derived from [4]	13
Figure 3 – Octave band spectrum for noisy industrial machinery derived from [4]	13
Figure 4 – Typical locations of microphone checkpoints (1 – 6) on a fictitious surface around a specimen.....	17

Figure A.1 – Typical microphone arrangement around a specimen in a reverberation chamber.....	22
Figure A.2 – Typical microphone checkpoint arrangement around a long cylindrical specimen	25
Table 1 – Tolerances for acoustic measurement.....	14
Table 2 – Overall sound pressure level and duration of exposure	18
Table A.1 – Octave band/room volume relationship	23
Table A.2 – Reverberation room, ratios of dimensions	23
Table A.3 – Examples of sound sources with waveforms and typical power outputs.....	28
Table A.4 – Typical OASPL and exposure durations	28

INTRODUCTION

Acoustic noise may produce significant vibration in components and equipment. In the acoustic noise field, sound pressure fluctuations impinge directly on the specimen and the response may be different to that produced by mechanical excitation.

Items particularly sensitive to acoustic noise include relatively lightweight items whose dimensions are comparable to an acoustic wavelength in the frequency range of interest and whose mass per unit area is low, such as dish antennas and solar panels, electronic devices, printed circuit boards, optical elements, etc.

Acoustic testing is applicable to components, equipment, functional units and other products, hereinafter referred to as “specimens”, which are liable to be exposed to and/or are required to function in conditions of high sound pressure levels. It should be noted that, under service conditions, the specimen may be subjected to simultaneous mechanical and acoustical excitation.

High sound pressure levels may be generated by jet engines and other aircraft propulsion systems, rocket motors, high-powered gas circulators, turbulent gas flow around aircraft or launchers, etc. This part of IEC 60068 deals with acoustic testing in compressible gases and can also be used to simulate the excitation response caused by turbulence resulting from high-velocity separated gas flows.

The intent of the test procedure contained in this standard is to produce a high intensity acoustic noise field by either reverberant methods (known as reverberant chamber testing) or by progressive wave methods (known as progressive wave tube testing).

Testing for the effects of vibration caused by acoustic noise demands a certain degree of engineering judgement and this should be recognized both by the manufacturer/supplier and the purchaser of the specimen. Based on the guidance provided in this standard, the writer of the relevant specification is expected to select the most appropriate method of test and values of severity, taking account of the nature of the specimen and its intended use.

Since the acoustic levels occurring during testing are high enough to be damaging to human hearing, appropriate protective measures need to be taken to reduce the noise exposure of operators performing the test to a level regarded as permissible from the standpoint of hearing conservation.

ENVIRONMENTAL TESTING –

Part 2-65: Tests – Test Fg: Vibration – Acoustically induced method

1 Scope

This part of IEC 60068 provides standard procedures and guidance for conducting acoustic tests in order to determine the ability of a specimen to withstand vibration caused by a specified sound-pressure level environment to which it is, or is liable to be, subjected.

For sound pressure level environments of less than 120 dB acoustic tests are not normally required.

This standard determines the mechanical weakness and/or degradation in the performance of specimens and to use this information, in conjunction with the relevant specification, to decide on their acceptability for use. The methods of test may also be used as a means of establishing the mechanical robustness or fatigue resistance of specimens.

Two procedures are described for conducting tests and for measurement of the sound pressure levels within the acoustic noise field and considers the need for measurement of the vibration responses at specified points on the specimen. It also gives guidance for the selection of the acoustic noise environment, spectrum, sound pressure level and duration of exposure.

The progressive wave tube method is relevant to material where aerodynamic turbulence will excite part, or all, of the total external surface. Such applications include aircraft panel assemblies where the excitation exists on one side only. The reverberant chamber method is relevant where it is preferable to induce vibration onto the entire external surface of equipment by distributed excitation rather than fixed points by means of electro-dynamic shakers.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61672-1, *Electroacoustics – Sound level meters – Part 1: Specifications*

ISO/IEC 17025:2005, *General requirements for the competence of testing and calibration laboratories*

3 Terms, definitions, symbols and abbreviations

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.