Plahvatusohtlikud keskkonnad. Osa 25: Sädemeohutud elektrilised süsteemid

Explosive atmospheres - Part 25: Intrinsically safe electrical systems



EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

Käesolev Eesti standard EVS-EN 60079-25:2010 sisaldab Euroopa standardi EN 60079-25:2010 ingliskeelset teksti.

Standard on kinnitatud Eesti Standardikeskuse 31.12.2010 käskkirjaga ja jõustub sellekohase teate avaldamisel EVS Teatajas.

Euroopa standardimisorganisatsioonide poolt rahvuslikele liikmetele Euroopa standardi teksti kättesaadavaks tegemise kuupäev on 15.10.2010.

Standard on kättesaadav Eesti standardiorganisatsioonist.

This Estonian standard EVS-EN 60079-25:2010 consists of the English text of the European standard EN 60079-25:2010.

This standard is ratified with the order of Estonian Centre for Standardisation dated 31.12.2010 and is endorsed with the notification published in the official bulletin of the Estonian national standardisation organisation.

Date of Availability of the European standard text 15.10.2010.

The standard is available from Estonian standardisation organisation.

ICS 29.260.20

Standardite reprodutseerimis- ja levitamisõigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonilisse süsteemi või edastamine ükskõik millises vormis või millisel teel on keelatud ilma Eesti Standardikeskuse poolt antud kirjaliku loata.

EUROPEAN STANDARD

EN 60079-25

NORME EUROPÉENNE EUROPÄISCHE NORM

October 2010

ICS 29.260.20

Supersedes EN 60079-25:2004

English version

Explosive atmospheres - Part 25: Intrinsically safe electrical systems(IEC 60079-25:2010)

Atmosphères explosives -Partie 25: Systèmes électriques de sécurité intrinsèque (CEI 60079-25:2010) Explosionsfähige Atmosphäre - Teil 25: Eigensichere Systeme (IEC 60079-25:2010)

This European Standard was approved by CENELEC on 2010-10-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 31G/202/FDIS, future edition 2 of IEC 60079-25, prepared by SC 31G, Intrinsically-safe apparatus, of IEC TC 31, Equipment for explosive atmospheres, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 60079-25 on 2010-10-01.

This European Standard supersedes EN 60079-25:2004.

The significant changes with respect to EN 60079-25:2004 are:

- extension of the scope from Group II to Groups I, II and III;
- introduction of level of protection "ic";
- addition of requirements for cables and multi-core cables;
- reference to EN 60079-11 regarding the termination of intrinsically safe circuits;
- requirements for the assessment of an expanded and clarified intrinsically safe system regarding level of protection "ic", simple apparatus and faults in multi-core cables;
- introduction of predefined systems and merging of the system requirements for FISCO from EN 60079-27;
- addition of requirements for simple intrinsically safe systems containing both lumped inductance and lumped capacitance;
- addition of a method for testing the electrical parameters of cables;
- additional information for the use of simple apparatus in systems.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN and CENELEC shall not be held responsible for identifying any or all such patent rights.

The following dates were fixed:

 latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement

(dop) 2011-07-01

 latest date by which the national standards conflicting with the FN have to be withdrawn

(dow) 2013-10-01

This European Standard has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association and covers essential requirements of EC Directive 94/9/EC. See Annex ZZ.

Annexes ZA and ZZ have been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 60079-25:2010 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following note has to be added for the standard indicated:

IEC 60529 NOTE Harmonized as EN 60529.

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

| <u>Publication</u> | <u>Year</u> | <u>Title</u> | EN/HD | <u>Year</u> |
|--------------------|-------------|---|-------------|-------------|
| IEC 60060-1 | - | High-voltage test techniques - Part 1: General definitions and test requirements | EN 60060-1 | - |
| IEC 60079-0 | - | Explosive atmospheres - Part 0: Equipment - General requirements | EN 60079-0 | - |
| IEC 60079-11 | 2006 | Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i" | EN 60079-11 | 2007 |
| IEC 60079-14 | 2007 | Explosive atmospheres - Part 14: Electrical installations design, selection and erection | EN 60079-14 | 2008 |
| IEC 60079-15 | - | Explosive atmospheres – Part 15: Equipment protection by type of protection "n" | EN 60079-15 | - |
| IEC 60079-27 | 2008 | Explosive atmospheres - Part 27: Fieldbus intrinsically safe concept (FISCO) | EN 60079-27 | 2008 |
| IEC 61158-2 | - | Industrial communication networks - Fieldbus specifications - Part 2: Physical layer specification and service definition | | - |
| IEC 61241-0 | - | Electrical apparatus for use in the presence of combustible dust - Part 0: General requirements | EN 61241-0 | - |
| IEC 61241-11 | - | Electrical apparatus for use in the presence of combustible dust - Part 11: Protection by intrinsic safety 'iD' | EN 61241-11 | - |

Annex ZZ

(informative)

Coverage of essential requirements of the directive 94/9/EC

This European Standard has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association and within its scope the standard covers only the following essential safety requirements out of those given in Annex II of the EC Directive 94/9/EC:

Compliance with this standard provides one means of conformity with the specified essential requirements of the Directive concerned.

WARNING: Other requirements and other EC Directives may be applicable to the products falling within the scope of this standard.

| ESR | Equivalent requirement in EN 60079-25:2010 |
|-----------------|--|
| 1.0.1 | fundamental basis of standard |
| 1.0.2 | Fundamental principle of intrinsic safety technique applied throughout this standard and apparatus standard EN 60079-11 and EN 60079-0 |
| 1.0.3 | Requirement primarily met by apparatus standard EN 60079-11 and the maintenance requirements specified in EN 60079-14 and EN 60079-17. |
| 1.0.4 | EN 60079-0 Clause 5, Subclauses 6.1, 6.2, 7.2 and 7.3 |
| 1.0.5 | Clause 14, EN 60079-0 Clause 29 and Foreword |
| 1.0.6 a | Clause 4 |
| 1.1.1 | EN 60079-0 Clause 8.1 |
| 1.1.3 | EN 60079-0 Clause 7, 8, 12 |
| 1.2.1 | The system and apparatus standards represent the latest state of the art |
| 1.2.2 | Requirement met by apparatus standard, EN 60079-0 Clause 13 and clause 13.2 of this standard |
| 1.2.4 | Clause 5 also covers Group III, details in EN 60079-0 and EN 60079-11 |
| 1.2.6 | Covered by EN 60079-11 |
| 1.3.1 | Sparks and hot surfaces covered in Clause 13 and in EN 60079-11. Other potential ignition sources covered in EN 60079-0 |
| 1.3.2 | EN 60079-0, Subclause 7.4 |
| 1.3.3 to 1.3.5 | EN 60079-0 |
| 1.4 | EN 60079-0 and EN 60079-11 |
| 2.0.1 and 2.0.2 | 'ia' apparatus and systems in accordance with EN 60079-11 and this standard meet the 'two fault' criterion (M1) and 'ib' apparatus and systems in accordance with EN 60079-11 and this standard meet the 'one fault' criterion (M2) and the other criterions |
| 2.1.1 and 2.1.2 | 'ia' apparatus and systems in accordance with EN 60079-11/EN 61241-11 and this standard meet the 'two fault' criterion (1G and 1D) and the other criterions |
| 2.2.1 and 2.2.2 | 'ib' apparatus and systems in accordance with EN 60079-11/EN 61241-11 and this standard meet the 'one fault' criterion (2G and 2D) and the other criterions |
| 2.3.1 and 2.3.2 | 'ic' apparatus and systems in accordance with EN 60079-11/EN 61241-11 and this standard meet the 'safe in normal operation' criterion (3G and 3D) and the other criterions |

CONTENTS

| FOREWORD | | | | | |
|----------|--|--|----|--|--|
| 1 | Scope | | | | |
| 2 | Normative references | | | | |
| 3 | Term | ns, definitions and abbreviations | 7 | | |
| | 3.1 | Terms and definitions | | | |
| | 3.2 | Abbreviations | | | |
| 4 | Desc | criptive system document | | | |
| 5 | | ping and classification | | | |
| 6 | Levels of protection | | | | |
| • | 6.1 | General | | | |
| | 6.2 | Level of protection "ia" | | | |
| | 6.3 | Level of protection "ib" | | | |
| | 6.4 | Level of protection "ic" | | | |
| 7 | Amb | ient temperature rating | | | |
| 8 | Inter | connecting wiring / cables used in an intrinsically safe electrical system | 10 | | |
| 9 | | uirements of cables and multi-core cables | | | |
| | 9.1 | General | | | |
| | 9.2 | Multi-core cables | | | |
| | 9.3 | Electrical parameters of cables | | | |
| | 9.4 | Conducting screens | | | |
| | 9.5 | Types of multi-core cables | 11 | | |
| | | 9.5.1 General | | | |
| | | 9.5.2 Type A cable | 11 | | |
| | | 9.5.3 Type B cable | | | |
| | | 9.5.4 Type C cable | 11 | | |
| 10 | | nination of intrinsically safe circuits | | | |
| 11 | Eartl | ning and bonding of intrinsically safe systems | 12 | | |
| 12 | Prote | ection against lightning and other electrical surges | 12 | | |
| 13 | Asse | essment of an intrinsically safe system | 13 | | |
| | 13.1 | General | 13 | | |
| | | Simple apparatus | | | |
| | | Analysis of inductive circuits | | | |
| | 13.4 | Faults in multi-core cables | 15 | | |
| | | 13.4.1 Type of multi-core cables | 15 | | |
| | | 13.4.2 Type A cable | 15 | | |
| | | 13.4.3 Type B cable | 15 | | |
| | | 13.4.4 Type C cable | | | |
| | 13.5 | Type verifications and type tests | 16 | | |
| 14 | 4 Marking1 | | | | |
| 15 | 5 Predefined systems | | | | |
| Anı | Annex A (informative) Assessment of a simple intrinsically safe system1 | | | | |
| Anı | Annex B (normative) Assessment of circuits with more than one source of power2 | | | | |
| Anı | Annex C (informative) Interconnection of non-linear and linear intrinsically safe circuits23 | | | | |
| Anı | Annex D (normative) Verification of inductive parameters | | | | |

EVS-EN 60079-25:2010

| Annex E (informative) A possible format for descriptive systems drawings and installation drawings | 61 |
|---|-----|
| Annex F (informative) Surge protection of an intrinsically safe circuit | 64 |
| Annex G (normative) Testing of cable electrical parameters | 67 |
| Annex H (informative) Use of simple apparatus in systems | 69 |
| Annex I (normative) FISCO systems | 71 |
| Bibliography | 74 |
| Figure 1. Systems englysis | 1.1 |
| Figure 1 – Systems analysis | |
| Figure 2 – Typical system using simple apparatus | |
| Figure B.1 – Sources of power connected in series | |
| Figure B.2 – Sources of power connected in parallel | |
| Figure B.3 – Sources of power not deliberately connected | |
| Figure C.1 – Equivalent circuit and output characteristic of resistive circuits | |
| Figure C.2 – Current and/or voltage addition for interconnections | 26 |
| Figure C.3 – Output characteristic and equivalent circuit of a source with trapezoidal characteristic | 29 |
| Figure C.4 – Example of an interconnection | 33 |
| Figure C.5 – Sum characteristics for the circuit as given in Figure C.4 | 35 |
| Figure C.6 – Current and/or voltage addition for the example given in Figure C.4 | 36 |
| Figure C.7 – Limit curve diagram for universal source characteristic – Group IIC | 47 |
| Figure C.8 – Limit curve diagram for universal source characteristic – Group IIB | 57 |
| Figure C.9 – Copy pattern for universal source diagrams | 58 |
| Figure D.1 – Typical inductive circuit | 60 |
| Figure E.1 – Typical block diagram for IS system descriptive system document | 62 |
| Figure E.2 – Typical installation drawing for IS system | 63 |
| Figure F.1 – Surge protection requirements of an instrument loop | 66 |
| Figure I.1 – Typical system | |
| Table A.1 – Simple system analysis | 19 |
| Table C.1 – Parameters necessary to describe the output characteristic | |
| Table C.2 – Assignment of diagrams to equipment groups and inductances | 31 |

EXPLOSIVE ATMOSPHERES –

Part 25: Intrinsically safe electrical systems

1 Scope

This part of IEC 60079 contains the specific requirements for construction and assessment of intrinsically safe electrical systems, type of protection "i", intended for use, as a whole or in part, in locations in which the use of Group I, II or III apparatus is required.

NOTE 1 This standard is intended for use by the designer of the system who may be a manufacturer, a specialist consultant or a member of the end-user's staff.

This standard supplements and modifies the general requirements of IEC 60079-0 and the intrinsic safety standard IEC 60079-11. Where a requirement of this standard conflicts with a requirement of IEC 60079-0 or IEC 60079-11, the requirement of this standard takes precedence.

This standard supplements IEC 60079-11, the requirements of which apply to electrical apparatus used in intrinsically safe electrical systems.

The installation requirements of Group II or Group III systems designed in accordance with this standard are specified in IEC 60079-14.

NOTE 2 Group I installation requirements are presently not provided in IEC 60079-14.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60060-1, High-voltage test techniques – Part 1: General definitions and test requirements

IEC 60079-0, Explosive atmospheres – Part 0: Equipment – General requirements

IEC 60079-11:2006, Explosive atmospheres – Part 11: Equipment protection by intrinsic safety "i"

IEC 60079-14:2007, Explosive atmospheres – Part 14: Electrical installations design, selection and erection

IEC 60079-15, Electrical apparatus for explosive gas atmospheres – Part 15: Construction, test and marking of type of protection "n" electrical apparatus

IEC 60079-27:2008, Explosive atmospheres – Part 27: Fieldbus intrinsically safe concept (FISCO)

IEC 61158-2, Industrial communication networks – Fieldbus specifications – Part 2: Physical layer specification and service definition

IEC 61241-0, Electrical apparatus for use in the presence of combustible dust – Part 0: General requirements

IEC 61241-11, Electrical apparatus for use in the presence of combustible dust – Part 11: Protection by intrinsic safety 'iD'

3 Terms, definitions and abbreviations

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions, specific to intrinsically safe electrical systems, apply. They supplement the terms and definitions which are given in IEC 60079-0 and IEC 60079-11.

3.1.1

intrinsically safe electrical system

assembly of interconnected items of electrical apparatus, described in a descriptive system document, in which the circuits or parts of circuits, intended to be used in an explosive atmosphere, are intrinsically safe circuits

3.1.2

certified intrinsically safe electrical system

intrinsically safe electrical system conforming to 3.1.1 for which a certificate has been issued confirming that the electrical system complies with IEC 60079-25

3.1.3

uncertified intrinsically safe electrical system

intrinsically safe electrical system conforming to 3.1.1 for which the knowledge of the electrical parameters of the items of certified intrinsically safe electrical apparatus, certified associated apparatus, simple apparatus and the knowledge of the electrical and physical parameters of the interconnecting wiring permit the unambiguous deduction that intrinsic safety is preserved

3.1.4

descriptive system document

document in which the items of electrical apparatus, their electrical parameters and those of the interconnecting wiring are specified

3.1.5

system designer

person who is responsible for the descriptive system document, has the necessary competence to fulfil the task and who is empowered to enter into the commitments on behalf of his employer

3.1.6

maximum cable capacitance

 C_{c}

maximum capacitance of the interconnecting cable that can be connected into an intrinsically safe circuit without invalidating intrinsic safety

3.1.7

maximum cable inductance

 L_{c}

maximum inductance of the interconnecting cable that can be connected into an intrinsically safe circuit without invalidating intrinsic safety