

Alarm systems - Intrusion and hold-up systems - Part
2-10: Intrusion detectors - Lock state contacts
(magnetic)

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 50131-2-10:2018 sisaldab Euroopa standardi EN 50131-2-10:2018 ingliskeelset teksti.	This Estonian standard EVS-EN 50131-2-10:2018 consists of the English text of the European standard EN 50131-2-10:2018.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 28.09.2018.	Date of Availability of the European standard is 28.09.2018.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 13.320

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

English Version

**Alarm systems - Intrusion and hold-up systems - Part 2-10:
Intrusion detectors - Lock state contacts (magnetic)**

Systèmes d'alarme - Systèmes d'alarme contre l'intrusion et les hold-up - Partie 2-10: Détecteurs d'intrusion - Contact d'état de verrouillage (magnétiques)

Alarmanlagen - Einbruch- und Überfallmeldeanlagen - Teil 2-10: Einbruchmelder - Verschluss- und Öffnungsüberwachungskontakte (magnetisch)

This European Standard was approved by CENELEC on 2018-05-10. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents

Page

European foreword.....	4
Introduction.....	5
1 Scope.....	6
2 Normative references.....	6
3 Terms, definitions and abbreviations.....	6
3.1 Terms and definitions.....	6
3.2 Abbreviations.....	8
4 Functional requirements.....	8
4.1 Events.....	8
4.2 Signals or messages.....	9
4.3 Detection.....	10
4.3.1 Detection performance.....	10
4.3.2 Indication of detection.....	11
4.4 Operational requirements.....	11
4.4.1 Time interval between intrusion signals or messages.....	11
4.4.2 Switch on delay.....	11
4.4.3 Fault condition signals.....	11
4.5 Tamper security.....	11
4.5.1 Tamper security requirements.....	11
4.5.2 Resistance to and detection of unauthorised access to the inside of the detector through covers and existing holes.....	12
4.5.3 Detection of removal from the mounting surface.....	12
4.5.4 Magnetic or electromagnetic field interference.....	12
4.5.5 Matched pairs, coding and encryption.....	12
4.6 Electrical requirements.....	13
4.6.1 Grade dependencies.....	13
4.6.2 Detector current consumption.....	13
4.6.3 Slow input voltage change and input voltage range limits.....	13
4.6.4 Input voltage ripple.....	13
4.6.5 Input voltage step change.....	13
4.6.6 Total loss of external power.....	13
4.6.7 Low supply voltage.....	14
4.6.8 Interconnection Integrity.....	14
4.7 Environmental classification and conditions.....	14
4.7.1 Environmental classification.....	14
4.7.2 Immunity to environmental conditions.....	14
5 Marking, identification and documentation.....	14
5.1 Marking and/or identification.....	14
5.2 Documentation.....	14
6 Testing.....	15
6.1 Generalities.....	15
6.2 General test conditions.....	15
6.2.1 Standard laboratory conditions for testing.....	15
6.2.2 General detection testing environment and procedures.....	15
6.2.3 Testing procedures.....	16
6.3 Basic test of detection capability.....	16
6.4 Verification of detection performance.....	16
6.4.1 Generalities.....	16

6.4.2	Measurement of make / break distances	16
6.5	Switch-on delay, time interval between signals, and indication of detection	16
6.6	Tamper security	16
6.6.1	Generalities	16
6.6.2	Resistance to and detection of unauthorized access to the inside of the detector through covers and existing holes	17
6.6.3	Detection of removal from the mounting surface	17
6.6.4	Resistance to magnetic field interference	17
6.6.5	Matched pairs, coding and encryption	18
6.7	Electrical tests	18
6.7.1	Generalities	18
6.7.2	Detector current consumption	18
6.7.3	Slow input voltage change and input voltage range limits	19
6.7.4	Input voltage ripple	19
6.7.5	Input voltage step change	19
6.7.6	Total loss of power supply	19
6.7.7	Low power supply voltage	20
6.7.8	Interconnection	20
6.8	Environmental classification and conditions	20
6.8.1	General	20
6.8.2	Special conditions	20
6.9	Marking, identification and documentation	21
6.9.1	Marking and/or identification	21
6.9.2	Documentation	21
Annex A	(normative) Dimensions and requirements of standardized interference test magnets	22
A.1	Normative references	22
A.2	Requirements	22
Annex B	(normative) General testing matrix	25
Annex C	(informative) List of small tools suitable for testing immunity of casing to unauthorised access	27
Annex D	(normative) Axes of movement	28
Annex E	(normative) Test surfaces for ferromagnetic material	29
Annex F	(normative) Test faces for interference test units	30
F.1	Surface mounted detector	30
F.2	Flush mounted detector	31
Bibliography		32

European foreword

This document (EN 50131-2-10:2018) has been prepared by CLC/TC 79 "Alarm systems".

The following dates are fixed:

- latest date by which this document has (dop) 2019-03-28
to be implemented at national level by
publication of an identical national
standard or by endorsement
- latest date by which the national (dow) 2021-09-28
standards conflicting with this document
have to be withdrawn

This document supersedes CLC/TS 50131-2-10:2014.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

EN 50131-2 is currently composed of the following parts:

- EN 50131-2-2, *Alarm systems — Intrusion and hold-up systems — Part 2-2: Intrusion detectors — Passive infrared detectors*;
- EN 50131-2-3, *Alarm systems — Intrusion and hold-up systems — Part 2-3: Requirements for microwave detectors*;
- EN 50131-2-4, *Alarm systems — Intrusion and hold-up systems — Part 2-4: Requirements for combined passive infrared and microwave detectors*;
- EN 50131-2-5, *Alarm systems — Intrusion and hold-up systems — Part 2-5: Requirements for combined passive infrared and ultrasonic detectors*;
- EN 50131-2-6, *Alarm systems — Intrusion and hold-up systems — Part 2-6: Opening contacts (magnetic)*;
- CLC/TS 50131-2-8, *Alarm systems — Intrusion and hold-up systems — Part 2-8: Intrusion detectors — Shock detectors*;
- CLC/TS 50131-2-9, *Alarm systems — Intrusion and hold-up systems — Part 2-9: Intrusion detectors — Active infrared beam detectors*;
- EN 50131-2-10, *Alarm systems — Intrusion and hold-up systems — Part 2-10: Intrusion detectors — Lock state contacts (magnetic)* [the present document];
- EN 50131-2-7-1, *Alarm systems — Intrusion and hold-up systems — Part 2-7-1: Intrusion detectors — Glass break detectors (acoustic)*;
- EN 50131-2-7-2, *Alarm systems — Intrusion and hold-up systems — Part 2-7-2: Intrusion detectors — Glass break detectors (passive)*;
- EN 50131-2-7-3, *Alarm systems — Intrusion and hold-up systems — Part 2-7-3: Intrusion detectors — Glass break detectors (active)*.

Introduction

This European Standard applies to lock state contacts (magnetic) used as part of intrusion and hold-up alarm systems (I&HAS) installed in buildings. It includes four security grades and four environmental classes.

The purpose of a lock state contact (magnetic) is to detect the lock/unlock state only or the lock/unlock state combined with the opening status/displacement from the defined closed position of a window or door simultaneously. The lock state contact comprises two separate contact-less units, the active connection between these units is at least one magnetic or electromagnetic based field. Separating the two units disturbs the connection and produces an intruder signal or message.

The scope for lock state contacts (magnetic) and the number and types of generated signals or messages will be more comprehensive for systems that are specified at the higher grades.

This European Standard is only concerned with the requirements and tests for lock state contacts (magnetic). Other types of detectors are covered by other documents identified as in the EN 50131-2 series.

1 Scope

This European Standard provides for security grades 1 to 4, (see EN 50131-1) specific or non-specific wired or wire-free lock state contacts, and includes the requirements for four environmental classes covering applications in internal and outdoor locations as specified in EN 50130-5.

Lock state contacts are installed in windows or doors and windows or doorframes to allow to monitor the lock/unlock status only or the lock/unlock status combined with the open/close status of a window/door simultaneously and are as such located in supervised premises. They provide the necessary range of signals or messages to be used by the rest of the intrusion alarm system.

A detector fulfils all the requirements of the specified grade.

Functions additional to the mandatory functions specified in this European Standard may be included in the detector, providing they do not influence the correct operation of the mandatory functions.

The combination of the two separate units of the lock state contact is referred to in the body of this European Standard as the detector.

This European Standard does not apply to system interconnections.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 10130, *Cold rolled low carbon steel flat products for cold forming — Technical delivery conditions*

EN 50130-4, *Alarm systems — Part 4: Electromagnetic compatibility — Product family standard: Immunity requirements for components of fire, intruder, hold up, CCTV, access control and social alarm systems*

EN 50130-5, *Alarm systems — Part 5: Environmental test methods*

EN 50131-1, *Alarm systems — Intrusion and hold-up systems — Part 1: System requirements*

3 Terms, definitions and abbreviations

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 50131-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1.1

connecting field

one or more generated magnetic or electromagnetic field(s) (e.g. magnetic, inductive, RFID, NFC) connecting actively the two units of the detector

Note 1 to entry: Separating the two units disturbs the connection and produces an intrusion signal or message.

3.1.2

prohibited area

mounting arrangement, as stated by the manufacturer, of the two units of the detector in which the detector no longer meets the requirements of this European Standard