

**Specifications for particular types of winding wires -
Part 60: Polyester glass fibre wound minimum class 155
resin or varnish impregnated or not impregnated, bare
or enamelled, rectangular copper wire, temperature
index 155**

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 60317-60:2012 sisaldab Euroopa standardi EN 60317-60:2012 ingliskeelset teksti.	This Estonian standard EVS-EN 60317-60:2012 consists of the English text of the European standard EN 60317-60:2012.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 03.08.2012.	Date of Availability of the European standard is 03.08.2012.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 29.060.10

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Aru 10, 10317 Tallinn, Eesti; www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:
Aru 10, 10317 Tallinn, Estonia; www.evs.ee; phone 605 5050; e-mail info@evs.ee

**Specifications for particular types of winding wires -
Part 60: Polyester glass fibre wound minimum class 155 resin or varnish
impregnated or not impregnated, bare or enamelled, rectangular copper
wire, temperature index 155
(IEC 60317-60:2012)**

Spécifications pour types particuliers de
fils de bobinage -
Partie 60: Fil de section rectangulaire en
cuivre nu ou émaillé, guipé de fibres de
verre avec polyester de classe d'au moins
155, imprégnées ou non de vernis ou de
résine, d'indice de température 155
(CEI 60317-60:2012)

Technische Lieferbedingungen für
bestimmte Typen von Wickeldrähten -
Teil 60: Flachdrähte aus Kupfer, blank
oder lackisoliert und umhüllt mit
Polyesterglasgewebe, imprägniert mit
Harz oder Lack oder unimprägniert,
Temperaturindex 155
(IEC 60317-60:2012)

This European Standard was approved by CENELEC on 2012-07-31. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 55/1320/FDIS, future edition 1 of IEC 60317-60, prepared by IEC/TC 55 "Winding wires" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 60317-60:2012.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2013-04-31
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2015-07-31

This standard is to be used in conjunction with FprEN 60317-0-8:2012.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 60317-60:2012 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60264 series	NOTE	Harmonized in EN 60264 series.
IEC 60317 series	NOTE	Harmonized in EN 60317 series.
IEC 60851 series	NOTE	Harmonized in EN 60851 series.

Annex ZA
(normative)
Normative references to international publications
with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60317-0-8	201X	Specifications for particular types of winding wires - Part 0-8: General requirements - Polyester glass-fibre wound, resin or varnish impregnated or not impregnated, bare or enamelled rectangular copper wire	FprEN 60317-0-8	2012

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	6
2 Normative references	6
3 Terms, definitions, general notes and appearance.....	6
3.1 Terms and definitions	6
3.2 General notes.....	6
3.2.1 Methods of test.....	6
3.2.2 Winding wire.....	7
3.3 Appearance.....	7
4 Dimensions	7
5 Electrical resistance	7
6 Elongation	7
7 Springiness	7
8 Flexibility and adherence.....	7
9 Heat shock	7
10 Cut-through	8
11 Resistance to abrasion	8
12 Resistance to solvents.....	8
13 Breakdown voltage	8
14 Continuity of insulation	8
15 Temperature index	8
16 Resistance to refrigerants.....	8
17 Solderability	8
18 Heat or solvent bonding.....	8
19 Dielectric dissipation factor.....	8
20 Resistance to transformer oil.....	8
23 Pin hole test	8
30 Packaging	9
Bibliography.....	10

INTRODUCTION

This part of IEC 60317 is one of a series which deals with insulated wires used for windings in electrical equipment. The series has three groups describing:

- 1) Winding wires – Test methods (IEC 60851);
- 2) Specifications for particular types of winding wires (IEC 60317);
- 3) Packaging of winding wires (IEC 60264).

SPECIFICATIONS FOR PARTICULAR TYPES OF WINDING WIRES –

Part 60: Polyester glass fibre wound, minimum class 155 resin or varnish impregnated or not impregnated, bare or enamelled, rectangular copper wire, temperature index 155

1 Scope

This part of IEC 60317 specifies the requirements of polyester glass fibre wound, impregnated or not impregnated, bare or enamelled rectangular copper winding wire, temperature index 155.

NOTE For this type of wire, the heat shock test is inappropriate and therefore a heat shock temperature cannot be established. Consequently, a class based on the requirements for temperature index and heat shock temperature cannot be specified.

The range of nominal conductor dimensions covered by this standard is:

- width: min. 2,0 mm; max. 16,0 mm;
- thickness: min. 0,80 mm; max. 5,60 mm.

The specified combinations of width and thickness as well as the specified width/thickness ratio are according to IEC 60317-0-8.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60317-0-8:2012, *Specifications for particular types of winding wires – Part 0-8: General requirements – Polyester glass fibre wound, resin or varnish impregnated or not impregnated, bare or enamelled rectangular copper wire*

3 Terms, definitions, general notes and appearance

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in 3.1 of IEC 60317-0-8:2012 apply.

3.2 General notes

3.2.1 Methods of test

Subclause 3.2 of IEC 60317-0-8:2012 applies.

In case of inconsistency between IEC 60317-0-8 and this standard, IEC 60317-60 shall prevail.