

# INTERNATIONAL STANDARD

# ISO 7425-2

First edition  
1989-12-01

---

---

## Hydraulic fluid power — Housings for elastomer-energized, plastic-faced seals — Dimensions and tolerances —

### Part 2 : Rod seal housings

*Transmissions hydrauliques — Logements pour joints en élastomère renforcé par  
des matières plastiques — Dimensions et tolérances —*

*Partie 2 : Logements de joints de tige*



Reference number  
ISO 7425-2 : 1989 (E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 7425-2 was prepared by Technical Committee ISO/TC 131, *Fluid power systems*.

ISO 7425 consists of the following parts, under the general title *Hydraulic fluid power — Housings, for elastomer-energized, plastic-faced seals — Dimensions and tolerances*:

- *Part 1: Piston seal housings*
- *Part 2: Rod seal housings*

© ISO 1989

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization  
Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

## Introduction

In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure within an enclosed circuit. Sealing devices are used to contain the pressurized fluid within components having elements with linear motion, i.e. hydraulic cylinders. These sealing devices are used with both cylinder rod and piston seal housings.

This part of ISO 7425 is one of a series of standards covering dimensions and tolerances, and relates to housings for a specific type of rod seal. Alternative choices of housing size may be found in ISO 5597 : 1987, *Hydraulic fluid power — Cylinders — Housings for piston and rod seals in reciprocating applications — Dimensions and tolerances*.

This document is a preview generated by EVS

This document is a preview generated by EVS

This page intentionally left blank

# Hydraulic fluid power — Housings for elastomer-energized, plastic-faced seals — Dimensions and tolerances —

## Part 2 : Rod seal housings

### 1 Scope

This part of ISO 7425 specifies the dimensions, and associated tolerances for a series of hydraulic cylinder rod seal housings to accommodate elastomer-energized, plastic-faced seals used in reciprocating applications.

It is not the intention of this part of ISO 7425 to stipulate details of seal design, since the manner of construction of seals varies with each manufacturer. The design and material of the seal and any incorporated anti-extrusion component are determined by conditions such as temperature and pressure.

This part of ISO 7425 applies only to the dimensional characteristics of products manufactured in accordance with this part of ISO 7425. It does not apply to their functional characteristics.

### 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 7425. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 7425 are encouraged to investigate the possibility of applying the most recent editions of the standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 286-2 : 1988, *ISO system of limits and fits — Part 2: Tables of standard tolerance grades and limit deviations for holes and shafts*.

ISO 3320 : 1987, *Fluid power systems and components — Cylinder bores and piston rod diameters — Metric series*.

ISO 5598 : 1985, *Fluid power systems and components — Vocabulary*.

### 3 Definitions

For the purposes of this part of ISO 7425, the definitions given in ISO 5598 apply.

### 4 Letter symbols

Letter symbols used in this part of ISO 7425 are as follows:

$C$  = axial length of the lead-in chamfer

$L$  = axial length of the seal housing (seal groove length)

$d$  = inside diameter of the seal housing (rod diameter)

$D$  = outside diameter of the seal housing (groove diameter)

$d_4$  = clearance diameter of the rod seal housing

$r$  = groove corner radius

$S = \frac{D - d}{2}$  = radial depth (cross-section) of the seal housing

### 5 Seal housings

#### 5.1 General

5.1.1 An illustrated example of a typical hydraulic cylinder rod seal housing covered by this part of ISO 7425 is shown in figure 1.

NOTE — The figure is diagrammatic only and does not represent an endorsement or a recommendation of a particular housing design.

5.1.2 All sharp edges and burrs shall be removed from corners of supporting surfaces, although it should be borne in mind that these surfaces are required to provide maximum support against extrusion.

5.1.3 The seal manufacturer shall be consulted for details of housing design which are not specified in this part of ISO 7425.

#### 5.2 Axial length

Axial lengths for the nominal rod diameters shown are given in table 2.