Tööstusprotsesside juhtimisventiilid. Osa 2-1: Vooluhulk. Mõõtmete valiku võrrandid vedelikuvoolu järgi paigaldusoludes

Industrial-process control valves - Part 2-1: Flow capacity rilow och character and the control of the control Sizing equations for fluid flow under installed conditions



#### **EESTI STANDARDI EESSÕNA**

#### **NATIONAL FOREWORD**

Käesolev Eesti standard EVS-EN 60534-2-
1:2011 sisaldab Euroopa standardi EN 60534-
2-1:2011 ingliskeelset teksti.

This Estonian standard EVS-EN 60534-2-1:2011 consists of the English text of the European standard EN 60534-2-1:2011.

Standard on kinnitatud Eesti Standardikeskuse 30.06.2011 käskkirjaga ja jõustub sellekohase teate avaldamisel EVS Teatajas.

This standard is ratified with the order of Estonian Centre for Standardisation dated 30.06.2011 and is endorsed with the notification published in the official bulletin of the Estonian national standardisation organisation.

Euroopa standardimisorganisatsioonide poolt rahvuslikele liikmetele Euroopa standardi teksti kättesaadavaks tegemise kuupäev on 20.05.2011.

Date of Availability of the European standard text 20.05.2011.

Standard on kättesaadav Eesti standardiorganisatsioonist.

The standard is available from Estonian standardisation organisation.

ICS 23.060.40, 25.040.40

Inglisekeelsed võtmesõnad: control valves, flow capacity, industrial-process, installed conditions, sizing equations,

#### Standardite reprodutseerimis- ja levitamisõigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonilisse süsteemi või edastamine ükskõik millises vormis või millisel teel on keelatud ilma Eesti Standardikeskuse poolt antud kirjaliku loata.

Kui Teil on küsimusi standardite autorikaitse kohta, palun võtke ühendust Eesti Standardikeskusega: Aru 10 Tallinn 10317 Eesti; <a href="www.evs.ee">www.evs.ee</a>; Telefon: 605 5050; E-post: <a href="mailto:info@evs.ee">info@evs.ee</a>

#### Right to reproduce and distribute belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without permission in writing from Estonian Centre for Standardisation.

If you have any questions about standards copyright, please contact Estonian Centre for Standardisation: Aru str 10 Tallinn 10317 Estonia; <a href="www.evs.ee">www.evs.ee</a>; Phone: 605 5050; E-mail: <a href="mailto:info@evs.ee">info@evs.ee</a>

### **EUROPEAN STANDARD**

## EN 60534-2-1

## NORME EUROPÉENNE EUROPÄISCHE NORM

May 2011

ICS 23.060.40; 25.040.40

Supersedes EN 60534-2-1:1998

English version

# Industrial-process control valves Part 2-1: Flow capacity Sizing equations for fluid flow under installed conditions

(IEC 60534-2-1:2011)

Vannes de régulation des processus industriels Partie 2-1: Capacité d'écoulement Equations de dimensionnement pour l'écoulement des fluides dans les conditions d'installation (CEI 60534-2-1:2011)

Stellventile für die Prozessregelung -Teil 2-1: Durchflusskapazität -Bemessungsgleichungen für Fluide unter Betriebsbedingungen (IEC 60534-2-1:2011)

This European Standard was approved by CENELEC on 2011-05-04. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

## CENELEC

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

#### **Foreword**

The text of document 65B/783/FDIS, future edition 2 of IEC 60534-2-1, prepared by SC 65B, Devices & process analysis, of IEC TC 65, Industrial-process measurement, control and automation, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 60534-2-1 on 2011-05-04.

This European Standard supersedes EN 60534-2-1:1998.

EN 60534-2-1:2011 includes the following significant technical changes with respect to EN 60534-2-1:1998:

- the same fundamental flow model, but changes the equation framework to simplify the use of the standard by introducing the notion of  $\Delta p_{sizing}$ ;
- changes to the non-turbulent flow corrections and means of computing results;
- multi-stage sizing as an Annex.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN and CENELEC shall not be held responsible for identifying any or all such patent rights.

The following dates were fixed:

 latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement

(dop) 2012-02-04

 latest date by which the national standards conflicting with the EN have to be withdrawn

(dow) 2014-05-04

Annex ZA has been added by CENELEC.

#### Endorsement notice

The text of the International Standard IEC 60534-2-1:2011 was approved by CENELEC as a European Standard without any modification.

# Annex ZA (normative)

# Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

Publication IEC 60534-1	<u>Year</u> 2005	Title Industrial-process control valves - Part 1: Control valve terminology and general considerations	EN/HD EN 60534-1	<u>Year</u> 2005
IEC 60534-2-3	1997	Part 1: Control valve terminology and general considerations Industrial-process control valves - Part 2-3: Flow capacity - Test procedures	EN 60534-2-3	1998

## CONTENTS

FOI	REWO	ORD	4			
1	1 Scope6					
2	Normative references					
3	Terms and definitions					
4	Symb	ools	8			
5	Insta	llation	9			
6	Sizin	g equations for incompressible fluids	10			
	6.1	Turbulent flow	10			
	6.2	Pressure differentials				
		6.2.1 Sizing pressure differential, ∆p <sub>sizing</sub>				
		6.2.2 Choked pressure differential, Δp <sub>choked</sub>				
	6.0	6.2.3 Liquid critical pressure ratio factor, F <sub>F</sub>				
7	6.3 Sizin	Non-turbulent (laminar and transitional) flow				
′	7.1	General				
	7.1	Pressure differentials				
		7.2.1 Sizing pressure drop ratio, x <sub>Sizing</sub>				
		7.2.2 Choked pressure drop ratio, x <sub>choked</sub>				
	7.3	Specific heat ratio factor, $F_{\gamma}$	12			
	7.4	Expansion factor, Y				
	7.5	Compressibility factor, Z				
0	7.6	Non-turbulent (laminar and transitional) flow				
8		ection factors common to both incompressible and compressible flow				
	8.1	Piping geometry correction factors				
	8.2 8.3	Estimated combined liquid pressure recovery factor and piping geometry	14			
	0.0	factor with attached fittings, $F_{LP}$	15			
	8.4	Estimated pressure differential ratio factor with attached fittings, $x_{TP}$	16			
9	-	olds Number, Re <sub>V</sub>				
Anr	nex A	(normative) Sizing equations for non-turbulent flow	18			
		(normative) Sizing equations for fluid flow through multistage control valves				
Anr	nex C	(informative) Piping factor computational considerations	28			
Anr	nex D	(informative) Engineering Data	34			
Anr	nex E	(informative) Reference calculations	41			
Bib	liogra	phy	54			
Fig	ure 1	- Reference pipe section for sizing	10			
		1 – Multistage multipath trim				
Fig	Figure B.2 – Multistage single path trim					
		.3 – Disk from a continuous resistance trim The complete trim consists of a of these disks stacked together.	25			
		4 – Sectional view of continuous resistance trim with multiple flow passages ertical undulations	25			
		.1 – Determination of the upper limit of the flow coefficient by the iterative	32			

Figure C.2 – Determination of the final flow coefficient by the iterative method	33
Figure D.1 – Piping geometry factors	37
Figure D.2 – Pressure recovery factors	39
Figure D.3 – Liquid critical pressure ratio factor $F_{F}$	40
Table 1 – Numerical constants N	17
Table B.1 – Values of the stage interaction factors, $k$ , and the reheat factors, $r$ for multistage single and multipath control valve trim	27
Table B.2 – Values of the stage interaction factors, $k$ , and the reheat factors, $r$ for continuous resistance control valve trim	
Table C.1 – Incompressible flow	
Table C.2 – Compressible flow	31
Table D.1 – Typical values of valve style modifier $F_d$ , liquid pressure recovery factor $F_L$ and pressure differential ratio factor $x_T$ at full rated travel a)	35
So openion of the state of the	

#### INDUSTRIAL-PROCESS CONTROL VALVES -

# Part 2-1: Flow capacity – Sizing equations for fluid flow under installed conditions

#### 1 Scope

This part of IEC 60534 includes equations for predicting the flow of compressible and incompressible fluids through control valves.

The equations for incompressible flow are based on standard hydrodynamic equations for Newtonian incompressible fluids. They are not intended for use when non-Newtonian fluids, fluid mixtures, slurries or liquid-solid conveyance systems are encountered. The equations for incompressible flow may be used with caution for non-vaporizing multi-component liquid mixtures. Refer to Clause 6 for additional information.

At very low ratios of pressure differential to absolute inlet pressure  $(\Delta p/p_1)$ , compressible fluids behave similarly to incompressible fluids. Under such conditions, the sizing equations for compressible flow can be traced to the standard hydrodynamic equations for Newtonian incompressible fluids. However, increasing values of  $\Delta p/p_1$  result in compressibility effects which require that the basic equations be modified by appropriate correction factors. The equations for compressible fluids are for use with ideal gas or vapor and are not intended for use with multiphase streams such as gas-liquid, vapor-liquid or gas-solid mixtures. Reasonable accuracy can only be maintained when the specific heat ratio,  $\gamma$ , is restricted to the range 1,08 <  $\gamma$  < 1,65. Refer to Clause 7.2 for more information.

For compressible fluid applications, this standard is valid for valves with  $x_T \le 0.84$  (see Table D.2). For valves with  $x_T > 0.84$  (e.g. some multistage valves), greater inaccuracy of flow prediction can be expected.

Reasonable accuracy can only be maintained for control valves if:

$$\frac{C}{N_{18}d^2} < 0.047$$

Note that while the equation structure utilized in this document departs radically from previous versions of the standard, the basic technology is relatively unchanged. The revised equation format was adopted to simplify presentation of the various equations and improve readability of the document.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60534-1:2005, Industrial-process control valves – Part 1: Control valve terminology and general considerations

IEC 60534-2-3:1997, Industrial-process control valves – Part 2-3: Flow capacity – Test procedures