Particular requirements for load-shedding equipment (LSE)



### EESTI STANDARDI EESSÕNA

### NATIONAL FOREWORD

See Eesti standard EVS-EN IEC 62962:2019 sisaldab Euroopa standardi EN IEC 62962:2019 ingliskeelset teksti.	This Estonian standard EVS-EN IEC 62962:2019 consists of the English text of the European standard EN IEC 62962:2019.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 01.11.2019.	Date of Availability of the European standard is 01.11.2019.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile <u>standardiosakond@evs.ee</u>.

### ICS 27.015, 29.020

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega: Koduleht <a href="www.evs.ee">www.evs.ee</a>; telefon 605 5050; e-post <a href="mailto:info@evs.ee">info@evs.ee</a>

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

## EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

**EN IEC 62962** 

November 2019

ICS 27.015; 29.020

### **English Version**

# Particular requirements for load-shedding equipment (LSE) (IEC 62962:2019)

Exigences spécifiques pour les délesteurs (LSE) (IEC 62962:2019)

Besondere Anforderungen für Lastabwurfeinrichtungen (LSE) (IEC 62962:2019)

This European Standard was approved by CENELEC on 2019-10-18. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

### **European foreword**

The text of document 23K/47/FDIS, future edition 1 of IEC 62962, prepared by SC 23K "Electrical Energy Efficiency products" of IEC/TC 23 "Electrical accessories" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 62962:2019.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2022-10-18

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

#### **Endorsement notice**

The text of the International Standard IEC 62962:2019 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60038	NOTE	Harmonized as EN 60038
IEC 60112	NOTE	Harmonized as EN 60112
IEC 60364-4-41	NOTE	Harmonized as HD 60364-4-41
IEC 60364-5-51:2005	NOTE	Harmonized as HD 60364-5-51:2009
IEC 60364-8-1:2019	NOTE	Harmonized as HD 60364-8-1:2019 (not modified)
IEC 60529	NOTE	Harmonized as EN 60529
IEC 60669-1:2017	NOTE	Harmonized as EN 60669-1:2018
IEC 60721-3-3	NOTE	Harmonized as EN IEC 60721-3-3
IEC 60947-1:2007	NOTE	Harmonized as EN 60947-1:2007 (not modified)
IEC 60998-2-2:2002	NOTE	Harmonized as EN 60998-2-2:2004
IEC 61000-3-2	NOTE	Harmonized as EN IEC 61000-3-2
IEC 61008-1:2010	NOTE	Harmonized as EN 61008-1:2012
IEC 61008-1:2010/A1:2012	NOTE	Harmonized as EN 61008-1:2012/A1:2014
IEC 61008-1:2010/A2:2013	NOTE	Harmonized as EN 61008-1:2012/A2:2014
IEC 61009-1:2010	NOTE	Harmonized as EN 61009-1:2012
IEC 61009-1:2010/A1:2012	NOTE	Harmonized as EN 61009-1:2012/A1:2014
IEC 61009-1:2010/A2:2013	NOTE	Harmonized as EN 61009-1:2012/A2:2014
IEC 61140	NOTE	Harmonized as EN 61140
ISO 2039-2:1987	NOTE	Harmonized as EN ISO 2039-2:1999 (not modified)

### Annex ZA

(normative)

# Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: <a href="https://www.cenelec.eu">www.cenelec.eu</a>.

<u>Publication</u> <u>Year</u>	<u>Title</u>	EN/HD	<u>Year</u>
IEC 60065 2001	Audio, video and similar electronic apparatus - Safety requirements	-	-
IEC 60085 -	Electrical insulation - Thermal evaluation and designation	EN 60085	-
IEC 60127 series	Miniature fuses	EN 60127	series
IEC 60212 -	Standard conditions for use prior to and during the testing of solid electrical insulating materials	EN 60212	-
IEC 60317-0-1 1997	Specifications for particular types of winding wires Part 0-1: General requirements - Enamelled round copper wire	-	-
IEC 60364 series	Low-voltage electrical installations	HD 60364	series
IEC 60384-14 1993	Fixed capacitors for use in electronic equipment Part 14: Sectional specification: Fixed capacitors for electromagnetic interference suppression and connection to the supply mains		-
IEC 60417 -	Graphical symbols for use on equipment. Index, survey and compilation of the single sheets.	-O-	-
IEC 60664-1 2007	Insulation coordination for equipment within low-voltage systems - Part 1: Principles, requirements and tests	EN 60664-1	2007
IEC 60695-2-10 2000	Fire hazard testing Part 2-10: Glowing/hot-wire based test methods - Glow-wire apparatus and common test procedure	-	
IEC 60695-2-11 2000	Fire hazard testing Part 2-11: Glowing/hot-wire based test methods - Glow-wire flammability test method for end-products	-	_

<u>Publication</u>	<u>Year</u>	<u>Title</u>	EN/HD	Year
IEC 60730	series	Automatic electrical controls	EN 60730	series
IEC 61000-2-2	-	Electromagnetic compatibility (EMC) - Part 2-2: Environment - Compatibility levels for low-frequency conducted disturbances and signalling in public low-voltage power supply systems	EN 61000-2-2	-
IEC 61000-4-2	-	Electromagnetic compatibility (EMC) - Part 4-2: Testing and measurement techniques - Electrostatic discharge immunity test	EN 61000-4-2	-
IEC 61000-4-3	3	Electromagnetic compatibility (EMC) - Part 4-3: Testing and measurement techniques - Radiated, radio-frequency, electromagnetic field immunity test	-	-
IEC 61000-4-4	- 7	Electromagnetic compatibility (EMC) - Part 4-4: Testing and measurement techniques - Electrical fast transient/burst immunity test	EN 61000-4-4	-
IEC 61000-4-5	-	Electromagnetic compatibility (EMC) - Part 4-5: Testing and measurement techniques - Surge immunity test	EN 61000-4-5	-
IEC 61000-4-6	-	Electromagnetic compatibility (EMC) - Part 4-6: Testing and measurement techniques - Immunity to conducted disturbances, induced by radio-frequency fields	EN 61000-4-6	-
IEC 61000-4-8	-	Electromagnetic compatibility (EMC) - Part 4-8: Testing and measurement techniques - Power frequency magnetic field immunity test	EN 61000-4-8	-
IEC 61000-4-11	-	Electromagnetic compatibility (EMC) - Part 4-11: Testing and measurement techniques - Voltage dips, short interruptions and voltage variations immunity tests	EN 61000-4-11	-
IEC 61032	1997	Protection of persons and equipment by enclosures - Probes for verification	EN 61032	1998
IEC 61558-2-6	-	Safety of transformers, reactors, power supply units and similar products for supply voltages up to 1 100 V - Part 2-6: Particular requirements and tests for safety isolating transformers and power supply units incorporating safety isolating transformers	EN 61558-2-6	-
ISO 306	-	Plastics - Thermoplastic materials - Determination of Vicat softening temperature (VST)	EN ISO 306	-
CISPR 15	-	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment	EN IEC 55015	7

### CONTENTS

FC	DREWO	RD	9
IN	TRODU	CTION	11
1	Scop	e	12
2	Norm	native references	13
3	Term	s and definitions	14
4		eral requirements	
_	4.1	General	
	4.2	Architecture	
	4.3	Standard conditions for operation in service	
5		eral remarks on tests	
Ü	5.1	Environmental conditions	
	5.1.1		
	5.1.1		
	5.1.2		
	5.1.4		
	5.2	General testing procedure and samples	
6	-	gs	
Ĭ	6.1	Rated values	
	6.1.1		
	6.1.2		
	6.1.3		
	6.1.4		
	6.1.5		
	6.1.6	- Hills	
	6.1.7		
	6.1.8		
	6.1.9	Preferred rated load-shedding current (power) values $(I_nL_s, P_nL_s)$	28
	6.2	Time-current characteristic for LSEs monitoring the current	28
	6.2.1	LSE operating principle	28
	6.2.2	Current limits (I <sub>n</sub> L <sub>s</sub> )	30
	6.2.3	Minimum switch OFF-time	30
	6.2.4	3	
	6.3	Time-power characteristic	32
	6.4	LSE shedding sequence	32
7	Class	sification	33
	7.1	General	
	7.2	According to the LSE functional category	
	7.3	According to the switching means	34
	7.4	According to the possibility of adjusting the rated load-shedding current(s) (or power)	34
	7.5	According to the shedding sequence	
	7.6	According to the design	
	7.6.1		
	7.6.2	-	
	7.6.3	Combined LSE (or assembled LSE)	34
	7.7	According to the method of mounting	34

	7.8	Acco	ording to the type of terminals	. 34
	7.9	Acco	ording to the contact openings	. 34
	7.10	Acco	ording to the protection against external influences	. 35
	7.11	Acco	ording to the number of poles	. 35
	7.12	Acco	ording to the type of monitored parameters	. 35
8	Mark	ings	and information	. 35
	8.1	Gen	eral	. 35
	8.2	Test	of markings	. 36
9	Prote	ction	against electric shock	. 36
	9.1		eral	
	9.2		for protection against electric shock	
10	Term		for external copper conductors	
. •	10.1		eral	
	10.1		ninals with screw clamping for external copper conductors	
	10.2.		General	
	10.2.		Conductor fitting	
	10.2.		Mechanical strength of terminals	
	10.2.		Resistance to corrosion of terminals	
	10.2.		Clamping effects on conductors	
	10.2.		Clamping reliability of terminals	
	10.2.		Clamping length of terminals	
	10.2.		Reliability of terminals	
	10.2.		Accidental loosening of earthing terminals	
	10.2.		Resistance to corrosion of earthing terminals	
	10.2.		Additional requirements for the design of pillar terminals	
	10.2.		Additional requirements for the design of lug terminals	
	10.2.		Additional requirements for terminals for the connection of external	
			conductors	. 50
	10.3	Scre	wless terminals for external copper conductors	
	10.3.	1	General	. 50
	10.3.	2	Conductor fittings	
	10.3.	3	Connection of conductors	. 51
	10.3.	4	Type of material	. 51
	10.3.	5	Conductors clamping	. 51
	10.3.	6	Operation of terminals	. 51
	10.3.	7	Multi conductor terminals	. 52
	10.3.	8	Introduction of conductors	. 52
	10.3.	9	Fixing of terminals	. 52
	10.3.	10	Mechanical strength	. 52
	10.3.		Electrical and thermal stress resistance	
	10.3.	12	Mechanical reliability	. 56
11	Cons	tructi	onal requirements	. 59
	11.1	Gen	eral	. 59
	11.2	Mec	hanical requirements for insulating means	. 59
	11.3	Insta	allation requirements	. 59
	11.4	Fixir	ng of covers, cover plates and actuating members	. 62
	11.4.	1	General	. 62
	11 4	2	Fixings based on screws or rivets	63

11.4.3	Fixings which may be removed by applying a force perpendicular to the surfaces	63
11.4.4	Fixings which may be removed using a tool	
11.5 Atta	achment of knobs	64
11.6 Mou	unting means	64
11.7 Acc	essories	64
12 Mechanis	m and operating means	64
12.1 Ger	neral	64
12.2 Indi	cation of the position	65
12.3 Res	t position	65
12.4 Mak	king and breaking	65
12.5 Acti	on of the mechanism without cover or cover plate	65
12.6 Fixi	ngs and removal of operating means	65
12.7 Loc	king	66
	tus indicators	
	ce to ageing and humidity	
	sistance to ageing	
	istance to humidity	
	resistance and dielectric strength	
14.1 Ger	neral	67
	ulation resistance of the main circuit	
	lectric strength of main circuits	
	ulation resistance and dielectric strength of other circuits	70
14.5 Veri	ification of impulse withstand voltages (across clearances and through d insulations)	71
14.5.1	General testing procedure	
14.5.2	Verification of clearances with the impulse withstand voltage tests	
15 Temperat	ture rise	
15.1 Ger	neral	72
	t setup	
	t procedure	
	nd breaking capacity	
	peration	
	ctional tests: disconnection and reclosing	
17.1.1	General	
17.1.2	Disconnection tests	
17.1.3	Reclosing tests	78
17.1.4	Load-shedding sequence(s) tests	
17.1.5	Remotely controlled LSE and LSE with connection to other external equipment	79
17.2 End	urance test	79
18 Mechanic	al strength	80
18.1 Ger	neral	80
18.2 Pen	dulum hammer test	81
18.3 Cov	ers, cover plates or actuating members – Accessibility to live parts	89
18.3.1	General	89
18.3.2	Verification of the non-removal of covers, cover plates or actuating members	89
18.3.3	Verification of the removal of covers, cover plates or actuating members.	89

	18.4	Covers, cover plates or actuating members – Accessibility to non-earthed metal parts separated from live parts	90
	18.5	Covers, cover plates or actuating members – Accessibility to insulating	
		parts, earthed metal parts, the live parts of SELV ≤ 25 V AC or metal parts separated from live parts	90
	18.6	Covers, cover plates or actuating members – Application of gauges	90
	18.7	Grooves, holes and reverse tapers	92
	18.8	Rail mounted LSEs	93
19	Resis	stance to heat	94
	19.1	General	94
	19.2	Basic heating test	94
	19.3	Ball-pressure test on parts of insulating material necessary to retain current-carrying parts and parts of the earthing circuit in position	95
	19.4	Ball-pressure test on parts of insulating material not necessary to retain current-carrying parts and parts of the earthing circuit in position	95
20	Scre	ws, current carrying capacity and connections	95
	20.1	General	95
	20.2	Correct insertion of screws	96
	20.3	Contact pressure of electrical connections	97
	20.4	Screws and rivets used both as electrical and mechanical connections	97
	20.5	Material of current-carrying parts	97
	20.6	Thread-forming and thread-cutting screws	98
21	Cree	page distances, clearances and distances through sealing compound	98
	21.1	General	98
	21.2	Measurements	98
	21.3	Insulating compound	99
22	Resis	stance of insulating material to abnormal heat and fire	101
	22.1	General	101
	22.2	Glow-wire test	101
23	Resis	stance to rusting	103
24	EMC	requirements	104
		General	
	24.2	Immunity	
	24.2.		104
	24.2.		
	24.2.		
	24.2.		106
	24.2.		
	24.2.		107
	24.2.		107
	24.2.		
	24.3	Emission	_
	24.3.		
	24.3.		
	24.3.		
25		dination with short-circuit devices	
_	25.1	General requirements for coordination	
	25.2	Testing conditions	
		1 Test circuit	108

25.2.2 Tolerances on test quantities	112
25.2.3 Power factor of the test circuit	112
25.2.4 Power frequency recovery voltage	113
25.2.5 Calibration of the test circuit	113
25.2.6 Sequence of operations	113
25.3 Tests of coordination between the LSE and the SCPD	113
25.3.1 General	113
25.3.2 Verification of the coordination at the rated conditional short-circuit	
current (I <sub>nc</sub> )	
25.3.3 Verification at the instantaneous tripping of the SCPD	
25.3.4 Condition of the LSE during and after tests	
26.1 General	
26.2 Tests under fault conditions	
26.3 Overload tests	
27.1 Fuses	
27.3 Resistors	
27.4.1 General	
27.4.2 Cut-outs	
27.4.3 Automatic protective devices	
27.5 Transformers	
Annex A (normative) Test sequences and number of specimens	
Annex B (informative) Correspondence between ISO and AWG copper conductors	
Annex C (normative) Determination of clearances and creepage distances	
C.1 General	
C.2 Orientation and location of a creepage distance	
C.3 Creepage distances where more than one material is used	
C.4 Creepage distances split by floating conductive part	
C.5 Measurement of creepage distances and clearances	
Annex D (normative) Arrangement for the detection of the emission of ionized gases during short-circuit tests	
Bibliography	
Dibliography	101
Figure 1 – Energy efficiency management system	11
Figure 2 – LSE general architecture	24
Figure 3 – Time-current characteristic of a Class A LSE	29
Figure 4 – Joined test finger (test probe B according to IEC 61032:1997)	
Figure 5 – Test pin for checking the protection against electric shock	
Figure 6 – Terminals with stirrup	
Figure 7 – Pillar terminals	
Figure 8 – Screw terminals and stud terminals	
Figure 9 – Saddle terminals	
Figure 10 – Lug terminals	
Figure 11 – Test apparatus for checking damage to conductors	

Figure 12 – Information for deflection test	57
Figure 13 – Determination of the direction of the forces to be applied	61
Figure 14 – Direction for the conductor pull of 30 N for 1 min	62
Figure 15 – Pendulum impact test apparatus	82
Figure 16 – Pendulum impact test apparatus (striking element)	83
Figure 17 – Mounting support of specimens	84
Figure 18 – Mounting block for a flush type LSE	85
Figure 19 – Example of mounting support of a panel board type LSE	86
Figure 20 – Example of mounting support for a rear fixed LSE	87
Figure 21 – Gauge (thickness: about 2 mm) for the verification of the outline of covers, cover-plates or actuating members	90
Figure 22 – Example of application of the gauge of Figure 21 on covers fixed without screws on a mounting surface or supporting surface	91
Figure 23 – Examples of applications of the gauge of Figure 21	92
Figure 24 – Gauge for verification of grooves, holes and reverse tapers	93
Figure 25 – Sketch showing the direction of application of the gauge of Figure 24	93
Figure 26 – Application of forces on a rail-mounted LSE	94
Figure 27 – Ball-pressure test apparatus	95
Figure 28 – Thread-cutting screw	96
Figure 29 – Thread-forming screw	96
Figure 30 – Diagrammatic representation	102
Figure 31 – Typical diagram for all coordination tests	110
Figure 32 – Detail of impedances Z and Z <sub>1</sub>	110
Figure C.1 – Example 1	125
Figure C.2 – Example 2	
Figure C.3 – Example 3	
Figure C.4 – Example 4	
Figure C.5 – Example 5	
Figure C.6 – Example 6	
Figure C.7 – Example 7	127
Figure D.1 – Test arrangement	129
Figure D.2 – Grid	
Figure D.3 – Grid circuit	130
Table 1 – Cross-sectional areas (S) of test copper conductors corresponding to the rated currents	26
Table 2 – Rated impulse voltage as a function of the nominal voltage of the installation	
Table 3 – Rated impulse voltage as a function of the nominal voltage of the installation  Table 3 – Load-shedding classes	
Table 4 – Disconnecting time	
Table 5 – Load-shedding classes	
Table 6 – Disconnecting time	
Table 7 – Load-shedding functional categories	
Table 9 Marking and position of marking	35

Table 9 – Relationship between rated currents and connectable cross-sectional areas of copper conductors	39
Table 10 – Dimensions and tightening torque of pillar terminals	42
Table 11 – Dimensions and tightening torque for screw and stud terminals	44
Table 12 – Dimensions and tightening torque for saddle terminals	
Table 13 – Dimensions and tightening torque for lug terminals	45
Table 14 – Tightening torque for the verification of the mechanical strength of screw-type terminals	
Table 15 – Test values for pulling out test	48
Table 16 – Relationship between rated currents and connectable cross-sectional areas of copper conductors for screwless terminals	51
Table 17 – Test values for flexion and pull out for copper conductors	53
Table 18 – Test current for the verification of electrical and thermal stresses in normal use of screwless terminals	55
Table 19 – Cross-sectional areas of rigid copper conductors for deflection test of screwless terminals	58
Table 20 – Deflection test forces	58
Table 21 – Forces to be applied to covers, cover-plates or actuating members whose fixing is not dependent on screws	63
Table 22 – Test voltage, points of application and minimum values of insulating resistance for the verification of dielectric strength	69
Table 23 – Test voltages of auxiliary circuits	71
Table 24 – Test voltage for verification of impulse withstand voltage	72
Table 25 – Temperature-rise test currents and cross-sectional areas of copper conductors	73
Table 26 – Permissible temperature rise values (based on Table 3 of IEC 60065:2001)	75
Table 27 – Number of operations for normal operation test	80
Table 28 – Height of fall for impact test	88
Table 29 – Minimum clearances and creepage distances	
Table 30 – Immunity tests (overview)	104
Table 31 – Voltage dip and short-interruption test values	105
Table 32 – Surge immunity test voltages	106
Table 33 – Fast transient test values	106
Table 34 – Minimum values of $I^2t$ and $I_{p}$	111
Table 35 – Power factors for short-circuit tests	112
Table 36 – Capacitors	
Table A.1 – Specimen for tests	122
Table B.1 – Correspondence between ISO and AWG copper conductors	123

### INTERNATIONAL ELECTROTECHNICAL COMMISSION

# PARTICULAR REQUIREMENTS FOR LOAD-SHEDDING EQUIPMENT (LSE)

### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62962 has been prepared by subcommittee 23K: Electrical energy efficiency products, of IEC technical committee 23: Electrical accessories.

The text of this standard is based on the following documents:

FDIS	Report on voting
23K/47/FDIS	23K/48/RVD

Full information on the voting for the approval of this document can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

In this document, the following print types are used:

conformity statements: in italic type.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT - The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer. is a preview senerated of the

### INTRODUCTION

The optimization of electrical energy usage can be facilitated by appropriate design and installation considerations. An electrical installation can provide the required level of service and safety for the lowest electrical consumption.

This is considered by designers as a general requirement of their design procedures to establish the best use of electrical energy.

The optimization of the use of electricity is based on energy efficiency management which is based on the price of electricity, electrical consumption and real-time adaptation, as described in Figure 1 according to IEC 60364-8-1:2019.




Figure 1 - Energy efficiency management system

This document applies to load-shedding equipment (LSE), for household and similar uses.

The LSE is an equipment able to respond to the monitored current or power, or alternative monitored parameters to switch ON and OFF selected loads when certain conditions are met.

The load-shedding function is used in energy management systems to optimize the overall use of electrical energy including production and storage, and can be used for example for energy efficiency purposes as per IEC 60364-8-1:2019.

## PARTICULAR REQUIREMENTS FOR LOAD-SHEDDING EQUIPMENT (LSE)

#### 1 Scope

The purpose of this document is to provide requirements for equipment to be used in energy efficiency systems. This document covers load-shedding equipment (LSE).

Guidelines relating to safety for LSE as given in IEC Guide 110 have been followed.

This document applies to load-shedding equipment for household and similar uses. The load-shedding function is used in energy management systems to optimize the overall use of electrical energy including production and storage. Load-shedding can be used for example for energy efficiency purposes as per IEC 60364-8-1:2019.

This document applies to LSE for operation under normal conditions:

- AC circuits with a rated frequency of 50 Hz, 60 Hz or both, with a rated voltage not exceeding 440 V (between phases), a rated current not exceeding 125 A and a rated short-circuit capacity not exceeding 25 000 A; or
- DC circuits<sup>1</sup>.

LSEs are intended to control the energy supplied to one or more load, circuit or mesh when:

- defined conditions of time and current are reached;
- a command or information from an external system is received.

An LSE is intended to serve as:

- a single equipment having all the necessary means able to control the loads (e.g. the electrical energy management function is embedded in such an equipment); or
- a unit integrated into a more complex equipment or an independent equipment being part of an electrical energy management system (EEMS); or
- an assembly of independent equipment forming an LSE (e.g. an LSE with external current sensors); or
- as a combination of the above points.

LSE can have a wireless interface.

LSE is part of the fixed installation.

NOTE 1 This document covers load shedding equipment in the fixed installations including portable appliances connected thereto.

LSE are intended for use in circuits with protection against electrical shock and over-current according to IEC 60364 (all parts).

NOTE 2 For example, fault protection (indirect contact protection) can be covered as follows:

- in TT systems, by an upstream RCBOs or RCCBs according to IEC 61008-1 and IEC 61009-1;

<sup>1</sup> LSE for DC circuits are under consideration.