MASINATE OHUTUS, KAHEKÄEJUHTIMISSEADISED. PROJEKTEERIMISE JA VALIKU PÕHIMÕTTED

Safety of machinery - Two-hand control devices - Principles for design and selection (ISO 13851:2019)



## EESTI STANDARDI EESSÕNA

### NATIONAL FOREWORD

See Eesti standard EVS-EN ISO 13851:2019 sisaldab Euroopa standardi EN ISO 13851:2019 ingliskeelset teksti.

This Estonian standard EVS-EN ISO 13851:2019 consists of the English text of the European standard EN ISO 13851:2019.

Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.

This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation and Accreditation.

Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 17.04.2019.

Date of Availability of the European standard is 17.04.2019.

Standard on kättesaadav Eesti Standardimis-ja Akrediteerimiskeskusest.

The standard is available from the Estonian Centre for Standardisation and Accreditation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile <u>standardiosakond@evs.ee</u>.

#### ICS 13.110

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardimis- ja Akrediteerimiskeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardimis-ja Akrediteerimiskeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardimis-ja Akrediteerimiskeskusega: Koduleht <a href="https://www.evs.ee">www.evs.ee</a>; telefon 605 5050; e-post <a href="mailto:info@evs.ee">info@evs.ee</a>

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation and Accreditation No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation and Accreditation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation and Accreditation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

# EUROPEAN STANDARD NORME EUROPÉENNE

# **EN ISO 13851**

EUROPÄISCHE NORM

April 2019

ICS 13.110

Supersedes EN 574:1996+A1:2008

### **English Version**

# Safety of machinery - Two-hand control devices - Principles for design and selection (ISO 13851:2019)

Sécurité des machines - Dispositifs de commande bimanuelle - Principes de conception et de choix (ISO 13851:2019) Sicherheit von Maschinen - Zweihandschaltungen - Funktionelle Aspekte und Gestaltungsleitsätze (ISO 13851:2019)

This European Standard was approved by CEN on 28 February 2019.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

# **European foreword**

This document (EN ISO 13851:2019) has been prepared by Technical Committee ISO/TC 199 "Safety of machinery" in collaboration with Technical Committee CEN/TC 114 "Safety of machinery" the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2019, and conflicting national standards shall be withdrawn at the latest by October 2019.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 574:1996+A1:2008.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For the relationship with EU Directive(s) see informative Annex ZA, which is an integral part of this document.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

#### **Endorsement notice**

The text of ISO 13851:2019 has been approved by CEN as EN ISO 13851:2019 without any modification.

Contents			Page
Fore	word		v
Intro	oductio	on	vi
1	Scon	e	1
2		native references	
3		ns and definitions	
4		D selection and THCD types	3
	4.1 4.2	SelectionTypes of THCD	
5		uirements for the design of two-hand control devices	
	5.1 5.2	General	
	5.2	Relationship between actuation by hand and output signal(s)	
	5.4	Cessation of the output signal	5
	5.5	Prevention of accidental operation	5
	5.6	Prevention of defeat	
	5.7	Re-initiation of the output signal	5
	5.8	Synchronous actuation	5
6	Two	hand control safety functions	6
	6.1	Prevention of unexpected start-up	6
	6.2	Releasing of actuators	6
	6.3	Synchronous actuation	6
7	Prevention of accidental actuation and of defeat		
	7.1	Common considerations	6
	7.2	Prevention of defeat using one hand	7
	7.3	Prevention of defeat using the hand and elbow of the same arm	7
	7.4 7.5	Prevention of defeat using the forearm(s) or elbow(s)	7
	7.5 7.6	Prevention of defeat using one hand and any other part of the body	 Ω
	7.7	Accidental actuation	8
0		eral requirements	
8	<b>Gene</b> 8.1	Ergonomic requirements	 Ω
	8.2	Operating conditions and environmental influences	 8
	8.3	Enclosures	9
	8.4	Selection, design and installation of control actuating devices	
	8.5	Prevention of unintended output signals by acceleration forces	9
	8.6	Unintended operation of hand-held machines	9
	8.7	Relocatable THCDs	10
	8.8	Safety distance	
9	Verification and validation		11
	9.1	General requirements for verification and validation	11
	9.2	Visual inspection	
	9.3 9.4	Performance test	
	9.4	MeasurementPrevention of defeat	
4.0			
10		king	
11		rmation for installation, use and maintenance	
	11.1	Information for use	
	11.2	Installation instructions	
	11.3	Operating instructions	14 11

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

This document was prepared by Technical Committee ISO/TC 199, Safety of machinery.

This second edition cancels and replaces the first edition (ISO 13851:2002), which has been technically revised.

The main change compared to the previous edition is the adaptation of the safety-related parts of the control system from the categories to the Performance Level (PL) (according to ISO 13849-1) or SIL with the allocated HTF (according to IEC 62061).

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org/members.html">www.iso.org/members.html</a>.

# Introduction

The structure of safety standards in the field of machinery is as follows:

- a) **type-A standards** (basic safety standards) giving basic concepts, principles for design and general aspects that can be applied to all machinery;
- b) **type-B standards** (generic safety standards) dealing with one safety aspect or one or more type(s) of safeguard that can be used across a wide range of machinery:
  - type-B1 standards on particular safety aspects (e.g. safety distances, surface temperature, noise);
  - type-B2 standards on safeguards (e.g. two-hand controls, interlocking devices, pressure sensitive devices, guards);
- c) **type-C standards** (machine safety standards) dealing with detailed safety requirements for a particular machine or group of machines.

This document is a type-B2 standard as stated in ISO 12100.

This document is of relevance, in particular, for the following stakeholder groups representing the market players with regard to machinery safety:

- machine manufacturers (small, medium and large enterprises);
- health and safety bodies (regulators, accident prevention organizations, market surveillance etc.).

Others can be affected by the level of machinery safety achieved with the means of the document by the above-mentioned stakeholder groups:

- machine users/employers (small, medium and large enterprises);
- machine users/employees (e.g. trade unions, organizations for people with special needs);
- service providers, e.g. for maintenance (small, medium and large enterprises);
- consumers (in case of machinery intended for use by consumers).

The above-mentioned stakeholder groups have been given the possibility to participate at the drafting process of this document.

In addition, this document is intended for standardization bodies elaborating type-C standards.

The requirements of this document can be supplemented or modified by a type-C standard.

For machines that are covered by the scope of a type-C standard and have been designed and built according to the requirements of that standard, the requirements of that type-C standard take precedence.

A two-hand control device (THCD) is a protective device. It provides protection for the operator against reaching danger zones during hazardous situations by locating the control actuating devices in a specific position and distance from the danger zone(s).

The selection of a THCD as an appropriate safety device depends upon the risk assessment made by designers, standard makers and others in accordance with ISO 12100.

The definition of a THCD is given in 3.1 and takes precedence over the definition given in ISO 12100.

In some arrangements, enabling devices (see ISO 12100) and/or hold-to-run devices (see ISO 12100) may comply with the definition of a THCD in this document. Additionally, some special control devices — such as some crane controls — require the use of two hands and can comply with the definition of a THCD in this document.

# Safety of machinery — Two-hand control devices — Principles for design and selection

# 1 Scope

This document specifies the safety requirements of a two-hand control device (THCD) and the dependency of the output signal from the actuation by hand of the control actuating devices.

This document describes the main characteristics of THCDs for the achievement of safety and sets out combinations of functional characteristics for three types. It does not apply to devices intended to be used as enabling devices, as hold-to-run devices or as special control devices.

This document does not specify with which machines THCDs shall be used. It also does not specify which types of two-hand-control device shall be used for a specific application. Moreover, while guidance is given, it does not specify the required distance between the THCD and the danger zone (see <u>8.8</u>).

This document provides requirements for design and guidance on the selection (based on a risk assessment) of THCDs including the prevention of defeat, the avoidance of faults and verification of compliance.

NOTE 1 A THCD only offers protection for the person using it.

NOTE 2 For specific machines, the suitability of a two-hand control as a suitable protective device can be defined in a type-C standard. If such a standard does not exist or is not appropriate, the risk assessment and determination of suitable protective measures is the responsibility of the manufacturer of the machine.

This document applies to all THCDs, independent of the energy used, including:

- THCDs which are fully assembled for installation;
- THCDs which are assembled by the machine manufacturer or integrator.

This document is not applicable to THCDs manufactured before the date of its publication.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 12100:2010, Safety of machinery — General principles for design — Risk assessment and risk reduction

ISO 13849-1:2015, Safety of machinery — Safety-related parts of control systems — Part 1: General principles for design

ISO 13849-2:2012, Safety of machinery — Safety-related parts of control systems — Part 2: Validation

ISO 13855:2010, Safety of machinery — Positioning of safeguards with respect to the approach speeds of parts of the human body

IEC 62061:2005+AMD1:2012+AMD2:2015, Safety of machinery — Functional safety of safety-related electrical, electronic and programmable electronic control systems

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12100 and the following apply.