



Edition 3.0 2018-01

INTERNATIONAL STANDARD

Cable networks for television signals, sound signals and interactive services – Part 2: Electromagnetic compatibility for equipment





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2018 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Tel.: +41 22 919 02 11 info@iec.ch

www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 21 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.



Edition 3.0 2018-01

INTERNATIONAL STANDARD

Cable networks for television signals, sound signals and interactive services – Part 2: Electromagnetic compatibility for equipment

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 33.160.99 ISBN 978-2-8322-5148-5

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

C	ONTENT	TS	2
F	OREWO	RD	5
ΙN	TRODU	ICTION	7
1	Scop	e	8
2		native references	
3		s, definitions, symbols and abbreviated terms	
Ŭ	3.1	Terms and definitions	
	3.2	Symbols	
	3.3	Abbreviated terms	
4		ods of measurements	
	4.1	General operating conditions	
	4.2	Disturbance voltages from equipment	
	4.2.1		10
		150 kHz to 30 MHz	18
	4.2.2	Disturbance voltages from equipment at the AC mains frequency and its harmonics	18
	4.2.3		
	4.3	Radiation from active equipment	
	4.3.1	General	19
	4.3.2	General measurement requirements	19
	4.3.3	Methods of measurements	20
	4.4	Immunity of active equipment	
	4.4.1		29
	4.4.2		
	4.4.3		
	4.4.4		
	4.5	Screening effectiveness of passive equipment	
	4.5.1		
	4.5.2		
	4.5.3	Methods of measurements Electrostatic discharge immunity test for active equipment	42
	4.6 4.6.1		44
	4.6.1		
	4.0.2	Electrical fast transient/burst immunity test for AC power ports	
	4.8	Methods of measurement for telecom signal ports of multimedia network	
	1.0	equipment	44
	4.9	Measurement of indoor receiving antennas for broadcast signals	44
	4.9.1	Indoor antennas with additional RF network input port	44
	4.9.2	Indoor antennas without additional RF network input port	45
5	Perfo	ormance requirements	
	5.1	General	45
	5.1.1	Emission performance requirements	45
	5.1.2	Immunity performance requirements	45
	5.2	Disturbance voltages from equipment	45
	5.2.1	9	
	5.2.2		
	5.3	Radiation	46

5.3.1 Radiation from active equipment	46
5.3.2 Local oscillator power at the outdoor unit input	46
5.4 Immunity of active equipment	47
5.4.1 External immunity to electromagnetic fields	47
5.4.2 Internal immunity	47
5.4.3 Immunity of outdoor units to image frequency signals	51
5.5 Screening effectiveness of passive equipment	52
5.6 Electrostatic discharge immunity test for active equipment	52
5.7 Electrical fast transient/burst immunity test for AC power ports	52
5.8 Performance requirements for telecom signal ports of multimedia network equipment	53
5.9 Applicability of EMC performance requirements and methods of measurement to different types of equipment	53
Bibliography	56
Figure 1 – Measurement set-up for radiation measurements in the frequency range 5 MHz to 30 MHz using the "coupling unit" method	21
Figure 2 – Absorbing clamp method (30 MHz to 1 000 MHz)	23
Figure 3 – Example of general measurement set-up	24
Figure 4 – Example of measurement set-up for measurements on the input port of active equipment	
Figure 5 – Measurement set-up for the "substitution" radiation method – First	
measurement step	27
Figure 6 – Measurement set-up for the "substitution" radiation method – Second measurement step	28
Figure 7 – Frequency allocation for out-of-band immunity measurement of active equipment in the frequency range ≤ 1 000 MHz	31
Figure 8 – Frequency allocation for out-of-band immunity measurement of active equipment in the frequency range ≥ 950 MHz	31
Figure 9 – Frequency allocation for in-band immunity measurement of active equipment in the frequency range ≤ 1 000 MHz	34
Figure 10 – Frequency allocation for in-band immunity measurement of active equipment in the frequency range ≥ 950 MHz	
Figure 11 – Measurement set-up for internal immunity test	37
Figure 12 – Levels of wanted and unwanted signals for the internal immunity of FSS receiving outdoor units	
Figure 13 – Levels of wanted and unwanted signals for the internal immunity of BSS receiving outdoor units	
Figure 14 – Levels of unwanted signals for the internal immunity of active equipment in Band I (47 MHz to 68 MHz)	
Figure 15 – Levels of unwanted signals for the internal immunity of active equipment in Band II (87,5 MHz to 108 MHz)	
Figure 17 – Levels of unwanted signals for the internal immunity of active equipment in Band IV/V (470 MHz to 862 MHz)	O'
Table 1 – Port structure of different network equipment	9
Table 2 – Limits of mains terminal disturbance voltage	
- · - · - · · · · · · · · · · · · · · ·	

to receiving antennasto receiving antennas	46
Table 4 – Limits of input terminal disturbance voltages for equipment directly connected to satellite outdoor units	
Table 5 – Limits of radiated disturbance power	46
Table 6 – Limit of local oscillator terminal power	47
Table 7 – Limits of out-of-band immunity	47
Table 8 – Limits of in-band immunity	47
Table 9 – Test specification for internal immunity	48
Table 10 – Limits of immunity to image frequency signals in terms of image suppression ratio	51
Table 11 – Limits of screening effectiveness of passive equipment within the nominal frequency ranges	52
Table 12 – Test specifications for electrostatic discharge immunity test for active equipment	52
Table 13 – Test specifications for electrical fast transient/burst immunity test	53
Table 14 – Port types and environmental conditions for EMC performance requirements and methods of measurement	
Table 15– Emission parameters	54
Table 10 – Illilliumity and screening effectiveness parameters	

INTERNATIONAL ELECTROTECHNICAL COMMISSION

CABLE NETWORKS FOR TELEVISION SIGNALS, SOUND SIGNALS AND INTERACTIVE SERVICES –

Part 2: Electromagnetic compatibility for equipment

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This International Standard IEC 60728-2 has been prepared by technical area 5: Cable networks for television signals, sound signals and interactive services, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This third edition cancels and replaces the second edition published in 2010. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) Frequency extensions

- 1) The upper frequency limit of conventional cable network equipment was extended from 862 MHz to 1 000 MHz due to market demands.
- 2) The first intermediate frequency range (1st IF range) for satellite signal transmission was extended to cover now frequencies from 950 MHz up to 3 500 MHz.

- 3) The methods of measurement and the EMC requirements in the overlapping frequency range from 950 MHz to 1 000 MHz were allocated in relation to the upper frequency limit, 1 000 MHz, and the lower frequency limit, 950 MHz, of the relevant equipment under test.
- b) New EMC environment in the 800 MHz band
 - 1) The European Commission has requested CENELEC and ETSI to draft immunity requirements for equipment, to protect against disturbance from the new wireless service in the 790 MHz to 862 MHz band.
 - NOTE. The lower frequency has been reconsidered in this document, as new frequency bands are allocated for wireless services starting from 694 MHz.
 - 2) A CENELEC/ETSI Joint Working Group "Digital Dividend" was formed to describe the new EMC environment and to advise on appropriate test methods and limits.
 - 3) IEC 60728-2 is the document specifying immunity requirements for active and passive cable network equipment.
 - 4) The method of measurement and the requirements for in-band immunity were extended taking into account this new EMC environment due to the allocation of broadband wireless services in the frequency band 694 MHz to 862 MHz. As a consequence, the limits of in-band immunity were specified for analogue and additionally for digital signals in this frequency range.
 - 5) Consequently it is recommended, that, where cable networks and wireless networks coexist, only the transmission of digitally modulated signals should be used in the frequency range 694 MHz to 862 MHz.
 - 6) For passive equipment, Class A and Class B specifications were kept in the standard but a note was added recommending that only Class A equipment should be used in the planning and implementation of new networks.
- c) Indoor antennas
 - 1) The methods of measurement for all kinds of indoor antennas were combined in the new 4.9.
- d) Bibliography
 - 1) A Bibliography has been added at the end of the document referencing, for example, CEPT Report 30 on "The identification of common and minimal (least restrictive) technical conditions for 790-862 MHz for the digital dividend in the European Union".

The text of this International Standard is based on the following documents:

CDV	Report on voting
100/2715/CDV	100/2859A/RVC

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

Standards and deliverables of the IEC 60728 series deal with cable networks including equipment and associated methods of measurement for headend reception, processing and distribution of television and sound signals and for processing, interfacing and transmitting all kinds of data signals for interactive services using all applicable transmission media. These signals are typically transmitted in networks by frequency-multiplexing techniques.

This includes, for instance:

- · regional and local broadband cable networks,
- extended satellite and terrestrial television distribution systems,
- · individual satellite and terrestrial television receiving systems,

and all kinds of equipment, systems and installations used in such cable networks, distribution and receiving systems.

The extent of this standardization work is from the antennas and/or special interfaces to the headend or other interface points to the network up to any terminal interface of the customer premises equipment.

The standardization work will consider coexistence with users of the RF spectrum in wired and wireless transmission systems.

The standardization of any user terminals (i.e. tuners, receivers, decoders, multimedia terminals, etc.) as well as of any coaxial, balanced and optical cables and accessories thereof is excluded.

CABLE NETWORKS FOR TELEVISION SIGNALS, SOUND SIGNALS AND INTERACTIVE SERVICES –

Part 2: Electromagnetic compatibility for equipment

1 Scope

This part of IEC 60728:

- applies to the radiation characteristics and immunity to electromagnetic disturbance of EM-active equipment (active and passive equipment) for the reception, processing and distribution of television, sound and interactive multimedia signals as dealt with in the following parts of IEC 60728 series:
 - IEC 60728-3, Active wideband equipment for cable networks;
 - IEC 60728-4, Passive wideband equipment for coaxial cable networks;
 - IEC 60728-5, Headend equipment;
 - IEC 60728-6, Optical equipment;
- covers the following frequency ranges:

disturbance voltage injected into the mains

150 kHz to 30 MHz;
radiation from active equipment

5 MHz to 25 GHz;
immunity of active equipment

150 kHz to 25 GHz ¹⁾;

screening effectiveness of passive equipment 5 MHz to 3,5 GHz (25 GHz) ²⁾;

- specifies requirements for maximum allowed radiation, minimum immunity and minimum screening effectiveness;
- · describes test methods for conformance testing.

No measurement needs to be performed at frequencies where no requirement is specified.

Due to the fact that cable networks, the former cabled distribution systems for television and sound signals, are more and more used for interactive services, these networks also incorporate equipment that carries, besides the cable network equipment ports, also one or more telecom signal port(s). This equipment is called "multimedia network equipment".

The EMC behaviour of cable network equipment, telecommunication network equipment and multimedia network equipment can be described by the port structure given in Table 1:

¹⁾ For "inband immunity of active equipment" and "out-of-band immunity of active equipment", no requirements apply at present for the frequency range 3,5 GHz to 25 GHz. Methods of measurement and limits are investigated for inclusion in a future amendment or revised edition.

²⁾ For "screening effectiveness of passive equipment", no requirements apply at present for the frequency range 3,5 GHz to 25 GHz. Methods of measurement and limits are being investigated for inclusion in a future amendment or revised edition.

Cable Telecommunication Multimedia Port name network equipment network equipment network equipment Enclosure Χ Earth Χ Χ Х AC/DC power supply Х Х Control (e.g. alarm) Χ Χ Х Χ Χ Antenna input port RF network port Х Χ Χ Х Telecom signal port

Table 1 - Port structure of different network equipment

Table 1 shows that cable network equipment and telecommunication network equipment have four common ports and, respectively, two and one individual ports. Multimedia network equipment carry, besides the common ports, an antenna input port and/or a RF network port as well as a telecom signal port.

The electromagnetic compatibility requirements for "telecommunication network equipment only" are standardized in ETSI EN 300 386 (mainly) and in ETSI EN 301 489-4, those for "cable network equipment only" are given in this document.

Equipment for multimedia networks of the above-mentioned type has to work under the same EMC conditions as equipment that is falling under the cable network and the telecommunication network EMC-standards. Due to the fact that this equipment has to work in close proximity, e.g. in the same operating room, the EMC environmental conditions for all three types of equipment are the same.

This means that multimedia network equipment has to fulfil the EMC requirements of one of the above mentioned standards and in addition the EMC requirements, laid down in the other EMC standard, for the additional port, by which it is connected to the other network.

By this procedure, it is ensured that multimedia network equipment fulfils the EMC conditions of one of the above-mentioned networks and will neither disturb the respective other system nor will be disturbed by the respective other system via the connecting port.

Coaxial cables for cable networks do not fall under the scope of this standard; reference is made to the EN 50117 series. Coaxial cable assemblies for radio and TV receivers (receiver leads) do not fall under the scope of this standard; reference is made to the IEC 60966 series. Requirements for the electromagnetic compatibility of receiver leads are laid down in IEC 60966-2-4, IEC 60966-2-5 and IEC 60966-2-6.

This document also covers indoor receiving antennas for broadcast signals for which the requirements and the applicable methods of measurement are limited to the emission and the electrostatic discharge phenomena.

Standardization in the field of "Electromagnetic compatibility" for any broadcast terminals (e.g. tuners, receivers, decoders, etc.) is covered by CISPR 13 and CISPR 16 and for multimedia terminals by CISPR 22 and CISPR 24.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

CISPR 13, Sound and television broadcast receivers and associated equipment – Radio disturbance characteristics – Limits and methods of measurement

CISPR 16-1-1, Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus

IEC 60728-3:2010, Cable networks for television signals, sound signals and interactive services – Part 3: Active wideband equipment for cable networks

IEC 61000-3-2, Electromagnetic compatibility (EMC) – Part 3-2: Limits – Limits for harmonic current emissions (equipment input current ≤ 16 A per phase)

IEC 61000-4-2, Electromagnetic compatibility (EMC) – Part 4-2: Testing and measurement techniques – Electrostatic discharge immunity test

IEC 61000-4-3, Electromagnetic compatibility (EMC) – Part 4-3: Testing and measurement techniques – Radiated, radio-frequency, electromagnetic field immunity test

IEC 61000-4-4, Electromagnetic compatibility (EMC) – Part 4-4: Testing and measurement techniques – Electrical fast transient/burst immunity test

IEC 61000-4-6, Electromagnetic compatibility (EMC) – Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields

IEC 61000-6-1:2016, Electromagnetic compatibility (EMC) – Part 6-1: Generic standards – Immunity for residential, commercial and light-industrial environments

IEC 61079-1:1992, Methods of measurement on receivers for satellite broadcast transmissions in the 12 GHz band – Part 1: Radiofrequency measurements on outdoor units

ETSI EN 300 386 V1.5.1, Electromagnetic compatibility and Radio spectrum Matters (ERM); Telecommunication network equipment; ElectroMagnetic Compatibility (EMC) requirements

IEC 60050-161:1990, International Electrotechnical Vocabulary (IEV), Chapter 161: Electromagnetic compatibility

IEC 60050-161:1990/AMD1:1997 IEC 60050-161:1990/AMD2:1998

3 Terms, definitions, symbols and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-161:1990 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

IEC Electropedia: available at http://www.electropedia.org/