

**Televisioonisignaaside, helisignaaside ja interaktiivsete teenuste kaabelvõrgud Osa 3: Aktiivsed lairiba seadmed kaabelvõrkudele**

Cable networks for television signals, sound signals and interactive services -- Part 3: Active wideband equipment for cable networks

## EESTI STANDARDI EESSÕNA

## NATIONAL FOREWORD

Käesolev Eesti standard EVS-EN 60728-3:2011 sisaldab Euroopa standardi EN 60728-3:2011 ingliskeelset teksti.

Standard on kinnitatud Eesti Standardikeskuse 31.03.2011 käskkirjaga ja jõustub sellekohase teate avaldamisel EVS Teatajas.

Euroopa standardimisorganisatsioonide poolt rahvuslikele liikmetele Euroopa standardi teksti kättesaadavaks tegemise kuupäev on 25.02.2011.

Standard on kättesaadav Eesti standardiorganisatsioonist.

This Estonian standard EVS-EN 60728-3:2011 consists of the English text of the European standard EN 60728-3:2011.

This standard is ratified with the order of Estonian Centre for Standardisation dated 31.03.2011 and is endorsed with the notification published in the official bulletin of the Estonian national standardisation organisation.

Date of Availability of the European standard text 25.02.2011.

The standard is available from Estonian standardisation organisation.

ICS 33.060.40, 33.170

### Standardite reprodutseerimis- ja levitamiseõigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonilisse süsteemi või edastamine ükskõik millises vormis või millisel teel on keelatud ilma Eesti Standardikeskuse poolt antud kirjaliku loata.

Kui Teil on küsimusi standardite autorikaitse kohta, palun võtke ühendust Eesti Standardikeskusega:  
Aru 10 Tallinn 10317 Eesti; [www.evs.ee](http://www.evs.ee); Telefon: 605 5050; E-post: [info@evs.ee](mailto:info@evs.ee)

### Right to reproduce and distribute belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without permission in writing from Estonian Centre for Standardisation.

If you have any questions about standards copyright, please contact Estonian Centre for Standardisation:  
Aru str 10 Tallinn 10317 Estonia; [www.evs.ee](http://www.evs.ee); Phone: 605 5050; E-mail: [info@evs.ee](mailto:info@evs.ee)

English version

**Cable networks for television signals, sound signals and interactive services -**

**Part 3: Active wideband equipment for cable networks**  
(IEC 60728-3:2010)

Réseaux de distribution par câbles pour signaux de télévision, signaux de radiodiffusion sonore et services interactifs -  
Partie 3: Matériel actif à large bande pour réseaux de distribution par câbles  
(CEI 60728-3:2010)

Kabelnetze für Fernsehsignale, Tonsignale und interaktive Dienste -  
Teil 3: Aktive Breitbandgeräte für koaxiale Kabelnetze  
(IEC 60728-3:2010)

This European Standard was approved by CENELEC on 2011-01-13. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

**CENELEC**

European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**Management Centre: Avenue Marnix 17, B - 1000 Brussels**

## Foreword

The text of document 100/1746/FDIS, future edition 4 of IEC 60728-3, prepared by Technical Area 5, Cable networks for television signals, sound signals and interactive services, of IEC TC 100, Audio, video and multimedia systems and equipment, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 60728-3 on 2011-01-13.

This European Standard supersedes EN 60728-3:2006.

EN 60728-3:2011 includes the following significant technical changes with respect to EN 60728-3:2006:

- extension of upper frequency range limit for cable network equipment from 862 MHz to 1 000 MHz;
- method of measurement and requirements for immunity to surge voltages;
- extension of scope to equipment using symmetrical ports;
- additional normative references;
- additional terms and definitions and abbreviations.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN and CENELEC shall not be held responsible for identifying any or all such patent rights.

The following dates were fixed:

- |  |       |            |
|--|-------|------------|
| – latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement | (dop) | 2011-10-13 |
| – latest date by which the national standards conflicting with the EN have to be withdrawn   | (dow) | 2014-01-13 |

Annex ZA has been added by CENELEC.

---

## Endorsement notice

The text of the International Standard IEC 60728-3:2010 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60728-6:2003	NOTE Harmonized as EN 60728-6:2003 (not modified).
IEC 60728-10	NOTE Harmonized as EN 60728-10.
IEC 61169-2	NOTE Harmonized as EN 61169-2.
IEC 61169-24	NOTE Harmonized as EN 61169-24.

---

## Annex ZA (normative)

### Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60065	-	Audio, video and similar electronic apparatus - Safety requirements	EN 60065	-
IEC 60068-1	1988	Environmental testing - Part 1: General and guidance	EN 60068-1	1994
IEC 60068-2-1	-	Environmental testing - Part 2-1: Tests - Test A: Cold	EN 60068-2-1	-
IEC 60068-2-2	-	Environmental testing - Part 2-2: Tests - Test B: Dry heat	EN 60068-2-2	-
IEC 60068-2-6	-	Environmental testing - Part 2-6: Tests - Test Fc: Vibration (sinusoidal)	EN 60068-2-6	-
IEC 60068-2-14	-	Environmental testing - Part 2-14: Tests - Test N: Change of temperature	EN 60068-2-14	-
IEC 60068-2-27	-	Environmental testing - Part 2-27: Tests - Test Ea and guidance: Shock	EN 60068-2-27	-
IEC 60068-2-29	-	Environmental testing - Part 2: Tests - Test Eb and guidance: Bump	EN 60068-2-29	-
IEC 60068-2-30	-	Environmental testing - Part 2-30: Tests - Test Db: Damp heat, cyclic (12 h + 12 h cycle)	EN 60068-2-30	-
IEC 60068-2-31	-	Environmental testing - Part 2-31: Tests - Test Ec: Rough handling shocks, primarily for equipment-type specimens	EN 60068-2-31	-
IEC 60068-2-32	-	Environmental testing. Part 2-32: Tests. Test Ed: Free fall	EN 60068-2-32	-
IEC 60068-2-40	-	Basic environmental testing procedures - Part 2-40: Tests - Test Z/AM: Combined cold/low air pressure tests	EN 60068-2-40	-
IEC 60068-2-48	-	Environmental testing - Part 2-48: Tests - Guidance on the application of the tests of IEC 60068 to simulate the effects of storage	EN 60068-2-48	-
IEC 60529	-	Degrees of protection provided by enclosures - (IP Code)		-

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60728-1	-	Cable networks for television signals, sound signals and interactive services - Part 1: System performance of forward paths	EN 60728-1	-
IEC 60728-2	-	Cabled distribution systems for television and sound signals - Part 2: Electromagnetic compatibility for equipment	EN 50083-2	-
IEC 60728-4	-	Cable networks for television signals, sound signals and interactive services - Part 4: Passive wideband equipment for coaxial cable networks	EN 60728-4	-
IEC 60728-5	-	Cable networks for television signals, sound signals and interactive services - Part 5: Headend equipment	EN 60728-5	-
IEC 60728-11	-	Cable networks for television signals, sound signals and interactive services - Part 11: Safety	EN 60728-11	-
IEC 60950-1	-	Information technology equipment - Safety - Part 1: General requirements	EN 60950-1	-
IEC 61000-4-5	-	Electromagnetic compatibility (EMC) - Part 4-5: Testing and measurement techniques - Surge immunity test	EN 61000-4-5	-
IEC 61319-1	-	Interconnections of satellite receiving equipment - Part 1: Europe	EN 61319-1	-
IEC 61319-2	-	Interconnections of satellite receiving equipment - Part 2: Japan	-	-
ITU-T Recommendation G.117	-	Transmission aspects of unbalance about earth	-	-
ITU-T Recommendation O.9	-	Measuring arrangements to assess the degree of unbalance about earth	-	-

## CONTENTS

FOREWORD.....	6
INTRODUCTION.....	8
1 Scope.....	9
2 Normative references .....	9
3 Terms, definitions, symbols and abbreviations.....	11
3.1 Terms and definitions .....	11
3.2 Symbols .....	15
3.3 Abbreviations .....	16
4 Methods of measurement .....	17
4.1 General.....	17
4.2 Linear distortion .....	18
4.2.1 Return loss.....	18
4.2.2 Flatness .....	19
4.2.3 Chrominance/luminance delay inequality for PAL/SECAM only .....	19
4.3 Non-linear distortion .....	20
4.3.1 General .....	20
4.3.2 Types of measurements.....	20
4.3.3 Intermodulation.....	20
4.3.4 Composite triple beat.....	22
4.3.5 Composite second order beat.....	25
4.3.6 Composite crossmodulation.....	26
4.3.7 Method of measurement of non-linearity for pure digital channel load .....	29
4.3.8 Hum modulation of carrier.....	29
4.4 Automatic gain and slope control step response .....	33
4.4.1 Definitions .....	33
4.4.2 Equipment required .....	33
4.4.3 Connection of equipment.....	34
4.4.4 Measurement procedure .....	34
4.5 Noise figure.....	35
4.5.1 General .....	35
4.5.2 Equipment required .....	35
4.5.3 Connection of equipment.....	35
4.5.4 Measurement procedure .....	35
4.6 Crosstalk attenuation.....	36
4.6.1 Crosstalk attenuation for loop through ports.....	36
4.6.2 Crosstalk attenuation for output ports .....	36
4.7 Signal level for digitally modulated signals .....	38
4.8 Measurement of composite intermodulation noise ratio ( <i>CINR</i> ).....	38
4.8.1 General .....	38
4.8.2 Equipment required .....	38
4.8.3 Connection of equipment.....	39
4.8.4 Measurement procedure .....	40
4.8.5 Presentation of the results.....	40
4.9 Immunity to surge voltages.....	41
4.9.1 General .....	41
4.9.2 Equipment required .....	42

4.9.3	Connection of equipment .....	42
4.9.4	Measurement procedure .....	42
5	Equipment requirements .....	42
5.1	General requirements .....	42
5.2	Safety .....	43
5.3	Electromagnetic compatibility (EMC) .....	43
5.4	Frequency range .....	43
5.5	Impedance and return loss .....	43
5.6	Gain .....	44
5.6.1	Minimum and maximum gain .....	44
5.6.2	Gain control .....	44
5.6.3	Slope and slope control .....	44
5.7	Flatness .....	44
5.8	Test points .....	45
5.9	Group delay .....	45
5.9.1	Chrominance/luminance delay inequality .....	45
5.9.2	Chrominance/luminance delay inequality for other television standards and modulation systems .....	45
5.10	Noise figure .....	45
5.11	Non-linear distortion .....	45
5.11.1	General .....	45
5.11.2	Second order distortion .....	45
5.11.3	Third order distortion .....	45
5.11.4	Composite triple beat .....	46
5.11.5	Composite second order .....	46
5.11.6	Composite crossmodulation .....	46
5.11.7	Maximum operating level for pure digital channel load .....	46
5.12	Automatic gain and slope control .....	46
5.13	Hum modulation .....	46
5.14	Power supply .....	46
5.15	Environmental .....	47
5.15.1	General .....	47
5.15.2	Storage (simulated effects of) .....	47
5.15.3	Transportation .....	47
5.15.4	Installation or maintenance .....	47
5.15.5	Operation .....	47
5.15.6	Energy efficiency of equipment .....	47
5.16	Marking .....	47
5.16.1	Marking of equipment .....	47
5.16.2	Marking of ports .....	47
5.17	Mean operating time between failure (MTBF) .....	48
5.18	Requirements for multi-switches .....	48
5.18.1	Control signals for multi-switches .....	48
5.18.2	Amplitude frequency response flatness .....	48
5.18.3	Return loss .....	48
5.18.4	Through loss .....	48
5.18.5	Isolation .....	48
5.18.6	Crosstalk attenuation .....	48
5.18.7	Satellite IF to terrestrial signal isolation .....	48



5.19 Immunity to surge voltages .....	49
5.19.1 Degrees of testing levels .....	49
5.19.2 Recommendation of testing level degree .....	49
Annex A (informative) Derivation of non-linear distortion .....	50
Annex B (normative) Test carriers, levels and intermodulation products.....	52
Annex C (normative) Checks on test equipment.....	54
Annex D (informative) Test frequency plan for composite triple beat (CTB), composite second order (CSO) and crossmodulation (XM) measurement .....	55
Annex E (informative) Measurement errors which occur due to mismatched equipment .....	56
Annex F (informative) Examples of signals, methods of measurement and network design for return paths.....	57
Bibliography.....	64
Figure 1 – Maximum error $a$ for measurement of return loss using VSWR-bridge with directivity $D = 46$ dB and 26 dB test port return loss.....	18
Figure 2 – Measurement of return loss.....	19
Figure 3 – Basic arrangement of test equipment for evaluation of the ratio of signal to intermodulation product .....	21
Figure 4 – Connection of test equipment for the measurement of non-linear distortion by composite beat.....	24
Figure 5 – Connection of test equipment for the measurement of composite crossmodulation.....	28
Figure 6 – Carrier/hum ratio .....	30
Figure 7 – Test set-up for local-powered objects.....	31
Figure 8 – Test set-up for remote-powered objects .....	31
Figure 9 – Oscilloscope display.....	32
Figure 10 – Time constant $T_C$ .....	33
Figure 11 – Measurement of AGC step response .....	34
Figure 12 – Measurement of noise figure .....	35
Figure 13 – Measurement of crosstalk attenuation for loop through ports of multi-switches.....	37
Figure 14 – Characteristic of the noise filter .....	39
Figure 15 – Test setup for the non-linearity measurement.....	39
Figure 16 – Presentation of the result of $CINR$ .....	41
Figure 17 – Measurement set-up for surge immunity test .....	42
Figure B.1 – An example showing products formed when $2f_a > f_b$ .....	52
Figure B.2 – An example showing products formed when $2f_a < f_b$ .....	53
Figure B.3 – Products of the form $f_a \pm f_b \pm f_c$ .....	53
Figure E.1 – Error concerning return loss measurement.....	56
Figure E.2 – Maximum ripple .....	56
Figure F.1 – Spectrum of a QPSK-modulated signal .....	57
Figure F.2 – Measurement of non-linearity using wideband noise.....	59
Figure F.3 – Network used in the design example .....	60
Figure F.4 – A test result measured from a real 20 dB return amplifier .....	61
Figure F.5 – The $CINR$ curve of one amplifier is modified to represent the $CINR$ of the whole coaxial section of the network .....	62

Figure F.6 – The *CINR* of an optical link as a function of *OMI*, example.....63

Table 1 – Correction factors where the modulation used is other than 100 % .....26

Table 2 – Notch filter frequencies .....39

Table 3 – Return loss requirements for all equipment.....44

Table 4 – Parameters of surge voltages for different degrees of testing levels .....49

Table 5 – Recommendations for degree of testing levels .....49

Table D.1 – Frequency allocation plan .....55

Table F.1 – Application of methods of measurement in IEC 60728-3 for return path equipment.....58

Table F.2 – Application of methods of measurement in IEC 60728-6 for return path equipment.....58

This document is a preview generated by EVS

## INTRODUCTION

Standards of the IEC 60728 series deal with cable networks including equipment and associated methods of measurement for headend reception, processing and distribution of television signals, sound signals and their associated data signals and for processing, interfacing and transmitting all kinds of signals for interactive services using all applicable transmission media.

This includes

- CATV<sup>1</sup>-networks;
- MATV-networks and SMATV-networks;
- individual receiving networks;

and all kinds of equipment, systems and installations installed in such networks.

For active equipment with balanced RF signal ports this standard applies to those ports which carry RF broadband signals for services as described in the scope of this standard.

The extent of this standardization work is from the antennas and/or special signal source inputs to the headend or other interface points to the network up to the terminal input.

The standardization of any user terminals (i.e., tuners, receivers, decoders, multimedia terminals, etc.) as well as of any coaxial, balanced and optical cables and accessories thereof is excluded.

---

<sup>1</sup> This word encompasses the HFC (Hybrid Fibre Cable) networks used nowadays to provide telecommunications services, voice, data, audio and video both broadcast and narrowcast.

## **CABLE NETWORKS FOR TELEVISION SIGNALS, SOUND SIGNALS AND INTERACTIVE SERVICES –**

### **Part 3: Active wideband equipment for cable networks**

#### **1 Scope**

This part of IEC 60728 lays down the measuring methods, performance requirements and data publication requirements for active wideband equipment of cable networks for television signals, sound signals and interactive services.

This standard

- applies to all broadband amplifiers used in cable networks;
- covers the frequency range 5 MHz to 3 000 MHz;

NOTE The upper limit of 3 000 MHz is an example, but not a strict value. The frequency range, or ranges, over which the equipment is specified, should be published.

- applies to one-way and two-way equipment;
- lays down the basic methods of measurement of the operational characteristics of the active equipment in order to assess the performance of this equipment;
- identifies the performance specifications to be published by the manufacturers;
- states the minimum performance requirements of certain parameters.

Amplifiers are divided into the following two quality levels:

Grade 1: amplifiers typically intended to be cascaded;

Grade 2: amplifiers for use typically within an apartment block, or within a single residence, to feed a few outlets.

Practical experience has shown that these types meet most of the technical requirements necessary for supplying a minimum signal quality to the subscribers. This classification is not a requirement but is provided to users and manufacturers for information about minimum quality criteria of the material required to install networks of different sizes. The system operator has to select appropriate material to meet the minimum signal quality at the subscriber's outlet, and to optimise cost/performance, taking into account the size of the network and local circumstances.

All requirements and published data are understood as guaranteed values within the specified frequency range and in well-matched conditions.

#### **2 Normative references**

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60065, *Audio, video and similar electronic apparatus – Safety requirements*

IEC 60068-1:1998, *Environmental testing – Part 1: General and guidance*

IEC 60068-2-1, *Environmental testing – Part 2-1: Tests – Tests A: Cold*

- IEC 60068-2-2, *Environmental testing – Part 2-2: Tests – Tests B: Dry heat*
- IEC 60068-2-6, *Environmental testing – Part 2-6: Tests – Test Fc: Vibration (sinusoidal)*
- IEC 60068-2-14, *Environmental testing – Part 2-14: Tests – Test N: Change of temperature*
- IEC 60068-2-27, *Environmental testing – Part 2-27: Tests – Test Ea and guidance: Shock*
- IEC 60068-2-29, *Basic environmental testing procedures – Part 2-29: Tests – Test Eb and guidance: Bump*
- IEC 60068-2-30, *Environmental testing – Part 2-30: Tests – Test Db: Damp heat, cyclic (12 h + 12 h cycle)*
- IEC 60068-2-31, *Environmental testing – Part 2-31: Tests – Test Ec: Rough handling shocks, primarily for equipment-type specimens*
- IEC 60068-2-32, *Basic environmental testing procedures – Part 2-32: Tests – Test Ed: Free fall*
- IEC 60068-2-40, *Basic environmental testing procedures – Part 2-40: Tests – Test Z/AM: Combined cold/low air pressure tests*
- IEC 60068-2-48, *Basic environmental testing procedures – Part 2-48: Tests – Guidance on the application of the tests of IEC publication 60068 to simulate the effects of storage*
- IEC 60529, *Degrees of protection provided by enclosures (IP Code)*
- IEC 60728-1, *Cable networks for television signals, sound signals and interactive services – Part 1: System performance of forward paths*
- IEC 60728-2, *Cable networks for television signals, sound signals and interactive services – Part 2: Electromagnetic compatibility for equipment*
- IEC 60728-4, *Cable networks for television signals, sound signals and interactive services – Part 4: Passive wideband equipment for coaxial cable networks*
- IEC 60728-5, *Cable networks for television signals, sound signals and interactive services – Part 5: Headend equipment*
- IEC 60728-11, *Cable networks for television signals, sound signals and interactive services – Part 11: Safety*
- IEC 60950-1, *Information technology equipment – Safety – Part 1: General requirements*
- IEC 61000-4-5, *Electromagnetic compatibility (EMC) – Part 4-5: Testing and measurement techniques – Surge immunity test*
- IEC 61319-1, *Interconnections of satellite receiving equipment – Part 1: Europe*
- IEC 61319-2, *Interconnections of satellite receiving equipment – Part 2: Japan*
- ITU-T Recommendation G.117, *Transmission systems and media – Digital systems and networks – International telephone connections and circuits – General recommendations on the transmission quality for an entire international telephone connection – Transmission aspects of unbalance about earth*
- ITU-T Recommendation O.9, *Specifications of measuring equipment – General – Measuring arrangements to assess the degree of unbalance about earth*