

Soil quality - Leaching procedures for subsequent chemical and ecotoxicological testing of soil and soil-like materials - Part 1: Batch test using a liquid to solid ratio of 2 l/kg dry matter (ISO 21268-1:2019)

## EESTI STANDARDI EESSÕNA

## NATIONAL FOREWORD

See Eesti standard EVS-EN ISO 21268-1:2019 sisaldab Euroopa standardi EN ISO 21268-1:2019 ingliskeelset teksti.	This Estonian standard EVS-EN ISO 21268-1:2019 consists of the English text of the European standard EN ISO 21268-1:2019.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 16.10.2019.	Date of Availability of the European standard is 16.10.2019.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile [standardiosakond@evs.ee](mailto:standardiosakond@evs.ee).

ICS 13.080.05

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:

Koduleht [www.evs.ee](http://www.evs.ee); telefon 605 5050; e-post [info@evs.ee](mailto:info@evs.ee)

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage [www.evs.ee](http://www.evs.ee); phone +372 605 5050; e-mail [info@evs.ee](mailto:info@evs.ee)

English Version

Soil quality - Leaching procedures for subsequent chemical  
and ecotoxicological testing of soil and soil-like materials -  
Part 1: Batch test using a liquid to solid ratio of 2 l/kg dry  
matter (ISO 21268-1:2019)

Qualité du sol - Modes opératoires de lixiviation en vue  
d'essais chimiques et écotoxicologiques ultérieurs des  
sols et matériaux analogues au sol - Partie 1: Essai en  
bâchée avec un rapport liquide/solide de 2 l/kg de  
matière sèche (ISO 21268-1:2019)

Bodenbeschaffenheit - Elutionsverfahren für die  
anschließende chemische und ökotoxikologische  
Untersuchung von Boden und von Bodenmaterialien -  
Teil 1: Schüttelverfahren mit einem  
Flüssigkeits/Feststoffverhältnis von 2 l/kg  
Trockenmasse (ISO 21268-1:2019)

This European Standard was approved by CEN on 1 September 2019.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

## European foreword

This document (EN ISO 21268-1:2019) has been prepared by Technical Committee ISO/TC 190 "Soil quality" in collaboration with Technical Committee CEN/TC 444 "Test methods for environmental characterization of solid matrices" the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2020, and conflicting national standards shall be withdrawn at the latest by April 2020.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes CEN ISO/TS 21268-1:2009.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

## Endorsement notice

The text of ISO 21268-1:2019 has been approved by CEN as EN ISO 21268-1:2019 without any modification.

# Contents

Page

<b>Foreword</b>	<b>iv</b>
<b>Introduction</b>	<b>v</b>
<b>1 Scope</b>	<b>1</b>
<b>2 Normative references</b>	<b>1</b>
<b>3 Terms and definitions</b>	<b>2</b>
<b>4 Principle</b>	<b>3</b>
<b>5 Reagents</b>	<b>3</b>
<b>6 Apparatus</b>	<b>4</b>
<b>7 Sample pretreatment</b>	<b>5</b>
7.1 Preparation of laboratory sample and specification of particle size	5
7.2 Preparation of test sample	6
7.3 Determination of dry matter content and water content	6
7.4 Preparation of the test portion	7
<b>8 Procedure</b>	<b>7</b>
8.1 Temperature	7
8.2 Description of the procedure	7
8.2.1 Preparation of the eluent	7
8.2.2 Leaching step	7
8.2.3 Liquid/Solid separation step	8
8.3 Further preparation of the eluate for analysis	9
8.4 Blank test for the application of the leaching procedure	9
<b>9 Calculation</b>	<b>10</b>
<b>10 Test report</b>	<b>10</b>
<b>11 Analytical determination</b>	<b>11</b>
11.1 General	11
11.2 Blank test information	11
<b>12 Performance characteristics</b>	<b>11</b>
12.1 General	11
12.2 Validation results obtained for DIN 19529	11
12.2.1 General	11
12.2.2 Results for test material containing inorganic substances	12
12.2.3 Results for test materials containing organic substances	12
<b>Annex A (informative) Information on the influence on the test results of the parameters that affect leaching</b>	<b>20</b>
<b>Annex B (informative) Example of a specific liquid-solid separation procedure for soil samples (applying only to the leaching of inorganic substances)</b>	<b>23</b>
<b>Annex C (informative) Calculation of centrifugation duration depending on centrifugation speed and rotor dimensions</b>	<b>25</b>
<b>Bibliography</b>	<b>27</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 190, *Soil quality*, Subcommittee SC 7, *Impact assessment*.

This first edition of ISO 21268-1:2019 cancels and replaces the first edition (ISO/TS 21268-1:2007), which has been technically revised. The main changes compared to the previous edition are as follows:

- the maximum grain size has been changed to <2 mm as usual for soil;
- the demineralized water has been added as possible leachant;
- [7.1](#) and [7.2](#) have been renumbered and renamed to read [7.1](#) "Particle size" and [7.2](#) "Sample preparation";
- [12.1](#) "General" and [12.2](#) "Validation results obtained for DIN 19529" have been added;
- [A.3.6](#) "Special requirements for tests considering semi-volatile substances" has been added;
- a new informative [Annex C](#) "Calculation of centrifugation duration depending on centrifugation speed and rotor dimensions" has been added;
- references in [Clause 2](#) and the Bibliography have been updated.

A list of all parts in the ISO 21268 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

In various countries, tests have been developed to characterize and assess the substances which can be released from materials. The release of soluble substances upon contact with water is regarded as a main mechanism of release, which results in a potential risk to the environment during the use or disposal of materials. The intent of these tests is to identify the leaching properties of materials. The complexity of the leaching process makes simplifications necessary<sup>[1]</sup>.

Not all of the relevant aspects of leaching behaviour can be addressed in one standard (see description of influencing factors in [Annex A](#)).

Tests to characterize the behaviour of materials can generally be divided into three categories addressed in ISO 18772<sup>[2]</sup> and EN 12920<sup>[3]</sup>. The relationships between these tests are summarized below.

- a) “Basic characterization” tests are used to obtain information on the short- and long-term leaching behaviour and characteristic properties of materials. Liquid/solid ratios (L/S), leachant composition, factors controlling leachability, such as pH, redox potential, complexing capacity, role of dissolved organic carbon (DOC), ageing of material and physical parameters, are addressed in these defined tests.
- b) “Compliance” tests are used to determine whether the material complies with a specific behaviour or with specific reference values. These tests focus on key variables and leaching behaviour previously identified by basic characterisation tests.
- c) “On-site verification” tests are used as a rapid check to confirm that the material is the same as that which has been subjected to the compliance test(s). On-site verification tests are not necessarily leaching tests.

The test procedure described in this method belongs to category b): compliance tests.

This document was originally elaborated on the basis of EN 12457-1:2004<sup>[4]</sup>. Especially, modifications considering requirements on subsequent ecotoxicological testing and analysis of organic substances have been included. Validation results have been adopted from DIN 19529<sup>[5]</sup>.

# Soil quality — Leaching procedures for subsequent chemical and ecotoxicological testing of soil and soil-like materials —

## Part 1: Batch test using a liquid to solid ratio of 2 l/kg dry matter

### 1 Scope

This document specifies a test providing information on leaching of soil and soil-like materials under the experimental conditions specified hereafter, and particularly at a liquid to solid ratio of 2 l/kg dry matter.

The document has been developed to measure the release of inorganic and organic substances from soil and soil-like material as well as to produce eluates for subsequent ecotoxicological testing. For ecotoxicological testing, see ISO 15799<sup>[6]</sup> and ISO 17616<sup>[7]</sup>.

NOTE 1 Volatile organic substances include the low-molecular-weight substances in mixtures such as mineral oil.

NOTE 2 It is not always possible to optimise test conditions simultaneously for inorganic and organic substances and optimum test conditions can also vary between different groups of organic substances. Test requirements for organic substances are generally more stringent than those for inorganic substances. The test conditions suitable for measuring the release of organic substances will generally also be applicable to inorganic substances.

NOTE 3 Within the category of organic substances, a significant difference in behaviour exists between the more polar, relatively water-soluble compounds and apolar, hydrophobic organic substances (HOCs). In the latter case, mechanisms of release (e.g. particle-bound or dissolved organic carbon-bound) can be more crucial as well as sorption losses of soluble HOCs on different materials with which they come in contact (e.g. bottles, filters). The test and the results should be used for leaching of organic substances only with thorough consideration of the specific properties of the substances in question and the associated potential problems.

NOTE 4 For ecotoxicological testing, eluates representing the release of both inorganic and organic substances are needed. In this document, ecotoxicological testing is also meant to include genotoxicological testing.

This test method produces eluates, which can subsequently be characterized by physical, chemical and ecotoxicological methods in accordance with existing standard methods. The test is not suitable for substances that are volatile under ambient conditions.

This procedure is not applicable to materials with a dry-matter-content ratio lower than 33 %.

This test is mainly aimed at being used for routine and control purposes, and it cannot be used alone to describe all leaching properties of a soil. Additional leaching tests are needed for that extended goal. This document does not address issues related to health and safety. It only determines the leaching properties as outlined in [Clause 4](#).

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3696, *Water for analytical laboratory use — Specification and test methods*



ISO 5667-3, *Water quality — Sampling — Part 3: Preservation and handling of water samples*

ISO 7027-1, *Water quality -- Determination of turbidity — Part 1: Quantitative methods*

ISO 10523, *Water quality — Determination of pH*

ISO 11465, *Soil quality — Determination of dry matter and water content on a mass basis — Gravimetric method*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

#### 3.1 leaching test

test during which a material is put into contact with a *leachant* (3.2) under strictly defined conditions and some substances of the material are extracted

#### 3.2 leachant

liquid used in a *leaching test* (3.1)

Note 1 to entry: For the purpose of this document, the leachant is specified in 5.1.

#### 3.3 eluate

solution recovered from a *leaching test* (3.1)

Note 1 to entry: Eluate is also referred to as leachate.

#### 3.4 liquid to solid ratio L/S

ratio between the total volume of liquid (L in litres), which in this extraction is in contact with the soil sample, and the dry mass of the sample (S in kg of dry matter)

Note 1 to entry: L/S is expressed in l/kg.

#### 3.5 dry matter content

$w_{dm}$   
ratio, expressed in percent, between the mass of the dry residue, determined in accordance with ISO 11465, and the corresponding raw mass

#### 3.6 water content

$w_{H_2O}$   
ratio, expressed in percent, between the mass of water contained in the material as received and the corresponding dry residue of the material

Note 1 to entry: The basis for the calculation of the water content is the mass of the dry residue in this document, as specified in ISO 11465 (for the determination of the water content of soil).