

INTERNATIONAL
STANDARD

ISO
11126-7

First edition
1995-12-15

**Preparation of steel substrates before
application of paints and related products —
Specifications for non-metallic blast-cleaning
abrasives —**

Part 7:
Fused aluminium oxide

*Préparation des subjectiles d'acier avant application de peintures et de
produits assimilés — Spécifications pour abrasifs non métalliques destinés
à la préparation par projection —*

Partie 7: Oxyde d'aluminium fondu



Reference number
ISO 11126-7:1995(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 11126-7 was prepared by Technical Committee ISO/TC 35, *Paints and varnishes*, Subcommittee SC 12, *Preparation of steel substrates before application of paints and related products*.

ISO 11126 consists of the following parts, under the general title *Preparation of steel substrates before application of paints and related products* — *Specifications for non-metallic blast-cleaning abrasives*:

- *Part 1: General introduction and classification*
- *Part 3: Copper refinery slag*
- *Part 4: Coal furnace slag*
- *Part 5: Nickel refinery slag*
- *Part 6: Iron furnace slag*
- *Part 7: Fused aluminium oxide*
- *Part 8: Olivine sand*
- *Part 9: Staurolite*
- *Part 10: Garnet*

At the time of publication of this part of ISO 11126, parts 9 and 10 were in the course of preparation. Part 2 has been deleted.

Annex A of this part of ISO 11126 is given for information only.

© ISO 1995

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Preparation of steel substrates before application of paints and related products — Specifications for non-metallic blast-cleaning abrasives —

Part 7:

Fused aluminium oxide

WARNING — Equipment, materials and abrasives used for surface preparation can be hazardous if used carelessly. Many national regulations exist for those materials and abrasives that are considered to be hazardous during or after use (waste management), such as free silica or carcinogenic or toxic substances. These regulations are therefore to be observed. It is important to ensure that adequate instructions are given and that all required precautions are exercised

1 Scope

This part of ISO 11126 specifies requirements for fused aluminium oxide abrasives, as supplied for blast-cleaning processes. It specifies ranges of particle sizes and values for apparent density, bulk density, Mohs hardness, moisture content, conductivity of aqueous extract and water-soluble chlorides.

The requirements specified in this part of ISO 11126 apply to abrasives supplied in the “new” condition only. They do not apply to abrasives either during or after use.

Test methods for non-metallic blast-cleaning abrasives are given in the various parts of ISO 11127.

NOTES

1 Information on commonly referenced national and international standards is given in annex A.

2 Although this part of ISO 11126 has been developed specifically to meet requirements for preparation of steelwork, the properties specified will generally be appropriate for use when preparing other material surfaces, or components, using blast-cleaning techniques. These techniques are described in ISO 8504-2:1992, *Preparation of steel substrates before application of paints and related products — Surface preparation methods — Part 2: Abrasive blast-cleaning*.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 11126. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 11126 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 11127-1:1993, *Preparation of steel substrates before application of paints and related products — Test methods for non-metallic blast-cleaning abrasives — Part 1: Sampling*.

ISO 11127-2:1993, *Preparation of steel substrates before application of paints and related products — Test methods for non-metallic blast-cleaning abrasives — Part 2: Determination of particle size distribution*.

ISO 11127-3:1993, *Preparation of steel substrates before application of paints and related products — Test methods for non-metallic blast-cleaning abrasives — Part 3: Determination of apparent density*.

ISO 11127-4:1993, *Preparation of steel substrates before application of paints and related products — Test methods for non-metallic blast-cleaning abrasives*

— Part 4: Assessment of hardness by a glass slide test.

ISO 11127-5:1993, *Preparation of steel substrates before application of paints and related products — Test methods for non-metallic blast-cleaning abrasives — Part 5: Determination of moisture.*

ISO 11127-6:1993, *Preparation of steel substrates before application of paints and related products — Test methods for non-metallic blast-cleaning abrasives — Part 6: Determination of water-soluble contaminants by conductivity measurement.*

ISO 11127-7:1993, *Preparation of steel substrates before application of paints and related products — Test methods for non-metallic blast-cleaning abrasives — Part 7: Determination of water-soluble chlorides.*

3 Definition

For the purposes of this part of ISO 11126, the following definition applies.

3.1 fused aluminium oxide: A synthetic mineral blast-cleaning abrasive, which is classified as two types, A and WA.

Type A: This type is mainly composed of crystalline corundum which is brown in colour and consists of a solid solution containing a minimum of 94 % aluminium oxide and a maximum of 4 % titanium dioxide. Type A is produced by fusing bauxite with the appropriate quantity of titanium dioxide and reducing agent in an electric furnace, cooling the form lumps and then crushing and sieving to size.

Type WA: This type consists of crystalline corundum which is whitish in colour and contains at least 99 % aluminium oxide. It is produced by fusing, in an electric furnace, pure aluminium and is refined.

4 Designation of abrasives

Fused aluminium oxide abrasives shall be identified by "Abrasive ISO 11126" and the abbreviation N/FA-A or N/FA-WA indicating non-metallic, fused aluminium oxide abrasive, Type A or WA. This shall be followed, without spaces, by an oblique stroke and then the symbol G to indicate the required particle shape of the abrasive, when purchased, as grit.

The designation shall be completed by numbers denoting the particle size range, in millimetres, required (see table 1).

EXAMPLE 1

Abrasive ISO 11126 N/FA-A/G 0,5-1

denotes a non-metallic abrasive of fused aluminium oxide, type A, complying with the requirements of this part of ISO 11126, of initial particle shape grit and particle size range 0,5 mm to 1 mm.

It is essential that this full product designation is quoted on all orders.

5 Sampling

Sampling procedures shall be as specified in ISO 11127-1.

6 Requirements

6.1 General requirements

Fused aluminium oxide abrasives shall absorb no water but may be wetted on the surface only.

Fused aluminium oxide used as an abrasive shall contain no free silica. All silica shall be chemically bound or present in glass form within the corundum crystal matrix.

The material shall be free from corrosive and adhesion-impairing contaminants.

6.2 Particular requirements

Particular requirements for fused aluminium oxide abrasive shall be as specified in table 2.

7 Identification and marking

All materials shall be clearly marked or identified using the appropriate designation as specified in clause 4, either directly or by the accompanying delivery note.

8 Information to be supplied by the manufacturer or supplier

The manufacturer or supplier shall supply, if requested, a test report detailing results for any relevant property as determined by the appropriate method specified in table 2.