

TECHNICAL SPECIFICATION



Electrical insulating materials and systems – Electrical measurement of partial discharges (PD) under short rise time and repetitive voltage impulses



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2011 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

TECHNICAL SPECIFICATION



Electrical insulating materials and systems – Electrical measurement of partial discharges (PD) under short rise time and repetitive voltage impulses

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

ICS 17.220.99; 29.035.01; 29.080.30

ISBN 978-2-88912-479-4

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	7
4 Measurement of partial discharge pulses during repetitive, short rise-time voltage impulses and comparison with power frequency	9
4.1 Measurement frequency	9
4.2 Measurement quantities	9
4.3 Test objects.....	10
4.3.1 General	10
4.3.2 Inductive test objects.....	10
4.3.3 Capacitive test objects.....	10
4.3.4 Distributed impedance test objects	10
4.4 Impulse generators.....	10
4.4.1 General	10
4.4.2 Impulse waveforms.....	11
4.5 Effect of testing conditions	11
4.5.1 General	11
4.5.2 Effect of environmental factors	12
4.5.3 Effect of testing conditions and ageing	12
5 PD detection methods	12
5.1 General	12
5.2 PD pulse coupling and detection devices.....	12
5.2.1 Introductory remarks.....	12
5.2.2 Coupling capacitor with multipole filter.....	13
5.2.3 HFCT with multipole filter	14
5.2.4 Electromagnetic couplers	15
5.2.5 Charge measurements	16
5.3 Source-controlled gating techniques.....	17
6 Measuring instruments	17
7 Sensitivity check of the PD measuring equipment.....	17
7.1 General	17
7.2 Test diagram for sensitivity check.....	18
7.3 PD detection sensitivity check	18
7.4 Background noise check.....	19
7.5 Detection system noise check	19
7.6 Sensitivity report	19
8 Test procedure for increasing and decreasing the repetitive impulse voltage magnitude	19
9 Test report.....	20
Annex A (informative) Voltage impulse suppression required by the coupling device	22
Annex B (informative) PD pulses extracted from a supply voltage impulse through filtering techniques	24
Annex C (informative) Result of round-robin tests of RPDIV measurement.....	26
Annex D (informative) Examples of noise levels of practical PD detectors.....	28

Bibliography.....	29
Figure 1 – Coupling capacitor with multipole filter	13
Figure 2 – Example of voltage impulse and PD pulse frequency spectra before and after filtering	14
Figure 3 – HFCT between supply and test object with multipole filter	14
Figure 4 – HFCT between test object and earth with multipole filter	15
Figure 5 – Circuit using an electromagnetic coupler (for example an antenna) to suppress impulses from the test supply.....	15
Figure 6 – Circuit using an electromagnetic UHF antenna.....	15
Figure 7 – Example of waveforms of repetitive bipolar impulse voltage and charge accumulation for a twisted-pair sample	16
Figure 8 – Charge measurements	16
Figure 9 – Example of PD detection using electronic source-controlled gating (other PD coupling devices can be used)	17
Figure 10 – Test diagram for sensitivity check	18
Figure 11 – Example of relation between the outputs of LVPG and PD detector.....	19
Figure 12 – Example of increasing and decreasing the impulse voltage magnitude	20
Figure A.1 – Example of overlap between voltage impulse and PD pulse spectra (dotted area).....	22
Figure A.2 – Example of voltage impulse and PD pulse spectra after filtering	22
Figure A.3 – Example of impulse voltage damping as a function of impulse voltage magnitude and rise time.....	23
Figure B.1 – Power supply waveform and recorded signal using an antenna during supply voltage commutation.....	24
Figure B.2 – Signal detected by an antenna from the record of Figure B.1, using a filtering technique (400 MHz high-pass filter)	25
Figure B.3 – Characteristic of the filter used to pass from Figure B.1 to Figure B.2	25
Figure C.1 – The sequence of negative voltage impulses used for RRT	26
Figure C.2 – PD pulses (under) corresponding to voltage impulses (above).....	26
Figure C.3 – Dependence of normalized RPDIV on 100 data (NRPIV/100) on relative humidity (A-F indicates the participants of RRT)	27
Table 1 – Example of parameter values of impulse voltage waveform without load	11
Table D.1 – Examples of bandwidths and noise levels for practical PD sensors	28

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**ELECTRICAL INSULATING MATERIALS AND SYSTEMS –
ELECTRICAL MEASUREMENT OF PARTIAL DISCHARGES (PD)
UNDER SHORT RISE TIME AND REPETITIVE VOLTAGE IMPULSES**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC/TS 61934, which is a technical specification, has been prepared by IEC technical committee 112: Evaluation and qualification of electrical insulating materials and systems.

This second edition cancels and replaces the first edition, published in 2006, and constitutes a technical revision.

The principal changes with regard to the previous edition concern the addition of

- an Introduction that provides some background information on the progress being made in the field of power electronics;
- impulse generators;
- PD detection methods;
- a new informative Annex C covering practical experience obtained from round-robin testing (RRT);
- example of noise levels, as shown in new informative Annex D.

The text of this technical specification is based on the following documents:

Enquiry draft	Report on voting
112/163/DTS	112/175/RVC

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- transformed into an International standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Power electronics has developed along with both control theory and semiconductor technology. Switching is one of the essential features of power electronics control. For higher efficiency and smoother operation, switching times of the latest devices such as insulated-gate bipolar transistor (IGBT) tend to be shorter than microseconds. Such a short rise time may cause transient overvoltage impulses or surges in the systems. When the voltage impulses reach the breakdown strength of an air gap, partial discharge (PD) may occur. In addition, the impulses are repetitive from power electronics modulation such as pulse width modulation (PWM). Since PD may cause degradation of electrical insulation parts in the system, it is one of the most important parameters to be measured.

The first edition of IEC/TS 61934 was issued in April 2006. Because of rapid development in this field, the revision activity for the latest information was approved in TC112 at the Berlin meeting in September 2006. In addition to technical and editorial changes, practical experience obtained through round-robin test (RRT) is also presented in Annex C.

This document is a preview generated by EVS

ELECTRICAL INSULATING MATERIALS AND SYSTEMS – ELECTRICAL MEASUREMENT OF PARTIAL DISCHARGES (PD) UNDER SHORT RISE TIME AND REPETITIVE VOLTAGE IMPULSES

1 Scope

IEC/TS 61934, which is a technical specification, is applicable to the off-line electrical measurement of partial discharges (PD) that occur in electrical insulation systems (EIS) when stressed by repetitive voltage impulses generated from electronic power devices.

Typical applications are EIS belonging to apparatus driven by power electronics, such as motors, inductive reactors and windmill generators.

NOTE 1 Use of this technical specification with specific products may require the application of additional procedures.

NOTE 2 The procedures described in this technical specification are emerging technologies. Experience and caution, as well as certain preconditions, are needed to apply it.

Excluded from the scope of this technical specification are

- methods based on optical or ultrasonic PD detection,
- fields of application for PD measurements when stressed by non-repetitive impulse voltages such as lightning impulse or switching impulses from switchgear.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60034 (all parts), *Rotating electrical machines*

IEC 60270:2000, *High-voltage test techniques – Partial discharge measurements*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

repetitive voltage impulses

voltage impulses which are used as test voltage for the evaluation of switching surges from power electronic devices with a carrier or driven frequency

3.2

partial discharge

PD

electric discharge that only partially bridges the insulation between conductors

[IEC 60270:2000, 3.1, modified]