

**Maritime navigation and radio-communication
equipment and systems - Shipborne radar -
Performance requirements, methods of testing and
required test results**

Maritime navigation and radio-communication
equipment and systems - Shipborne radar -
Performance requirements, methods of testing and
required test results

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

Käesolev Eesti standard EVS-EN 62388:2008 sisaldab Euroopa standardi EN 62388:2008 ingliskeelset teksti.

Standard on kinnitatud Eesti Standardikeskuse 28.04.2008 käskkirjaga ja jõustub sellekohase teate avaldamisel EVS Teatajas.

Euroopa standardimisorganisatsioonide poolt rahvuslikele liikmetele Euroopa standardi teksti kättesaadavaks tegemise kuupäev on 28.03.2008.

Standard on kättesaadav Eesti standardiorganisatsioonist.

This Estonian standard EVS-EN 62388:2008 consists of the English text of the European standard EN 62388:2008.

This standard is ratified with the order of Estonian Centre for Standardisation dated 28.04.2008 and is endorsed with the notification published in the official bulletin of the Estonian national standardisation organisation.

Date of Availability of the European standard text 28.03.2008.

The standard is available from Estonian standardisation organisation.

ICS 47.020.70

Võtmesõnad:

Standardite reprodutseerimis- ja levitamiseõigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonilisse süsteemi või edastamine ükskõik millises vormis või millisel teel on keelatud ilma Eesti Standardikeskuse poolt antud kirjaliku loata.

Kui Teil on küsimusi standardite autorikaitse kohta, palun võtke ühendust Eesti Standardikeskusega:
Aru 10 Tallinn 10317 Eesti; www.evs.ee; Telefon: 605 5050; E-post: info@evs.ee

English version

**Maritime navigation and radiocommunication equipment and systems -
Shipborne radar -
Performance requirements, methods of testing and required test results
(IEC 62388:2007)**

Equipements et systèmes de navigation
et de radio-communications maritimes -
Radars embarqués -
Exigences de performance,
méthodes de test et résultats attendus
(CEI 62388:2007)

Navigations- und
Funkkommunikationsgeräte und -systeme
für die Seeschifffahrt -
Radar für Schiffe -
Leistungsanforderungen, Prüfverfahren
und geforderte Prüfergebnisse
(IEC 62388:2007)

This European Standard was approved by CENELEC on 2008-02-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in two official versions (English and German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

Foreword

The text of document 80/494/FDIS, future edition 1 of IEC 62388, prepared by IEC TC 80, Maritime navigation and radiocommunication equipment and systems, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 62388 on 2008-02-01.

This European Standard supersedes EN 60936 series (radar) and EN 60872 series (plotting).

Contents from the previous radar series (EN 60936-1, EN 60936-2 and EN 60936-3) and plotting series (EN 60872-1, EN 60872-2 and EN 60872-3) of standards have been included, as appropriate.

EN 62388:2008 supports the new IMO performance standards for shipborne radar, Resolution MSC.192(79) adopted by the IMO in December 2004. Resolution MSC.192(79) supersedes all previous IMO resolutions relating to radar and plotting, including IMO Resolutions A.278(VIII), A.477(XII) and MSC 64(67) Annex 4.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2008-11-01
- latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2011-02-01

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 62388:2007 was approved by CENELEC as a European Standard without any modification.

preview generated by EVS

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60945	- ¹⁾	Maritime navigation and radiocommunication equipment and systems - General requirements - Methods of testing and required test results	EN 60945	2002 ²⁾
IEC 61162	Series	Maritime navigation and radiocommunication equipment and systems - Digital interfaces	EN 61162	Series
IEC 61174	- ¹⁾	Maritime navigation and radiocommunication equipment and systems - Electronic chart display and information system (ECDIS) - Operational and performance requirements, methods of testing and required test results	EN 61174	2001 ²⁾
IEC 61966-4	- ¹⁾	Multimedia systems and equipment - Colour measurement and management - Part 4: Equipment using liquid crystal display panels	EN 61966-4	2000 ²⁾
IEC 61996	Series	Maritime navigation and radiocommunication equipment and systems - Shipborne voyage data recorder (VDR)	-	-
ISO 9000	- ¹⁾	Quality management systems - Fundamentals and vocabulary	EN ISO 9000	2005 ²⁾
ISO 9241-8	- ¹⁾	Ergonomic requirements for office work with visual display terminals (VDTs) - Part 8: Requirements for displayed colours	EN ISO 9241-8	1997 ²⁾
ISO 9241-12	- ¹⁾	Ergonomic requirements for office work with visual display terminals (VDTs) - Part 12: Presentation of information	EN ISO 9241-12	1998 ²⁾
ISO 13406-2	- ¹⁾	Ergonomic requirements for work with visual displays based on flat panels - Part 2: Ergonomic requirements for flat panel displays	EN ISO 13406-2	2001 ²⁾
ISO 80416-4	- ¹⁾	Basic principles for graphical symbols for use on equipment - Part 4: Guidelines for the adaptation of graphical symbols for use on screens and displays (icons)	-	-
ITU-R Recommendation M.628-4	2006	Technical characteristics for search and rescue radar transponders	-	-

¹⁾ Undated reference.

²⁾ Valid edition at date of issue.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
ITU-R Recommendation M.824-3	2007	Technical parameters of radar beacons (racons)	-	-
ITU-R Recommendation M.1176	1995	Technical parameters of radar target enhancers	-	-
IHO S-52	1996	Specifications for chart content and display aspects of ECDIS	-	-
IHO S-52 Appendix 1	1996	Guidance on updating the ENC	-	-
IHO S-52 Appendix 2	2004	Colour and symbol specifications for ECDIS	-	-
IMO SOLAS	1974	Convention for Safety Of Life At Sea (SOLAS)-	-	-
IMO Resolution A.694 (17)	1991	General requirements for shipborne radio equipment forming part of the Global Maritime Distress and Safety System (GMDSS) and for electronic navigational aids	-	-
IMO Resolution A.817(19)	1995	Performance standards for Electronic Chart Display and Information Systems (ECDIS)	-	-
IMO Resolution MSC.96(72)	- ¹⁾	Performance standards for devices to measure and indicate speed and distance	-	-
IMO Resolution MSC.112(73)	- ¹⁾	Performance standards for shipborne Global Positioning System (GPS) receiver equipment	-	-
IMO Resolution MSC.191(79)	2004	Performance standards for the presentation of - navigation-related information on shipborne navigational displays	-	-
IMO Resolution MSC.192(72)	2004	Revised performance standards for radar equipment	-	-
IMO SN/Circ.243	2004	Guidelines for the presentation of navigation related symbols, terms and abbreviation	-	-
CIE 15	2004	Colorimetry	-	-
VESA-2001-6	2001	Flat Panel Display Measurements (FPDM)	-	-

Generated by EVS

CONTENTS

FOREWORD.....	11
1 Scope.....	13
1.1 Purpose.....	13
1.2 Application of these standards.....	14
1.3 Equipment categories.....	14
2 Normative references.....	15
3 Terms and definitions.....	16
4 General.....	25
4.1 Establishing equipment type and status.....	25
4.2 Conditions of measurement and related definitions.....	26
4.3 Test sites and simulation.....	26
4.3.1 Environmental and RF testing.....	26
4.3.2 Over-sea radar performance tests.....	26
4.3.3 Test targets and target simulation for performance tests.....	27
4.4 Quality requirements.....	27
4.5 Test terminology and format.....	27
4.5.1 General.....	27
4.5.2 Test requirement terminology.....	27
4.5.3 Testing method terminology.....	28
5 Radar performance.....	28
5.1 General.....	28
5.2 Transmission and interference.....	28
5.2.1 Transmission frequency.....	28
5.2.2 Interference.....	29
5.3 Performance optimisation and monitoring.....	29
5.3.1 General.....	29
5.3.2 Optimum performance.....	29
5.4 Gain and anti-clutter functions.....	30
5.4.1 General.....	30
5.4.2 Gain function.....	30
5.4.3 Manual and automatic sea anti-clutter.....	31
5.4.4 Rain anti-clutter.....	31
5.5 Signal processing.....	31
5.5.1 General.....	31
5.5.2 Target enhancement.....	31
5.5.3 Radar signal correlation.....	32
5.5.4 Signal processing and radar image latency.....	32
5.5.5 Second-time-around echoes.....	33
5.5.6 Transmission format.....	33
5.5.7 Picture update.....	33
5.5.8 Additional processing.....	33
5.5.9 Signal processing description.....	34
5.6 Operation with SARTs, target enhancers (RTEs) and beacons.....	34
5.6.1 General.....	34
5.6.2 Radar beacons, SARTs and enhancers.....	34

5.7	Minimum range and range compensation	35
5.7.1	General	35
5.7.2	Range compensation	35
5.7.3	Minimum range	35
5.8	Range and bearing discrimination	36
5.8.1	General	36
5.8.2	Measurement conditions	36
5.8.3	Range discrimination	36
5.8.4	Bearing discrimination	37
5.8.5	Fundamental radar accuracy	37
5.9	Target detection performance assessment	37
5.9.1	General	37
5.9.2	Range of first detection in minimal clutter	38
5.9.3	Assessment of target detection with clutter	40
5.9.4	Radar performance documentation	46
5.10	Radar antenna (including pitch and roll)	47
5.10.1	General	47
5.10.2	Vertical radiation pattern/pitch and roll	47
5.10.3	Antenna horizontal pattern.....	47
5.10.4	Antenna side lobes	48
5.11	Radar availability.....	49
5.11.1	Standby and transmit.....	49
6	Display presentation.....	49
6.1	General	49
6.2	Performance standards	49
6.3	Presentation of information.....	50
6.3.1	Consistency of layout	50
6.3.2	Consistency of presentation.....	50
6.3.3	Separation of operational display area.....	51
6.3.4	Operational display area information	51
6.4	Readability	51
6.4.1	Readability under all ambient light conditions	51
6.4.2	Legibility of alphanumeric data, information and text.....	53
6.4.3	Presentation of text	54
6.4.4	Icons	54
6.5	Colours and intensity.....	54
6.5.1	Use and discrimination of colour	54
6.6	Symbols	56
6.6.1	Operational information	56
6.7	Coding of information	56
6.7.1	Colour coding of alarm-related information	56
6.7.2	Colour coding in combination with other attributes	56
6.7.3	Flashing of information	57
6.8	Integrity marking	57
6.8.1	Indication of source, validity and integrity status	57
6.8.2	Colour coding of validity and integrity	57
6.9	Alarms and indications	58
6.9.1	Operational status	58
6.9.2	List of alarms.....	58

6.9.3	Alarm related information from multiple sources	59
6.10	Presentation of radar information	59
6.10.1	Radar video images.....	59
6.10.2	Linearity and index delay.....	60
6.11	Physical requirements	61
6.11.1	Operational display area.....	61
6.11.2	Contrast and brightness adjustment.....	61
6.11.3	Temporal stability	62
6.11.4	Physical controls and status indicators	62
6.12	Colours	63
6.12.1	Requirement.....	63
6.12.2	Method of test and required results	63
6.13	Screen resolution	63
6.13.1	Requirement.....	63
6.13.2	Methods of test and required results.....	63
6.14	Screen viewing angle	64
6.14.1	Requirement.....	64
6.14.2	Methods of test and required results.....	64
6.15	Magnetic interference.....	64
6.15.1	Requirement.....	64
6.15.2	Methods of test and required results.....	64
7	CCRP and own ship	64
7.1	Consistent common reference point (CCRP)	64
7.1.1	CCRP position.....	64
7.1.2	Measurements.....	65
7.1.3	Antenna offset	65
7.2	Own ship	66
7.2.1	General	66
7.2.2	Own ship's outline and minimised symbol.....	66
7.2.3	Heading line	66
7.2.4	Stern line.....	67
8	Navigation tools.....	67
8.1	General.....	67
8.1.1	Units of measurement.....	67
8.1.2	Presentation	68
8.2	Display range scales	68
8.2.1	Mandatory range scales	68
8.3	Variable range marker (VRM).....	69
8.3.1	General	69
8.3.2	VRM measurements	69
8.4	Electronic bearing line (EBL)	70
8.4.1	General	70
8.4.2	EBL measurements	70
8.4.3	EBL origin position	70
8.5	Cursor.....	71
8.5.1	General	71
8.5.2	Cursor measurement	71
8.5.3	Selection by cursor.....	72
8.6	Offset measurement of range and bearing.....	72

8.6.1	General	72
8.6.2	Electronic range/bearing line (ERBL)	72
8.7	Parallel index lines (PI)	73
8.7.1	General	73
8.7.2	PI lines and positioning	73
8.8	Bearing scale	73
8.8.1	General	73
8.8.2	Bearing scale presentation	74
8.9	Range rings	74
8.9.1	General	74
8.9.2	Range ring presentation and measurement	74
8.10	Radar maps	75
8.10.1	General	75
8.10.2	Map functions and display simple user-defined maps	75
8.10.3	Map memory and transfer	76
8.10.4	Map presentation properties	76
8.11	Navigation routes	76
8.11.1	General	76
8.11.2	Route display and monitoring	76
9	Orientation, motion and stabilisation	77
9.1	General	77
9.2	Azimuth stabilisation	77
9.2.1	Accuracy of alignment	77
9.2.2	Heading readout and reference	78
9.2.3	Azimuth stabilisation update	79
9.3	Motion and orientation modes	79
9.3.1	General	79
9.3.2	True and relative motion	79
9.4	Off-centring	79
9.4.1	General	79
9.4.2	Manual and automatic off-centring	79
9.4.3	Automatic reset	80
9.4.4	Display orientation	80
9.5	Ground and sea stabilisation	81
9.5.1	Mode and source	81
9.5.2	Ground stabilisation	81
9.5.3	Sea stabilisation	82
10	Aids for collision avoidance	82
10.1	General	82
10.2	Target trails and past positions	83
10.2.1	General	83
10.2.2	Time and plot requirements	83
10.2.3	Trails/past position availability	84
10.3	Target tracking (TT)	84
10.3.1	General	84
10.3.2	Presentation of targets	85
10.3.3	Tracking calculations	85
10.3.4	Target tracking availability	86
10.3.5	Classification and tracked target capacity	86

10.3.6	Manual acquisition	87
10.3.7	Automatic acquisition	87
10.3.8	Motion trend.....	88
10.3.9	Visibility of 50 %	88
10.3.10	Tracking algorithm	88
10.3.11	Target swap	88
10.3.12	Cease tracking	89
10.3.13	Target tracking scenarios	89
10.3.14	Target motion and tracking accuracy.....	89
10.3.15	Tracker range and bearing accuracy	97
10.3.16	Reference target	98
10.4	Tracking limitations	99
10.4.1	Tracking warnings	99
10.4.2	Documentation	99
10.5	Automatic identification system	99
10.5.1	General	99
10.5.2	AIS target capacity	100
10.5.3	Filtering of AIS sleeping targets.....	101
10.5.4	Activation and deactivation of AIS targets.....	101
10.5.5	AIS functionality and presentation	102
10.6	Radar and AIS target data	104
10.6.1	General	104
10.6.2	Bow crossing range and time (BCR/BCT)	105
10.7	Operational target alarms	105
10.7.1	General	105
10.7.2	CPA and TCPA.....	105
10.7.3	New target alarm	106
10.7.4	Lost tracked radar target	106
10.7.5	Lost AIS target criteria	107
10.8	Target association.....	108
10.8.1	General	108
10.8.2	Association and priority	108
10.9	Trial manoeuvre	112
10.9.1	General	112
10.9.2	Trial functions.....	112
11	Chart radar (optional classification)	113
11.1	General.....	113
11.1.1	Chart operation and source	114
11.1.2	Chart elements and availability.....	114
11.1.3	Chart reference	115
11.1.4	Primary chart information set.....	115
11.1.5	Chart stabilisation and chart redraw	116
11.1.6	Chart position and latency.....	117
11.1.7	Matching and adjustment	117
11.1.8	Chart symbols, colours, and size	118
11.1.9	Chart display size.....	119
11.1.10	Chart alarms and indications	119
11.1.11	Chart malfunction	119
11.1.12	Chart radar malfunction.....	120

11.2	Additional requirements for standalone radar with chart facilities	120
11.2.1	General	120
11.2.2	Provision and updating of chart information	120
11.2.3	Content and structure of chart data	120
12	Ergonomic criteria (control functions and display)	121
12.1	General	121
12.1.1	Operational controls	121
12.1.2	Primary controls	122
12.1.3	Control properties	122
13	Interfacing	123
13.1	General	123
13.2	Input interfacing	123
13.2.1	Input data	123
13.2.2	Input quality, integrity and latency	123
13.3	Output interfacing	124
13.3.1	Output format	124
13.3.2	Output target data	124
13.3.3	VDR interface	125
14	Design, servicing and installation	125
14.1	General	125
14.1.1	Fault diagnosis and servicing	125
14.1.2	Display design	126
14.2	Transceiver design	126
14.2.1	General	126
14.2.2	Sector blanking	127
14.3	Antenna design	127
14.3.1	Requirement	127
14.3.2	Methods of test and required results	127
14.4	Inter-switched and multiple radars	128
14.4.1	General	128
14.4.2	System safeguards	128
14.4.3	Combining radar	128
14.4.4	Multiple radar system status	129
14.5	Multiple operational displays	129
14.5.1	Additional information and conformity	129
14.6	Safety – antenna and radiation	130
14.6.1	General	130
14.6.2	Antenna radiation and rotation	130
14.6.3	Microwave radiation levels	130
15	Alarms and failures	131
15.1	General	131
15.1.1	Alarms and indications	131
15.1.2	Alarm outputs	131
15.1.3	Picture freeze	132
15.1.4	Sensor failure alarm	132
15.2	Backup and fallback arrangements	132
15.2.2	Failure of heading information (azimuth stabilisation)	132
15.2.3	Failure of speed through the water information	133

15.2.4	Failure of course and speed over ground information.....	133
15.2.5	Failure of position input information.....	133
15.2.6	Failure of radar video input information.....	133
15.2.7	Failure of AIS input information.....	134
15.2.8	Failure of an integrated or networked system.....	134
16	Environmental testing.....	134
16.1	General.....	134
16.1.1	Testing to IEC 60945.....	134
16.2	Additional environmental tests.....	135
16.2.1	General.....	135
16.2.2	Antenna shock test.....	135
17	Equipment familiarisation and documentation.....	136
17.1	General.....	136
17.1.1	User requirements.....	136
17.2	Instructions and documentation.....	136
17.2.1	General.....	136
17.2.2	Documentation.....	137
17.2.3	Operating instructions.....	137
17.3	Radar system installation.....	138
Annex A (informative) Guidelines for radar functionality on navigation displays.....		139
Annex B (normative) Unwanted emissions of radar systems.....		140
Annex C (informative) Radar target size (RCS) and detection range calculations.....		145
Annex D (informative) Factors that influence target detection.....		149
Annex E (normative) Sensor errors.....		158
Annex F (informative) Target scenario simulator/reported target simulator.....		160
Annex G (informative) Tracked and reported target states.....		161
Annex H (normative) IEC 61162 sentence formats.....		162
Annex I (normative) Radar control function/indication grouping.....		172
Annex J (normative) Presentation colours and symbols.....		176
Annex K (normative) Colour calibration for chart radar.....		200
Figure 1 – Reduction of range to first detection due to rain at S-band.....		41
Figure 2 – Reduction of range to first detection due to rain at X-band.....		42
Figure 3 – TT scenario 1.....		91
Figure 4 – TT scenario 2.....		93
Figure 5 – TT scenario 3.....		94
Figure 6 – TT scenario 4.....		95
Figure 7 – TT scenario 5.....		96
Figure B.1 – B ₄₀ falls within the allocated band.....		143
Figure B.2 – B ₄₀ falls outside the allocated band.....		144
Figure C.1 – Enhancement by reflection (dB) over free-space (9,41 GHz).....		148
Figure C.2 – Enhancement by reflection (dB) over free-space (3,05 GHz).....		148
Figure D.1 – Effect of sea spikes on target detection.....		151
Figure D.2 – Multi-path plots for S-band.....		153

Figure D.3 – Multi-path plot for X-band	153
Figure G.1 – Tracked target states.....	161
Figure G.2 – AIS target states.....	161
Table 1 – Performance requirements for categories of ship/craft for SOLAS V	15
Table 2 – Range of first detection in clutter-free conditions	39
Table 3 – X-band pass/fail assessment criteria	45
Table 4 – S-band pass/fail assessment criteria	45
Table 5 – Pass/fail assessment.....	45
Table 6 – Douglas sea state parameters	46
Table 7 – Main horizontal beam pattern	48
Table 8 – Effective side-lobes	48
Table 9 – Ambient light conditions	52
Table 10 – Operational alarm status	58
Table 11 – Tracked target capacity (subset of Table 1).....	86
Table 12 – Typical tracked target accuracy (95 % probability figures)	90
Table 13 – TT scenario 1, with sensor errors applied	90
Table 14 – TT scenario 1, times of measurement task	91
Table 15 – TT scenario 1, accuracies after 1 min and 3 min (all \pm values).....	92
Table 16 – TT scenario 2, own ship turning through $\pm 180^\circ$	92
Table 17 – TT scenario 3, initial target data	93
Table 18 – TT scenario 4, initial target data for fast targets (standard speed ships)	94
Table 19 – TT scenario 4, initial target data for fast targets (HSC)	94
Table 20 – TT scenario 5: initial target data for standard craft.....	95
Table 21 – TT scenario 5: initial target data for collision scenario for HSC	96
Table 22 – Measurement points and results at 3 min and 6 min for HSC	96
Table 23 – Measurement points and results at 11 min and 14 min for HSC	97
Table 24 – Measurement points and results at 3 min and 6 min for standard craft.....	97
Table 25 – Measurement points and results at 11 min and 14 min for standard craft.....	97
Table 26 – Measurement of tracked target accuracy	98
Table 27 – AIS target display capacity (subset of Table 1).....	100
Table 28 – AIS reporting rates	107
Table 29 – Association scenario 1, initial TT and AIS target position and data	109
Table 30 – Association scenario 1, AIS target data for diverging and converging tracks.....	110
Table 31 – Association scenario 2, initial TT and AIS target position and data	110
Table 32 – Association scenario 2, AIS target data for changing speed.....	111
Table 33 – Association scenario 3, TT and AIS target start position and data	111
Table 34 – Association scenario 4, initial TT and AIS target position and data	112
Table 35 – Association scenario 4, TT and AIS target with the same course and speed	112
Table 36 – Antenna shock test severity (half sine pulse).....	135
Table B.1 – Measurement frequency ranges	141
Table D.1 – Spread of RCS values for typical ships	150
Table D.2 – S-band performance predictions ($P_{fa} = 10^{-4}$) for ranges of 0,2, 0,4, 0,7 NM....	152

Table D.3 – X-band performance predictions ($P_{fa} = 10^{-4}$) for ranges of 0,2, 0,7 NM	152
Table D.4 – Parameters for attenuation in uniform rain conditions.....	154
Table D.5 – Typical values for attenuation and backscatter in uniform rain conditions.....	154
Table D.6 – Additional radar system parameters (X/S-band).....	154
Table D.7 – Target size, height and RCS values	155
Table D.8 – S-band radar parameters (LP)	156
Table D.9 – X-band radar parameters (LP)	157
Table H.1 – Mandatory IEC 61162-1 sentences	162
Table H.2 – Tracked target data structure	164
Table H.3 – Description of terms.....	165
Table H.4 – Header format.....	166
Table H.5 – Package data format.....	168
Table I.1 – Top-level grouping of data and control functions for radar applications.....	172
Table I.2 – Icons for common function controls	173
Table J.1 – Features and colours to be used for radar maps	178
Table J.2 – Own ship symbols	178
Table J.3 – Radar and AIS symbols	183
Table J.4 – Navigation symbols	193
Table J.5 – Navigation tools.....	198
Table J.6 – Other symbols	199

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS –

Shipborne radar – Performance requirements, methods of testing and required test results

1 Scope

This International Standard specifies the minimum operational and performance requirements, methods of testing and required test results conforming to performance standards not inferior to those adopted by the IMO in Resolution MSC.192(79).

(MSC.192/2) The radar installation, in addition to meeting the general requirements as set out in resolution A.694(17) and the related general standard, IEC 60945, should comply with the performance standards of MSC.192(79). When a requirement of this standard is different from IEC 60945 the requirement in this standard takes precedence.

All text in this standard with wording identical to that in IMO resolution MSC.192(79) is printed in italics. Reference to MSC.192(79) is by the relevant requirement clause as indicated in brackets, for example (MSC.192/4.2.3). Some clauses from Resolution MSC.192(79) may be split and the requirements in this case are addressed separately.

(MSC.192/5) The design and performance of the radar should be based on user requirements and up-to-date navigational technology. It should provide effective target detection within the safety-relevant environment surrounding own ship and should permit fast and easy situation evaluation.

(MSC.192/1) The radar equipment should assist in safe navigation and in avoiding collision by providing an indication, in relation to own ship, of the position of other surface craft, obstructions and hazards, navigation objects and shorelines. For this purpose, radar should provide the integration and display of radar video, target tracking information, positional data derived from own ship's position (EPFS) and geo referenced data.

The integration and display of AIS information should be provided to complement radar. The capability of displaying selected parts of Electronic Navigation Charts (ENC) and other vector chart information may also be provided to aid navigation and for position monitoring. Radar is a technology that should be applied together with other sensor information applicable for the task in hand.

NOTE Radar is a system and its performance is a factor of all of its component parts. The type test should include the radar sensor, ancillary units and display, complete with its processing and presentation display. All of these component parts contribute to the requirements and approval to these radar standards. Other navigational systems and equipment that provide radar and/or target tracking functions, should comply with the relevant clauses of this standard according to the guidelines in Annex A. A navigation display or INS may be approved as part of a radar system when tested with the specific radar sensor and relevant ancillary units. Where the intended application for a navigation system is for collision avoidance, as a minimum requirement, the radar image should always be presented, together with the relevant functionality and performance as described in Annex A.

1.1 Purpose

(MSC.192/1) The radar, when combined with other sensor, or reported information (for example AIS), should improve the safety of navigation by assisting in the efficient navigation of ships and protection of the environment by satisfying the following functional requirements:

- *in coastal navigation and harbour approaches, by giving a clear indication of land and other fixed hazards;*

- as a means to provide an enhanced traffic image and improved situation awareness;
- in a ship-to-ship mode for aiding collision avoidance of both detected and reported hazards;
- in the detection of small floating and fixed hazards, for collision avoidance and the safety of own ship; and
- in the detection of floating and fixed aids to navigation.

1.2 Application of these standards

(MSC.192/2) *The Performance Standards defined by MSC.192(79) shall apply to all shipborne radar installations used in any configuration mandated by SOLAS independent of the type of ship, frequency band in use and the type of display, providing that no special requirements are specified in Table 1 and that additional requirements for specific classes of ship (in accordance with SOLAS Chapters V and X) are met.*

(MSC.192/2) *Close interaction between different navigation equipment and systems makes it essential to consider this standard in association with other relevant IMO and IEC standards.*

This standard applies to radar systems, navigation systems and navigation equipment which have the task of target detection and collision avoidance. Any equipment which combines these tasks and meets all of the requirements in this standard is regarded as a radar system. In support of the Collision Regulations, all available means shall be used to enhance the role of radar for safe navigation and collision avoidance. The usage of other sensors shall, where practical, observe the requirements of the standards associated with those sensors. This standard also provides guidelines and requirements for radar functionality on all navigational displays supporting the tasks of target detection, collision avoidance, general navigation and position referencing on the bridge of a ship.

The successful integration of radar with AIS, charts, databases and other sensors demands that the radar equipment is correctly set up with special attention to the critical alignment of heading(s), system index delay(s), CCRP offsets and gyro. Failure to align these parameters may cause unacceptable registration with other information and may detract from the purpose of integration. This standard has mandated requirements to provide for these alignments.

NOTE While X-band radar systems remain compatible with radar beacons, SARTs and radar enhancers, S-band systems are permitted to harness new radar technology which may not be compatible with those devices. All tests (or their equivalent) in this standard apply to both non-coherent (for example conventional-based radar) and coherent radar systems (for example pulse compression radar).

1.3 Equipment categories

This standard covers the testing of all SOLAS shipborne radar equipment. Individual equipment may be tested for a specific category of vessel. Table 1 provides a summary of the categories and basic differential capabilities for each category. The category should be indicated on the type label of the main radar electronics unit and on the related Certification of Test. Equipment approved for high speed applications should include a suffix H (for example CAT 1H) and equipment approved with a chart option should include a suffix C (for example CAT 1HC).

(MSC.192/5.3.1.1) *Recognising the high relative speeds possible between own ship and target, the equipment should be specified and approved as being suitable for classes of ship having normal (≤ 30 kn) or high (> 30 kn) own ship speeds (100 kn and 140 kn relative speeds respectively).*

The additional characteristics for equipment qualified to be approved for HSC and/or for chart radar are identified in this standard. For example, HSC equipment should be compatible with own ship speeds of up to 70 kn, should be capable of tracking targets with a 140 kn relative speed and should operate between latitudes of 70° N and 70° S.

A chart radar should conform to all the requirements of Clause 11 in this standard. References are made to IEC 61174 (ECDIS) for specific and standalone chart functionality.

Table 1 – Performance requirements for categories of ship/craft for SOLAS V

	Category of ship/craft		
	CAT 3	CAT 2	CAT 1
Size of ship/craft	<500 gt	500 gt to <10 000 gt and HSC<10 000 gt	All ships/craft ≥10 000 gt
Minimum operational display area diameter	180 mm	250 mm	320 mm
Minimum display area	195 mm x 195 mm	270 mm x 270 mm	340 mm x 340 mm
Auto acquisition of targets	-	-	Yes
Minimum <u>acquired</u> radar target capacity	20	30	40
Minimum <u>activated</u> AIS target capacity	20	30	40
Minimum <u>sleeping</u> AIS target capacity	100	150	200
Trial manoeuvre	-	-	Yes
NOTE The processing capacity of AIS information should be in accordance with 10.5.2.			

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61162 (all parts), *Maritime navigation and radiocommunication equipment and systems – Digital interfaces*

IEC 61174, *Maritime navigation and radiocommunication equipment and systems – Electronic chart display and information systems (ECDIS) – Operational and performance requirements, methods of testing and required test results*

IEC 61966-4, *Multimedia systems and equipment – Colour measurement and management – Part 4: Equipment using liquid crystal display panels*

IEC 61996 (all parts), *Maritime navigation and radiocommunication equipment and systems – Shipborne voyage data recorder (VDR) – Performance requirements – Methods of testing and required test results*

ISO 9000, *Quality management systems – Fundamentals and vocabulary*

ISO 9241-8, *Ergonomic requirements for office work with visual display terminals (VDTs) – Part 8: Requirements for displayed colours*

ISO 9241-12, *Ergonomic requirements for office work with visual display terminals (VDTs) – Part 12: Presentation of information*

ISO 13406-2, *Ergonomic requirements for work with visual displays based on flat panels – Part 2: Ergonomic requirements for flat panel displays*

ISO 80416-4, *Basic principles for graphical symbols for use on equipment – Part 4: Guidelines for the adaptation of graphical symbols for use on screens and displays (icons)*

ITU-R Recommendation M.628-4:2006, *Technical characteristics for search and rescue radar transponders*

ITU-R Recommendation M.824-3:2007, *Technical parameters of radar beacons (racons)*

ITU-R Recommendation M.1176:1995, *Technical parameters of radar target enhancers*

IHO S-52:1996, *Specifications for chart content and display aspects of ECDIS*

IHO S-52 Appendix 1:1996, *Guidance on updating the ENC*

IHO S-52 Appendix 2:2004, *Colour and symbol specifications for ECDIS*

IMO SOLAS:1974, *International Convention for the Safety of Life at Sea, as amended*

IMO Resolution A.694(17):1991, *General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids*

IMO Resolution A.817(19):1995, *Performance standards for electronic chart display and information systems (ECDIS)* (as amended by MSC.64(67) Annex 5 and MSC.86(70) Annex 4)

IMO Resolution MSC.96(72), *Amendments to IMO Resolution A.824(19), Performance standards for devices to indicate speed and distance*

IMO Resolution MSC.112(73), *Revised performance standards for shipborne global positioning system (GPS) receiver equipment*

IMO Resolution MSC.191(79):2004, *Performance standards for the presentation of navigation-related information on shipborne navigational displays*

IMO Resolution MSC.192(72):2004, *Revised performance standards for radar equipment*

IMO SN/Circ.243:2004, *Guidelines for the presentation of navigation related symbols, terms and abbreviations*

CIE 15:2004, *Colorimetry*

VESA-2001-6:2001, *Flat Panel Display Measurements (FPDM)*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

activated AIS target

target representing the automatic or manual activation of a sleeping target for the display of additional graphically presented information. The target is displayed by an “activated target” symbol including a vector; the heading; and the ROT or direction of turn indication (if available) to indicate initiated course changes

3.2

acquisition of a radar target

process of acquiring a target and initiating its tracking