

**Alumiinium ja alumiiniumisulamid.
Ribitoorik. Osa 2: Mehaanilised
omadused**

Aluminium and aluminium alloys - Finstock - Part 2:
Mechanical properties

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

<p>Käesolev Eesti standard EVS-EN 683-2:2007 sisaldab Euroopa standardi EN 683-2:2006 ingliskeelset teksti.</p> <p>Käesolev dokument on jõustatud 29.01.2007 ja selle kohta on avaldatud teade Eesti standardiorganisatsiooni ametlikus väljaandes.</p> <p>Standard on kättesaadav Eesti standardiorganisatsioonist.</p>	<p>This Estonian standard EVS-EN 683-2:2007 consists of the English text of the European standard EN 683-2:2006.</p> <p>This document is endorsed on 29.01.2007 with the notification being published in the official publication of the Estonian national standardisation organisation.</p> <p>The standard is available from Estonian standardisation organisation.</p>
--	---

<p>Käsitlusala: This document specifies the mechanical properties of wrought aluminium and wrought aluminium alloy finstock. The chemical composition limits of these materials are specified in EN 573-3, unless otherwise agreed between supplier and purchaser. The designations of wrought aluminium and wrought aluminium alloys and the temper designations used in this standard are specified in EN 573-3, and the temper designations are defined in EN 515.</p>	<p>Scope: This document specifies the mechanical properties of wrought aluminium and wrought aluminium alloy finstock. The chemical composition limits of these materials are specified in EN 573-3, unless otherwise agreed between supplier and purchaser. The designations of wrought aluminium and wrought aluminium alloys and the temper designations used in this standard are specified in EN 573-3, and the temper designations are defined in EN 515.</p>
--	--

ICS 77.150.10

Võtmesõnad: alumiinium, alumiiniumisulamid, mehaanilised karakteristikud, soojusvahetid, tabelid (andmed), tõmbeteimid, valtstooted, õhukesed kiled

English Version

Aluminium and aluminium alloys - Finstock - Part 2: Mechanical properties

Aluminium et alliages d'aluminium - Bandes pour échangeurs thermiques - Partie 2 : Caractéristiques mécaniques

Aluminium und Aluminiumlegierungen - Vormaterial für Wärmeaustauscher (Finstock) - Teil 2: Mechanische Eigenschaften

This European Standard was approved by CEN on 25 November 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

Page

Foreword.....	3
1 Scope	4
2 Normative references	4
3 Tensile testing	4
4 Mechanical properties	6
5 Rounding of test results	6
Annex A (normative) Rules for rounding.....	11
Bibliography	12

Figures

Figure 1 — Parallel sided test piece	5
Figure 2 — Example of double-bladed cutter	5

Tables

Table 1 — Mechanical properties for finstock (H14, H16, H18, H19)	7
Table 2 — Mechanical properties for finstock (O, H22, H24)	9

Foreword

This document (EN 683-2:2006) has been prepared by Technical Committee CEN/TC 132 "Aluminium and aluminium alloys", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2007, and conflicting national standards shall be withdrawn at the latest by June 2007.

This document supersedes EN 683-2:1996.

Within its program of work, Technical Committee CEN/TC 132 entrusted CEN/TC 132/WG 6 "Foil and finstock" to revise EN 683-2:1996.

The following modifications have been made:

- Table 1 has been split into Table 1 and Table 2;
- Table 1 and Table 2 give the mechanical properties for gauge ranges from 60 μm to 400 μm . Mechanical properties have been amended. Alloys EN AW-6060 and EN AW 6951 have been deleted.

EN 683 comprises the following parts under the general title "*Aluminium and aluminium alloys — Finstock*":

- *Part 1: Technical conditions for inspection and delivery*
- *Part 2: Mechanical properties*
- *Part 3: Tolerances on dimensions and form*

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent right. CEN shall not be held responsible for identifying any or all such patent right.

CEN/TC 132 affirms it is its policy that in the case when a patentee refuses to grant licenses on standardised standard products under reasonable and not discriminatory conditions, then this product shall be removed from the corresponding standard.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

1 Scope

This document specifies the mechanical properties of wrought aluminium and wrought aluminium alloy finstock.

The chemical composition limits of these materials are specified in EN 573-3, unless otherwise agreed between supplier and purchaser.

The designations of wrought aluminium and wrought aluminium alloys and the temper designations used in this standard are specified in EN 573-3, and the temper designations are defined in EN 515.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 683-1, *Aluminium and aluminium alloys — Finstock — Part 1: Technical conditions for inspection and delivery*

EN 10002-1, *Metallic materials — Tensile testing — Part 1: Method of test at ambient temperature*

3 Tensile testing

The selection and number of specimens and test pieces shall be as specified in EN 683-1.

Tensile testing shall be carried out according to EN 10002-1 noting the following:

- applies to gauges between 60 μm and 400 μm ;
- test pieces shall be either parallel-sided (see Figure 1) or with shoulders and a reduced parallel section.

Parallel sided test pieces shall be prepared using a double bladed cutter (see Figure 2) or a precision ground sample shear of "punch and die" construction.

Shouldered test pieces shall have a similar sample shear or can be machined in packs using a milling-type cutter.

Parallel sided test pieces shall have a width of $(15 \pm 0,1)$ mm and a gauge length of (50 ± 1) mm or (100 ± 1) mm.

Shouldered test pieces shall be in accordance with EN 10002-1.

During the part of the test to determine proof stress, the strain rate shall not exceed 10 MPa/s. The strain rate can then be increased until rupture but it shall not exceed 50 % of the gauge length per minute.

Considering the difficulty in marking thin gauge material, the gauge length may be measured by the distance between the grips of the testing machine. The elongation is then determined from the difference in the distance between the grips before testing and at fracture, or by direct reading from the load vs crosshead displacement diagram when available. This provision only applies to parallel-sided test pieces.