

Plastics piping systems for the supply of gaseous fuels -
Unplasticized polyamide (PA-U) piping systems with
fusion jointing and mechanical jointing - Part 4: Valves
(ISO 16486-4:2022)

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN ISO 16486-4:2022 sisaldab Euroopa standardi EN ISO 16486-4:2022 ingliskeelset teksti.	This Estonian standard EVS-EN ISO 16486-4:2022 consists of the English text of the European standard EN ISO 16486-4:2022.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation and Accreditation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 26.01.2022.	Date of Availability of the European standard is 26.01.2022.
Standard on kättesaadav Eesti Standardimis- ja Akrediteerimiskeskusest.	The standard is available from the Estonian Centre for Standardisation and Accreditation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 75.200, 83.140.30

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardimis- ja Akrediteerimiskeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardimis- ja Akrediteerimiskeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autoriõiguse kaitse kohta, võtke palun ühendust Eesti Standardimis- ja Akrediteerimiskeskusega: Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation and Accreditation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation and Accreditation.

If you have any questions about standards copyright protection, please contact the Estonian Centre for Standardisation and Accreditation: Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

EUROPEAN STANDARD

EN ISO 16486-4

NORME EUROPÉENNE

EUROPÄISCHE NORM

January 2022

ICS 75.200; 83.140.30

English Version

Plastics piping systems for the supply of gaseous fuels -
Unplasticized polyamide (PA-U) piping systems with
fusion jointing and mechanical jointing - Part 4: Valves
(ISO 16486-4:2022)

Systèmes de canalisations en matières plastiques pour
la distribution de combustibles gazeux - Systèmes de
canalisations en polyamide non plastifié (PA-U) avec
assemblages par soudage et assemblages mécaniques -
Partie 4: Robinets (ISO 16486-4:2022)

Kunststoff-Rohrleitungssysteme für die Gasversorgung
- Rohrleitungssysteme aus weichmacherfreiem
Polyamid (PA-U) mit Schweißverbindungen und
mechanischen Verbindungen - Teil 4: Armaturen (ISO
16486-4:2022)

This European Standard was approved by CEN on 15 January 2022.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

This document (EN ISO 16486-4:2022) has been prepared by Technical Committee ISO/TC 138 "Plastics pipes, fittings and valves for the transport of fluids" in collaboration with Technical Committee CEN/TC 155 "Plastics piping systems and ducting systems" the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by July 2022, and conflicting national standards shall be withdrawn at the latest by July 2022.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national standards body/national committee. A complete listing of these bodies can be found on the CEN website.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 16486-4:2022 has been approved by CEN as EN ISO 16486-4:2022 without any modification.

Annex (informative)

A-deviation

A-deviation: National deviation due to regulations, the alteration of which is for the time being outside the competence of the CEN-CENELEC national member.

This European Standard does not fall under any Directive of the EU.

In the relevant CEN-CENELEC countries these A-deviations are valid instead of the provisions of the European Standard until they have been removed.

Country	Clause	Deviation
ITALY	S1 Scope	<p>According to Italian legislation concerning the safety of gas installation</p> <ul style="list-style-type: none"> - DM 16 April 2008 (DSO) prescribes that piping and components used in distribution system shall be in accordance with national standard UNI 9034 (pipes with MOP below 5 bar). In case of MOP greater than 5 bar DM 17 April 2008 shall be followed. (Official Journal Italian Republic GU n. 107 of 8th May 2008 https://www.gazzettaufficiale.it/eli/id/2008/05/08/08A02871/sg) - DM 17 April 2008 (TSO) prescribes that piping and components used in transmission system shall be made of steel (art. 3.1 of Technical Annex A to Decree). (Official Journal Italian Republic GU n. 107 of 8th May 2008 https://www.gazzettaufficiale.it/atto/serie_generale/caricaDettaglioAtto/originario?atto.dataPubblicazioneGazzetta=2008-05-08&atto.codiceRedazionale=08A02872&elenco30giorni=false)

Contents

Page

Foreword	v
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
3.1 General.....	3
3.2 Terms relating to design.....	3
4 Symbols and abbreviated terms	3
5 Material	4
5.1 Compound for valve body.....	4
5.1.1 Compound.....	4
5.1.2 Fusion compatibility.....	4
5.2 Material for non-polyamide parts.....	4
5.2.1 General.....	4
5.2.2 Metal parts.....	4
5.2.3 Elastomers.....	5
5.2.4 Greases and lubricants.....	5
5.2.5 Assembly.....	5
6 General characteristics	5
6.1 Appearance of the valve.....	5
6.2 Colour.....	5
6.3 Design.....	5
6.3.1 General.....	5
6.3.2 Valve body.....	5
6.3.3 Valve terminal ends.....	5
6.3.4 Operating device.....	5
6.3.5 Seals.....	6
7 Geometrical characteristics	6
7.1 General.....	6
7.2 Measurement of dimensions.....	6
7.3 Dimensions of spigot ends for valves.....	6
7.4 Dimensions of valves with electrofusion sockets.....	6
7.5 Dimensions of the operating device.....	6
8 Mechanical characteristics of assembled valves and regional requirements	7
8.1 General.....	7
8.2 Conditioning.....	7
8.3 Requirements.....	7
8.3.1 Generals.....	7
8.3.2 Air flow rate.....	12
8.4 Regional requirement.....	12
9 Physical characteristics	13
9.1 Conditioning.....	13
9.2 Requirement.....	13
10 Performance requirements	13
11 Technical File	13
12 Marking	14
12.1 General.....	14
12.2 Minimum required marking of valves.....	14
12.3 Additional marking.....	15

13	Delivery Conditions	15
Annex A (normative)	Determination of the leaktightness of seat(s) and packing	16
Annex B (normative)	Test method for leaktightness and ease of operation after tensile loading	18
Bibliography	20

This document is a preview generated by EVS

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 138, *Plastics pipes, fittings and valves for the transport of fluids*, Subcommittee SC 7, *Valves and auxiliary equipment of plastics materials*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 155, *Plastics piping systems and ducting systems*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 16486-4:2016), which has been technically revised.

The main changes are as follows:

- the Scope highlights that this document is valid for On/Off valves;
- the Scope shows 16 bar¹⁾ as the regional CEN requirement for the limitation of the maximum operating pressure (MOP);
- in [7.3](#) and [7.4](#) the nominal diameter of spigot ends or electrofusion sockets has been expanded to d_n 400 mm;
- a new subclause, [5.2.4](#) Greases and lubricants, has been added;
- [subclause 5.2](#) for non-unplasticized polyamide parts has been redrafted to bring it in line with EN 1555-4. A NOTE for regional requirements has been introduced;
- [subclauses 6.3.1](#) General, [6.3.2](#) Valve body, [7.5](#) Dimensions of the operating device and [8.1](#) General have been redrafted;
- a new subclause, [6.3.3](#) Valve terminal ends, has been introduced for valve terminal ends;
- [subclauses 6.3.4](#) Operating device and [6.3.5](#) Seals have been modified to bring them in line with EN 1555-4;

1) 1 bar = 0,1 MPa = 10⁵ Pa; 1 MPa = 1 N/mm².

- [subclause 7.2](#) Measurement of dimensions has been modified to bring it in line with EN 1555-4 with the exception that PA-U conditioning does not allow the use of test pieces earlier than 48 h after their manufacture;
- [subclause 8.4](#) Regional requirements has been added with reference to an extension of [subclause B.1.1](#) for CEN;
- in [Table 1](#), the number of test pieces has been added and new footnote ^b has been inserted relating to this addition;
- in [Table 1](#), the condition period has been changed to 16 h;
- in [Table 1](#), the test period has been changed to 1 000 h for hydrostatic strength (20 °C, 1 000 h);
- in [Table 1](#), the pressure drop test been deleted, as this is covered in the new [subclause 8.3.2](#);
- in [Table 1](#), the operating torque for $125 \text{ mm} < d_n \leq 400 \text{ mm}$ has been changed to $10 \text{ Nm} < M \leq 150$;
- in [Table 1](#), leaktightness after tensile load is added, including footnote ^j for limiting the diameter;
- a new subclause, [5.1.2](#) Fusion compatibility, substitutes the former subclause 6.4;
- a new [Clause 11](#) Technical File has become an individual paragraph in line with EN 1555-4;
- [subclause 12.1](#) General includes a NOTE for regional marking requirements on packaging, with reference to CEN/TS 12007-6, for CEN member countries, for example;
- [Table 3](#) for minimum required marking of valves has been modified in line with EN 1555-4;
- former subclause 12.5 Packaging has become [Clause 13](#) Delivery conditions, and has been modified and extended;
- [Annex A](#) has been updated in line with EN 1555-4;
- [Annex B](#) has been modified according longitudinal stress parameters in line with ISO 17885:2021, Table F.1;
- in [Clause B.2](#) Test piece, the definition for the length of test piece has been redrafted;
- in [Annex B](#), [subclause B.4.4](#) has been added including a regional requirement.

A list of all parts in the ISO 16486 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document specifies the requirements for valves used in a piping system made from unplasticized polyamide (PA-U) that is intended to be used for the supply of gaseous fuels.

General requirements for unplasticized polyamide (PA-U) materials used for a piping system and its components, intended for the supply of gaseous fuels, are specified in ISO 16486-1.

Requirements and test methods for pipes are specified in ISO 16486-2 and for fittings in ISO 16486-3.

Characteristics for fitness for purpose of the system and generic fusion parameters are specified in ISO 16486-5.

Recommended practice for installation is given in ISO 16486-6, which will not be implemented as a European Standard under the Vienna Agreement.

NOTE Recommended practice for installation is also given in CEN/TS 12007-6^[2], which has been prepared by Technical Committee CEN/TC 234, *Gas infrastructure*.

Assessment of conformity of the system is to form the subject of the future ISO/TS 16486-7:—²⁾.

For CEN member countries, all components are to conform to the relevant EN standard(s). Alternative standards may be applied in cases where the suitable EN standard(s) do not exist.

The ISO 16486 series covers a range of maximum operating pressures and gives requirements concerning colours.

It is the responsibility of the purchaser or specifier to make the appropriate selections from these aspects, taking into consideration their particular requirements and any relevant national regulations and installation practices or codes.

2) Under preparation. Stage at the time of publication: ISO/WD TS 16486-7:2022.

Plastics piping systems for the supply of gaseous fuels — Unplasticized polyamide (PA-U) piping systems with fusion jointing and mechanical jointing —

Part 4: Valves

1 Scope

This document specifies the characteristics of valves made from unplasticized polyamide (PA-U) in accordance with ISO 16486-1, intended to be buried and used for the supply of gaseous fuels.

It is applicable to isolating unidirectional and bi-directional valves with spigot ends or electrofusion sockets intended to be fused with PA-U pipes or fittings conforming to ISO 16486-2 and ISO 16486-3 respectively.

Valves made from material other than unplasticized polyamide designed for the supply of gaseous fuels conforming to the relevant standards are permitted to be used in PA-U piping systems according to the ISO 16486 series provided they have relevant PA-U connections for butt fusion or electrofusion ends (see ISO 16486-3). The component, i.e. the complete valve, is required to fulfil the requirements of this document.

This document also specifies the test parameters for the test methods it describes.

In conjunction with ISO 16486-1, ISO 16486-2, ISO 16486-3 and ISO 16486-5, this document is applicable to PA-U valves and their joints and to joints with components of PA-U and other materials intended to be used under the following conditions:

- a) a maximum operating pressure (MOP) of up to and including 18 bar³⁾, or limited to 16 bar under regional CEN requirements, at a reference temperature of 20 °C for design purposes;

NOTE 1 For the purpose of this document and the references to ISO 8233, MOP is considered to be nominal pressure.

- b) an operating temperature of -20 °C to 40 °C;

NOTE 2 For operating temperatures between 20 °C and 40 °C, derating coefficients are specified in ISO 16486-5.

This document covers valves for pipes with a nominal outside diameter, d_n , ≤ 400 mm.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 291, *Plastics — Standard atmospheres for conditioning and testing*

ISO 307, *Plastics — Polyamides — Determination of viscosity number*

3) 1 bar = 0,1 MPa = 10⁵ Pa; 1 MPa = 1 N/mm².