

RAUDTEEALASTE RAKENDUSTE PÜSIPAIGALDISED.
ELEKTRIOHUTUS, MAANDAMINE JA
TAGASIVOOLUAHEL. OSA 1: KAITSEMEETMED
ELEKTRILÖÖGI EEST

Fixed installations for railway application - Electrical
safety, earthing and the return circuit - Part 1:
Protective provisions against electric shock

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

<p>See Eesti standard EVS-EN 50122-1:2022 sisaldab Euroopa standardi EN 50122-1:2022 ingliskeelset teksti.</p> <p>Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.</p> <p>Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 02.09.2022.</p> <p>Standard on kättesaadav Eesti Standardimis- ja Akrediteerimiskeskusest.</p>	<p>This Estonian standard EVS-EN 50122-1:2022 consists of the English text of the European standard EN 50122-1:2022.</p> <p>This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation and Accreditation.</p> <p>Date of Availability of the European standard is 02.09.2022.</p> <p>The standard is available from the Estonian Centre for Standardisation and Accreditation.</p>
--	---

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 29.280

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardimis- ja Akrediteerimiskeskusele. Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardimis- ja Akrediteerimiskeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardimis- ja Akrediteerimiskeskusega: Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation and Accreditation. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation and Accreditation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation and Accreditation: Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

EUROPEAN STANDARD

EN 50122-1

NORME EUROPÉENNE

EUROPÄISCHE NORM

September 2022

ICS 29.280

Supersedes EN 50122-1:2011; EN 50122-1:2011/A1:2011; EN 50122-1:2011/AC:2012; EN 50122-1:2011/A2:2016; EN 50122-1:2011/A3:2016; EN 50122-1:2011/A4:2017

English Version

Railway applications - Fixed installations - Electrical safety, earthing and the return circuit - Part 1: Protective provisions against electric shock

Applications ferroviaires - Installations fixes - Sécurité électrique, mise à la terre et circuit de retour - Partie 1: Mesures de protection contre les chocs électriques

Bahnanwendungen - Ortsfeste Anlagen - Elektrische Sicherheit, Erdung und Rückleitung - Teil 1: Schutzmaßnahmen gegen elektrischen Schlag

This European Standard was approved by CENELEC on 2022-07-25. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents	Page
European foreword	7
1 Scope	8
2 Normative references	9
3 Terms and definitions	10
3.1 Electrical safety and hazards	10
3.2 Earthing and equipotential bonding	12
3.3 Return circuit	14
3.4 Electric traction power supply system	16
3.5 Contact line	17
3.6 Corrosion and corrosion protection	20
3.7 Current collection	20
3.8 Residual current devices	21
3.9 General terms	21
4 Contact line zone and current collector zone	24
4.1 Overhead contact line	24
4.2 Ground level conductor rail	27
4.3 Trolleybuses and road vehicles using an overhead contact line	27
4.4 Limitation of the zones	28
5 Protective provisions against direct contact	29
5.1 Preconditions	29
5.1.1 General	29
5.1.2 Design procedure	29
5.1.3 Electrical clearances	30
5.1.4 Standing surface	31
5.2 Protection by clearance	32
5.2.1 Calculation method for protection by clearance	32
5.2.2 Dimensions of clearances	33
5.2.3 Clearances for working persons	35
5.2.4 Warning signs	35
5.2.5 Minimum height of wires of an overhead contact line system above traffic areas	36
5.2.6 Clearances above standing surfaces on vehicles	36
5.2.7 Feeders above loading roads	36
5.2.8 Clearance between live parts of overhead contact line systems and trees and bushes	36
5.3 Protection by electrically protective obstacles	36
5.3.1 General	36
5.3.2 Common requirements for electrically protective obstacles	37
5.3.3 Methods for determining reach	38
5.3.4 Requirements for electrically protective obstacles	40
5.3.5 Specific requirements for electrically protective obstacles in restricted areas	46
5.3.6 Anti climbing provisions	47
5.4 Protection against direct contact with live parts mounted on vehicles	47
5.5 Protective provisions allowing working under live conditions	48
5.5.1 General	48
5.5.2 Overhead contact lines for railways beneath structures	49
5.5.3 Overhead contact lines for trolley busses and electric road vehicles beneath structures	49

5.6	Specific protective provisions against electric shock in ground level conductor rail systems	51
5.6.1	Location of conductor rail at platforms	51
5.6.2	Exceptions	51
5.6.3	Protection provisions in workshops and depots	51
5.6.4	Protective boarding for ground level conductor rails in restricted areas	52
5.6.5	Requirements for top contact ground level conductor rails in public areas	52
5.6.6	Requirements for top contact ground level conductor rails in restricted areas	52
5.7	Specific protective provisions against electric shock in systems in which the wheels of the vehicles are not used for return circuit	55
5.7.1	General	55
5.7.2	Railway systems	55
5.7.3	Trolleybus systems and systems for electric road vehicles	55
6	Protective provisions against indirect contact and non-galvanic coupling	56
6.1	General	56
6.2	Protective provisions for exposed-conductive-parts	56
6.2.1	AC railways	56
6.2.2	DC railways	57
6.2.3	Exceptions for low voltage electric traction power supply systems	57
6.2.4	Stays of non-conductive masts	58
6.3	Protective provisions for wholly or partly conductive structures in the overhead contact line zone or the current collector zone	58
6.3.1	Protective provisions by means of connection to the return circuit	58
6.3.2	Exceptions for small wholly and partly conductive parts	59
6.3.3	Exceptions for temporarily stored parts close to the rails	59
6.3.4	Protective provisions preventing contact between conductive parts and live parts	59
6.3.5	Protective provisions by means of bare conductive parts connected to the return circuit	60
6.3.6	Protective provisions by automatic disconnection of supply	60
6.4	Parts which can become hazardous due to inductive or capacitive coupling	60
7	Protective provisions for low voltage non-traction power supply systems	60
7.1	General	60
7.2	Protective provisions for electrical installations in the overhead contact line zone or the current collector zone	61
7.2.1	Equipment of protection Class I	61
7.2.2	Equipment of protection Class II	63
7.2.3	Cables	63
7.2.4	Low voltage connected equipment	63
7.3	Protective provisions for installations which are endangered by the traction power supply return circuit	63
7.3.1	Design of low voltage non-traction power supply	63
7.3.2	Low voltage power supply by a TT system on the railway side	64
7.3.3	Low voltage power supply by TN system	67
7.3.4	Low voltage power supply by IT system	69
7.3.5	Special provisions	71
8	Protective provisions where track systems, which are utilized for carrying traction return current, or/and overhead contact line systems pass through hazardous zones	74
8.1	General	74
8.2	Equipotential bonding	75
8.3	Parallel pipework	76

8.4	Insulating joints	76
8.5	Surge arrester	76
8.6	Overhead contact line of loading sidings	77
9	Limits for touch voltage and protective provisions against the danger of rail potential	77
9.1	General	77
9.1.1	Preconditions	77
9.1.2	Body voltage and touch voltage	77
9.1.3	Touch voltage at vehicles	77
9.1.4	Short-circuit duration	78
9.1.5	Voltage limits and time duration aspects	78
9.2	Touch voltage limits in AC railways	78
9.2.1	General	78
9.2.2	AC voltage limits for the safety of persons	79
9.3	Touch voltage limits in DC railways	82
9.3.1	General	82
9.3.2	DC voltage limits for the safety of persons	82
9.4	Access Control	85
10	Additional requirements	85
10.1	Traction substations and traction switching stations	85
10.2	Cables	85
10.2.1	General requirements	85
10.2.2	Cables in AC electric traction power supply systems	86
10.2.3	Cables in DC electric traction systems	86
10.3	Extended return circuit connections and earthing conductors	86
10.3.1	General requirements	86
10.3.2	Continuity of the extended return circuit	86
10.3.3	Cross bonding of the return circuit	87
10.3.4	Railway systems in which the traction current is confined within insulated conductors	87
10.4	Removing of decommissioned contact lines	87
10.5	Means of achieving safe isolation between sections	87
10.6	Lightning protection	87
Annex A (normative)	Clearances from standing surfaces for exceptional use on existing lines with restricted gauge	88
Annex B (informative)	Typical layouts of protective obstacles	90
B.1	General	90
B.2	Examples	92
Annex C (normative)	Warning sign	99
Annex D (informative)	Guiding values for rail potential gradient	100
D.1	AC railways	100
D.2	DC railways	101
Annex E (informative)	Effective touch voltage and body voltage with respect to the body current	102
E.1	Preconditions for the calculation	102
E.2	Impedances	102
E.3	Body current and related body voltage	105
Annex F (normative)	Measurement methods for effective touch voltages	108
Annex G (normative)	Use of voltage-limiting devices	109
G.1	General	109

G.2	Types.....	109
G.3	Technical requirements.....	109
	Bibliography.....	111

Figures

Figure 1	— Overhead contact line zone and current collector zone.....	26
Figure 2	— Overhead contact line zone and current collector zone for trolley bus systems and electric road vehicles using a bipolar contact line.....	28
Figure 3	— Design procedure to achieve protection against direct contact.....	30
Figure 4	— Manikin model to be used for the analysis of the arm's reach.....	32
Figure 5	— Minimum distances to accessible live parts from standing surfaces accessible to persons.....	34
Figure 6	— Application of taut string line method compared with manikin method.....	39
Figure 7	— Minimum distance behind electrically protective obstacles with openings.....	42
Figure 8	— Example for a gap between a standing surface and an electrically protective obstacle, side view.....	44
Figure 9	— Effect of an electrically protective obstacle on arms reach of person including an object, top view.....	45
Figure 10	— Live parts below standing surfaces.....	46
Figure 11	— Method for the determination of clearances for live parts on the outside of vehicles.....	48
Figure 12	— Example of an insulated obstacle beneath a structure.....	49
Figure 13	— Example of an insulated electrically protective obstacle beneath a structure for an unearthed installation.....	50
Figure 14	— Example of an insulated electrically protective obstacle beneath a structure for a bipolar overhead contact line in which the negative contact wire is earthed or connected to the return circuit of a tramway system.....	51
Figure 15	— Public level crossing, private level crossing.....	52
Figure 16	— Trackside structures.....	53
Figure 17	— Track-side telephone mounted on a signal-post.....	53
Figure 18	— Authorized trackside walking route.....	54
Figure 19	— Railway controlled crossing (depots, goods yard, station crossing).....	54
Figure 20	— Protection Class I equipment installed outside the overhead contact line zone and the current collector zone.....	62
Figure 21	— Typical TT system for AC railways.....	65
Figure 22	— Typical TT system for DC railways.....	66
Figure 23	— Typical TN system for AC railways.....	68
Figure 24	— Typical TN system for DC railways.....	69
Figure 25	— Typical IT system for AC railways.....	70
Figure 26	— TN system for AC railways with interconnected earth system.....	72
Figure 27	— TN system for AC railways with multiple supply points.....	73
Figure 28	— Disposition of rail-to-rail cross bonds and track-to-track cross bonds (double-rail illustration) and connection of the contact line in case of the loading siding having a contact line.....	76
Figure 29	— Location of a surge arrester outside the overhead contact line zone of a loading siding if there is a possibility of flashovers of the insulating pieces through lightning strikes.....	76
Figure 30	— Design of return circuit, with regard to permissible effective touch voltage by checking the rail potential or the effective touch voltage.....	79
Figure A.1	— Alternative clearances for existing lines/networks.....	89
Figure B.1	— Typical protective obstacles and obstacle combinations and their dimensions and properties.....	91

Figure B.2 — Inclined protective obstacle, total height 1,00 m, solid-wall	92
Figure B.3 — Solid-wall protective obstacle, total height 1,69 m (balustrade wall).....	93
Figure B.4 — Combined protective obstacle with an inclined part on the top of the main protective obstacle, total height 1,50 m.....	94
Figure B.5 — Combined protective obstacle with an inclined part (0,50 m width) on the standing surface level, total height 1,00 m.....	95
Figure B.6 — Combined protective obstacle with an inclined part (1,60 m width) on the standing surface level, total height 1,00 m.....	96
Figure B.7 — Combined protective obstacle with a total height of 1,80 m.....	97
Figure B.8 — Arrangement of three protective obstacles.....	98
Figure C.1 — Warning sign	99
Figure D.1 — Guidance values for the rail potential gradient measured at the mast in a right angle to the track of an AC railway.....	100
Figure E.1 — Equivalent circuit for the calculation of the permissible touch voltage	104

Tables

Table 1 — Electrical clearances	31
Table 2 — Protection clearances.....	31
Table 3 — Minimum vertical height V of accessible live parts above standing surfaces for public areas.....	35
Table 4 — Minimum distance d_O between live parts and an electrically protective obstacle	43
Table 5 — Maximum dimensions for small wholly and partly conductive parts	59
Table 6 — Types of low voltage non-traction supplies.....	64
Table 7 — Maximum permissible body voltages $U_{b, \max}$ in AC electric traction power supply systems as a function of time duration	80
Table 8 — Maximum permissible effective touch voltages $U_{te, \max}$ in AC electric traction power supply systems as a function of time duration.....	81
Table 9 — Maximum permissible body voltages $U_{b, \max}$ in DC electric traction power supply systems as a function of time duration	83
Table 10 — Maximum permissible effective touch voltages $U_{te, \max}$ in DC electric traction power supply systems as a function of time duration.....	83
Table D.1 — Guidance values for the rail potential gradient (see Figure D.1).....	101
Table E.1 — Body impedance Z_b , body resistance R_b and body current I_b	103
Table E.2 — Example of the maximum permissible prospective touch voltage for AC railways for short-term conditions and $R_a = 1\ 150\ \Omega$	105
Table E.3 — Body currents, body voltages and touch voltages as function of time duration in AC electric traction power supply systems.....	106
Table E.4 — Body currents, body voltages and touch voltages as function of time duration in DC electric traction power supply systems.....	107

European foreword

This document (EN 50122-1:2022) has been prepared by CLC/SC 9XC "Electric supply and earthing systems for public transport equipment and ancillary apparatus (Fixed installations)".

The following dates are fixed:

- latest date by which this document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2023-07-25
- latest date by which the national standards conflicting with this document have to be withdrawn (dow) 2025-07-25

This document supersedes EN 50122-1:2011 and all of its amendments and corrigenda (if any).

EN 50122-1:2022 includes the following significant technical changes with respect to EN 50122-1:2011:

- some definitions were modified;
- the dimensions for protection by clearance were modified, and there are now voltage dependent differences for high voltage electric traction power supply systems;
- methods for the use of protective obstacles were significantly changed.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a Standardization Request given to CENELEC by the European Commission and the European Free Trade Association.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

1 Scope

This document specifies requirements for the protective provisions relating to electrical safety in fixed installations associated with AC and/or DC traction systems and to any installations that can be endangered by the electric traction power supply system. This also includes requirements applicable to vehicles on electrified lines.

It also applies to all aspects of fixed installations which are necessary to ensure electrical safety during maintenance work within electric traction power supply systems.

This document applies to new electric traction power supply systems and major revisions to electric traction power supply systems for:

- a) railways;
- b) guided mass transport systems such as
 - 1) tramways,
 - 2) elevated and underground railways,
 - 3) mountain railways,
 - 4) trolleybus systems,
 - 5) electric traction power supply systems for road vehicles, which use an overhead contact line system, and
 - 6) magnetically levitated systems, which use a contact line system;
- c) material transportation systems.

This document does not apply to:

- a) electric traction power supply systems in underground mines,
- b) cranes, transportable platforms and similar transportation equipment on rails, temporary structures (e.g. exhibition structures) in so far as these are not supplied directly or via transformers from the contact line system and are not endangered by the electric traction power supply system,
- c) suspended cable cars,
- d) funicular railways,
- e) existing vehicles.

This document does not specify working rules for maintenance.

The requirements within this document related to protection against electric shock are applicable to persons only.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50119:2020, *Railway applications - Fixed installations - Electric traction overhead contact lines*

EN 50122-2:2022, *Railway applications – Fixed installations – Electrical safety, earthing and the return circuit - Part 2: Provisions against the effects of stray currents caused by d.c. traction systems*

EN 50124-1:2017, *Railway applications - Insulation coordination - Part 1: Basic requirements - Clearances and creepage distances for all electrical and electronic equipment*

EN 50153:2014,¹ *Railway applications - Rolling stock - Protective provisions relating to electrical hazards*

EN 50163:2004,² *Railway applications - Supply voltages of traction systems*

EN 50341 (series), *Overhead electrical lines exceeding AC 1 kV*

EN 50522:2010, *Earthing of power installations exceeding 1 kV a.c.*

EN 60529:1991,³ *Degrees of protection provided by enclosures (IP Code) (IEC 60529:1989)*

EN 60898-1:2019, *Electrical accessories - Circuit-breakers for overcurrent protection for household and similar installations - Part 1: Circuit-breakers for a.c. operation (IEC 60898-1:2016)*

EN 61140:2016, *Protection against electric shock - Common aspects for installation and equipment (IEC 61140:2016)*

EN 61936-1:2010,⁴ *Power installations exceeding 1 kV a.c. - Part 1: Common rules (IEC 61936-1:2010)*

EN 62305 (series), *Protection against lightning (IEC 62305 series)*

HD 60364-4-41:2017,⁵ *Low-voltage electrical installations – Part 4-41: Protection for safety – Protection against electric shock (IEC 60364-4-41:2005, modified)*

IEC 60755:2017, *General safety requirements for residual current operated protective devices*

ISO 3864-1:2011, *Graphical symbols — Safety colours and safety signs — Part 1: Design principles for safety signs and safety markings*

ISO 7010:2019, *Graphical symbols — Safety colours and safety signs — Registered safety signs*

¹ As impacted by EN 50153:2014/A1:2017 and EN 50153:2014/A2:2020.

² As impacted by EN 50163:2004/AC:2013 and EN 50163:2004/A2:2020.

³ As impacted by EN 60529:1991/A1:2000 and EN 60529:1991/A2:2013.

⁴ As impacted by EN 61936-1:2010/AC:2011, EN 61936-1:2010:2013 and EN 61936-1:2010/A1:2014.

⁵ As impacted by HD 60364-4-41:2017/A11:2017 and HD 60364-4-41:2017/A12:2019.