

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Universal serial bus interfaces for data and power –
Part 1-3: Common components – USB Type-C® Cable and Connector
Specification**

**Interfaces de bus universel en série pour les données et l'alimentation
électrique –
Partie 1-3: Composants communs – Spécification des câbles et connecteurs
USB Type-C®**



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2022 USB-IF

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from IEC, or USB-IF at the respective address given below. Any questions about USB-IF copyright should be addressed to the USB-IF. Enquiries about obtaining additional rights to this publication and other information requests should be addressed to the IEC or your local IEC member National Committee.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

USB Implementers Forum, Inc.
3855 S.W. 153rd Drive
Beaverton, OR 97003
United States of America
Tel. +1 503-619-0426
Admin@usb.org
www.usb.org

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC -

webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 300 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 19 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Universal serial bus interfaces for data and power –
Part 1-3: Common components – USB Type-C® Cable and Connector
Specification**

**Interfaces de bus universel en série pour les données et l'alimentation
électrique –
Partie 1-3: Composants communs – Spécification des câbles et connecteurs
USB Type-C®**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 33.120.20; 33.120.30; 35.200

ISBN 978-2-8322-5289-5

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

INTERNATIONAL ELECTROTECHNICAL COMMISSION

UNIVERSAL SERIAL BUS INTERFACES FOR DATA AND POWER –

Part 1-3: Common components – USB Type-C® Cable and Connector Specification

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62680-1-3 has been prepared by technical area 18: Multimedia home systems and applications for end-user networks, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this standard was prepared by the USB Implementers Forum (USB-IF). The structure and editorial rules used in this publication reflect the practice of the organization which submitted it.

The text of this International Standard is based on the following documents:

Draft	Report on voting
100/3715/CDV	100/3762/RVC

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

A list of all parts in the IEC 62680 series, published under the general title *Universal serial bus interfaces for data and power*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The IEC 62680 series is based on a series of specifications that were originally developed by the USB Implementers Forum (USB-IF). These specifications were submitted to the IEC under the auspices of a special agreement between the IEC and the USB-IF.

This standard is the USB-IF publication Universal Serial Bus Type-C Cable and Connector Specification Revision 2.0.

The USB Implementers Forum, Inc.(USB-IF) is a non-profit corporation founded by the group of companies that developed the Universal Serial Bus specification. The USB-IF was formed to provide a support organization and forum for the advancement and adoption of Universal Serial Bus technology. The Forum facilitates the development of high-quality compatible USB peripherals (devices), and promotes the benefits of USB and the quality of products that have passed compliance testing.

ANY USB SPECIFICATIONS ARE PROVIDED TO YOU "AS IS, "WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE. THE USB IMPLEMENTERS FORUM AND THE AUTHORS OF ANY USB SPECIFICATIONS DISCLAIM ALL LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATING TO USE OR IMPLEMENTATION OR INFORMATION IN THIS SPECIFICATION.

THE PROVISION OF ANY USB SPECIFICATIONS TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS.

Entering into USB Adopters Agreements may, however, allow a signing company to participate in a reciprocal, RAND-Z licensing arrangement for compliant products. For more information, please see:

<https://www.usb.org/documents>

IEC DOES NOT TAKE ANY POSITION AS TO WHETHER IT IS ADVISABLE FOR YOU TO ENTER INTO ANY USB ADOPTERS AGREEMENTS OR TO PARTICIPATE IN THE USB IMPLEMENTERS FORUM."

Preview generated by EVS

Universal Serial Bus Type-C Cable and Connector Specification

Release 2.1
May 2021

This document is a preview generated by EVS

**Copyright © 2014-2021, USB 3.0 Promoter Group:
Apple Inc., HP Inc., Intel Corporation, Microsoft
Corporation, Renesas, STMicroelectronics, and Texas Instruments
All rights reserved.**

NOTE: Adopters may only use the USB Type-C® cable and connector to implement USB or third-party functionality as expressly described in this Specification; all other uses are prohibited.

LIMITED COPYRIGHT LICENSE: The USB 3.0 Promoters grant a conditional copyright license under the copyrights embodied in the USB Type-C Cable and Connector Specification to use and reproduce the Specification for the sole purpose of, and solely to the extent necessary for, evaluating whether to implement the Specification in products that would comply with the specification. Without limiting the foregoing, use of the Specification for the purpose of filing or modifying any patent application to target the Specification or USB compliant products is not authorized. Except for this express copyright license, no other rights or licenses are granted, including without limitation any patent licenses. In order to obtain any additional intellectual property licenses or licensing commitments associated with the Specification a party must execute the USB 3.0 Adopters Agreement. NOTE: By using the Specification, you accept these license terms on your own behalf and, in the case where you are doing this as an employee, on behalf of your employer.

INTELLECTUAL PROPERTY DISCLAIMER

THIS SPECIFICATION IS PROVIDED TO YOU “AS IS” WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE. THE AUTHORS OF THIS SPECIFICATION DISCLAIM ALL LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATING TO USE OR IMPLEMENTATION OF INFORMATION IN THIS SPECIFICATION. THE PROVISION OF THIS SPECIFICATION TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS.

All implementation examples and reference designs contained within this Specification are included as part of the limited patent license for those companies that execute the USB 3.0 Adopters Agreement.

USB Type-C®, USB-C® and USB4™ are trademarks of the Universal Serial Bus Implementers Forum (USB-IF). DisplayPort™ is a trademark of VESA. All product names are trademarks, registered trademarks, or service marks of their respective owners.

Thunderbolt™ is a trademark of Intel Corporation. You may only use the Thunderbolt™ trademark or logo in conjunction with products designed to this specification that complete proper certification and executing a Thunderbolt™ trademark license – see usb.org/compliance for further information.

CONTENTS

Specification Work Group Chairs / Specification Editors.....	19
Specification Work Group Contributors	19
Pre-Release Draft Industry Reviewing Companies That Provided Feedback	25
Revision History.....	25
1 Introduction	26
1.1 Purpose	26
1.2 Scope.....	26
1.3 Related Documents	26
1.4 Conventions	27
1.4.1 Precedence	27
1.4.2 Keywords	27
1.4.3 Numbering.....	28
1.5 Terms and Abbreviations.....	28
2 Overview	33
2.1 Introduction	33
2.2 USB Type-C Receptacles, Plugs and Cables.....	34
2.3 Configuration Process	35
2.3.1 Source-to-Sink Attach/Detach Detection	35
2.3.2 Plug Orientation/Cable Twist Detection.....	36
2.3.3 Initial Power (Source-to-Sink) Detection and Establishing the Data (Host-to-Device) Relationship	36
2.3.4 USB Type-C VBUS Current Detection and Usage	37
2.3.5 USB PD Communication	37
2.3.6 Functional Extensions	37
2.4 VBUS	38
2.5 VCONN	38
2.6 Hubs	39
3 Mechanical.....	40
3.1 Overview	40
3.1.1 Compliant Connectors	40
3.1.2 Compliant Cable Assemblies	40
3.1.3 Compliant USB Type-C to Legacy Cable Assemblies.....	41
3.1.4 Compliant USB Type-C to Legacy Adapter Assemblies.....	41
3.2 USB Type-C Connector Mating Interfaces	42
3.2.1 Interface Definition	42
3.2.2 Reference Designs	63
3.2.3 Pin Assignments and Descriptions.....	71
3.3 Cable Construction and Wire Assignments	72
3.3.1 Cable Construction (Informative)	72
3.3.2 Wire Assignments.....	74
3.3.3 Wire Gauges and Cable Diameters (Informative)	75
3.4 Standard USB Type-C Cable Assemblies	77
3.4.1 USB Full-Featured Type-C Cable Assembly.....	77
3.4.2 USB 2.0 Type-C Cable Assembly	78
3.4.3 USB Type-C Captive Cable Assemblies.....	79
3.4.4 USB Type-C Thumb Drive Assemblies.....	79
3.5 Legacy Cable Assemblies	79

3.5.1	USB Type-C to <i>USB 3.1</i> Standard-A Cable Assembly	80
3.5.2	USB Type-C to <i>USB 2.0</i> Standard-A Cable Assembly	82
3.5.3	USB Type-C to <i>USB 3.1</i> Standard-B Cable Assembly	83
3.5.4	USB Type-C to <i>USB 2.0</i> Standard-B Cable Assembly	84
3.5.5	USB Type-C to <i>USB 2.0</i> Mini-B Cable Assembly	85
3.5.6	USB Type-C to <i>USB 3.1</i> Micro-B Cable Assembly	86
3.5.7	USB Type-C to <i>USB 2.0</i> Micro-B Cable Assembly	87
3.6	Legacy Adapter Assemblies	88
3.6.1	USB Type-C to <i>USB 3.1</i> Standard-A Receptacle Adapter Assembly	88
3.6.2	USB Type-C to <i>USB 2.0</i> Micro-B Receptacle Adapter Assembly	90
3.7	Electrical Characteristics	91
3.7.1	Raw Cable (Informative)	91
3.7.2	USB Type-C to Type-C Passive Cable Assemblies (Normative)	92
3.7.3	Mated Connector (Informative – USB 3.2 Gen2 and USB4 Gen2)	111
3.7.4	Receptacle Connector SI Requirements and Testing (Normative – USB4 Gen3)	114
3.7.5	USB Type-C to Legacy Cable Assemblies (Normative)	115
3.7.6	USB Type-C to USB Legacy Adapter Assemblies (Normative)	119
3.7.7	Shielding Effectiveness Requirements (Normative)	120
3.7.8	DC Electrical Requirements (Normative)	122
3.8	Mechanical and Environmental Requirements (Normative)	125
3.8.1	Mechanical Requirements	126
3.8.2	Environmental Requirements	131
3.9	Docking Applications (Informative)	132
3.10	Implementation Notes and Design Guides	133
3.10.1	EMC Management (Informative)	133
3.10.2	Stacked and Side-by-Side Connector Physical Spacing (Informative)	135
3.10.3	Cable Mating Considerations (Informative)	136
3.11	Extended Power Range (EPR) Cables	136
3.11.1	Electrical Requirements	136
3.11.2	EPR Cable Identification Requirements	137
4	Functional	138
4.1	Signal Summary	138
4.2	Signal Pin Descriptions	138
4.2.1	SuperSpeed USB Pins	138
4.2.2	USB 2.0 Pins	138
4.2.3	Auxiliary Signal Pins	139
4.2.4	Power and Ground Pins	139
4.2.5	Configuration Pins	139
4.3	Sideband Use (SBU)	139
4.4	Power and Ground	139
4.4.1	IR Drop	139
4.4.2	V _{BUS}	140
4.4.3	V _{CONN}	142
4.5	Configuration Channel (CC)	147
4.5.1	Architectural Overview	147
4.5.2	CC Functional and Behavioral Requirements	160
4.5.3	USB Port Interoperability Behavior	195
4.6	Power	213

4.6.1	Power Requirements during USB Suspend	214
4.6.2	VBUS Power Provided Over a USB Type-C Cable	215
4.7	USB Hubs	220
4.8	Power Sourcing and Charging	221
4.8.1	DFP as a Power Source	221
4.8.2	Non-USB Charging Methods	223
4.8.3	Sinking Host	223
4.8.4	Sourcing Device	224
4.8.5	Charging a System with a Dead Battery	224
4.8.6	USB Type-C Multi-Port Chargers	224
4.9	Electronically Marked Cables	227
4.9.1	Parameter Values	228
4.9.2	Active Cables	228
4.10	VCONN-Powered Accessories (VPAs) and VCONN-Powered USB Devices (VPDs)	228
4.10.1	VCONN-Powered Accessories (VPAs)	228
4.10.2	VCONN-Powered USB Devices (VPDs)	229
4.11	Parameter Values	230
4.11.1	Termination Parameters	230
4.11.2	Timing Parameters	232
4.11.3	Voltage Parameters	235
5	USB4 Discovery and Entry	237
5.1	Overview of the Discovery and Entry Process	237
5.2	USB4 Functional Requirements	238
5.2.1	USB4 Host Functional Requirements	238
5.2.2	USB4 Device Functional Requirements	238
5.2.3	USB4 Alternate Mode Support	238
5.2.3.1	USB4 Alternate Mode Support on Hosts	238
5.2.3.2	USB4 Alternate Mode Support on Hubs and USB4-based Docks	238
5.3	USB4 Power Requirements	238
5.3.1	Source Power Requirements	239
5.3.2	Sink Power Requirements	239
5.3.3	Device Power Management Requirements	239
5.4	USB4 Discovery and Entry Flow Requirements	240
5.4.1	USB Type-C Initial Connection	240
5.4.2	USB Power Delivery Contract	240
5.4.3	USB4 Discovery and Entry Flow	240
5.4.3.1	USB4 Device Discovery (SOP)	241
5.4.3.2	USB4 Cable Discovery (SOP')	242
5.4.3.3	USB4 Operational Entry	244
5.4.4	USB4 Post-Entry Operation	244
5.4.4.1	During USB4 Operation	244
5.4.4.2	Exiting USB4 Operation	244
5.5	USB4 Hub Connection Requirements	244
5.5.1	USB4 Hub Port Initial Connection Requirements	245
5.5.2	USB4 Hub UFP and Host Capabilities Discovery	245
5.5.3	Hub DFP Connection Requirements	246
5.5.3.1	Speculative Connections	246
5.5.3.2	Operational Connections	246

5.5.4	Hub Ports Connection Behavior Flow Examples	246
5.5.5	Connecting to Downstream USB4 Hubs	252
5.5.6	Fallback Functional Requirements for USB4 Hubs	252
5.6	USB4 Device Connection Requirements	252
5.6.1	Fallback Mapping of USB4 Peripheral Functions to USB Device Class Types	252
5.7	Parameter Values	253
5.7.1	Timing Parameters	253
6	Active Cables	255
6.1	USB Type-C State Machine	257
6.2	USB PD Requirements	257
6.2.1	Active Cable USB PD Requirements	259
6.2.2	USB PD Messages for OIAC	260
6.2.3	Short Active Cable Behaviors in Response to Power Delivery Events	270
6.3	OIAC Connection Flow and State Diagrams	270
6.3.1	OIAC Connection Flow – Discovery – Phase 1	271
6.3.2	OIAC Connection Flow – Reboot – Phase 2	272
6.3.3	OIAC Connection Flow – Configuration – Phase 3	273
6.3.4	OIAC Connection State Diagram Plug-A	276
6.3.5	OIAC Connection State Diagram Plug-B	283
6.4	Active Cable Power Requirements	288
6.4.1	VBUS Requirements	288
6.4.2	OIAC VBUS Requirements	288
6.4.3	USB PD Rules in Active State	289
6.4.4	VCONN Requirements	290
6.5	Mechanical	290
6.5.1	Thermal	290
6.5.2	Plug Spacing	291
6.6	Electrical Requirements	291
6.6.1	Shielding Effectiveness Requirement	291
6.6.2	Low Speed Signal Requirement	291
6.6.3	USB 2.0	292
6.6.4	USB 3.2	293
6.6.5	USB4	299
6.6.6	Return Loss	312
6.7	Active Cables That Support Alternate Modes	312
6.7.1	Discover SVIDs	312
6.7.2	Discover Modes	313
6.7.3	Enter/Exit Modes	313
6.7.4	Power in Alternate Modes	313
A	Audio Adapter Accessory Mode	314
A.1	Overview	314
A.2	Detail	314
A.3	Electrical Requirements	315
A.4	Example Implementations	316
A.4.1	Passive 3.5 mm to USB Type-C Adapter – Single Pole Detection Switch	316
A.4.2	3.5 mm to USB Type-C Adapter Supporting 500 mA Charge-Through	317
B	Debug Accessory Mode	319

B.1	Overview	319
B.2	Functional	319
B.2.1	Signal Summary	320
B.2.2	Port Interoperability	320
B.2.3	Debug Accessory Mode Entry	320
B.2.4	Connection State Diagrams	321
B.2.5	DTS Port Interoperability Behavior	329
B.2.6	Orientation Detection	337
B.3	Security/Privacy Requirements:	338
C	USB Type-C Digital Audio	339
C.1	Overview	339
C.2	USB Type-C Digital Audio Specifications	339
D	Thermal Design Considerations for Active Cables	341
D.1	Introduction	341
D.2	Model	341
D.2.1	Assumptions	341
D.2.2	Model Architecture	342
D.2.3	Heat Sources	342
D.2.4	Heat Flow	343
D.3	USB 3.2 Single Lane Active Cable	344
D.3.1	USB 3.2 Single-Lane Active Cable Design Considerations	344
D.4	Dual-Lane Active Cables	346
D.4.1	USB 3.2 Dual-Lane Active Cable Design Considerations	347
D.4.2	USB 3.2 Dual-Lane Active Cable in a Multi-Port Configuration	349
D.5	USB 3.2 Host and Device Design Considerations	350
D.5.1	Heat Spreading or Heat Sinking from Host or Device	350
D.5.2	Motherboard Temperature Control	351
D.5.3	Wider Port Spacing for Multi-Port Applications	351
D.5.4	Power Policies	351
E	Alternate Modes	352
E.1	Alternate Mode Architecture	352
E.2	Alternate Mode Requirements	352
E.2.1	Alternate Mode Pin Reassignment	353
E.2.2	Alternate Mode Electrical Requirements	353
E.3	Parameter Values	356
E.4	Example Alternate Mode – USB DisplayPort™ Dock	356
E.4.1	USB DisplayPort™ Dock Example	357
E.4.2	Functional Overview	357
E.4.3	Operational Summary	358
F	Thunderbolt 3 Compatibility Discovery and Entry	360
F.1	TBT3 Compatibility Mode Functional Requirements	360
F.1.1	TBT3-Compatible Power Requirements	360
F.1.2	TBT3-Compatible Host Requirements	360
F.1.3	TBT3-Compatible Device Upstream Requirements	360
F.1.4	TBT3-Compatible Device Downstream Requirements	360
F.1.5	TBT3-Compatible Self-Powered Device Without Predefined Upstream Port Rules	361
F.1.6	TBT3-Compatible Devices with a Captive Cable	361
F.2	TBT3 Discovery and Entry Flow	361

F.2.1	TBT3 Passive Cable Discover Identity Responses	363
F.2.2	TBT3 Active Cable Discover Identity Responses	365
F.2.3	TBT3 Device Discover Identity Responses	368
F.2.4	TBT3 Discover SVID Responses	369
F.2.5	TBT3 Device Discover Mode Responses	370
F.2.6	TBT3 Cable Discover Mode Responses	371
F.2.7	TBT3 Cable Enter Mode Command	372
F.2.8	TBT3 Device Enter Mode Command	373
F.2.9	TBT3 Cable Functional Difference Summary	374
G	Extracting Pulse Response from Sampled Data and Calculating Non-Linearity Noise	375
H	USB PD High-Voltage Design Considerations	377
H.1	Potential for Arcing Damage During Cable Withdrawal	377
H.2	USB Type-C Cable Withdrawal Arcing Due to Sink Discharge	377
H.3	Mitigating Arcing Damage During Cable Withdrawal	379
H.3.1	Limiting Sink Discharge Rate	380
H.3.2	Load Removal	381
H.3.3	Limiting Source Current Capability	383

FIGURES

Figure 2-1	USB Type-C Receptacle Interface (Front View)	33
Figure 2-2	USB Full-Featured Type-C Plug Interface (Front View)	34
Figure 3-1	USB Type-C Receptacle Interface Dimensions	45
Figure 3-2	Reference Design USB Type-C Plug External EMC Spring Contact Zones	48
Figure 3-3	USB Full-Featured Type-C Plug Interface Dimensions	49
Figure 3-4	Reference Footprint for a USB Type-C Vertical Mount Receptacle (Informative)	52
Figure 3-5	Reference Footprint for a USB Type-C Dual-Row SMT Right Angle Receptacle (Informative)	53
Figure 3-6	Reference Footprint for a USB Type-C Hybrid Right-Angle Receptacle (Informative)	54
Figure 3-7	Reference Footprint for a USB Type-C Mid-Mount Dual-Row SMT Receptacle (Informative)	55
Figure 3-8	Reference Footprint for a USB Type-C Mid-Mount Hybrid Receptacle (Informative)	56
Figure 3-9	Reference Footprint for a USB 2.0 Type-C Through Hole Right Angle Receptacle (Informative)	57
Figure 3-10	Reference Footprint for a USB 2.0 Type-C Single Row Right Angle Receptacle (Informative)	58
Figure 3-11	USB 2.0 Type-C Plug Interface Dimensions	60
Figure 3-12	USB Type-C Plug EMC Shielding Spring Tip Requirements	63
Figure 3-13	Reference Design of Receptacle Mid-Plate	64
Figure 3-14	Reference Design of the Retention Latch	64
Figure 3-15	Illustration of the Latch Soldered to the Paddle Card Ground	65
Figure 3-16	Reference Design of the USB Full-Featured Type-C Plug Internal EMC Spring	66
Figure 3-17	Reference Design of the USB 2.0 Type-C Plug Internal EMC Spring	67
Figure 3-18	Reference Design of Internal EMC Pad	68
Figure 3-19	Reference Design of a USB Type-C Receptacle with External EMC Springs	69
Figure 3-20	Reference Design for a USB Full-Featured Type-C Plug Paddle Card	70
Figure 3-21	Illustration of a USB Full-Featured Type-C Cable Cross Section, a Coaxial Wire Example with Vconn	73
Figure 3-22	Illustration of a USB Full-Featured Type-C Cable Cross Section, a Coaxial Wire Example without Vconn	73
Figure 3-23	USB Full-Featured Type-C Standard Cable Assembly	77
Figure 3-24	USB Type-C to USB 3.1 Standard-A Cable Assembly	80
Figure 3-25	USB Type-C to USB 2.0 Standard-A Cable Assembly	82
Figure 3-26	USB Type-C to USB 3.1 Standard-B Cable Assembly	83

Figure 3-27	USB Type-C to USB 2.0 Standard-B Cable Assembly	84
Figure 3-28	USB Type-C to USB 2.0 Mini-B Cable Assembly	85
Figure 3-29	USB Type-C to USB 3.1 Micro-B Cable Assembly	86
Figure 3-30	USB Type-C to USB 2.0 Micro-B Cable Assembly	87
Figure 3-31	USB Type-C to USB 3.1 Standard-A Receptacle Adapter Assembly	88
Figure 3-32	USB Type-C to USB 2.0 Micro-B Receptacle Adapter Assembly	90
Figure 3-33	Illustration of Test Points for a Mated Cable Assembly	92
Figure 3-34	Recommended Differential Insertion Loss Requirement (USB 3.2 Gen2 and USB4 Gen2)	93
Figure 3-35	Recommended Differential Return Loss Requirement	93
Figure 3-36	Recommended Differential Crosstalk Requirement	94
Figure 3-37	Recommended Differential Near-End and Far-End Crosstalk Requirement between USB D+/D- Pair and TX/RX Pair	94
Figure 3-38	Recommended Differential Insertion Loss Requirement (USB4 Gen3)	95
Figure 3-39	Illustration of Insertion Loss Fit at Nyquist Frequency	96
Figure 3-40	Input Pulse Spectrum	96
Figure 3-41	IMR Limit as Function of ILfitatNq	97
Figure 3-42	IRL Limit as Function of ILfitatNq	99
Figure 3-43	Differential-to-Common-Mode Conversion Requirement	99
Figure 3-44	IMR Limit as Function of ILfit at 10 GHz (USB4 Gen3)	102
Figure 3-45	Definition of Port, Victim, and Aggressor	103
Figure 3-46	IXT_DP and IXT_USB Limit as Function of ILfit at 10 GHz (USB4 Gen3)	103
Figure 3-47	IRL Limit as Function of ILfitatNq (USB4 Gen3)	104
Figure 3-48	Differential-to-Common-Mode Conversion Requirement (USB4 Gen3)	104
Figure 3-49	Cable Assembly in System	105
Figure 3-50	Requirement for Differential Coupling between CC and D+/D-	107
Figure 3-51	Requirement for Single-Ended Coupling between CC and D- in USB 2.0 Type-C Cables	107
Figure 3-52	Requirement for Single-Ended Coupling between CC and D- in USB Full-Featured Type-C Cables	108
Figure 3-53	Requirement for Differential Coupling between Vbus and D+/D-	108
Figure 3-54	Requirement for Single-Ended Coupling between SBU_A and SBU_B	109
Figure 3-55	Requirement for Single-Ended Coupling between SBU_A/SBU_B and CC	109
Figure 3-56	Requirement for Coupling between SBU_A and differential D+/D-, and SBU_B and differential D+/D-	110
Figure 3-57	Illustration of USB Type-C Mated Connector	111
Figure 3-58	Recommended Impedance Limits of a USB Type-C Mated Connector	111
Figure 3-59	Recommended Ground Void Dimensions for USB Type-C Receptacle	112
Figure 3-60	Recommended Differential Near-End and Far-End Crosstalk Limits between D+/D- Pair and TX/RX Pairs	113
Figure 3-61	Recommended Limits for Differential-to-Common-Mode Conversion	114
Figure 3-62	IMR Limit as Function of ILfitatNq for USB Type-C to Legacy Cable Assembly	118
Figure 3-63	IRL Limit as Function of ILfitatNq for USB Type-C to Legacy Cable Assembly	118
Figure 3-64	Cable Assembly Shielding Effectiveness Testing	121
Figure 3-65	Shielding Effectiveness Pass/Fail Criteria	122
Figure 3-66	LLCR Measurement Diagram	123
Figure 3-67	Temperature Measurement Point	124
Figure 3-68	Example Current Rating Test Fixture Trace Configuration	125
Figure 3-69	Example of 4-Axis Continuity Test Fixture	127
Figure 3-70	Example Wrenching Strength Test Fixture for Plugs without Overmold	129
Figure 3-71	Reference Wrenching Strength Continuity Test Fixture	129
Figure 3-72	Example of Wrenching Strength Test Mechanical Failure Point	130
Figure 3-73	Wrenching Strength Test with Cable in Fixture	130
Figure 3-74	USB Type-C Cable Receptacle Flange Example	133
Figure 3-75	EMC Guidelines for Side Latch and Mid-plate	134
Figure 3-76	EMC Finger Connections to Plug Shell	134
Figure 3-77	EMC Pad Connections to Receptacle Shell	135
Figure 3-78	Examples of Connector Apertures	135
Figure 3-79	Recommended Minimum Spacing between Connectors	135
Figure 3-80	Recommended Minimum Plug Overmold Clearance	136
Figure 3-81	Cable Plug Overmold and an Angled Surface	136
Figure 4-1	Cable IR Drop	140

Figure 4-2 Cable IR Drop for powered cables.....	140
Figure 4-3 Logical Model for Single-Lane Data Bus Routing across USB Type-C-based Ports	149
Figure 4-4 Logical Model for USB Type-C-based Ports for a Single-Lane Direct Connect Device	149
Figure 4-5 Pull-Up/Pull-Down CC Model.....	151
Figure 4-6 Current Source/Pull-Down CC Model	151
Figure 4-7 Source Functional Model for CC1 and CC2	154
Figure 4-8 Source Functional Model Supporting USB PD PR_Swap	155
Figure 4-9 Sink Functional Model for CC1 and CC2.....	155
Figure 4-10 Sink Functional Model Supporting USB PD PR_Swap and Vconn_Swap	156
Figure 4-11 DRP Functional Model for CC1 and CC2	156
Figure 4-12 Connection State Diagram: Source	161
Figure 4-13 Connection State Diagram: Sink.....	162
Figure 4-14 Connection State Diagram: Sink with Accessory Support.....	163
Figure 4-15 Connection State Diagram: DRP	164
Figure 4-16 Connection State Diagram: DRP with Accessory and Try.SRC Support	165
Figure 4-17 Connection State Diagram: DRP with Accessory and Try.SNK Support.....	166
Figure 4-18 Connection State Diagram: Charge-Through VPD.....	167
Figure 4-19 Sink Power Sub-States	189
Figure 4-20 Passive Cable eMarker State Diagram.....	190
Figure 4-21 Active Cable eMarker State Diagram	191
Figure 4-22 Cable Ra Management State Diagram.....	192
Figure 4-23 Source to Sink Functional Model	195
Figure 4-24 Source to DRP Functional Model.....	196
Figure 4-25 DRP to Sink Functional Model	197
Figure 4-26 DRP to DRP Functional Model – CASE 1	198
Figure 4-27 DRP to DRP Functional Model – CASE 2 & 3.....	199
Figure 4-28 Source to Source Functional Model.....	201
Figure 4-29 Sink to Sink Functional Model.....	201
Figure 4-30 DRP to VPD Model	202
Figure 4-31 Example DRP to Charge-Through Vconn-Powered USB Device Model.....	203
Figure 4-32 Source to Legacy Device Port Functional Model.....	210
Figure 4-33 Legacy Host Port to Sink Functional Model.....	210
Figure 4-34 DRP to Legacy Device Port Functional Model.....	212
Figure 4-35 Legacy Host Port to DRP Functional Model	213
Figure 4-36 Sink Monitoring for Current in Pull-Up/Pull-Down CC Model.....	216
Figure 4-37 Sink Monitoring for Current in Current Source/Pull-Down CC Model	217
Figure 4-38 USB PD over CC Pins	218
Figure 4-39 USB PD BMC Signaling over CC.....	218
Figure 4-40 USB Type-C Cable's Output as a Function of Load for Non-PD-based USB Type-C Charging	222
Figure 4-41 0 – 3 A USB PD-based Charger USB Type-C Cable's Output as a Function of Load ..	223
Figure 4-42 3 – 5 A USB PD-based Charger USB Type-C Cable's Output as a Function of Load ..	223
Figure 4-43 Electronically Marked Cable with Vconn connected through the cable	227
Figure 4-44 Electronically Marked Cable with SOP' at both ends	228
Figure 4-45 Example Charge-Through Vconn-Power USB Device Use Case	230
Figure 4-46 DRP Timing.....	233
Figure 5-1 USB4 Discovery and Entry Flow Model.....	241
Figure 5-2 USB4 Hub with USB4 Host and Device Connection Flow Alignment.....	247
Figure 5-3 USB4 Hub with USB 3.2 Host and USB4 Device Host Connection Flow.....	248
Figure 5-4 USB4 Hub with USB4 Host and USB 3.2 Device Connection Flow	249
Figure 5-5 USB4 Hub with USB 3.2 Host and Device Connection Flow.....	250
Figure 5-6 USB4 Hub with USB4 Host and DP Alt Mode Device Connection Flow	251
Figure 5-7 USB4 Hub with USB 3.2 Host and DP Alt Mode Device Connection Flow	252
Figure 6-1 Electronically Marked Short Active Cable with SOP' Only	258
Figure 6-2 Electronically Marked Short Active Cable with SOP' and SOP".....	258
Figure 6-3 Electronically Marked Optically Isolated Active Cable	259
Figure 6-4 OIAC USB PD Message Forwarding	265
Figure 6-5 OIAC Successful Data Role Swap.....	268
Figure 6-6 OIAC Rejected Data Role Swap	268
Figure 6-7 OIAC Wait Data Role Swap	269

Figure 6-8	OIAC Initiator Reject Data Role Swap	269
Figure 6-9	OIAC Initiator Wait Data Role Swap	270
Figure 6-10	OIAC Discovery – Phase 1	272
Figure 6-11	OIAC Reboot – Phase 2	273
Figure 6-12	OIAC Plug-A Configure as DFP – Phase 3	274
Figure 6-13	OIAC Plug-A Configure as UFP – Phase 3	275
Figure 6-14	OIAC Plug-A No Connection Possible Billboard – Phase 3	276
Figure 6-15	OIAC Plug-A State Diagram Part 1 (Phase 1 and 2)	277
Figure 6-16	OIAC Plug-A State Diagram Part 2 (Phase 3)	278
Figure 6-17	OIAC Plug-B State Diagram	284
Figure 6-18	Active Cable Topologies	293
Figure 6-19	Illustrations of Usages for OIAC That Require an Adapter or Hub	295
Figure 6-20	SuperSpeed USB Electrical Test Points	296
Figure 6-21	SuperSpeed USB Compliance Test Setup	297
Figure 6-22	Compliance Points Definition	300
Figure 6-23	RX Differential Return-Loss Mask	301
Figure 6-24	Active Cable Compliance Test Setup	302
Figure 6-25	Example for Transmitter Frequency Variation During Clock Switching	304
Figure 6-26	Active Cable Functional Test Setup	305
Figure 6-27	Linear Re-driver-based Active Cable Compliance Setup	306
Figure 6-28	Gain Parameters Specified for the Linear Re-driver Active Cable	309
Figure 6-29	OUTPUT_NOISE Limit Versus ILfitatNq	310
Figure A-1	Example Passive 3.5 mm to USB Type-C Adapter	317
Figure A-2	Example 3.5 mm to USB Type-C Adapter Supporting 500 mA Charge-Through	318
Figure B-1	USB Type-C Debug Accessory Layered Behavior	319
Figure B-2	DTS Plug Interface	320
Figure B-3	Connection State Diagram: DTS Source	321
Figure B-4	Connection State Diagram: DTS Sink	322
Figure B-5	Connection State Diagram: DTS DRP	322
Figure B-6	TS Sink Power Sub-States	327
Figure D-1	Active Cable Model (Single Port, Top Mount Receptacle)	342
Figure D-2	Model Architecture	342
Figure D-3	Heat Sources and Heat Flow Paths	343
Figure D-4	Vertically Stacked Horizontal Connectors 3x1 Configuration (VERT)	344
Figure D-5	Horizontally Stacked Vertical Connectors 1x3 Configuration (HZ90)	345
Figure D-6	Horizontally Stacked Horizontal Connector 1x3 Configuration (HORZ)	345
Figure D-7	USB 3.2 Single-Lane 3A Active Cable in a 3-Port Configuration	346
Figure D-8	USB 3.2 Single-Lane 5A Active Cable in a 3-Port Configuration	346
Figure D-9	Impact of Over-mold Power PO and Thermal Boundary Temperature TMB at 3 A Vbus in a Single Port Configuration	348
Figure D-10	Impact of Over-mold Power PO and Thermal Boundary Temperature TMB at 5 A Vbus in a Single Port Configuration	348
Figure D-11	USB 3.2 Active Cable Dongle Design (One End Shown)	349
Figure D-12	USB 3.2 Dual-Lane 3A Active Cable in a 3-Port Configuration	349
Figure D-13	USB 3.2 Dual-Lane 5A Active Cable in a 3-Port Configuration	350
Figure D-14	Example: Additional Heat Spreader on Receptacle in Host or Device	351
Figure D-15	Example: Heat Sinking by Chassis of Host or Device	351
Figure E-1	Pins Available for Reconfiguration over the Full-Featured Cable	353
Figure E-2	Pins Available for Reconfiguration for Direct Connect Applications	353
Figure E-3	Alternate Mode Implementation using a USB Type-C to USB Type-C Cable	355
Figure E-4	Alternate Mode Implementation using a USB Type-C to Alternate Mode Cable or Device	355
Figure E-5	USB DisplayPort Dock Example	357
Figure F-1	TBT3 Discovery Flow	362
Figure H-1	Arcing Damage to USB Type-C Vbus Contacts	377
Figure H-2	Arcing Due to Discharge	378
Figure H-3	Arcing Prevention During Sink Discharge by Limiting Slew Rate	380
Figure H-4	Arcing Prevention During Sink Discharge by Load Removal	382

TABLES

Table 2-1 Summary of power supply options	38
Table 3-1 USB Type-C Standard Cable Assemblies	40
Table 3-2 USB Type-C Legacy Cable Assemblies	41
Table 3-3 USB Type-C Legacy Adapter Assemblies	41
Table 3-4 USB Type-C Receptacle Interface Pin Assignments	71
Table 3-5 USB Type-C Receptacle Interface Pin Assignments for USB 2.0-only Support.....	72
Table 3-6 USB Type-C Standard Cable Wire Assignments.....	74
Table 3-7 USB Type-C Cable Wire Assignments for Legacy Cables/Adapters.....	75
Table 3-8 Reference Wire Gauges for standard USB Type-C Cable Assemblies	76
Table 3-9 Reference Wire Gauges for USB Type-C to Legacy Cable Assemblies	76
Table 3-10 USB Full-Featured Type-C Standard Cable Assembly Wiring	78
Table 3-11 USB 2.0 Type-C Standard Cable Assembly Wiring	79
Table 3-12 USB Type-C to USB 3.1 Standard-A Cable Assembly Wiring	81
Table 3-13 USB Type-C to USB 2.0 Standard-A Cable Assembly Wiring	82
Table 3-14 USB Type-C to USB 3.1 Standard-B Cable Assembly Wiring	83
Table 3-15 USB Type-C to USB 2.0 Standard-B Cable Assembly Wiring	84
Table 3-16 USB Type-C to USB 2.0 Mini-B Cable Assembly Wiring	85
Table 3-17 USB Type-C to USB 3.1 Micro-B Cable Assembly Wiring	86
Table 3-18 USB Type-C to USB 2.0 Micro-B Cable Assembly Wiring	87
Table 3-19 USB Type-C to USB 3.1 Standard-A Receptacle Adapter Assembly Wiring	89
Table 3-20 USB Type-C to USB 2.0 Micro-B Receptacle Adapter Assembly Wiring	90
Table 3-21 Differential Insertion Loss Examples for TX/RX with Twisted Pair Construction	91
Table 3-22 Differential Insertion Loss Examples for USB TX/RX with Coaxial Construction	92
Table 3-23 Key Parameters in COM Configuration File	105
Table 3-24 Electrical Requirements for CC and SBU wires.....	106
Table 3-25 Coupling Matrix for Low Speed Signals	106
Table 3-26 Maximum Mutual Inductance (M) between Vbus and Low Speed Signal Lines.....	109
Table 3-27 USB D+/D- Signal Integrity Requirements for USB Type-C to USB Type-C Passive Cable Assemblies	110
Table 3-28 USB Type-C Mated Connector Recommended Signal Integrity Characteristics (Informative)	112
Table 3-29 USB Type-C Receptacle Connector Signal Integrity Characteristics for USB4 Gen3 (Normative).....	114
Table 3-30 USB D+/D- Signal Integrity Requirements for USB Type-C to Legacy USB Cable Assemblies	116
Table 3-31 Design Targets for USB Type-C to USB 3.1 Gen2 Legacy Cable Assemblies (Informative).....	116
Table 3-32 USB Type-C to USB 3.1 Gen2 Legacy Cable Assembly Signal Integrity Requirements (Normative).....	117
Table 3-33 USB D+/D- Signal Integrity Requirements for USB Type-C to Legacy USB Adapter Assemblies (Normative)	119
Table 3-34 Design Targets for USB Type-C to USB 3.1 Standard-A Adapter Assemblies (Informative).....	119
Table 3-35 USB Type-C to USB 3.1 Standard-A Receptacle Adapter Assembly Signal Integrity Requirements (Normative).....	120
Table 3-36 Current Rating Test PCB	124
Table 3-37 Maximum DC Resistance Requirement (Normative)	125
Table 3-38 Force and Moment Requirements.....	128
Table 3-39 Environmental Test Conditions	131
Table 3-40 Reference Materials	132
Table 4-1 USB Type-C List of Signals.....	138
Table 4-2 Vbus Source Characteristics	141
Table 4-3 Vbus Sink Characteristics	142
Table 4-4 USB Type-C Source Port's Vconn Requirements Summary	143
Table 4-5 Vconn Source Characteristics.....	144
Table 4-6 Cable Vconn Sink Characteristics.....	145
Table 4-7 Vconn-Powered Accessory (VPA) Sink Characteristics	146
Table 4-8 Vconn-Powered USB Device (VPD) Sink Characteristics	147
Table 4-9 USB Type-C-based Port Interoperability.....	150
Table 4-10 Source Perspective	152

Table 4-11	Source (Host) and Sink (Device) Behaviors by State	152
Table 4-12	USB PD Swapping Port Behavior Summary	158
Table 4-13	Power Role Behavioral Model Summary	159
Table 4-14	Source Port CC Pin State	168
Table 4-15	Sink Port CC Pin State	168
Table 4-16	Mandatory and Optional States	193
Table 4-17	Precedence of power source usage	214
Table 4-18	USB Type-C Current Advertisement and PDP Equivalent	216
Table 4-19	Sink Maximum Current Limit When Attached to CTVPD	219
Table 4-20	Example Charge-Through VPD Sink Maximum Currents based on Vbus Impedance and GND Impedance	220
Table 4-21	SOP' and SOP" Timing	228
Table 4-22	Charge-Through VPD CC Impedance (RccCON) Requirements	230
Table 4-23	CTVPD Charge-Through Port Vbus Bypass Requirements	230
Table 4-24	Source CC Termination (Rp) Requirements	231
Table 4-25	Sink CC Termination (Rd) Requirements	231
Table 4-26	Powered Cable Termination Requirements	231
Table 4-27	CC Termination Requirements for Disabled state, ErrorRecovery state, and Unpowered Source	232
Table 4-28	SBU Termination Requirements	232
Table 4-29	Vbus and Vconn Timing Parameters	232
Table 4-30	DRP Timing Parameters	233
Table 4-31	CC Timing	234
Table 4-32	CC Voltages on Source Side – Default USB	235
Table 4-33	CC Voltages on Source Side – 1.5 A @ 5 V	235
Table 4-34	CC Voltages on Source Side – 3.0 A @ 5 V	236
Table 4-35	Voltage on Sink CC Pins (Default USB Type-C Current only)	236
Table 4-36	Voltage on Sink CC pins (Multiple Source Current Advertisements)	236
Table 4-37	CC Pin Clamping Voltage	236
Table 5-1	Certified Cables Where USB4-compatible Operation is Expected	242
Table 5-2	Fallback Mapping USB4 Peripheral Functions to USB Device Class Types	253
Table 5-3	USB Billboard Device Class Availability Following USB4 Device Entry Failure	254
Table 6-1	Comparison of Active Cables	256
Table 6-2	Summary of Active Cable Features	257
Table 6-3	USB4 Cable Identity Summary	260
Table 6-4	OIAC USB PD Message Behavior on Initial Connection	261
Table 6-5	OIAC USB PD Messages Which Do Not Traverse in Active State	263
Table 6-6	OIAC USB PD Messages Addressed to SOP Which Traverse the OIAC in the Active State	264
Table 6-7	OIAC USB PD Message Timing	265
Table 6-8	OIAC SOP Messages Which Terminate at the Cable Plug	266
Table 6-9	Port and Plug Capabilities	271
Table 6-10	OIAC Sink_Capabilities PDO (SOP) on Initial Connection	288
Table 6-11	OIAC Sink_Capabilities_Extended PDO (SOP) on Initial Connection	289
Table 6-12	OIAC Sink RDO (SOP) on Initial Connection	289
Table 6-13	OIAC Active Sink RDO (SOP)	290
Table 6-14	OIAC Sink_Capabilities PDO (SOP) in Active	290
Table 6-15	Cable Temperature Requirements	291
Table 6-16	Summary of Active Cable Features	292
Table 6-17	Active Cable Power-on Requirements	294
Table 6-18	OIAC Maximum USB 3.2 U0 Delay	294
Table 6-19	Usages for OIAC That Require an Adapter or Hub	295
Table 6-20	USB 3.2 U-State Requirements	296
Table 6-21	Active Cable USB 3.2 Stressed Source Swing, TP1	297
Table 6-22	Active Cable USB 3.2 Stressed Source Jitter, TP1	298
Table 6-23	Active Cable USB 3.2 Input Swing at TP2 (Informative)	298
Table 6-24	Active Cable USB 3.2 Output Swing at TP3 (Informative)	299
Table 6-25	Compliance Points Definition	300
Table 6-26	Re-timer-based USB4 Active Cable Output Specifications Applied for All Speeds (at TP3')	302
Table 6-27	Stressed Received Conditions for USB4 Gen2 and Gen3 Cable Compliance Testing (at TP2)	304

Table 6-28 Linear Re-driver-based Active Cable Output Parameters	307
Table 6-29 Input Signal at TP2 for Compliance Testing	307
Table 6-30 USB4 CL-State Requirements	312
Table A-1 USB Type-C Analog Audio Pin Assignments	314
Table A-2 USB Type-C Analog Audio Pin Electrical Parameter Ratings	315
Table B-1 DTS to TS Port Interoperability	320
Table B-2 Rp/Rp Charging Current Values for a DTS Source	327
Table B-3 Mandatory and Optional States	329
Table D-1 Heat Sources and Heat Dissipation Example (1.5 W cable and 5 A)	343
Table D-2 USB 3.2 Active Cable Design Single Port Case Study at 35 °C Ambient and 60 °C Thermal Boundary (Single Lane)	344
Table D-3 USB 3.2 Active Cable Design Single Port Case Study at 35 °C Ambient and 60 °C Thermal Boundary (Dual Lane)	347
Table E-1 USB Safe State Electrical Requirements	356
Table E-2 USB Billboard Device Class Availability Following Alternate Mode Entry Failure	356
Table E-3 Alternate Mode Signal Noise Ingression Requirements	356
Table F-1 TBT3 Passive Cable Discover Identity VDO Responses	363
Table F-2 TBT3 Passive Cable VDO for USB PD Revision 2.0, Version 1.3	364
Table F-3 TBT3 Passive Cable VDO for USB PD Revision 3.0, Version 1.2	364
Table F-4 TBT3 Active Cable Discover Identity VDO Responses	365
Table F-5 TBT3 Active Cable VDO for USB PD Revision 2.0, Version 1.3	366
Table F-6 TBT3 Active Cable VDO 1 for USB PD Revision 3.0, Version 1.2	367
Table F-7 TBT3 Active Cable VDO 2 for USB PD Revision 3.0, Version 1.2	367
Table F-8 TBT3 Device Discover Identity VDO Responses	368
Table F-9 TBT3 Discover SVID VDO Responses	369
Table F-10 TBT3 Device Discover Mode VDO Responses	370
Table F-11 TBT3 Cable Discover Mode VDO Responses	371
Table F-12 TBT3 Cable Enter Mode Command	372
Table F-13 TBT3 Device Enter Mode Command	373
Table F-14 TBT3 Cable Functional Difference Summary	374
Table G-1 Linear Fit Pulse Extraction Parameters	376

Preview generated by EVS

Specification Work Group Chairs / Specification Editors

Intel Corporation (USB Promoter company)	Yun Ling – Mechanical WG co-chair, Mechanical Chapter Co-editor Brad Saunders – Plenary/Functional WG chair, Specification Co-author
Specwerkz	Bob Dunstan – Functional WG co-chair, Specification Co-author
Seagate	Alvin Cox, Mechanical WG co-chair, Mechanical Chapter Co-editor

Specification Work Group Contributors

Note: For historical reasons, the following list also includes individual contributors that were members of the work group and associated with their company affiliations at the time of the original Release 1.0 through to the latest release.

Advanced-Connectek, Inc. (ACON)	Victory Chen Glen Chandler Dennis Cheung Jeff Chien Lee (Dick Lee) Ching	Conrad Choy Vicky Chuang Jessica Feng Aven Kao Danny Liao	Alan Tsai Wayne Wang Stephen Yang Sunney Yang
Advanced Micro Devices	Steve Capezza Walter Fry Will Harris	Jason Hawken Gerald Merits Tim Perley	Joseph Scanlon Peter Teng Sujan Thomas
Allion Labs, Inc.	Howard Chang Alex Chuang Maroco Fan Terry Kao	Yan Ken Stan Lin Minoru Ohara Brian Shih	Chester Tsai Chou Tsungbo
Amphenol Corporation	Louis Chan Zhineng Fan Jesse Jaramillo	Terry Ke Martin Li Lino Liu	Shawn Wei Alan Yang
Agilent Technologies, Inc.	James Choate		
Analogix Semiconductor, Inc.	Mehran Badii Greg Stewart	Haijian Sui	Yueke Tang
Apple Inc. (USB Promoter company)	Colin Abraham Mahmoud Amini Sree Anantharaman Brian Baek Paul Baker Michael Bonham Carlos Calderon Jason Chung David Conroy Bill Cornelius Christophe Daniel Raju Desai William Ferry	Brian Follis Zheng Gao Derek Iwamoto Scott Jackson Girault Jones Keong Kam Kevin Keeler Min Kim Woopoung Kim Alan Kobayashi Alexei Kosut Christine Krause Chris Ligtenberg	Matthew Mora Nathan Ng James Orr Keith Porthouse Breton Saunders Reese Schreiber Sascha Tietz Jennifer Tsai Colin Whitby- Stevens Jeff Wilcox Eric Wiles Dan Wilson Dennis Yarak
ASMedia Technology Inc.	Kuo Lung Li		
Bizlink Technology, Inc.	Alex Chou	Morphy Hsieh	Kevin Tsai
Cadence Design Systems, Inc.	Marcin Behrendt Huzaifa Dalal Pawel Eichler Sathish Kumar Ganesan	Dariusz Kaczmarczyk Tomasz Klimek Jie Min Asila Nahas Uyen Nguyen	Neelabh Singh Michal Staworko Fred Stivers Mark Summers Claire Ying

Canova Tech	Piergiorgio Beruto Andrea Maniero	Michael Marioli Antonio Orzelli	Paola Pilla Nicola Scantamburlo
Cirrus Logic Inc.	Sean Davis	Darren Holding	Brad Lambert
Corning Optical Communication LLC	Wojciech Giziewicz	Ian McKay	Jamie Silva
Cosemi Technologies Inc.	Samir Desai	Devang Parekh	
Cypress Semiconductor	Chia Hua Chang Mark Fu Naman Jain Savan Javia	Rushil Kadakia Benjamin Kropf Venkat Mandagulathur Anup Nayak	Jagadeesan Raj Sanjay Sancheti Subu Sankaran Anita Thimma Govarthanarajan
Dell	Mohammed Hijazi David Meyers Sean O'Neal	Ken Nicholas Ernesto Ramirez Siddhartha Reddy	Thomas Voor Merle Wood
Dialog Semiconductor (UK) Ltd.	Yimin Chen		
Diodes Incorporated	Kay Annamalai Justin Lee Paul Li	Bob Lo Jaya Shukla Qun Song	Jin-sheng Wang Ada Yip
DisplayLink (UK) Ltd.	Pete Burgers		
DJI Technology Co., Ltd.	Steve Huang		
Electronics Testing Center, Taiwan	Sophia Liu		
Elka International Ltd.	Roy Ting		
Ellisys	Abel Astley Rick Bogart	Mario Pasquali Chuck Trefts	Tim Wei
Etron Technology, Inc.	Chien-Cheng Kuo		
Feature Integration Technologies Inc.	Jacky Chan Chen Kris Yulin Lan	KungAn Lin Yuchi Tsao	Paul Yang Amanda Ying
Foxconn / Hon Hai	Patrick Casher Asroc Chen Brandon Chen Joe Chen Allen Cheng Jason Chou Edmond Choy Fred Fons	Chris Goralka Bob Hall Chien-Ping Kao Ji Li Ann Liu Terry Little Steve Sedio Christine Tran	Pei Tsao AJ Yang Yuan Zhang Jessica Zheng Jie Zheng Andy Yao
Foxlink/Cheng Uei Precision Industry Co., Ltd.	Robert Chen Sunny Chou Carrie Chuang Wen-Chuan Hsu Alex Hsue	Armando Lee Dennis Lee Justin Lin Robert Lu Tse Wu Ting	Steve Tsai Wen Yang Wiley Yang Junjie Yu
Fresco Logic Inc.	Brian Collins	Bob McVay	Christopher Meyers
Google	Naga Viswanadha Udaya Kiran Ammu Alec Berg Joshua Boilard Alec Berg Todd Broch Chao Fei Jim Guerin Jeffrey Hayashida Mark Hayter	Eric Herrmann Nithya Jagannathan Nathan Kolluru Lawrence Lam Adam Langley Benson Leung Abraham Levkoy Ingrid Lin Richard Palatin	Vincent Palatin Dylan Reid Adam Rodriguez David Schneider Stephan Schooley Toshak Singhal Ken Wu Songping Wu

Granite River Labs	Yung Han Ang Velmurugan Ayyakkannu Hariprasad Bhat Sandy Chang Allen Chen Swee Guan Chua	Alan Chuang Mike Engbretson Vishal Kakade Jesson Li Caspar Lin Bala M	Prasannakumar Marikunte Nagaraju Krishna Murthy Amy Peng Johnson Tan Annie Tao Chin Hun Yaep
Honor Device Co., Ltd.	Wang Feng		
Hirose Electric Co., Ltd.	Jeremy Buan William Kysiak Sang-Muk Lim	William MacKillop Gourgen Oganessyan	Eungsoo Shin Sid Tono
Hosiden Corporation	Takahisa Otsuji	Fumitake Tamaki	
HP Inc. (USB Promoter company)	Lee Atkinson Srinath Balaraman Rami Bathaniah Roger Benson Alan Berkema	Robin Castell Steve Chen Michael Krause Rahul Lakdawala	Jim Mann Linden McClure Mike Pescetto Asjad Shamim
I-PEX (Dai-ichi Seiko)	Alan Kinningham	Ro Richard	
Indie Semiconductor	Ian Board	Jim Wilshire	
Infineon Technologies	Tue Fatt David Wee		
Intel Corporation (USB Promoter company)	Dave Ackelson Mike Bell Dmitriy Berchanskiy Brad Berlin Pierre Bossart Kuan-Yu Chen Hengju Cheng Oded David Jhuda Dayan Paul Durley Saranya Gopal Yaniv Hayat Howard Heck Hao-Han Hsu Seppo Ingalsuo Abdul (Rahman) Ismail James Jaussi Ziv Kabiry	Vijaykumar Kadgi Luke Johnson Jerzy Kolinski Rolf Kuhnis Henrik Leegaard Edmond Lau Xiang Li Yun Ling Guobin Liu Steve McGowan Sankaran Menon Udaya Natarajan Aruni Nelson Chee Lim Nge Sagar Pawar Duane Quiet Kannappan Rajaraman Sridharan Ranganathan	Rajaram Regupathy Oren Salomon Brad Saunders Tomer Savariego Ehud Shoor Amit Srivastava Einat Suriyan Ron Swartz David Thompson Karthi Vadivelu Tsion Vidal Stephanie Wallick Rafal Wielicki Devon Worrell Li Yuan Reza M. Zamani Vitaly Zhivov
Japan Aviation Electronics Industry Ltd. (JAE)	Kenji Hagiwara Hiroaki Ikeda Masaki Kimura Toshio Masumoto Kenta Minejima Toshiyuki Moritake Joe Motojima Ron Muir	Tadashi Okubo Kazuhiro Saito Kimiaki Saito Yuichi Saito Mark Saubert Toshio Shimoyama Tatsuya Shioda Atsuo Tago	Masaaki Takaku Jussi Takaneva Junichi Takeuchi Tomohiko Tamada Kentaro Toda Kouhei Ueda Takakazu Usami Masahide Watanabe Youhei Yokoyama
JPC/Main Super Inc.	Sam Tseng	Ray Yang	
Kandou Bus SA	Hitaish Sharma	David Stauffer	Paul Wilson
Keysight Technologies Inc.	Pedro Merlo		
Kinetic Technologies, Inc.	Ramesh Dandapani	Jay Slivkoff	Sireesha Vemulapalli
Leadtrend	Yao-Wei Hsieh		

LeCroy Corporation	Mike Engbretson Daniel H. Jacobs	Tyler Joe	Giuseppe Leccia
Lenovo	Rob Bowser Tomoki Harada	Jianye Li Wei Liu	Howard Locker
LG Electronics Inc.	Do Kyun Kim	Yoon Jong Lee	
Lintes Technology Co., Ltd.	Tammy Huang Charles Kaun RD Lintes	Max Lo CT Pien	JinYi Tu Jason Yang
Lotes Co., Ltd.	Ariel Delos Reyes Ernest Han Mark Ho Regina Liu-Hwang	Charles Kaun Chi-Chang Lin James Lin Max Lo	John Lynch JinYi Tu Jason Yang
LSI Corporation	Dave Thompson		
Luxshare-ICT	Josue Castillo Daniel Chen Kenny Chen Lisen Chen Sally Chiu CY Hsu Blue Ho	Alan Kinningham Antony Lin Gorden Lin John Lin Stone Lin Alan Liu Sean O'Neal	Scott Shuey James Stevens Carr Wang Yangli Wang Eric Wen Pat Young
Maxim Integrated Products	Forrest Christo Ken Helfrich	Sang Kim Jeff Lo	Michael Miskho Jacob Scott
MCCI Corporation	Terry Moore		
MediaTek Inc.	Alex YC Lin		
MegaChips Corporation	Alan Kobayashi	Satoru Kumashiro	
Mercedes-Benz Research & Development, North America, Inc.	Hans Wickler		
Microchip (SMSC)	Josh Averyt Mark Bohm Shannon Cash Thomas Farkas Fernando Gonzalez	Matthew Kalibat Donald Perkins Richard Petrie Mohammed Rahman Andrew Rogers	John Sisto Anthony Tarascio Kiet Tran Christopher Twigg Prasanna Vengateshan
Microsoft Corporation (USB Promoter company)	Randy Aull Jim Belesiu Michelle Bergeron Fred Bhesania Anthony Chen Philip Froese Vivek Gupta David Hargrove Robbie Harris Teemu Helenius Robert Hollyer Lily Huang	Dan Iatco Kai Inha Jayson Kastens Andrea Keating Shoaib Khan Patrick Law Eric Lee Ivan McCracken Arvind Murching Gene Obie Toby Nixon Arjun Padmanabhan	Praveen Kumar Palacharla Rahul Ramadas Srivatsan Ravindran Nathan Sherman Bala Sivakumar Timo Toivola Vahid Vassey David Voth Andrew Yang Panu Ylihaavisto
Molex LLC	Adib Al Abaji	Alan MacDougall	
Monolithic Power Systems	Junyong Gong Di Han Yuncong Jiang	Istvan Nagy Chris Sporck	Ao Sun Vincent Wu
MQP Electronics Ltd.	Sten Carlsen	Pat Crowe	
Multilane Inc.	Fadi Daou	Rita Khawaja	Elias Houry

NEC Corporation	Kenji Oguma		
Newnex Technology Corp.	Sam Liu	Nimrod Peled	
Nokia Corporation	Daniel Gratiot	Samuli Makinen	Timo Toivola
	Pekka Leinonen	Pekka Talmola	Panu Ylihaavisto
Nuvoton Technology Corp.	Nimrod Peled		
NVIDIA	Jamie Aitken		
NXP Semiconductors	Mahmoud EL Sabbagh	Ken Jaramillo	Guru Prasad
	Dennis Ha	Vijendra Kuroodi	Krishnan TN
Oculus VR LLC	Amish Babu	Marty Evans	Joaquin Fierro
ON Semiconductor	Edward Berrios	Oscar Freitas	Eric Maier
	Rod Comer	Christian Klein	Rick Pierce
	Eduardo De Reza	Amir Lahooti	Michael Smith
Parade Technologies, Inc.	Jian Chen	Craig Wiley	Alan Yuen
	Brian Collins	Paul Xu	Jingfan Zhang
	Robert McVay		
Power Integrations	Shruti Anand	Aditya Kulkarni	Amruta Patra
	Rahul Joshi	Akshay Nayaknur	
Qualcomm, Inc.	Lior Amarilio	James Goel	Jack Pham
	Vara Prasad Arikatla	Amit Gupta	Vamsi Samavedam
	Aris Balatsos	Philip Hardy	Matthew Sienko
	Nicholas Cadieux	Will Kun	Dmitrii Vasilchenko
	David Chang	Jonathan Luty	Joshua Warner
	Tomer Ben Chen	Lalan Mishra	Chris Wiesner
	Richard Burrows	George Paparrizos	
	Amit Gil	Vatsal Patel	
Realtek Semiconductor Corp.	Marco Chiu	Ty Kingsmore	Terry Lin
	Tsung-Peng Chuang	Ray Lee	Chuting Su
	Charlie Hsu	Jay Lin	Changhung Wu
	Fan-Hau Hsu	Ryan Lin	
Renesas Electronics Corp. (USB Promoter company)	Kai Bao	Philip Leung	Hajime Nozaki
	Yen-Mo Chen	Kiichi Muto	Yosuke Sasaki
	Nobuo Furuya	Ziba Nami	Toshifumi Yamaoka
Richtek Technology Corp.	Ben Chiang	Leo Kang	Ken Shih
	Max Huang	Roger Lo	Alex Yang
Rohde & Schwarz GmbH & Co. KG	Kai Uwe Schmidt	Martin Stumpf	Randy White
Rohm Co., Ltd.	Mark Aaldering	Yusuke Kondo	Yoshinori Ohwaki
	Kris Bahar	Arun Kumar	Takashi Sato
	Ruben Balbuena	Chris Lin	Hiroshi Yoshimura
	Nobutaka Itakura	Kazuomi Nagai	
Samsung Electronics Co., Ltd.	Jaedeok Cha	Sung Geun Joo	Jun Bum Lee
	KangSeok Cho	Koyoungwon Kim	Jinyoung Oh
	Junhwa Choi	Sangju Kim	Chahoon Park
	Woojin Choi	Soondo Kim	Chulwoo Park
	Yeongbok Choi	Woonki Kim	Youngjin Park
	Cheolyoon Chung	Jagoun Koo	Jung Waneui
	Ilhyung Chung	Termi Kwon	Sunggeun Yoon
	JaeRyong Han	Cheolho Lee	
	Jaehyeok Jang	Edward Lee	
	Wonseok Jang		
SB C&S Corp.	Toshinari Nakamura	Eiji Sakai	Kenji Watanabe
	Morito Ogikubo		

Seagate	Alvin Cox Emmanuel Lemay	Tony Priborsky Tom Skaar	Dan Smith
Shenzhen Deren Electronic Co., Ltd.	Smark (Zhudong) Huo Wen Fa Lei	Yang Lirong	Lucy Zhang
Silicon Line GmbH	Ian Jackson	Boleslaw Wojtowicz	Zhiying Zhang
SiliConch Systems Private Limited	Jaswanth Ammineni Pavitra Balasubramanian Kaustubh Kumar Aniket Mathad	Shubham Paliwal Jinisha Patel Vinay Patel Rakesh Polasa	Vishnu Pusuluri Ranjith S Abhishek Sardeshpande Satish Anand Verkila
Simula Technology Inc.	John Chang Voss Cheng Thomas Li	Jung Lin Jyunming Lin Doris Liu	Richard Liu CK Wang Alice Yu
Softnautics LLP	Bhavesh Desai Hetal Jariwala	Dipakkumar Modi Ishita Shah	Ujjwal Talati
Sony Corporation	Shinichi Hirata	Shigenori Tagami	
Spectra7 Microsystems Corp.	Andrew Kim	James McGrath	John Mitchell
Specwerkz	Robert Dunstan	Amanda Hosler	Diane Lenox
STMicroelectronics (USB Promoter company)	Jerome Bach Nathalie Ballot Filippo Bonaccorso Guenael Cadier Dominique Chaillot Christophe Cochard Nicolas Florenchie	Cedric Force Gregory Gosciniak Chekib Hammami Joel Huloux Christophe Lorin Yohann Martiniault Patrizia Milazzo	Federico Musarra Pascal Legrand Richard O'Connor Massimo Panzica Nicolas Perrin
Sumitomo Electric Ind., Ltd.	Takeshi Inoue Yasuhiro Maeda	Wataru Sakurai Sainer Siagian	Masaki Suzuki Mitsuaki Tamura
Synaptics Inc.	Daniel Bogard Dan Ellis	Jeff Lukanc	Prashant Shamarao
Synopsys, Inc.	Subramaniam Aravindhan	Morten Christiansen Nivin George	Satya Patnala John Stonick
Taiwan Testing and Certification Center	Sophia Liu		
Tektronix, Inc.	Sourabh Das Mark Guenther	Abhijeet Shinde	Randy White
Texas Instruments (USB Promoter company)	Jawaid Ahmad Mike Campbell Greg Collins Gary Cooper Anant Gole GP Gopalakrishnan Craig Greenberg Richard Hubbard Nate Johnson Michael Koltun IV Yoon Lee Grant Ley	Win Maung Shafiuddin Mohammed Lauren Moore Jacob Ontiveros Brian Parten Martin Patoka Jason Peck John Perry Louis Peryea Brian Quach	Sai Karthik Rajaraman Wes Ray Dafydd Roche Anwar Sadat Cory Stewart Sue Vining Bill Waters Deric Waters Gregory Watkins Roy Wojciechowski
Thine Electronica, Inc.	Yuseke Fujita	Shuhei Yamamoto	
Total Phase	Chris Yokum		

Tyco Electronics Corp. (TE Connectivity Ltd.)	Max Chao Robert E. Cid Calvin Feng Kengo Ijiro Eiji Ikematsu Joan Leu Clark Li	Mike Lockyer Jeff Mason Takeshi Nakashima Luis A. Navarro Masako Saito Yoshiaki Sakuma Gavin Shih	Hiroshi Shirai Hidenori Taguchi Nathan Tracy Bernard Vetten Ryan Yu Noah Zhang Sjoerd Zwartkruis
UL LLC	Leo Chung Michael Hu Dylan Su	Henry Tsou Paul Vanderlaan Eric Wall	Lance Yang Chien-Wei Yeh
Unigraf OY	Steven Chen	Sergey Grushin	
Varjo Technologies	Kai Inha		
Ventev Mobile	Brad Cox	Colin Vose	
VIA Technologies Inc.	Terrance Shih	Jay Tseng	Fong-Jim Wang
Weltrend Semiconductor	Hung Chiang Jeng Cheng Liu	Wayne Lo Ho Wen Tsai	Eric Wu
Western Digital, HGST	Larry McMillan		
Xiaomi Communications Co., Ltd.	Xiaoxing Yang	Juejia Zhou	

Pre-Release Draft Industry Reviewing Companies That Provided Feedback

Aces	JST Mfg. Co., Ltd.	Pericom
Fairchild Semiconductor	Korea Electric Terminal	Semtech Corporation
Fujitsu Ltd.	Marvell Semiconductor	Silicon Image
Industrial Technology Research Institute (ITRI)	Motorola Mobility LLC	SMK Corporation
Joinsoon Electronics Mfg. Co. Ltd.	PalCONN/PalNova (Palpilot International Corp.)	Toshiba Corporation

Revision History

Revision	Date	Description
1.0	August 11, 2014	Initial Release
1.1	April 3, 2015	Reprint release including incorporation of all approved ECNs as of the revision date plus editorial clean-up.
1.2	March 25, 2016	Reprint release including incorporation of all approved ECNs as of the revision date plus editorial clean-up.
1.3	July 14, 2017	Reprint release including incorporation of all approved ECNs as of the revision date plus editorial clean-up.
1.4	March 29, 2019	Reprint release including incorporation of all approved ECNs as of the revision date plus editorial clean-up.
2.0	August 2019	New release primarily for enabling USB4 over USB Type-C connectors and cables. Also includes incorporation of all approved ECNs as of the revision date plus editorial clean-up.
2.1	May 2021	New release primarily for enabling Extended Power Range (EPR) and defining EPR cables aligning with USB Power Delivery Specification R3.1 V1.0. Also includes incorporation of all approved ECNs as of the revision date plus editorial clean-up.

1 Introduction

With the continued success of the USB interface, there exists a need to adapt USB technology to serve newer computing platforms and devices as they trend toward smaller, thinner and lighter form-factors. Many of these newer platforms and devices are reaching a point where existing USB receptacles and plugs are inhibiting innovation, especially given the relatively large size and internal volume constraints of the Standard-A and Standard-B versions of USB connectors. Additionally, as platform usage models have evolved, usability and robustness requirements have advanced and the existing set of USB connectors were not originally designed for some of these newer requirements. This specification is to establish a new USB connector ecosystem that addresses the evolving needs of platforms and devices while retaining all of the functional benefits of USB that form the basis for this most popular of computing device interconnects.

1.1 Purpose

This specification defines the USB Type-C[®] receptacles, plug and cables.

The USB Type-C Cable and Connector Specification is guided by the following principles:

- Enable new and exciting host and device form-factors where size, industrial design and style are important parameters
- Work seamlessly with existing USB host and device silicon solutions
- Enhance ease of use for connecting USB devices with a focus on minimizing user confusion for plug and cable orientation

The USB Type-C Cable and Connector Specification defines a new receptacle, plug, cable and detection mechanisms that are compatible with existing USB interface electrical and functional specifications. This specification covers the following aspects that are needed to produce and use this new USB cable/connector solution in newer platforms and devices, and that interoperate with existing platforms and devices:

- USB Type-C receptacles, including electro-mechanical definition and performance requirements
- USB Type-C plugs and cable assemblies, including electro-mechanical definition and performance requirements
- USB Type-C to legacy cable assemblies and adapters
- USB Type-C-based device detection and interface configuration, including support for legacy connections
- USB Power Delivery optimized for the USB Type-C connector

The USB Type-C Cable and Connector Specification defines a standardized mechanism that supports [Alternate Modes](#), such as repurposing the connector for docking-specific applications.

1.2 Scope

This specification is intended as a supplement to the existing [USB 2.0](#), [USB 3.2](#), [USB4™](#) and [USB Power Delivery](#) specifications. It addresses only the elements required to implement and support the USB Type-C receptacles, plugs and cables.

Normative information is provided to allow interoperability of components designed to this specification. Informative information, when provided, may illustrate possible design implementations.

1.3 Related Documents

USB	<i>Universal Serial Bus Revision 2.0 Specification</i>
2.0	This includes the entire document release package.

USB 3.2	<i>Universal Serial Bus Revision 3.2 Specification</i> This includes the entire document release package. <i>USB 3.1 Legacy Cable and Connector Specification, Revision 1.0</i>
USB4	<i>USB4™ Specification, Version 1.0, August 2019</i> (including posted errata and ECNs)
TBT3	Chapter 13 of <i>USB4 Specification, Version 1.0, August 2019</i>
USB PD	<i>USB Power Delivery Specification, Revision 2.0, Version 1.3, January 12, 2017</i> <i>USB Power Delivery Specification, Revision 3.1, Version 1.0, May 2021</i> (including posted errata and ECNs)
USB BB	<i>USB Billboard Device Class Specification, Revision 1.2.2, January 29, 2021</i>
USB BC	<i>Battery Charging Specification, Revision 1.2 (including errata and ECNs through March 15, 2012), March 15, 2012</i>
DP AM	<i>DisplayPort™ Alt Mode on USB Type-C Standard, Version 2.0, 12 March 2020</i>

All USB-specific documents are available for download at <http://www.usb.org/documents>. The DisplayPort Alt Mode specification is available from VESA (<http://www.vesa.org>).

1.4 Conventions

1.4.1 Precedence

If there is a conflict between text, figures, and tables, the precedence shall be tables, figures, and then text.

1.4.2 Keywords

The following keywords differentiate between the levels of requirements and options.

1.4.2.1 Informative

Informative is a keyword that describes information with this specification that intends to discuss and clarify requirements and features as opposed to mandating them.

1.4.2.2 May

May is a keyword that indicates a choice with no implied preference.

1.4.2.3 N/A

N/A is a keyword that indicates that a field or value is not applicable and has no defined value and shall not be checked or used by the recipient.

1.4.2.4 Normative

Normative is a keyword that describes features that are mandated by this specification.

1.4.2.5 Optional

Optional is a keyword that describes features not mandated by this specification. However, if an optional feature is implemented, the feature shall be implemented as defined by this specification (optional normative).

1.4.2.6 Reserved

Reserved is a keyword indicating reserved bits, bytes, words, fields, and code values that are set-aside for future standardization. Their use and interpretation may be specified by future extensions to this specification and, unless otherwise stated, shall not be utilized or adapted by vendor implementation. A reserved bit, byte, word, or field shall be set to zero by the sender and shall be ignored by the receiver. Reserved field values shall not be sent by the sender and, if received, shall be ignored by the receiver.