



**International
Standard**

ISO 11898-1

**Road vehicles — Controller area
network (CAN) —**

**Part 1:
Data link layer and physical coding
sublayer**

*Véhicules routiers — Gestionnaire de réseau de
communication (CAN) —*

*Partie 1: Couche liaison de données et sous-couche de codage
physique*

**Third edition
2024-05**

This document is a preview generated by EMS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	6
5 Basic concepts of CAN	8
5.1 CAN properties.....	8
5.2 Frame transmissions.....	9
5.3 Bus access method.....	11
5.4 Information routing.....	11
5.5 Network flexibility.....	11
5.6 Remote data request.....	11
5.7 Error detection.....	11
5.8 Error signalling and recovery time.....	11
5.9 Fault confinement.....	12
5.10 Error-active.....	12
5.11 Error-passive.....	12
5.12 Bus-off.....	12
5.13 ACK.....	12
5.14 Repetition of transmission attempts.....	12
5.15 Network-wide data consistency.....	12
5.16 Switchable operating modes of the PMA.....	13
5.17 Bus states and MAC sub-layer phases.....	13
6 CAN DLL specification	14
6.1 General.....	14
6.2 Time stamping.....	14
6.3 DLL protocol.....	14
6.4 LLC sub-layer.....	15
6.4.1 Overview.....	15
6.4.2 Notifications.....	16
6.4.3 Structure of LLC frames.....	16
6.4.4 Limited LLC frames.....	17
6.4.5 Services of LLC sub-layer.....	17
6.5 Functions of the LLC sub-layer.....	21
6.5.1 General.....	21
6.5.2 Flow control on re-arbitration.....	21
6.5.3 Flow control on retransmission.....	21
6.5.4 Frame acceptance filtering.....	22
6.5.5 Overload notification.....	22
6.5.6 Recovery management.....	22
6.5.7 Time stamping.....	22
6.6 MAC sub-layer.....	23
6.6.1 Functions and rules.....	23
6.6.2 Services of the MAC sub-layer.....	23
6.6.3 Time reference points.....	23
6.6.4 Functional model of MAC sub-layer architecture.....	23
6.6.5 Specification of EF.....	27
6.6.6 Specification of OF.....	28
6.6.7 Inter-frame space specification.....	28
6.6.8 SOF.....	30
6.6.9 Elements of the MAC frame.....	30
6.6.10 MAC frame in CBFF and CEFF.....	31

6.6.11	MAC frame in FBFF and FEFF.....	33
6.6.12	MAC frame in XLFF.....	37
6.6.13	MAC frame coding.....	42
6.6.14	Data frame acknowledgement.....	43
6.6.15	Frame validation.....	43
6.6.16	Order of bit transmission.....	43
6.6.17	Medium access method.....	43
6.6.18	MAC data consistency.....	45
6.6.19	Restricted operation.....	45
6.6.20	Bus monitoring.....	45
6.6.21	Error handling and overload handling.....	45
7	PL specifications.....	49
7.1	General and functional modelling.....	49
7.2	Services of the PCS interface.....	50
7.2.1	Requirements.....	50
7.2.2	PCS_Data.Request.....	50
7.2.3	PCS_Data.Indicate.....	50
7.2.4	PCS_Mode.Request.....	50
7.2.5	PCS_Status.Transmitter.....	51
7.2.6	PCS_Status.Receiver.....	51
7.3	PCS.....	51
7.3.1	Bit encoding/decoding.....	51
7.3.2	Bit time.....	51
7.3.3	Configuration of the bit time parameters.....	55
7.3.4	Transmitter delay compensation.....	56
7.3.5	Synchronization.....	58
7.3.6	Tolerance range of the oscillator frequencies.....	60
7.4	Attachment unit interface.....	61
7.4.1	General.....	61
7.4.2	PCS to PMA symbols.....	61
7.4.3	PMA to PCS symbol.....	62
7.5	PWM encoding.....	62
7.5.1	General function and definitions.....	62
7.5.2	PCS without PWM encoding.....	63
7.5.3	PCS sub-layer with PWM encoding.....	63
8	Description of supervisor FCE.....	66
8.1	Fault confinement.....	66
8.1.1	Objectives.....	66
8.1.2	Strategies.....	66
8.1.3	Fault confinement interface specification.....	66
8.1.4	Rules of fault confinement.....	69
8.1.5	Node start-up.....	71
8.2	Bus failure management.....	71
Annex A (normative) CAN FD light — Data link layer and physical coding sub-layer requirements of responder nodes.....		72
Annex B (informative) Configuration interface.....		80
Annex C (informative) Additional information.....		81
Bibliography.....		82

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 31, *Data communication*.

This third edition cancels and replaces the second edition (ISO 11898-1:2015), which has been technically revised.

The main changes are as follows:

- CAN XL requirements added;
- CAN FD light protocol ([Annex A](#)) requirements added;
- editorial corrections.

A list of all parts in the ISO 11898 series can be found on the ISO website.


Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The ISO 11898 series provides requirement specifications for the controller area network (CAN) data link layer and physical layer. It is intended for chip implementers, e.g. this document can be used for CAN protocol controllers and ISO 11898-2 for CAN transceivers. The CAN data link layer models the open systems interconnection (OSI) data link layer; it is internally subdivided into logic link control (LLC) and medium access control (MAC). This document also specifies the physical coding sub-layer (PCS) by means of the attachment unit interface (AUI). The PCS also provides the pulse-width modulation (PWM) encoding to be linked to a CAN SIC XL transceiver, which provides the PWM decoding.

The OSI layers above the data link layer (e.g. the network layer) are not specified in the ISO 11898 series of specifications.

Figure 1 shows the relationship between the OSI layers and the CAN sub-layers.



Key

- AUI attachment unit interface
- LLC logic link control
- MAC medium access control
- MDI medium dependent interface
- PCS physical coding sub-layer
- PMA physical medium attachment
- PMD physical medium dependent
- PWM pulse-width modulation

Figure 1 — CAN data link and physical sub-layers in relation to the OSI model

Road vehicles — Controller area network (CAN) —

Part 1: Data link layer and physical coding sublayer

1 Scope

This document specifies the controller area network (CAN) data link layer (DLL) and the physical coding sub-layer (PCS). The CAN DLL features data fields of up to 2048 byte when the CAN extended data field length (XL) frame format is used.

This document divides the CAN DLL into the logical link control (LLC) and the medium access control (MAC) sub-layers. The DLL's service data unit (SDU), which interfaces the LLC and the MAC, is implemented by means of the LLC frame. The LLC frame also features the service data unit type (SDT) and the virtual CAN channel identifier (VCID), which provide higher-layer protocol configuration and identification information. How the higher-layer functions are handled is not specified in this document. There are five implementation options:

- 1 support of the CAN classic frame format only, not tolerating the CAN flexible data rate (FD) frame format;
- 2 support of the CAN classic frame format and tolerating the CAN FD frame format;
- 3 support of the CAN classic frame format and the CAN FD frame format;
- 4 support of the CAN classic frame format, the CAN FD frame format and the CAN XL frame format;
- 5 support of the CAN FD frame format for CAN FD light responders ([Annex A](#)).

NOTE Nodes of the first option can communicate with nodes of the third and fourth option when only the CAN classic frame format is used. Nodes of the first option cannot communicate with nodes of the fifth option: any attempt at communication generates error frames. Therefore, new designs implementing the fourth option can communicate with all other nodes.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

arbitration mode

operating mode of the physical coding sub-layer (PCS) in which it is allowed that dominant bits can overwrite recessive bits