

Railway applications - Testing and simulation for the acceptance of running characteristics of railway vehicles - Running safety under longitudinal compressive force

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

<p>See Eesti standard EVS-EN 15839:2024 sisaldab Euroopa standardi EN 15839:2024 ingliskeelset teksti.</p> <p>Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.</p> <p>Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 16.10.2024.</p> <p>Standard on kättesaadav Eesti Standardimis- ja Akrediteerimiskeskusest.</p>	<p>This Estonian standard EVS-EN 15839:2024 consists of the English text of the European standard EN 15839:2024.</p> <p>This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation and Accreditation.</p> <p>Date of Availability of the European standard is 16.10.2024.</p> <p>The standard is available from the Estonian Centre for Standardisation and Accreditation.</p>
--	---

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 45.060.20

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardimis- ja Akrediteerimiskeskusele. Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardimis- ja Akrediteerimiskeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardimis- ja Akrediteerimiskeskusega: Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation and Accreditation. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation and Accreditation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation and Accreditation: Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

EUROPEAN STANDARD

EN 15839

NORME EUROPÉENNE

EUROPÄISCHE NORM

October 2024

ICS 45.060.20

Supersedes EN 15839:2012+A1:2015

English Version

Railway applications - Testing and simulation for the acceptance of running characteristics of railway vehicles - Running safety under longitudinal compressive force

Applications ferroviaires - Essais et simulations en vue de la validation du comportement dynamique des véhicules ferroviaires - Sécurité de circulation sous force longitudinale de compression

Bahnanwendungen - Versuche und Simulationen für die Zulassung der fahrtechnischen Eigenschaften von Eisenbahnfahrzeugen - Fahrsicherheit unter Längsdruckkräften

This European Standard was approved by CEN on 26 August 2024.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents	Page
European foreword	4
Introduction	6
1 Scope	7
2 Normative references	8
3 Terms and definitions	8
4 Deviations from requirements	10
5 Proof of the endurable longitudinal compressive force	10
5.1 Assessment of endurable longitudinal compressive force	10
5.2 Required endurable longitudinal compressive force for use in conventional trains	10
5.3 Assessment of endurable longitudinal compressive force for use in high-capacity trains	11
5.4 Assessment of endurable longitudinal compressive force for vehicles equipped with centre couplers	11
5.5 Special vehicle layout	11
5.5.1 Permanently coupled units consisting of 2-axle wagons with standard ends or diagonal buffers	11
5.5.2 Permanently coupled units with bar couplers	12
Annex A (normative) Symbols	13
Annex B (normative) Conditions for the execution and evaluation of propelling tests for the determination of the endurable longitudinal compressive force of vehicles with side buffers	14
B.1 Test track	14
B.2 Test train	14
B.2.1 Standard configuration	14
B.2.2 Supplementary configuration for 2-axle vehicles with $LoB \geq 15,75$ m	16
B.3 Execution of the tests	16
B.4 Measured values	17
B.4.1 Measurements during the tests	17
B.4.2 Other measurements	18
B.5 Used criteria for the evaluation of the endurable longitudinal compressive force	18
B.6 Analysis	18
B.7 Documentation of results	19
B.7.1 General	19
B.7.2 Characteristics of the track on which the tests were carried out	20
B.7.3 Characteristics of the test vehicle	20
B.7.4 Test results	20

Annex C (informative) Vehicles incorporated in conventional trains: Conditions for dispensation from the assessment of running safety under longitudinal compressive force.....	21
C.1 General.....	21
C.2 2-axle wagons.....	21
C.3 Wagons with two 2-axle bogies.....	23
C.4 Wagons with 3-axle bogies.....	26
C.5 Railbound construction and maintenance machines.....	27
Annex D (informative) Conventional trains: Design characteristics of standardized interfaces of permanent coupled units for dispensation from the assessment of running safety under longitudinal compressive force - Specification of interface with diagonal buffers.....	29
Annex E (informative) Requirements for the use of simulations as proof for endurable longitudinal compressive force.....	30
E.1 Introduction.....	30
E.2 State of the art for the heavy rail system in ENs related to running dynamics.....	30
E.3 Modelling for simulations.....	30
E.3.1 General.....	30
E.3.2 Intermediate wagons and trailing flanking wagon.....	31
E.3.3 Leading flanking wagon.....	32
E.3.4 Test track.....	32
E.4 Validation of the model.....	32
E.5 Performance of simulations.....	33
E.5.1 Required parameters (friction, track, speed etc).....	33
E.5.2 Criteria applied for evaluation.....	33
Annex F (informative) Scenarios for the assessment of endurable longitudinal compressive force of a vehicle incorporated in a high-capacity train.....	34
Annex G (informative) Vehicle incorporated in a high-capacity trains: conditions for dispensation from the assessment of running safety under longitudinal compressive force.....	36
G.1 Introduction.....	36
G.2 Wagons with 2 bogies.....	36
G.3 Articulated wagons with 3 bogies.....	37
Annex H (informative) Vehicles with centre couplers.....	38
Bibliography.....	39

European foreword

This document (EN 15839:2024) has been prepared by Technical Committee CEN/TC 256 “Railway applications”, the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2025, and conflicting national standards shall be withdrawn at the latest by April 2025.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 15839:2012+A1:2015.

This document includes the following significant technical changes with respect to EN 15839:2012+A1:2015:

- railbound construction and maintenance machines added in the scope, which explains why the term vehicle has mostly replaced the term wagon in this document;
- requirements for endurable longitudinal compressive force in EN 15839:2012+A1:2015 kept in the present document and mainly reported in 5.2 for conventional trains. New optional requirements in 5.3, informative Annex F and informative Annex G added for endurable longitudinal compressive force in high-capacity trains. The reason is to make the link between the present document and the methodology for assessment of high-capacity trains (described in IRS 40421);
- 5.4 and informative Annex H on assessment of endurable longitudinal compressive force for vehicles with centre couplers added;
- 5.5 about special vehicle layout and more particularly 5.5.2 “Permanently coupled units with a bar coupler” added;
- Clause 5 “Evaluation of the torsional coefficient of a car body c_t^* ” and 6 “Condition for dispensation from tests or calculations regarding the safety against derailment on twisted track” removed as these sections are already in EN 14363:2016+A2:2022;
- Clause 7 (except 7.2) relocated in normative Annex B. Some precisions in normative Annex B added and 7.2 relocated in Annex C. Dispensation from the assessment of endurable longitudinal compressive force for wagon with 3 axle bogies and railbound construction and maintenance machines added. Dispensation from the assessment of endurable longitudinal compressive force for machines comes from EN 14033-1:2017;
- possibility to assess endurable longitudinal compression force with simulation added in 5.1 and informative Annex E.

This document has been prepared under a standardization request addressed to CEN by the European Commission. The Standing Committee of the EFTA States subsequently approves these requests for its Member States.

Any feedback and questions on this document should be directed to the users’ national standards body. A complete listing of these bodies can be found on the CEN website.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.

This document is a preview generated by EVS

Introduction

Due to the operating conditions of braking or propelling, high longitudinal compressive force can occur between coupled freight vehicles. This force can be safety-related especially in S-shaped curves with small radii under some conditions depending also on the design of the vehicle and the coupling.

This document defines the acceptance process to be followed by vehicles that are operated in a way that high longitudinal compressive force can occur in the trains.

The establishment of this document was based on currently existing rules, practices, and procedures to define acceptance criteria ensuring running safety under the existing operating conditions. It provides a defined assessment method between vehicle design, track layout and braking operation. Investigations according to this document are not necessary if operating practice shows that running safety is achieved without them.

The following principles are applied:

- a) the railway system requires comprehensive technical rules to ensure an acceptable interaction between vehicle and track;
- b) due to the numerous national and international regulations, new railway vehicles are tested and homologated before putting them into service. In addition, existing acceptance are checked when operating conditions are extended;
- c) in view of the significance of international traffic, the harmonization of existing regulations is required. In some cases, additional rules are required as well: an update of existing regulations is also needed due to the considerable progress achieved in the field of railway-specific methods for measuring, evaluation, and data processing;
- d) it is of particular importance that the existing level of safety and reliability is not compromised even when changes in design and operating practices are demanded.

This document is derived in essential parts from UIC 530-2:2011, which is based on practical tests performed in ERRI-B12.

Variations from the conditions specified in this document are allowed as specified by Article 7 of Directive 2016/797/EU.

For national or multilateral operations, variations to the defined conditions can be authorized.

1 Scope

This document defines the assessment of endurable longitudinal compressive force (LCF) of a vehicle. The endurable longitudinal compressive force is a parameter depending on the vehicle design. It is used to estimate the risk of derailment of a vehicle as a result of being subjected to longitudinal compressive force, under operating conditions.

NOTE 1 As operating conditions can vary in several aspects (infrastructure, train configurations etc.), this document defines uniform assessments of endurable longitudinal compressive force per vehicle in specific operating conditions. The main assessment of endurable longitudinal compressive force for conventional trains is derived from UIC 530-2:2011, which is based on practical tests performed in ERRI-B12. Assessments of endurable longitudinal compressive force for high-capacity trains in this document are required by the methodology of IRS 40421. IRS 40421 assesses operational train parameters.

This document applies to the following types of vehicles:

- single wagons;
- permanently coupled units with standard ends between the vehicles;
- permanently coupled units with diagonal buffers and screw couplers between the vehicles;
- permanently coupled units with a bar coupler between the vehicles;
- articulated units with 2-axle bogies;
- wagons with 3-axle bogies;
- low-floor wagons with eight or more axles (e.g. rolling road wagon);
- vehicles with centre couplers;
- railbound construction and maintenance machines as defined in EN 14033-1:2017.

NOTE 2 This document defines the acceptance process to be followed by vehicles that are operated in a way that high longitudinal compressive force occur in the trains due to their operational environment (e.g. train composition, brake mode, track layout).

The following vehicles are not in the scope of this document:

- locomotives and passenger rolling stocks;
- vehicles that are only operated in passenger trains.

NOTE 3 Locomotives, passenger rolling stocks and vehicles operated in passenger trains only are not in the scope of this document as they either are subject to low longitudinal compressive force in operation or have sufficient endurable longitudinal compressive force due to their axle load.

Acceptance criteria and test conditions as well as conditions for simulation are defined in this document. Conditions for dispensation of the assessment of the endurable longitudinal compressive force are also defined in this document.

This document applies principally to vehicles which operate without restrictions on tracks with a gauge of 1 435 mm in Europe.

NOTE 4 The influence on railway systems using other gauges is not sufficiently understood to extend the scope of this document to gauges other than 1 435 mm.

NOTE 5 For wagons with centre couplers, a need for assessment of derailment risk due to Longitudinal Forces on other gauges (1 524 mm, 1 600 mm, 1 668 mm) has been expressed. The influence on railway systems using other gauges is not sufficiently understood. This document only introduces some notions to assess it independently from the gauge.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 15551:2022, *Railway applications — Railway rolling stock — Buffers*

EN 15566:2022, *Railway applications — Railway Rolling stock — Draw gear and screw coupling*

EN 16235:2023, *Railway applications — Testing for the acceptance of running characteristics of railway vehicles - Freight wagons — Conditions for dispensation of freight wagons with defined characteristics from on-track tests according to EN 14363*

EN 17343:2023, *Railway applications — General terms and definitions*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 17343:2023, the symbols given in Annex A, and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp/>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

torsional coefficient of vehicle body

relevant parameter for running safety under compressive forces and safety against derailment on twisted track

Note 1 to entry: Test conditions for deriving the torsional coefficient of a carbody are defined in EN 14363:2016+A2:2022.

3.2

safety against derailment on twisted track

safety of a vehicle against wheel climbing of a guiding wheel whilst negotiating a curved track with limit conditions of twist

Note 1 to entry: Test conditions are defined in EN 14363:2016+A2:2022.

3.3

longitudinal compressive force

longitudinal force which is applied on a vehicle through its interfaces with flanking vehicles

Note 1 to entry: The longitudinal compressive force depends on many parameters such as the composition of the train, the track layout, the driving manoeuvre, and dynamic parameters.