



**International
Standard**

ISO 13825

**Petroleum and related products —
Determination of arsenic in
crude petroleum using atomic
fluorescence spectrometry**

*Pétrole et produits connexes — Détermination de l'arsenic dans
le pétrole brut par spectrométrie de fluorescence atomique*

**First edition
2025-10**

This document is a preview generated by EMS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	1
5 Reagents	1
6 Apparatus	3
7 Sampling and sample preparation	4
7.1 Sampling.....	4
7.2 Mixing samples.....	4
7.3 Preparation of test solution.....	4
8 Instrumental set-up	5
9 Procedure	5
10 Calculation using the calibration curve	6
11 Expression of results	6
12 Precision	6
12.1 Repeatability, <i>r</i>	6
12.2 Reproducibility, <i>R</i>	6
13 Test report	7
Annex A (normative) Homogenization of samples	8
Bibliography	9

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 28, *Petroleum and related products, fuels and lubricants from natural or synthetic sources*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Arsenic compounds have a wide range of contents in crude oil. During the refining process, it is easy for the arsenic compounds to be adsorbed by the catalyst, leading to catalyst poisoning. It has been confirmed that arsenic compounds in crude oil at a concentration level of 10^{-3} mg/kg can cause permanent poisoning and deactivation of platinum-based catalysts for reforming. The presence of arsenic compounds can directly lead to contamination of straight run fractions of oil products such as naphtha or heavy fraction oil.

The determination of arsenic content plays an important role in guiding the removal of arsenic, determining the arsenic tolerance of catalysts, and extending the service life of catalysts.

This document provides a method to determine the arsenic content in crude oil. Since arsenic occurs naturally in organic and inorganic compounds, a closed state is maintained during the digestion process in order to fully decompose all arsenic containing compounds and avoid losses.

Petroleum and related products — Determination of arsenic in crude petroleum using atomic fluorescence spectrometry

WARNING — It is absolutely essential that tests conducted according to this document be carried out by suitably trained staff. This document does not purport to address all of the safety problems, if any, associated with its use. It is the responsibility of the user to establish appropriate safety and health practices and to ensure compliance with any national regulatory conditions.

1 Scope

This document specifies a method for the determination of arsenic content in crude oil pretreated by a closed microwave digestion method by atomic fluorescence spectrometry.

The precision statement of this test method was determined in an interlaboratory study and is valid for samples with an arsenic content between 0,35 mg/kg and 3,57 mg/kg. The test method can also be applied to samples with either a higher or lower arsenic content, however, no precision data has been determined at levels outside of this range.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3696, *Water for analytical laboratory use — Specification and test methods*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

4 Principle

After adding acid to the sample and pre-treating it by a closed microwave digestion method, adding thiourea-ascorbic acid mixed solution to reduce the arsenic (V) to arsenic (III) in the solution, add sodium tetrahydroborate solution under acidic conditions to convert the arsenic into gaseous arsenic hydrogen. At the same time, when the hydrogen generated by the reaction of sodium borohydride and acid is brought into the atomizer by argon, the hydrogen is ignited and forms an argon hydrogen flame, and arsine leads into the atomizer by means of argon gas flow. The arsenic content in the sample is quantitatively measured by atomic fluorescence spectrometry.

5 Reagents

It is important to use high purity reagents in all cases. Use only reagents of recognized analytical grade, unless otherwise specified.