

INFOTEHNOLOOGIA

Raadiosageduse tuvastaja üksuse haldamiseks

**Osa 6: Raadioliidese edastusparameetrid 860 MHz kuni
960 MHz juures**

Information technology

Radio frequency identification for item management

Part 6: Parameters for air interface communications

at 860 MHz to 960 MHz

(ISO/IEC 18000-6:2010)

EVS

EESTI STANDARDI EESSÕNA

See Eesti standard EVS-ISO/IEC 18000-6:2011 „Infotehnoloogia. Raadiosageduse tuvastaja üksuse haldamiseks. Osa 6: Raadioliidese edastusparameetrid 860 MHz kuni 960 MHz juures“ sisaldab rahvusvahelise standardi ISO/IEC 18000-6:2010 „Information technology — Radio frequency identification for item management — Part 6: Parameters for air interface communications at 860 MHz to 960 MHz“ identset ingliskeelset teksti.

Standard EVS-ISO/IEC 18000-6:2011 on jõustunud sellekohase teate avaldamisega EVS Teataja 2011. aasta oktoobrikuu numbris.

Standard on kättesaadav Eesti Standardikeskusest.

NATIONAL FOREWORD

This Estonian Standard EVS-ISO/IEC 18000-6:2011 consists of the identical English text of the International Standard ISO/IEC 18000-6:2010 „Information technology — Radio frequency identification for item management — Part 6: Parameters for air interface communications at 860 MHz to 960 MHz“.

This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.

The standard is available from the Estonian Centre for Standardisation.

Käsitlusala

See ISO/IEC 18000 osa defineerib raadioliidese raadiosageduse tuvastamise (RFID) seadmetele, mis töötavad 860 MHz kuni 960 MHz tööstusliku, teadusliku ja meditsiinilise (ISM) eesmärgiga raadiosagedusalas, mida kasutatakse üksuse haldamise rakendustes. See pakub ühtset tehnilist kirjeldust RFID seadmetele, mida saavad kasutada RFID rakenduse standardeid arendavad ISO komisjonid. Selle ISO/IEC 18000 osa eesmärk on võimaldada ühilduvust ja julgustada toodete koostalitlusvõimet kasvaval RFID rahvusvahelisel turul. Standard defineerib edastus- ja tagasisidelingi tehniliste omaduste parameetrid, sealhulgas, aga mitte ainult, töösageduse, töökanali täpsuse, kasutatava kanali ribalaiuse, maksimaalse efektiivse isotroopse kiirgusvõimsuse (EIRP), vääremissiooni, modulatsiooni, töötsükli, andmekodeerimise, andmemahu, andmemahu täpsuse, andmete saatmise järjekorra ning vajadusel töökanalite, sageduse hüpitamise kiiruse, vahetamise meetodi, jaotusjada ja koodiedastuskiiruse parameetrid. Lisaks määratleb see kommunikatsiooniprotokolli, mida kasutatakse raadioliidese.

See ISO/IEC 18000 osa täpsustab füüsilised ja loogilised nõuded RFID süsteemile passiivtagasipeegeldaja, ülekuulaja-räägib-esimesena (ITF) ja märgistatu-räägib-ainult-pärast-kuulamist (TOTAL). Süsteem hõlmab Ülekuulajajaid ja Märgistatuid, mis on samuti tuntud kui sildid. Ülekuulaja saab Märgistatult informatsiooni, edastades püsiva laine (CW) RF signaali Märgistatule; Märgistatu vastab, moduleerides oma antenni peegelduse koefitsiendi ja seeläbi peegeldades informatsioonisignaali tagasi Ülekuulajale.

Scope

This part of ISO/IEC 18000 defines the air interface for radio frequency identification (RFID) devices operating in the 860 MHz to 960 MHz Industrial, Scientific, and Medical (ISM) band used in item management applications. It provides a common technical specification for RFID devices that can be used by ISO committees developing RFID application standards. This part of ISO/IEC 18000 is intended to allow for compatibility and to encourage interoperability of products for the growing RFID market in the international marketplace. It defines the forward and return link parameters for technical attributes including, but not limited to, operating frequency, operating channel accuracy, occupied channel bandwidth, maximum effective isotropic radiated power (EIRP), spurious emissions, modulation, duty cycle, data coding, bit rate, bit rate accuracy, bit transmission order, and, where appropriate, operating channels, frequency hop rate, hop sequence, spreading sequence, and chip rate. It further defines the communications protocol used in the air interface.

This part of ISO/IEC 18000 specifies the physical and logical requirements for a passive-backscatter, Interrogator-Talks-First (ITF) or tag-talks-only-after-listening (TOTAL) RFID system. The system comprises Interrogators, and tags, also known as labels. An Interrogator receives information from a tag by transmitting a continuous-wave (CW) RF signal to the tag; the tag responds by modulating the reflection coefficient of its antenna, thereby backscattering an information signal to the Interrogator.

<p>Süsteem on ITF, tähendades seda, et Märgistatu moduleerib oma antenni peegelduse koefitsiendi koos infosignaali ainult pärast Ülekuulajalt või TOTAL-ilt saadud juhiseid, tähendades seda, et Märgistatu moduleerib oma antenni peegelduse koefitsiendi koos infosignaali pärast sisenemist Ülekuulaja alale pärast esimest Ülekuulaja modulatsiooni kuulmist, selgitamaks välja, kas süsteem on ITF või mitte.</p> <p>Detailsemalt, see ISO/IEC 18000 osa sisaldab ühte neljatüübilist režiimi. Nelja tüübi detailsed tehnilised erinevused on esitatud parameetrite tabelis.</p> <p>Tüübid A, B ja C on ITF. Tüüp A kasutab edastuslingis impulsisageduse kodeerimist (PIE) ning adaptiivset ALOHA põrkearbitraaži algoritmi. Tüüp B kasutab edastuslingis Manchesteri ja adaptiivset kahendpuu põrkearbitraaži algoritmi. Tüüp C kasutab edastuslingis PIE-t ja juhuslikku põrkearbitraaži algoritmi.</p> <p>Tüüp D on TOTAL, põhinedes pulss-positsioonikodeeringul, või Miller M=2 kodeeritud alakandjal.</p> <p>See ISO/IEC 18000 osa täpsustab</p> <ul style="list-style-type: none"> — ülekuulaja ja märgistatu vahelised (kommunikatsioonilingi signaali kihi) füüsilised sidemed, — ülekuulaja ja märgistatu opereerimisprotseduurid ja käsud, — põrkearbitraaži skeemi, mida kasutatakse spetsiifilise märgi identifitseerimiseks mitmemärgilises keskkonnas. 	<p>The system is ITF, meaning that a tag modulates its antenna reflection coefficient with an information signal only after being directed to do so by an Interrogator, or TOTAL, meaning that a tag modulates its antenna reflection coefficient with an information signal upon entering an Interrogator's field after first listening for Interrogator modulation in order to determine if the system is ITF or not.</p> <p>In detail, this part of ISO/IEC 18000 contains one mode with four types. The detailed technical differences between the four types are shown in the associated parameter tables.</p> <p>Types A, B and C are ITF. Type A uses Pulse-Interval Encoding (PIE) in the forward link and an adaptive ALOHA collision-arbitration algorithm. Type B uses Manchester in the forward link and an adaptive binary-tree collision-arbitration algorithm. Type C uses PIE in the forward link and a random slotted collision-arbitration algorithm.</p> <p>Type D is TOTAL based on Pulse Position Encoding or Miller M=2 encoded subcarrier.</p> <p>This part of ISO/IEC 18000 specifies</p> <ul style="list-style-type: none"> — physical interactions (the signalling layer of the communication link) between Interrogators and tags, — Interrogator and tag operating procedures and commands, — the collision arbitration scheme used to identify a specific tag in a multiple-tag environment.
--	--

ICS 35.040

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Aru 10, 10317 Tallinn, Eesti; www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:
Aru 10, 10317 Tallinn, Estonia; www.evs.ee; phone 605 5050; e-mail info@evs.ee

Contents

Page

Foreword	xiii
Introduction.....	xiv
1 Scope	1
2 Conformance	2
2.1 Claiming conformance	2
2.2 Interrogator conformance and obligations	2
2.3 Tag conformance and obligations	2
3 Normative references	3
4 Terms, definitions, symbols and abbreviated terms	3
4.1 Terms and definitions	3
4.2 Symbols	6
4.3 Abbreviated terms	7
4.4 Notation	10
5 Overview	10
5.1 General	10
5.2 Parameter tables	12
6 Common elements of the physical layer for Types A, B, and D	21
6.1 General	21
6.2 Interrogator power-up waveform	21
6.3 Interrogator power-down	22
6.4 Frequency hopping carrier rise and fall times	23
6.5 FM0 return link	24
6.5.1 FM0 return link general	24
6.5.2 Modulation	24
6.5.3 Data rate	24
6.5.4 Data coding	24
6.5.5 Message format	25
6.5.6 Return preamble	25
6.5.7 Cyclic redundancy check (CRC)	26
7 Type A	28
7.1 Physical layer and data coding	28
7.1.1 PIE (Pulse interval encoding) forward link	28
7.2 Data elements	32
7.2.1 Unique identifier (Tag ID)	32
7.2.2 Sub-UID	33
7.2.3 Application family identifier	33
7.2.4 Data storage format identifier (DSFID)	34
7.3 Protocol elements	34
7.3.1 Tag memory organisation	34
7.3.2 Support of battery-assisted tags	34
7.3.3 Block lock status	35
7.3.4 Tag signature	35
7.4 Protocol description	36
7.4.1 Protocol concept	36
7.4.2 Command format	37
7.4.3 Command flags	37
7.4.4 Round size	38
7.4.5 Command code definition and structure	39

7.4.6	Command classes	39
7.4.7	Command codes and CRC.....	40
7.4.8	Response format.....	43
7.4.9	Tag states	45
7.4.10	Collision arbitration	47
7.4.11	General explanation of the collision arbitration mechanism	47
7.5	Timing specifications	50
7.5.1	Timing specifications general	50
7.5.2	Tag state storage	50
7.5.3	Forward link to return link handover	50
7.5.4	Return link to forward link handover	51
7.5.5	Acknowledgement time window	51
7.6	Command format examples.....	53
7.7	Mandatory commands.....	53
7.7.1	Mandatory commands general.....	53
7.7.2	Next_slot.....	53
7.7.3	Standby_round.....	54
7.7.4	Reset_to_ready	56
7.7.5	Init_round_all	56
7.8	Optional commands	59
7.8.1	Optional commands general	59
7.8.2	Init_round	59
7.8.3	Close_slot.....	60
7.8.4	New_round	61
7.8.5	Select (by SUID)	63
7.8.6	Read_blocks.....	64
7.8.7	Get_system_information.....	68
7.8.8	Begin_round.....	71
7.8.9	Write_single_block	73
7.8.10	Write_multiple_blocks.....	75
7.8.11	Lock_blocks	77
7.8.12	Write_AFI	79
7.8.13	Lock_AFI.....	81
7.8.14	Write_DSFID command	83
7.8.15	Lock_DSFID.....	85
7.8.16	Get_blocks_lock_status.....	87
7.8.17	Init_Fast_Slots	89
7.9	Custom commands.....	92
7.10	Proprietary commands.....	93
8	Type B	93
8.1	Physical layer and data coding	93
8.1.1	Forward link.....	93
8.1.2	Return link	96
8.1.3	Protocol concept.....	96
8.1.4	Command format	97
8.1.5	Response format.....	99
8.1.6	WAIT	99
8.1.7	Examples of a command packet	99
8.1.8	Communication sequences at packet level	100
8.2	Btree protocol and collision arbitration	101
8.2.1	Definition of data elements, bit and byte ordering.....	101
8.2.2	Tag memory organisation	102
8.2.3	Block security status.....	103
8.2.4	Overall protocol description, Btree protocol	103
8.2.5	Collision arbitration	108
8.2.6	Commands	110
8.2.7	Command types	110
8.2.8	Transmission errors	137

9	Type C.....	138
9.1	Protocol overview.....	138
9.1.1	Physical layer.....	138
9.1.2	Tag-identification layer.....	138
9.2	Command types and command structure.....	138
9.2.1	General.....	138
9.2.2	Mandatory.....	138
9.2.3	Optional.....	138
9.2.4	Custom.....	139
9.2.5	Proprietary.....	139
9.3	Description of operating procedure.....	139
9.3.1	Signalling.....	139
9.3.2	Tag selection, inventory, and access.....	154
10	Type D.....	202
10.1	Applicability.....	202
10.2	Protocol overview.....	203
10.2.1	General.....	203
10.2.2	Protocol parameter values.....	204
10.2.3	Tag arbitration.....	204
10.2.4	Operating procedure.....	205
10.2.5	TagMsg.....	207
10.2.6	CW control.....	208
10.2.7	Message encoding.....	208
10.2.8	Symbol modulation.....	208
10.2.9	Page modulation.....	208
10.2.10	Interrogator modulation detection.....	211
10.3	Type D Data.....	211
10.3.1	General.....	211
10.3.2	TID.....	212
10.3.3	Structured data encoding.....	214
10.3.4	Tag configuration.....	218
10.4	Encoding and decoding TID-S Tags.....	218
10.4.1	Encoding rules.....	218
10.4.2	Decoding rules.....	219
11	Battery Assisted Passive (BAP) Interrogator Talks First Type C systems (optional).....	220
11.1	Applicability.....	220
11.2	General overview, definitions, and requirements of BAP.....	220
11.3	Battery Assisted Passive inventoried flag and state machine behaviour modifications.....	222
11.3.1	Modification to ready state and power-down support for BAP Tags.....	222
11.3.2	Signal loss tolerance via timer (mandatory).....	222
11.3.3	Modified persistence of BAP PIE inventory flags (optional).....	225
11.4	Battery Assisted Passive PIE (optional).....	227
11.4.1	<i>Flex_Query</i> command (optional).....	227
11.4.2	BAP PIE detailed operation including optional Battery Saver Mode.....	228
11.5	Manchester mode Battery Assisted operation protocol extensions.....	235
11.5.1	Introduction.....	235
11.5.2	Physical layer.....	236
11.5.3	Manchester Activation.....	241
11.5.4	Commands summary.....	257
11.6	Extended Protocol Control and Battery Tag Capabilities Reporting and Setting.....	271
11.6.1	General.....	271
11.6.2	Extended Protocol Control definition.....	272
11.6.3	Battery Assisted Passive Tag Capability Reporting, Setting, and duty cycle/mode control (optional).....	274
12	Sensor support.....	303
12.1	Applicability.....	303
12.2	Overview.....	303

12.3	Real Time Clock (RTC)	304
12.3.1	General.....	304
12.3.2	Setting the RTC	304
12.3.3	<i>BroadcastSync</i> command (optional, for Type C)	305
12.3.4	Time synchronisation.....	306
12.4	<i>HandleSensor</i> command (optional, for Type C)	307
12.5	Simple Sensor	308
12.5.1	Type C and Simple Sensor	308
12.5.2	Type D and Simple Sensor	310
12.6	Sensor Directory System and Full Function Sensors.....	310
12.6.1	Sensor Access – General Approach.....	310
Annex A	(informative) Calculation of 5-bit and 16-bit cyclic redundancy checks for ISO/IEC 18000-6 Type A, Type B, Type C, and Type D.....	317
A.1	Example CRC-5 encoder/decoder	317
A.2	Example CRC-16 encoder/decoder	317
A.3	Example CRC-16 calculations	318
Annex B	(normative) Memory mapping for ISO/IEC 18000-6 Type B.....	322
B.1	Unique identifier (normative).....	322
B.1.1	Unique identifier general.....	322
B.1.2	Unique identifier format	322
B.1.3	Unique identifier according to ANSI 256	322
B.1.4	Remaining system memory	323
Annex C	(informative) Tag memory map for ISO/IEC 18000-6 Type B.....	327
C.1	Tag memory map	327
Annex D	(normative) Extensible bit vectors (EBV) for ISO/IEC 18000-6 Type C	328
Annex E	(normative) State-transition tables for ISO/IEC 18000-6 Type C.....	329
E.1	Contents	329
E.2	State transition tables for passive	329
E.2.1	Present state: Ready	329
E.2.2	Present state: Arbitrate	330
E.2.3	Present state: Reply	331
E.2.4	Present state: Acknowledged.....	332
E.2.5	Present state: Open	333
E.2.6	Present state: Secured.....	334
E.2.7	Present state: Killed	335
E.3	State transition tables for BAP PIE.....	336
E.3.1	Present state: sleep	336
E.3.2	Present state: low power listen	336
E.3.3	Present state: listen or stateful listen.....	336
E.3.4	Present state: stateful sleep or stateful low power listen	336
E.3.5	Present state: battery ready	337
E.3.6	Present state: Arbitrate	337
E.3.7	Present state: Reply	338

E.3.8	Present state: Acknowledged	339
E.3.9	Present state: Open.....	340
E.3.10	Present state: Secured.....	342
E.3.11	Present state: Killed	344
E.4	State transition tables for BAP Manchester	344
E.4.1	Present state: Hibernate	344
E.4.2	Present state: Activation code check.....	345
E.4.3	Present state: Stateful Hibernate.....	345
E.4.4	Present state: Battery Ready	346
E.4.5	Present state: Arbitrate.....	348
E.4.6	Present state: Reply	350
E.4.7	Present state: Acknowledged	352
E.4.8	Present state: Open.....	354
E.4.9	Present state: Secured.....	356
E.4.10	Present state: Killed	359
Annex F	(normative) Command-response tables for ISO/IEC 18000-6 Type C	360
F.1	Contents	360
F.2	Command response tables for passive	360
F.2.1	Command response: Power-up	360
F.2.2	Command response: <i>Query</i>	360
F.2.3	Command response: <i>QueryRep</i>	361
F.2.4	Command response: <i>QueryAdjust</i>	361
F.2.5	Command response: <i>ACK</i>	362
F.2.6	Command response: <i>NAK</i>	362
F.2.7	Command response: <i>Req_RN</i>	362
F.2.8	Command response: <i>Select</i>	363
F.2.9	Command response: <i>Read</i>	363
F.2.10	Command response: <i>Write</i>	363
F.2.11	Command response: <i>Kill</i>	364
F.2.12	Command response: <i>Lock</i>	364
F.2.13	Command response: <i>Access</i>	365
F.2.14	Command response: <i>BlockWrite</i>	365
F.2.15	Command response: <i>BlockErase</i>	366
F.2.16	Command response: <i>BlockPermalock</i>	366
F.2.17	Command response: T ₂ timeout	367
F.2.18	Command response: Invalid command	367
F.3	Command response tables for BAP PIE	368
F.3.1	Command response: <i>Flex_Query</i> (optional for BAP PIE)	368
F.3.2	Command response: <i>INACT_T</i> or Selective Global Timeout.....	368
F.3.3	Command response: Global Timeout	369

F.3.4	Command response: <i>HandleSensor</i>	369
F.3.5	Command response: <i>BroadcastSync</i>	369
F.4	Command Response Tables for Manchester.....	370
F.4.1	Command response: Power-up.....	370
F.4.2	Command response: <i>QueryRep</i>	370
F.4.3	Command response: <i>QueryAdjust</i>	370
F.4.4	Command response: <i>ACK</i>	371
F.4.5	Command response: <i>NAK</i>	372
F.4.6	Command response: <i>Req_RN</i>	372
F.4.7	Command response: <i>Select</i>	372
F.4.8	Command response: <i>Read</i>	372
F.4.9	Command response: <i>Write</i>	372
F.4.10	Command response: <i>Kill</i>	372
F.4.11	Command response: <i>Lock</i>	372
F.4.12	Command response: <i>Access</i>	373
F.4.13	Command response: <i>BlockWrite</i>	373
F.4.14	Command response: <i>BlockErase</i>	373
F.4.15	Command response: <i>BlockPermalock</i>	373
F.4.16	Command response: T ₂ timeout	373
F.4.17	Command response: <i>Long Activation</i>	373
F.4.18	Command response: <i>Short Activation</i>	374
F.4.19	Command response: <i>Query_BAT</i>	375
F.4.20	Command response: <i>Next</i>	376
F.4.21	Command response: <i>Deactivate_BAT</i>	376
F.4.22	Command response: <i>Broadcast ID</i>	377
F.4.23	Command response: <i>Multirate_Reset</i>	378
F.4.24	Command response: <i>HandleSensor</i>	378
F.4.25	Command response: <i>BroadcastSync</i>	378
F.4.26	Command response: Session Flag timer timeout.....	379
F.4.27	Command response: INACT_T or Selective Global Timeout.....	379
F.4.28	Command response: Global Timeout.....	379
F.4.29	Command response: T _A	380
F.4.30	Command response: OpRegister Read/Write.....	380
F.4.31	Command response: Invalid command	381
Annex G	(informative) Example slot-count (Q) selection algorithm for ISO/IEC 18000-6 Type C.....	382
G.1	Example algorithm an Interrogator might use to choose Q.....	382
Annex H	(informative) Example of Tag inventory and access for ISO/IEC 18000-6 Type C	383
H.1	Example inventory and access of a single Tag.....	383

Annex I (normative) Dense- and Multiple-Interrogator channelised signalling for ISO/IEC 18000-6 Type C	387
I.1 General	387
I.2 Overview of Dense-Interrogator channelised signalling (informative)	387
Annex J (informative) Interrogator-to-Tag link modulation for ISO/IEC 18000-6 Type C	390
J.1 Baseband waveforms, modulated RF, and detected waveforms	390
Annex K (normative) Error codes for ISO/IEC 18000-6 Type C	392
K.1 Tag error codes and their usage	392
Annex L (normative) Slot counter for ISO/IEC 18000-6 Type C	394
L.1 Slot-counter operation	394
Annex M (informative) Example data-flow exchange for ISO/IEC 18000-6 Type C	395
M.1 Overview of the data-flow exchange	395
M.2 Tag memory contents and lock-field values	395
M.3 Data-flow exchange and command sequence	396
Annex N (informative) Optional Tag features for ISO/IEC 18000-6 Type C	397
N.1 General	397
N.2 Optional Tag passwords	397
N.2.1 Kill password	397
N.2.2 Access password	397
N.3 Optional Tag memory banks and memory-bank sizes	397
N.3.1 Reserved memory	397
N.3.2 Ull memory	397
N.3.3 TID memory	397
N.3.4 User memory	397
N.4 Optional Tag commands	398
N.5 Optional Tag error-code reporting format	398
N.6 Optional Tag backscatter modulation format	398
N.7 Optional Tag functionality	398
Annex O (informative) Cyclic redundancy check (CRC) for ISO/IEC 18000-6 Type D	399
O.1 Type D TID CRC-16	399
Annex P (informative) Battery Assisted Tag to Interrogator synchronization for ISO/IEC 18000-6 Type C	400
P.1 Introduction	400
P.2 General concept	400
P.3 Tag to Interrogator synchronization	401
Annex Q (normative) Simple Sensors Data Block for ISO/IEC 18000-6 Type C and Type D	403
Q.1 Simple sensor types	403
Q.2 General bit-based rules	404
Q.3 Temperature sensor with 14° C span	404
Q.3.1 Monitored measurement span	404

Q.3.2	Accuracy	404
Q.3.3	Sampling regime	405
Q.3.4	High in-range limit level	405
Q.3.5	Low in-range limit level	406
Q.3.6	Monitor delay.....	406
Q.3.7	High out-of-range alarm delay.....	407
Q.3.8	Low out-of-range alarm delay.....	407
Q.3.9	Alarms	408
Q.4	Temperature sensor with 28° C span	409
Q.4.1	Monitored measurement span.....	409
Q.4.2	Accuracy	409
Q.4.3	Sampling regime	409
Q.4.4	High in-range limit	409
Q.4.5	Low in-range limit	409
Q.4.6	Monitor delay.....	410
Q.4.7	High out-of-range alarm delay.....	410
Q.4.8	Low out-of-range alarm delay.....	410
Q.4.9	Alarms	410
Q.5	Relative humidity	410
Q.5.1	Monitored measurement span.....	410
Q.5.2	Accuracy	410
Q.5.3	Sampling regime	411
Q.5.4	High in-range limit level	411
Q.5.5	Low in-range limit level	411
Q.5.6	Monitor delay.....	411
Q.5.7	High out-of-range alarm delay.....	411
Q.5.8	Low out-of-range alarm delay.....	411
Q.5.9	Alarms	411
Q.6	Impact	412
Q.6.1	Monitored measurement span.....	412
Q.6.2	Accuracy	412
Q.6.3	Sampling regime	412
Q.6.4	High in-range limit	412
Q.6.5	Low in-range limit	412
Q.6.6	Monitor delay.....	412
Q.6.7	High out-of-range alarm delay.....	412
Q.6.8	Low out-of-range alarm delay.....	413
Q.6.9	Alarms	413
Q.7	Tilt.....	413
Q.7.1	Monitored measurement span.....	413

Q.7.2	Accuracy.....	413
Q.7.3	Sampling regime.....	413
Q.7.4	High in-range limit.....	413
Q.7.5	Low in-range limit.....	413
Q.7.6	Monitor delay.....	413
Q.7.7	High out-of-range alarm delay.....	414
Q.7.8	Low out-of-range alarm delay.....	414
Q.7.9	Alarms.....	414
Annex R	(normative) Record structures and commands for Ported Simple Sensors for ISO/IEC 18000-6 Type C and Type D.....	415
R.1	Record structure types.....	415
R.1.1	Simple sensor data block.....	416
R.1.2	Sensor characteristics record block.....	416
R.1.3	Manufacturer record block.....	416
R.1.4	Authorisation password record block.....	417
R.1.5	Calibration record block.....	417
R.1.6	Sample and configuration record block.....	419
R.1.7	Event record block.....	420
R.1.8	Time synchronisation record block.....	421
R.2	Ported Simple Sensor commands.....	421
R.2.1	Read-Simple-Sensor-Data-Block.....	422
R.2.2	Read-Manufacturer-Record.....	422
R.2.3	Write-Password.....	423
R.2.4	Read-Calibration-Record.....	423
R.2.5	Write-Sample-And-Configuration-Record.....	424
R.2.6	Initialise-Sensor-Monitoring.....	425
R.2.7	Read-Sample-And-Configuration-Record.....	425
R.2.8	Read-Event-Record.....	426
R.2.9	Write-UTC-Timestamp.....	427
R.2.10	Read-Time-Synchronisation-Record.....	428
R.2.11	Erase-Monitored-Data.....	428
R.2.12	Activate-Simple-Sensor.....	429
R.2.13	Deactivate-Simple-Sensor.....	429
Annex S	(informative) BAP PIE and Manchester mode tutorial guide for ISO/IEC 18000-6 Type C.....	430
S.1	Executive summary of Battery Assisted Passive RFID in this standard.....	430
S.2	Battery Assisted Passive fundamentals.....	432
S.2.1	Propagation physics and resulting relationship between Interrogator and Tag sensitivity.....	432
S.2.2	Tag receiver issues.....	434
S.3	BAP PIE.....	435
S.4	Manchester.....	435

S.5	Guidance on using Next vs. Deactivate_BAT (PIE and Manchester)	436
S.6	Reliable inventory status tracking	436
S.7	Environmental validation	437
S.7.1	INACT_T and (Selective) Global Timeout timer refresh	437
S.8	Fade delay tolerance via INACT_T and Global Timeout	438
S.9	Clocks and commanded data rates and BLFs	438
S.10	Tag Capabilities Reporting and Setting (TCRS)	439
S.11	BAP PIE persistence compliance	439
Annex T (informative)	Manchester mode RF power control for ISO/IEC 18000-6 Type C	440
T.1	General	440
T.2	Power levelling description	440
T.3	Power leveling algorithm	442
Bibliography	445

EVS

Introduction

This part of ISO/IEC 18000 describes a passive backscatter radio frequency identification (RFID) system that supports the following system capabilities:

- identification and communication with multiple tags in the field;
- selection of a subgroup of tags for identification or with which to communicate;
- reading from and writing to or rewriting data many times to individual tags;
- user-controlled permanently lockable memory;
- data integrity protection;
- Interrogator-to-tag communications link with error detection;
- tag-to-Interrogator communications link with error detection;
- support for both passive back-scatter tags with or without batteries.

This part of ISO/IEC 18000 specifies the physical and logical requirements for a passive-backscatter, RFID system operating in the 860 MHz to 960 MHz frequency range. The system comprises Interrogators, also known as readers, and tags, also known as labels.

An Interrogator transmits information to a tag by modulating an RF signal in the 860 MHz to 960 MHz frequency range. The tag receives both information and operating energy from this RF signal. Passive tags are those which receive all of their operating energy from the Interrogator's RF waveform. If tags maintain a battery then they may operate using some passive principles; however, they do not necessarily get all their operating energy from the Interrogator's RF waveform.

An Interrogator receives information from a tag by transmitting a continuous-wave (CW) RF signal to the tag; the tag responds by modulating the reflection coefficient of its antenna, thereby backscattering an information signal to the Interrogator. The system is Interrogator-Talks-First (ITF) for Types A, B and C, meaning that a tag modulates its antenna reflection coefficient with an information signal only after being directed to do so by an Interrogator.

Interrogators and tags are not required to talk simultaneously; rather, communications are half-duplex, meaning that Interrogators talk and tags listen, or vice versa.

This part of ISO/IEC 18000 further contains an optional "tag only talks after listening" Type D, an enhanced Tag Talks Only (TTO) technique. Type D uses Pulse-Position Encoding (PPE) or Miller encoding in the return link and does not define a dedicated forward link. In fact, tags may implement one of the types defined in this part of ISO/IEC 18000 (A, B, or C) besides Type D in order to allow enhanced tag access techniques.

The International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC) draw attention to the fact that it is claimed that compliance with this document may involve the use of patents concerning radio frequency identification technology.

ISO and IEC take no position concerning the evidence, validity and scope of these patent rights.

The holders of these patent rights have assured ISO and IEC that they are willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of these patent rights are registered with ISO and IEC.

Information on the declared patents may be obtained from:

Contact details	
Patent Holder:	
Legal Name	Alien Technology Corporation
Contact for license application:	
Name & Department	Dr. John Stephen Smith, Chief Technology Officer and Founder
Address	18220 Butterfield Blvd
Address	Morgan Hill, CA, 95037, USA
Tel.	+1 (408) 782 - 3900
Fax	+1 (408) 782 - 3910
E-mail	ssmith@alientechnology.com
URL (optional)	www.alientechnology.com
Patent Holder:	
Legal Name	Atmel Automotive GmbH
Contact for license application:	
Name & Department	Leo Merken, Legal department, ATMEL Corporation
Address	2325 Orchard Parkway
Address	San Jose, CA, 95131, USA
Tel.	+1 (408) 436 - 4251
Fax	+1 (408) 436 - 2615
E-mail	Leo.merken@atmel.com
URL (optional)	

EVS

Patent Holder:	
Legal Name	CISC Semiconductor Design+Consulting GmbH
Contact for license application:	
Name & Department	Markus Pistauer, CEO
Address	Lakeside B07
Address	9020 Klagenfurt, Austria
Tel.	+43(463) 508 808
Fax	+43(463) 508 808-18
E-mail	m.pistauer@cisc.at
URL (optional)	www.cisc.at
Patent Holder:	
Legal Name	EM Microelectronic Marin SA
Contact for license application:	
Name & Department	G. Meusburger, IP manager
Address	Rue des Sors
Address	CH-2074 MARIN, Switzerland
Tel.	+41(32) 755 5111
Fax	+41(32) 755 5403
E-mail	info@emmicroelectronic.com
URL (optional)	http://www.emmicroelectronic.com

EVS

Patent holder:	
ETRI (Electronics Telecommunication Research Institute)	
Contact for license application:	
Name & Department: Min-Sheo Choi, Intellectual Property Management Team	
Address	138 Gajeongno, Yuseong-gu
Address	Daejeon, 305-700, Korea
Tel.	+82-42-860-0756
Fax	+82-42-860-3831
E-mail	choims@etri.re.kr
URL (optional)	www.etri.re.kr
Patent Holder:	
Legal Name	Impinj, Inc.
Contact for license application:	
Name & Department	Chris Diorio, CTO
Address	701 N. 34th Street, Suite 300
Address	Seattle, WA 98103, USA
Tel.	+1.206.517.5300
Fax	+1.206.517.5262
E-mail	diorio@impinj.com
URL (optional)	www.impinj.com

EVS

Patent Holder:	
Legal Name	Intellex Corporation
Contact for license application:	
Name & Department	Peter Mehring (CEO & President), Executive Department
Address	2465 Augustine Drive
Address	Santa Clara CA 95054, USA
Tel.	+1 408 200 6516
Fax	+1 408 200 6599
E-mail	pmehring@intellex.com
URL (optional)	www.intellex.com
Patent Holder:	
Legal Name	Intermec IP Corporation
Contact for license application:	
Name & Department	Phyllis T. Turner-Brim, Esq.; Legal Department
Address	6001 36 th Ave W
Address	Everett, Washington 98203, USA
Tel.	+1 (425) 265 2480
Fax	+1 (425) 501 6587
E-mail:	phyllis.turnerbrim@intermec.com
URL (optional)	www.intermec.com

EVS

Patent Holder:	
Legal Name	IPICO Innovation Inc.
Contact for license application:	
Name & Department	Hendrik van Eeden - CTO
Address	4480 Harvester Road
Address	BURLINGTON, Ontario – Canada L7L 4X2
Tel.	+1 (905) 631 6310
Fax	+1 (905) 631 6614
E-mail	hendrik.van.eeden@ipcio.com
URL (optional)	www.ipico.com
Patent Holder:	
Legal Name	IPICO South Africa (Pty) Ltd
Contact for license application:	
Name & Department	Luther Erasmus – President Innovation
Address	B5 Project Close, 311 Regeny Drive, R21 Corporate Park
Address	IRENE, 0157, South Africa
Tel.	+27 (12) 345 9520
Fax	+27 (12) 345 5834
E-mail	luther.erasmus@ipcio.com
URL (optional)	www.ipico.com

EVS

Patent Holder:	
Legal Name	Magellan Technology Pty. Limited
Contact for license application:	
Name & Department	Ms Jean Angus
Address	65 Johnston St
Address	Annandale, NSW 2038, Australia
Tel.	+61 2 9562 9800
Fax	+61 2 9518 7620
E-mail	jeana@magellan-technology.com
URL (optional)	www.magellan-technology.com
Patent Holder:	
Legal Name	NXP B.V.
Contact for license application:	
Name & Department	Harald Roeggla – Intellectual Property & Licensing
Address	Gutheil-Schoder-Gasse 8-12
Address	1102 Vienna, Austria
Tel.	+43 (1) 60 870 1469
Fax	+43 (1) 60 870 1101
E-mail	harald.roeggla@nxp.com
URL (optional)	

EVS

Patent Holder:	
Legal Name	Symbol Technologies, Inc.
Contact for license application:	
Name & Department	Aaron Bernstein, Legal Department
Address	One Motorola Plaza, MSA6
Address	Holtsville, NY 11742, USA
Tel.	+1 (631) 738 - 4055
Fax	+1 (631)738-4110
E-mail	Aaron Bernstein@symbol.com
URL (optional)	
Patent Holder:	
Legal Name	University of Pittsburgh – Of the Commonwealth of Pennsylvania
Contact for license application:	
Name & Department	Marc S. Malandro, Ph.D., CLP
Address	University of Pittsburgh, 200 Gardner Steel Conference Center
Address	Thackeray & O'Hara Streets, Pittsburgh, PA 15260
Tel.	+1 (412) 624 - 8787
Fax	+1 (412) 648 2259
E-mail	
URL (optional)	

EVS

Patent Holder:

Legal Name Zebra Technologies Corporation

Contact for license application:

Name & Department Eric McAlpine, IP Counsel Legal Department

Address 333 Corporate Woods Parkway

Address Vernon Hills, Illinois 60061-3109

Tel. +1 (847) 793-5640

Fax +1 (847) 955-4514

E-mail emcalpine@zebra.com

URL (optional)

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

The latest information on IP that may be applicable to this part of ISO/IEC 18000 can be found at www.iso.org/patents

EVS

Information technology — Radio frequency identification for item management —

Part 6: Parameters for air interface communications at 860 MHz to 960 MHz

1 Scope

This part of ISO/IEC 18000 defines the air interface for radio frequency identification (RFID) devices operating in the 860 MHz to 960 MHz Industrial, Scientific, and Medical (ISM) band used in item management applications. It provides a common technical specification for RFID devices that can be used by ISO committees developing RFID application standards. This part of ISO/IEC 18000 is intended to allow for compatibility and to encourage inter-operability of products for the growing RFID market in the international marketplace. It defines the forward and return link parameters for technical attributes including, but not limited to, operating frequency, operating channel accuracy, occupied channel bandwidth, maximum effective isotropic radiated power (EIRP), spurious emissions, modulation, duty cycle, data coding, bit rate, bit rate accuracy, bit transmission order, and, where appropriate, operating channels, frequency hop rate, hop sequence, spreading sequence, and chip rate. It further defines the communications protocol used in the air interface.

This part of ISO/IEC 18000 specifies the physical and logical requirements for a passive-backscatter, Interrogator-Talks-First (ITF) or tag-talks-only-after-listening (TOTAL) RFID system. The system comprises Interrogators, and tags, also known as labels. An Interrogator receives information from a tag by transmitting a continuous-wave (CW) RF signal to the tag; the tag responds by modulating the reflection coefficient of its antenna, thereby backscattering an information signal to the Interrogator. The system is ITF, meaning that a tag modulates its antenna reflection coefficient with an information signal only after being directed to do so by an Interrogator, or TOTAL, meaning that a tag modulates its antenna reflection coefficient with an information signal upon entering an Interrogator's field after first listening for Interrogator modulation in order to determine if the system is ITF or not.

In detail, this part of ISO/IEC 18000 contains one mode with four types. The detailed technical differences between the four types are shown in the associated parameter tables.

Types A, B and C are ITF. Type A uses Pulse-Interval Encoding (PIE) in the forward link and an adaptive ALOHA collision-arbitration algorithm. Type B uses Manchester in the forward link and an adaptive binary-tree collision-arbitration algorithm. Type C uses PIE in the forward link and a random slotted collision-arbitration algorithm.

Type D is TOTAL based on Pulse Position Encoding or Miller M=2 encoded subcarrier.

This part of ISO/IEC 18000 specifies

- physical interactions (the signalling layer of the communication link) between Interrogators and tags,
- Interrogator and tag operating procedures and commands,
- the collision arbitration scheme used to identify a specific tag in a multiple-tag environment.

2 Conformance

2.1 Claiming conformance

To claim conformance with this part of ISO/IEC 18000, an Interrogator or tag shall comply with all relevant clauses of this part of ISO/IEC 18000, except those marked as “optional”. The Interrogator or tag shall also operate within local radio regulations, which can further restrict operation.

Relevant conformance test methods are provided in ISO/IEC TR 18047-6.

Conformance can also require a license from the owner of any intellectual property utilized by said device.

2.2 Interrogator conformance and obligations

To conform to this part of ISO/IEC 18000, an Interrogator shall

- support at least one Type of A, B, C or D – it can optionally support two, three or all four;
- implement the mandatory commands defined in this part of ISO/IEC 18000;
- modulate/transmit and receive/demodulate a sufficient set of the electrical signals defined in the signalling layer of this part of ISO/IEC 18000 to communicate with conformant tags; and
- operate within the applicable local regulations.

To conform to this part of ISO/IEC 18000, an Interrogator may

- implement any subset of the optional commands defined in this part of ISO/IEC 18000, and
- implement any proprietary and/or custom commands in conformance with this part of ISO/IEC 18000.

To conform to this part of ISO/IEC 18000, the Interrogator shall not

- implement any command that conflicts with this part of ISO/IEC 18000, or
- require the use of an optional, proprietary, or custom command to meet the requirements of this part of ISO/IEC 18000.

2.3 Tag conformance and obligations

To conform to this part of ISO/IEC 18000, a tag shall:

- support at least one Type of A, B, C or D;
- operate over the frequency range from 860 MHz to 960 MHz, inclusive;
- implement the mandatory commands defined in this part of ISO/IEC 18000 for the supported types;
- modulate a backscatter signal only after receiving the requisite command from an Interrogator or, in the case of Type D, only after listening for the absence of ITF modulation; and
- conform to local radio regulations.

To conform to this part of ISO/IEC 18000, a tag may

- implement any subset of the optional commands defined in this part of ISO/IEC 18000; and

- implement any proprietary and/or custom commands as defined in Clauses 7, 8 and 9.

To conform to this part of ISO/IEC 18000, a tag shall not:

- implement any command that conflicts with this part of ISO/IEC 18000;
- require the use of an optional, proprietary, or custom command to meet the requirements of this part of ISO/IEC 18000; or
- modulate a backscatter signal unless commanded to do so by an Interrogator using the signalling layer defined in this part of ISO/IEC 18000 or, in the case of Type D, before listening for the absence of ITF modulation.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 7816-6, *Identification cards — Integrated circuit cards — Part 6: Interindustry data elements for interchange*

ISO/IEC 15961, *Information technology — Radio frequency identification (RFID) for item management — Data protocol: application interface*

ISO/IEC 15962, *Information technology — Radio frequency identification (RFID) for item management — Data protocol: data encoding rules and logical memory functions*

ISO/IEC 15963, *Information technology — Radio frequency identification for item management — Unique identification for RF tags*

ISO/IEC 19762 (all parts), *Information technology — Automatic identification and data capture (AIDC) techniques — Harmonized vocabulary*

EPCglobal Tag Data Standards version 1.3 and above, EPCglobal Inc.

4 Terms, definitions, symbols and abbreviated terms

4.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 19762 (all parts) and the following apply.

4.1.1

battery saver mode

battery saving functionality based on low power threshold detection with optional duty cycling