

This document is a preview generated by EVS

Satellite signal distribution over a single coaxial cable -
Second generation

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 50607:2015 sisaldab Euroopa standardi EN 50607:2015 ingliskeelset teksti.	This Estonian standard EVS-EN 50607:2015 consists of the English text of the European standard EN 50607:2015.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 09.01.2015.	Date of Availability of the European standard is 09.01.2015.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 33.060.40

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:

Aru 10, 10317 Tallinn, Eesti; koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Aru 10, 10317 Tallinn, Estonia; homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

English Version

Satellite signal distribution over a single coaxial cable - Second generation

Distribution de signaux par satellite sur un seul câble coaxial - Deuxième génération

Verteilen von Satellitensignalen über ein Koaxialkabel
Zweite Generation

This European Standard was approved by CENELEC on 2014-10-20. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents	Page
Foreword.....	3
Introduction.....	4
1 Scope.....	5
2 Normative references.....	5
3 Terms, definitions and abbreviations.....	6
3.1 Terms and definitions.....	6
3.2 Abbreviations.....	8
3.3 Used commands.....	8
4 System architecture.....	9
5 SCIF control signals.....	12
5.1 DC levels.....	12
5.2 Method of the data bit signalling.....	14
6 Structure and format of the messages of the 2nd generation single cable distribution system (SCD2).....	14
6.1 Backwards Compatibility to EN 50494.....	14
6.2 Non-DiSEqC structure.....	14
6.3 Uni-directional operation.....	15
6.4 Bi-directional operation.....	15
7 SCD2 commands.....	15
7.1 ODU_Channel_change.....	15
7.1.1 Formats.....	15
7.1.2 "Special" frequencies.....	16
7.2 ODU_Channel_change_PIN.....	16
7.3 ODU_UB_avail.....	17
7.4 ODU_UB_PIN.....	18
7.5 ODU_UB_inuse.....	18
7.6 ODU_UB_freq.....	19
7.7 ODU_UB_switches.....	20
8 Conventions.....	21
8.1 UB slots numbering.....	21
8.2 Numbering of satellite IF banks.....	22
9 Traffic collision management rules.....	22
9.1 General.....	22
9.2 Automatic detection of SCIF control signal failure.....	22
9.3 Pseudo-random repeat.....	23
9.3.1 Handling of SCIF control signal.....	23
9.3.2 Random delay generation law.....	23
Annex A (normative) Implementation rules.....	25
A.1 User interface.....	25
A.2 Installation impedance.....	25
A.3 Signal reflection and return loss in installations.....	26
A.4 Power supply of the SCIF.....	26
A.5 Remarks concerning power supply.....	27
Bibliography.....	28

Foreword

This document (EN 50607:2015) has been prepared by CLC/TC 209 “Cable networks for television signals, sound signals and interactive services”.

The following dates are fixed:

- latest date by which this document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2015-10-20
- latest date by which the national standards conflicting with this document have to be withdrawn (dow) 2017-10-20

This document supersedes CLC/TS 50607:2013.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Document preview generated by EVS

Introduction

In EN 61319-1:1996, the interfaces for the control and command of the devices associated with the satellite receivers are described in the following clauses:

- Clause 4: Interfaces requirements for polarizer and polar switchers;
- Clause 5: Interfaces requirements for low-noise block converters (LNB).

In these clauses, analogue techniques are described for controlling the LNB and polar switchers.

In the DiSEqC™ Bus Functional Specification, the “Digital Satellite Equipment Control Bus” (called DiSEqC) is introduced as a single method of communication between the satellite and the peripheral equipment, using only the existing coaxial cables. The existing EN 50494 “Satellite signal distribution over a single coaxial cable in single dwelling installations” describes a system for distributing signals via single coaxial cable issued from different bands and polarisations to several satellite receivers. This specification is limited to 8 units per output of the Single Cable Interface and to 8 Satellite IF banks (bands, feeds, polarisations).

The second generation described in this standard is intended for single and multiple dwelling installations and includes the following enhancements compared to EN 50494:

- The number of demodulators is extended to a maximum of 32 units per output of the Single Cable Interface (hereafter referred to as SCIF) device.
- The system is scaled for a maximum number of 256 Satellite IF banks (bands, feeds, polarisations)
- The SCIF replies, which may be used during installation process, are also based on DiSEqC.
- Equipment according to this standard is downwards compatible to the specifications provided by EN 50494.

1 Scope

This European Standard describes:

- the system physical structure;
- the system control signals, which implement a set of messages using DiSEqC physical layer but not the DiSEqC message structure;
- the definition of identified configurations;
- the management of the potential collisions in the control signals traffic.

Figure 1 illustrates the physical system configuration considered in this standard.

Several satellite signal demodulators can receive signals from any of the input signal banks (Bank 1, Bank 2, Bank M, with $M \leq 256$) of the LNB or the switch. The signals selected by the demodulators (or receivers) are transported via a single cable to these demodulators (Receiver 1, Receiver 2, Receiver N, with $N \leq 32$).

To achieve these single cable distributions, the Single Cable Interface (SCIF, likely embedded in a LNB or a Switch) features some specific functions and characteristics.




Figure 1 — General architecture of the single cable distribution

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50494, *Satellite signal distribution over a single coaxial cable in single dwelling installations*

EN 60728-1, *Cable networks for television signals, sound signals and interactive services – Part 1: System performance of forward paths (IEC 60728-1)*

EN 60728-4, *Cable networks for television signals, sound signals and interactive services – Part 4: Passive wideband equipment for coaxial cable networks (IEC 60728-4)*

EN 61319-1:1996, *Interconnections of satellite receiving equipment – Part 1: Europe (IEC 61319-1:1995)*

IEC 60050-371, *International Electrotechnical Vocabulary - Chapter 371: Telecontrol*

IEC 60050-721, *International Electrotechnical Vocabulary - Chapter 721: Telegraphy, facsimile and data communication*