

**Agglomerated stone - Test methods - Part 13:
Determination of electrical resistivity**

This document is a preview generated by EVS

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 14617-13:2013 sisaldab Euroopa standardi EN 14617-13:2013 ingliskeelset teksti.	This Estonian standard EVS-EN 14617-13:2013 consists of the English text of the European standard EN 14617-13:2013.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 10.04.2013.	Date of Availability of the European standard is 10.04.2013.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 91.100.15

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Aru 10, 10317 Tallinn, Eesti; www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:
Aru 10, 10317 Tallinn, Estonia; www.evs.ee; phone 605 5050; e-mail info@evs.ee

English Version

Agglomerated stone - Test methods - Part 13: Determination of electrical resistivity

Pierre agglomérée - Méthodes d'essai - Partie 13 :
Détermination de la résistivité électrique

Künstlich hergestellter Stein - Prüfverfahren - Teil 13:
Bestimmung des spezifischen elektrischen Widerstands

This European Standard was approved by CEN on 1 March 2013.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....	3
1 Scope	4
2 Normative references	4
3 Principle	4
4 Terms and definitions and symbols	4
5 Sampling and test specimen preparation	5
6 Specimen conditioning	5
7 Electrode system and measuring equipment	6
8 Procedure	6
9 Expression of results	6
10 Report	7
Annex A (informative) DC electrical conduction and polarisation phenomena in insulating materials	10
Annex B (informative) Statistical evaluation of test results	12
B.1 Scope	12
B.2 Symbols and definitions	12
B.3 Statistical evaluation of test results	12
Annex C (informative) Determination of DC volume resistance and resistivity and the corresponding electrical conductance and conductivity	14
C.1 Scope	14
C.2 Test specimen preparation	14
C.3 Specimen conditioning	14
C.4 Electrode system and measuring equipment	14
C.5 Procedure	14
C.6 Expression of results	15
C.7 Report	15
Bibliography	16

Foreword

This document (EN 14617-13:2013) has been prepared by Technical Committee CEN/TC 246 "Natural stones", the secretariat of which is held by UNI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2013, and conflicting national standards shall be withdrawn at the latest by October 2013.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 14617-13:2005.

Clauses 6, 7, 8, 9 and 10 have been modified and a new Annex C has been added since the last edition of this European Standard.

This European Standard is one of a series of standards for test methods for agglomerated stones which includes the following:

- *Part 1: Determination of apparent density and water absorption*
- *Part 2: Determination of flexural strength (bending)*
- *Part 4: Determination of the abrasion resistance*
- *Part 5: Determination of freeze and thaw resistance*
- *Part 6: Determination of thermal shock resistance*
- *Part 8: Determination of resistance to fixing (dowel hole)*
- *Part 9: Determination of impact resistance*
- *Part 10: Determination of chemical resistance*
- *Part 11: Determination of linear thermal expansion coefficient*
- *Part 12: Determination of dimensional stability*
- *Part 13: Determination of electrical resistivity*
- *Part 15: Determination of compressive strength*
- *Part 16: Determination of dimensions, geometric characteristics and surface quality of modular tiles*

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

1 Scope

This European Standard covers the determination of DC insulation resistance, surface resistance and resistivity, and the corresponding electrical conductance and conductivity of specimens of agglomerated stone products conforming to the definition reported in EN 14618. These products are usually made by stone aggregates bound via either resin and filler or cement and water (paste components), or a mixture of polymer/cement and related addition (such as reinforcing fibres, electrically insulating/conducting fillers, etc.).

Resistivity/conductivity may also be used as an indirect measure of some properties of agglomerated stone products (see Annex A - informative).

Volume resistance and resistivity test method and the corresponding electrical conductance and conductivity of specimens of agglomerated stone products are also included (see Annex C - informative).

2 Normative references

Not applicable.

3 Principle

The resistance/conductance of an agglomerated stone specimen is evaluated by the measurement of direct current (DC) flow in the specimen under specified conditions by appropriate electrode systems. The resistivity/conductivity shall be calculated from specimen and electrode dimensions and shapes.

4 Terms and definitions and symbols

4.1 insulation resistance

$\Omega \rightarrow \Omega = \text{ohm}$

insulation resistance between two electrodes that are in electrical contact with an agglomerated stone specimen, calculated as the ratio of the direct voltage applied to the electrodes to the total current flowing between them

Note 1 to entry: It is dependent upon the shape and size as well as the volume and surface resistance of the specimen.

4.2 surface resistance

$R_s (\Omega)$

surface resistance between two electrodes that are in electrical contact with the surface of an agglomerated stone specimen, calculated as the ratio of the direct voltage applied to the electrodes to that portion of the current between them which is primarily distributed on the specimen surface and a thin material layer beneath the specimen surface

Note 1 to entry: Surface conductivity cannot be accurately known, only conventionally, because more or less volume contribution is usually involved in the measurement, depending on the nature of the specimen and environment.

4.3 surface resistivity

$\rho_s (\Omega)$

surface resistivity of the agglomerated stone material, which is calculated as the ratio of the potential gradient parallel to the current direction along its surface to the current per unit width of the surface