

**RAUDTEEALASED RAKENDUSED.
RONGITUVASTUSSÜSTEEMIDE TEHNILISED ANDMED
ÜLE-EUROOPALISE RAUDTEESÜSTEEMI
KOOSTALITUSVÕIME TAGAMISEKS. OSA 2:
TELJELOENDURID**

**Railway Applications - Technical parameters of train
detection systems for the interoperability of the trans-
European railway system - Part 2: Axle counters**

EESTI STANDARDI EESSÕNA**NATIONAL FOREWORD**

See Eesti standard EVS-EN 50617-2:2015 sisaldab Euroopa standardi EN 50617-2:2015 ingliskeelset teksti.	This Estonian standard EVS-EN 50617-2:2015 consists of the English text of the European standard EN 50617-2:2015.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 24.04.2015.	Date of Availability of the European standard is 24.04.2015.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 29.280

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Aru 10, 10317 Tallinn, Eesti; koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Aru 10, 10317 Tallinn, Estonia; homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

ICS 29.280

English Version

Railway Applications - Technical parameters of train detection systems for the interoperability of the trans-European railway system - Part 2: Axle counters

Applications ferroviaires - Paramètres techniques des systèmes de détection des trains - Partie 2: Compteurs d'essieux

Bahnanwendungen - Technische Parameter von Gleisfreimeldesystemen - Teil 2: Achszähler

This European Standard was approved by CENELEC on 2015-03-09. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword	6
Introduction.....	7
1 Scope.....	8
2 Normative references.....	8
3 Terms, definitions and abbreviations.....	9
3.1 Terms and definitions	9
3.2 Abbreviations.....	11
4 Description of train detection system.....	12
5 Safety relevance per parameter.....	13
6 Axle counter system parameters.....	15
6.1 RAMS	15
6.1.1 Reliability.....	15
6.1.2 Availability.....	15
6.1.3 Rate of miscounts	15
6.1.4 Maintainability.....	16
6.1.5 Safety	16
6.2 Immunity against Magnetic fields – in-band and out-of-band	18
6.2.1 General	18
6.2.2 Derivation of Immunity requirements.....	18
6.2.3 Immunity levels for axle counters / Compatibility margins	19
6.2.4 Frequency range of an ACD	19
6.3 Immunity to traction and short circuit current in the rail	19
6.4 Immunity to harmonics of traction current in the rail.....	20
6.5 Sensor position integrity control (functional parameter).....	20
6.6 Integration time.....	20
6.6.1 General	20
6.6.2 Product specific integration time	21
6.6.3 Derivation of the integration time – Example	21
6.7 Signalling power supply quality with respect to availability	22
6.8 Requirements on the connection cables	23
7 Requirements for axle counter systems based on train parameters.....	23
7.1 General	23
7.2 Vehicle, wheel and speed dependent parameters	23
7.2.1 General	23
7.2.2 Wheel parameters.....	24
7.2.3 Vehicle and speed depending parameters	25
7.3 Material properties of vehicle parts in the detection area (metal free space).....	26
7.4 Sinusoidal sway of train	26
7.5 Magnetic track brakes and eddy current brakes.....	27
8 Track based parameters	27
8.1 Material of sleepers	27
8.2 Rail fittings/mounting area	28
8.3 Slab track	28
9 Environmental and other parameters.....	29
9.1 General	29
9.2 Pressure	29

9.3	Movement of surrounding air	29
9.4	Ambient temperatures	29
9.4.1	General	29
9.4.2	Ambient temperature for axle counter evaluator equipment	30
9.4.3	Ambient temperature for ACD (without axle counter sensor)	30
9.4.4	Ambient temperature for axle counter sensor	30
9.5	Humidity	30
9.6	Precipitation	31
9.7	Sealing of housing	31
9.8	Solar radiation	31
9.9	Overvoltage protection (incl. indirect lightning effects)	32
9.10	Contamination	32
9.10.1	General	32
9.10.2	In the track, nearby the track	32
9.10.3	Indoor	32
9.11	Fire Protection	32
9.12	Vibrations / shock	33
9.13	EMC	33
9.13.1	General	33
9.13.2	Requirement and validation for EMC	33
9.14	Definition of Influence from other components	33
Annex A	(informative) Design guide for measurement antennas	34
A.1	Measurement antennas characteristics	34
A.2	Termination impedance	34
Annex B	(normative) Frequency Management (reproduced from CCS TSI, Index 77)	36
Annex C	(normative) Test Equipment, test methodologies and reports to be performed	38
C.1	Test equipment	38
C.1.1	Antenna for generating magnetic fields (FGA)	38
C.1.2	Reference antenna	39
C.1.3	Test signal generator	39
C.2	Test conditions	39
C.2.1	Equipment under test (EUT)	39
C.2.2	Susceptibility criteria	39
C.3	Accuracy of magnetic field measurement	40
C.4	Test methodology to determine immunity (susceptibility border of ACD) to homogenous fields – in-band	40
C.4.1	General	40
C.4.2	Test set up for X-Z direction	41
C.4.3	Test set up for Y-Z direction	41
C.4.4	Test procedure to determine immunity to homogenous steady state fields	42
C.4.5	Transient immunity test / Immunity to intermittent interference	43
C.4.6	Immunity within the filter bandwidth of the EUT	46
C.5	Test methodology to determine immunity to inhomogeneous fields – in band	46
C.5.1	General	46
C.5.2	Test set-up for the movement in X-direction	47
C.5.3	Test set-up for the movement in Y-direction	48
C.5.4	Test procedure	49
C.6	Test methodology for establishing immunity to fields produced by in-band interference currents in the rail	50
C.6.1	General	50
C.6.2	Test set-up	51
C.6.3	Test procedure	52
C.7	Test methodology for out of-band measurements	52
C.8	Immunity to ETCS telepowering fields	52
C.8.1	General	52
C.8.2	Limits and requirements	53
C.8.3	Test methodology to check immunity to ETCS telepowering fields	53

C.9	Test report	57
C.10	Test results according to CCS TSI Index 77	58
C.10.1	General	58
C.10.2	In-band	58
C.10.3	Out-band (10 kHz to 1,3 MHz)	58
Annex ZZ (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2008/57/EC		59
Bibliography		63

Figures

Figure 1 – System boundary of an axle counter system	12
Figure 2 – Correlation between hazard rate and time between trains	17
Figure 3 – Areas for evaluation	19
Figure 4 – Immunity versus duration of interference field	21
Figure 5 – ACD immunity as a function of time duration of in-band disturbance	22
Figure 6 – Filter curves measured and calculated	22
Figure 7 – Definition of the parameters	24
Figure 8 – Axle to axle distance	26
Figure 9 – Definition of sinusoidal sway	27
Figure A.1 – Side view (Y and Z coils, dimensions 50 mm to 150 mm).....	34
Figure B.1 – Areas for evaluation.....	37
Figure C.1 – Homogeneity of field generation antenna (FGA).....	39
Figure C.2 – ACD, schematic diagram.....	40
Figure C.3 – Test set-up for homogeneous fields in X-Z-direction (front view for $\alpha = 0^\circ$).....	41
Figure C.4 – Test set-up for homogeneous fields in X-Z-direction (side view for $\alpha = 0^\circ$)	41
Figure C.5 – Test set-up for homogeneous fields in Y-Z-direction (front view).....	42
Figure C.6 – Test set-up for homogeneous fields in Y-Z-direction (side view for $\alpha = 0^\circ$)	42
Figure C.7 – ACD response to intermittent sinusoidal waves	44
Figure C.8 – Test set-up for inhomogeneous field tests in X-direction (side view).....	47
Figure C.9 – Test set-up for inhomogeneous field tests in X-direction (front view)	48
Figure C.10 – Test set-up for inhomogeneous field tests in Y-direction (side view).....	48
Figure C.11 – Test set-up for inhomogeneous field tests in Y-direction (front view)	49
Figure C.12 – FGA movement / field distribution for inhomogeneous field tests	50
Figure C.13 – Test set-up for rail current tests.....	51
Figure C.14 – Frequency mask	53
Figure C.15 – Influence zones of magnetic fields	54
Figure C.16 – Test setup	55
Figure C.17 – Test set-up for conducted immunity testing.....	56

Tables

Table 1 – Overview of safety relevance in the subclauses	14
Table B.1 – Emission limits and evaluation parameters (narrow band).....	36
Table B.2 – Increased magnetic field limits.....	37

Foreword

This document (EN 50617-2:2015) has been prepared by CLC/SC 9XA "Communication, signalling and processing systems" of CLC/TC 9X "Electrical and electronic applications for railways".

The following dates are fixed:

- latest date by which this document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2016-03-09
- latest date by which the national standards conflicting with this document have to be withdrawn (dow) 2018-03-09

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EU Directive 2008/57/EC amended by Commission Directive 2011/18/EU, see informative Annex ZZ, which is an integral part of this document.

This document is Part 2 of the EN 50617 series, which consists of the following parts under the common title "*Railway Applications - Technical parameters of train detection systems*":

- Part 1: Track circuits;
- Part 2: Axle counters.

Introduction

The working group CENELEC/SC9XA WGA4-2 has developed the limits for electromagnetic compatibility between rolling stock and train detection systems, specifically track circuits and axle counter systems, and correspondingly published two technical specifications: CLC/TS 50238-2 and CLC/TS 50238-3. These limits and associated measurement methods are based on characteristics of existing systems that are well established and still put forward for signalling renewals by infrastructure managers.

To meet the requirements for compatibility between train detection systems and rolling stock in the future and to achieve interoperability and free movement within the European Union, it is necessary to define a “FrM” and a complete set of interface requirements.

Track circuits and axle counter systems, are an integral part of the CCS trackside subsystem in the context of the Rail Interoperability Directive. The relevant basic parameters are enumerated in the CCS and LOC&PAS TSI and specified in the mandatory Specification CCS TSI Index 77 “Interfaces between Control-Command and Signalling Trackside and other Subsystems”. This standard refers whenever needed to the mandatory specification.

The already published specifications CLC/TS 50238-2 and CLC/TS 50238-3 can be used to ascertain conformity of individual train detection systems to the requirements of the TSIs and to the Notified National Rules, which will be in place for the parameters still declared “open points” in CCS TSI Index 77.

The requirements defined in this standard are either compliant with those of CCS TSI Index 77 or can be used as input information for the closure of open points of the CCS TSI Index 77. Where applicable, the standard should refer to the rolling stock FrM in the TSI CCS and the parameter values defined in the CCS TSI Index 77.

1 Scope

This European Standard specifies parameters for the design and usage of axle counter systems.

For this, the standard specifies the technical parameters of axle counter systems associated with the magnetic field limits for RST in the context of interoperability. In addition test methods are defined for establishing the conformity and the performance of axle counter products.

The specified parameters are structured and allocated according to their basic references as follows:

- Axle counter system parameters
- Train based parameters
- Track based parameters
- Environmental and other parameters

Each parameter is defined by a short general description, the definition of the requirement, the relation to other standards and a procedure to show the fulfilment of the requirement as far as necessary. An overview on the safety relevance of each parameter is given – in the context of this European Standard – in a separate table.

This European Standard is intended to be used to assess compliance of axle counter systems and other forms of wheel sensors used for train detection, in the context of the European Directive on the interoperability of the trans-European railway system and the associated technical specification for interoperability relating to the control-command and signalling track-side subsystems.

The frequency bands and rolling stock emission limits are currently defined in the axle counter FrM as specified in the CCS TSI Index 77.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50121-4, *Railway applications — Electromagnetic compatibility — Part 4: Emission and immunity of the signalling and telecommunications apparatus*

EN 50124-2, *Railway applications — Insulation coordination — Part 2: Overvoltages and related protection*

EN 50125-3:2003, *Railway applications — Environmental conditions for equipment — Part 3: Equipment for signaling and telecommunications*

EN 50126 (all parts), *Railway applications — The specification and demonstration of Reliability, Availability, Maintainability and Safety (RAMS)*

EN 50128, *Railway applications — Communication, signalling and processing systems — Software for railway control and protection systems*

EN 50129, *Railway applications — Communications, signalling and processing systems — Safety related electronic systems for signalling*

EN 50238-1, *Compatibility between rolling stock and train detection systems — Part 1: General*

EN 60068-2-1, *Environmental testing — Part 2-1: Tests — Tests A: Cold (IEC 60068-2-1)*

EN 60068-2-2, *Environmental testing — Part 2-2: Tests — Test B: Dry heat (IEC 60068-2-2)*

EN 60068-2-30, *Environmental testing — Part 2-30: Tests - Test Db: Damp heat, cyclic (12 h + 12 h cycle) (IEC 60068-2-30)*

EN 60529, *Degrees of protection provided by enclosures (IP Code) (IEC 60529)*

EN 61000 (all parts), *Electromagnetic compatibility (EMC) (IEC 61000, all parts)*

CCS TSI Index 77, *ERTMS/ETCS UNIT — Interfaces between control-command and signalling trackside and other subsystems*

UNISIG SUBSET-023, *Glossary of UNISIG Terms and Abbreviations*

UNISIG SUBSET-036, *FFFIS for Eurobalise*

UNISIG SUBSET-085, *Test Specification for Eurobalise FFFIS*

3 Terms, definitions and abbreviations

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1.1

antenna for generating magnetic fields

square loop antenna to generate the magnetic fields for testing of the immunity

3.1.2

axle counter detector (ACD)

detector consisting of the axle counter sensor and of the detection circuit, which includes in general filters and rectifiers

3.1.3

axle counter sensor

sensor head mounted in the track

3.1.4

axle counter system

whole system including the axle counter detector ACD with its sensor, and the evaluation unit

3.1.5

bandwidth

difference between the upper and lower frequencies in a contiguous set of frequencies and is typically measured in Hz

3.1.6

direct safety relevant

failure results in a wrong side failure

3.1.7

equipment under test

test object is the set of ACD connected to a rail

3.1.8

immunity level

maximum level of interfering signal at which the correct operation of the equipment is granted to be in line with expectations