
**Connections for fluid power and general
use — Ports and stud ends with ISO 261
metric threads and O-ring sealing —**

**Part 4:
Dimensions, design, test methods and
requirements for external hex and
internal hex port plugs**

*Raccordements pour transmissions hydrauliques et applications
générales — Orifices et éléments mâles à filetage métrique ISO 261 et
joint torique —*

*Partie 4: Dimensions, conception, méthodes d'essai et exigences des
bouchons d'orifice à six pans externes et à six pans internes*



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview generated by EVS

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	2
4 Dimensions.....	2
4.1 Plug dimensions.....	2
4.2 Hex tolerances.....	2
4.3 Screw threads.....	2
5 Requirements.....	2
5.1 Working pressures and working temperatures.....	2
5.2 Performance.....	3
6 O-rings.....	3
7 Test methods.....	3
8 Designation of port plugs.....	3
9 Identification.....	4
10 Manufacture.....	4
10.1 Construction.....	4
10.2 Workmanship.....	4
10.3 Finish.....	4
11 Procurement information.....	4
12 Marking.....	4
13 Identification statement (reference to this part of ISO 6149).....	5

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 6149-4 was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 4, *Connectors and similar products and components*.

ISO 6149 consists of the following parts, under the general title *Connections for fluid power and general use — Ports and stud ends with ISO 261 metric threads and O-ring sealing*:

- *Part 1: Ports with truncated housing for O-ring seal*
- *Part 2: Dimensions, design, test methods and requirements for heavy-duty (S series) stud ends*
- *Part 3: Dimensions, design, test methods and requirements for light-duty (L series) stud ends*
- *Part 4: Dimensions, design, test methods and requirements for external hex and internal hex port plugs*

Introduction

In fluid power systems, power is transmitted and controlled through a fluid (liquid or gas) under pressure within an enclosed circuit. In general applications, a fluid can be conveyed under pressure.

Components are connected through their threaded ports by stud ends on fluid conductor connectors to tubes and pipes or to hose fittings and hoses. Fluid ports are closed by inserting a plug in the port.

This document is a preview generated by EVS

This document is a preview generated by EVS

Connections for fluid power and general use — Ports and stud ends with ISO 261 metric threads and O-ring sealing —

Part 4:

Dimensions, design, test methods and requirements for external hex and internal hex port plugs

1 Scope

This part of ISO 6149 specifies dimensions and performance requirements for external hex and internal hex port plugs for use with ISO 6149-1 ports.

Port plugs in accordance with this part of ISO 6149 can be used at working pressures up to 63 MPa (630 bar¹). The permissible working pressure depends upon the plug end size, materials, design, working conditions, application, etc.

Conformance to the dimensional information in this part of ISO 6149 does not guarantee rated performance. It is necessary that each manufacturer perform testing according to the specification contained in this part of ISO 6149 to assure that components comply with the performance ratings.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 48, *Rubber, vulcanized or thermoplastic — Determination of hardness (hardness between 10 IRHD and 100 IHRD)*

ISO 261:1998, *ISO general-purpose metric screw threads — General plan*

ISO 1629, *Rubber and latices — Nomenclature*

ISO 3601-3:2005, *Fluid power systems — O-rings — Part 3: Quality acceptance criteria*

ISO 4042, *Fasteners — Electroplated coatings*

ISO 4759-1:2000, *Tolerances for fasteners — Part 1: Bolts, screws, studs and nuts — Product grades A, B and C*

ISO 5598², *Fluid power systems and components — Vocabulary*

ISO 6149-1, *Connections for fluid power and general use — Ports and stud ends with ISO 261 metric threads and O-ring sealing — Part 1: Ports with truncated housing for O-ring seal*

1) 1 bar = 0,1 MPa = 10⁵ Pa; 1 MPa = 1 N/mm².

2) To be published. (Revision of ISO 5598:1985)

ISO 6149-2, *Connections for fluid power and general use — Ports and stud ends with ISO 261 metric threads and O-ring sealing — Part 2: Dimensions, design, test methods and requirements for heavy-duty (S series) stud ends*

ISO 7789, *Hydraulic fluid power — Two-, three- and four-port screw-in cartridge valves — Cavities*

ISO 9227, *Corrosion tests in artificial atmospheres — Salt spray tests*

ISO 10683, *Fasteners — Non-electrolytically applied zinc flake coatings*

ISO 19879, *Metallic tube connections for fluid power and general use — Test methods for hydraulic fluid power connections*

3 Terms and definitions

For the purpose of this document, the terms and definitions given in ISO 5598 and the following apply.

3.1

plug

stud end with no through hole for fluid passage, used to contain hydraulic fluid.

4 Dimensions

4.1 Plug dimensions

External hex and internal hex plugs shall conform to the dimensions shown in Figures 1 and 2 and given in Tables 1 and 2, respectively.

4.2 Hex tolerances

External hex tolerances across flats shall be in accordance with ISO 4759-1:2000, product grade C. Minimum across corner dimensions are 1,092 times the nominal width across flats. The minimum side flat is 0,43 times the nominal width across flats. Internal hex tolerances across flats shall be in accordance with ISO 4759-1:2000, product grade A. External hex corners shall be chamfered 10° to 30° to a diameter equal to the width across flats, with a tolerance of $0_{-0,4}$ mm.

4.3 Screw threads

The screw threads on the plug shall be metric screw threads conforming to ISO 261:1998, class 6g.

5 Requirements

5.1 Working pressures and working temperatures

External hex and internal hex plugs conforming to this part of ISO 6149 shall be suitable for use at the working pressures given in Table 3 when used at temperatures between -40 °C and +120 °C. For use at pressures and/or temperatures outside of this range, the manufacturer shall be consulted.

Plugs conforming to this part of ISO 6149 may contain elastomeric seals. Unless otherwise specified, plugs are made and delivered with elastomeric seals for use within the specified working temperature range with petroleum-based hydraulic fluids. The use of these plugs and elastomeric seals with other hydraulic fluids can result in a reduced working temperature range or can render the plugs unsuitable for the application. Manufacturers may supply, upon request, plugs with elastomeric seals for use with hydraulic fluids other than petroleum-based hydraulic fluids that meet the specified working temperature range of the plugs.