

Industrial networks - Wireless communication network
and communication profiles - WIA-FA

This document is a preview generated by EVS

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

| | |
|---|--|
| See Eesti standard EVS-EN 62948:2017 sisaldab Euroopa standardi EN 62948:2017 ingliskeelset teksti. | This Estonian standard EVS-EN 62948:2017 consists of the English text of the European standard EN 62948:2017. |
| Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas | This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation. |
| Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 01.12.2017. | Date of Availability of the European standard is 01.12.2017. |
| Standard on kättesaadav Eesti Standardikeskusest. | The standard is available from the Estonian Centre for Standardisation. |

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 25.040.40, 35.110

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

ICS 25.040.40; 35.110

English Version

**Industrial networks - Wireless communication network
and communication profiles - WIA-FA
(IEC 62948:2017)**

Réseaux industriels - Réseau de communication sans fil et
profils de communication - WIA-FA
(IEC 62948:2017)

Industrielle Kommunikationsnetze - Kommunikationsnetze
und Kommunikationsprofile - WIA-FA
(IEC 62948:2017)

This European Standard was approved by CENELEC on 2017-08-31. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

The text of document 65C/877/FDIS, future edition 1 of IEC 62948, prepared by SC 65C "Industrial networks" of IEC/TC 65 "Industrial-process measurement, control and automation" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62948:2017.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2018-06-01
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2020-12-01

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 62948:2017 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following note has to be added for the standard indicated:

IEC 62657-2 NOTE Harmonized as EN 62657-2.

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

| <u>Publication</u> | <u>Year</u> | <u>Title</u> | <u>EN/HD</u> | <u>Year</u> |
|--------------------|-------------|--|--------------|-------------|
| IEC 61588 | - | Precision clock synchronization protocol for networked measurement and control systems | - | - |
| IEEE 802.11 | 2012 | IEEE Standard for Information technology -- Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications | -- | - |

CONTENTS

| | |
|---|----|
| FOREWORD..... | 12 |
| 1 Scope..... | 14 |
| 2 Normative references | 14 |
| 3 Terms, definitions, abbreviated terms, and conventions..... | 14 |
| 3.1 Terms and definitions..... | 14 |
| 3.2 Abbreviated terms..... | 17 |
| 3.3 Conventions..... | 19 |
| 4 Data coding..... | 20 |
| 4.1 Overview..... | 20 |
| 4.2 Basic data type coding..... | 21 |
| 4.2.1 Integer coding..... | 21 |
| 4.2.2 Unsigned coding..... | 21 |
| 4.2.3 Float coding..... | 22 |
| 4.2.4 Octetstring coding..... | 23 |
| 4.2.5 BitField coding..... | 23 |
| 4.2.6 Bitstring coding..... | 24 |
| 4.2.7 TimeData coding..... | 24 |
| 4.2.8 KeyData coding..... | 25 |
| 4.3 Structured data type coding..... | 25 |
| 4.3.1 Structure type coding..... | 25 |
| 4.3.2 List type coding..... | 25 |
| 5 WIA-FA overview..... | 25 |
| 5.1 Device types..... | 25 |
| 5.1.1 General..... | 25 |
| 5.1.2 Host computer..... | 25 |
| 5.1.3 Gateway device..... | 25 |
| 5.1.4 Access device..... | 26 |
| 5.1.5 Field device..... | 26 |
| 5.1.6 Handheld device..... | 26 |
| 5.2 Network topology..... | 26 |
| 5.3 Protocol architecture..... | 27 |
| 6 System management..... | 29 |
| 6.1 Overview..... | 29 |
| 6.2 Device Management Application Process..... | 30 |
| 6.2.1 General..... | 30 |
| 6.2.2 Network manager..... | 32 |
| 6.2.3 Security manager..... | 32 |
| 6.2.4 Network management module..... | 32 |
| 6.2.5 Security management module..... | 32 |
| 6.2.6 DMAP state machines..... | 32 |
| 6.3 Addressing and address assignment..... | 44 |
| 6.4 Communication resource allocation..... | 45 |
| 6.4.1 General..... | 45 |
| 6.4.2 Communication resource allocation..... | 45 |
| 6.5 Joining and leave process of field device..... | 46 |
| 6.5.1 Join process of a field device..... | 46 |

| | | |
|-------|--|-----|
| 6.5.2 | Communication resource allocation to field device | 47 |
| 6.5.3 | Leaving process of a field device | 48 |
| 6.6 | Network performance monitoring..... | 49 |
| 6.6.1 | Device status report..... | 49 |
| 6.6.2 | Channel condition report..... | 50 |
| 6.7 | Management information base and services..... | 50 |
| 6.7.1 | Management information base..... | 50 |
| 6.7.2 | MIB services..... | 61 |
| 7 | Physical layer | 64 |
| 7.1 | General..... | 64 |
| 7.2 | General requirements based on IEEE STD 802.11-2012 | 64 |
| 7.3 | Additional requirements | 65 |
| 7.3.1 | General | 65 |
| 7.3.2 | Frequency band..... | 65 |
| 7.3.3 | Channel bitmap | 65 |
| 7.3.4 | Transmit power..... | 67 |
| 7.3.5 | Data rate | 67 |
| 8 | Data Link Layer | 67 |
| 8.1 | General..... | 67 |
| 8.1.1 | DLL functions | 67 |
| 8.1.2 | Protocol architecture..... | 67 |
| 8.1.3 | WIA-FA superframe | 68 |
| 8.1.4 | Communication based on multiple access devices | 70 |
| 8.1.5 | Time synchronization..... | 72 |
| 8.1.6 | Frame aggregation/disaggregation..... | 73 |
| 8.1.7 | Fragmentation and reassembly..... | 74 |
| 8.1.8 | Retransmission..... | 74 |
| 8.2 | Data link sub-layer data services | 77 |
| 8.2.1 | General | 77 |
| 8.2.2 | DLDE-DATA.request primitive..... | 77 |
| 8.2.3 | DLDE-DATA.indication primitive | 78 |
| 8.2.4 | Time sequence of DLL data service | 79 |
| 8.3 | Data link sub-layer management services | 80 |
| 8.3.1 | General | 80 |
| 8.3.2 | Network discovery services | 81 |
| 8.3.3 | Time synchronization services | 83 |
| 8.3.4 | Device joining services | 85 |
| 8.3.5 | Device status report services..... | 88 |
| 8.3.6 | Channel condition report services | 90 |
| 8.3.7 | Remote attribute get services | 92 |
| 8.3.8 | Remote attribute set services | 96 |
| 8.3.9 | Device leaving services | 100 |
| 8.4 | DLL frame formats | 102 |
| 8.4.1 | General frame format..... | 102 |
| 8.4.2 | Date frame format..... | 103 |
| 8.4.3 | Aggregation frame format | 104 |
| 8.4.4 | NACK frame format | 104 |
| 8.4.5 | GACK frame format | 104 |
| 8.4.6 | Beacon frame format | 105 |

| | | |
|--------|---|-----|
| 8.4.7 | Join request frame format | 106 |
| 8.4.8 | Join response frame format | 106 |
| 8.4.9 | Leave request frame format | 106 |
| 8.4.10 | Leave response frame format | 106 |
| 8.4.11 | Device status report frame format | 106 |
| 8.4.12 | Channel condition report frame format | 107 |
| 8.4.13 | Time synchronization request frame format | 107 |
| 8.4.14 | Time synchronization response frame format | 107 |
| 8.4.15 | Remote attribute get request frame format | 107 |
| 8.4.16 | Remote attribute get response frame format | 108 |
| 8.4.17 | Remote attribute set request frame format | 108 |
| 8.4.18 | Remote attribute set response frame format | 109 |
| 8.5 | Data link layer state machines | 109 |
| 8.5.1 | DLL state machine of access device | 109 |
| 8.5.2 | DLL state machine of field device | 117 |
| 8.5.3 | Functions used in DLL state machines | 123 |
| 9 | Wired specifications between GW and AD | 124 |
| 9.1 | Overview | 124 |
| 9.2 | Join process of access device | 124 |
| 9.3 | Frame formats between GW and AD | 124 |
| 9.4 | Communication based on multiple access device | 127 |
| 10 | Application Layer | 127 |
| 10.1 | Overview | 127 |
| 10.2 | AL protocol stack | 127 |
| 10.3 | AL functions | 128 |
| 10.3.1 | Data functions | 128 |
| 10.3.2 | Management functions | 128 |
| 10.3.3 | Communication models | 129 |
| 10.4 | Application data | 129 |
| 10.4.1 | General | 129 |
| 10.4.2 | Attribute data | 129 |
| 10.4.3 | Process data | 129 |
| 10.4.4 | Event data | 130 |
| 10.5 | User application process | 131 |
| 10.5.1 | General | 131 |
| 10.5.2 | User application object | 132 |
| 10.5.3 | IO data image on gateway device | 132 |
| 10.5.4 | Alarm mechanism | 133 |
| 10.5.5 | Application configuration | 134 |
| 10.6 | Application services | 140 |
| 10.6.1 | Confirmed services and unconfirmed services | 140 |
| 10.6.2 | Read service | 141 |
| 10.6.3 | Write service | 143 |
| 10.6.4 | Publish service | 144 |
| 10.6.5 | Report service | 145 |
| 10.6.6 | Report ACK service | 146 |
| 10.6.7 | Start service | 147 |
| 10.6.8 | Stop service | 148 |
| 10.7 | Application sub-layer | 149 |

| | | |
|--------------|--|-----|
| 10.7.1 | Overview | 149 |
| 10.7.2 | ASL data service | 149 |
| 10.7.3 | ASL management service | 152 |
| 10.7.4 | ASL message format | 153 |
| 11 | Security | 172 |
| 11.1 | General..... | 172 |
| 11.1.1 | Security management architecture..... | 172 |
| 11.1.2 | Security functions | 174 |
| 11.1.3 | Keys | 174 |
| 11.2 | Security services | 175 |
| 11.2.1 | General | 175 |
| 11.2.2 | Key establish service | 175 |
| 11.2.3 | Key update service | 178 |
| 11.2.4 | Security alarm service | 180 |
| 11.3 | Secure join | 181 |
| 11.3.1 | General | 181 |
| 11.3.2 | Secure join process of FD..... | 182 |
| 11.4 | Key management..... | 183 |
| 11.4.1 | General | 183 |
| 11.4.2 | Key establish process..... | 183 |
| 11.4.3 | Key update process | 184 |
| 11.5 | DLL secure communication | 186 |
| 11.6 | Security alarm..... | 187 |
| 11.7 | Secure frame format | 187 |
| 11.7.1 | General secure DLL frame format..... | 187 |
| 11.7.2 | Secure aggregation frame format..... | 188 |
| 11.7.3 | Key establish request frame format..... | 188 |
| 11.7.4 | Key establish response frame format..... | 189 |
| 11.7.5 | Key update request frame format..... | 189 |
| 11.7.6 | Key update response frame format | 189 |
| 11.7.7 | Security alarm request frame format | 190 |
| Annex A | (informative) Security strategy for WIA-FA network | 191 |
| A.1 | Risk analysis for WIA-FA network | 191 |
| A.2 | Security principles for WIA-FA network | 191 |
| A.3 | Security objectives for WIA-FA network | 191 |
| A.4 | Security grade of WIA-FA network | 191 |
| Annex B | (informative) Regional modification for compliance with ETSI standards | 193 |
| B.1 | General..... | 193 |
| B.2 | Compliance with ETSI EN 300 440-2 V1.4.1 | 193 |
| B.3 | Compliance with ETSI EN 300 328V1.9.1..... | 193 |
| Bibliography | | 197 |
| Figure 1 | – Conventions used for state machines | 19 |
| Figure 2 | – Integer coding | 21 |
| Figure 3 | – Unsigned coding | 21 |
| Figure 4 | – Single float coding | 22 |
| Figure 5 | – Double float coding | 23 |
| Figure 6 | – WIA-FA redundant star topology | 27 |

| | |
|--|-----|
| Figure 7 – OSI basic reference model mapped to WIA-FA..... | 27 |
| Figure 8 – Protocol architecture of WIA-FA | 28 |
| Figure 9 – Data flow over WIA-FA network..... | 29 |
| Figure 10 – System management scheme..... | 29 |
| Figure 11 – DMAP of management system..... | 30 |
| Figure 12 – DMAP state machine of gateway device | 33 |
| Figure 13 – DMAP sub-state machine of gateway device for each field device | 33 |
| Figure 14 – DMAP state machine of a field device | 37 |
| Figure 15 – DMAP state machine of an access device | 40 |
| Figure 16 – Long address structure of device..... | 45 |
| Figure 17 – Join process of field device | 47 |
| Figure 18 – Communication resource allocation process for a field device | 48 |
| Figure 19 – Passive leave process of a field device | 49 |
| Figure 20 – Device status report process of field device | 49 |
| Figure 21 – Channel condition report process of field device | 50 |
| Figure 22 – BitMap format..... | 66 |
| Figure 23 – WIA-FA DLL protocol architecture | 68 |
| Figure 24 – The template of timeslot..... | 68 |
| Figure 25 – WIA-FA default superframe | 69 |
| Figure 26 – WIA-FA superframe..... | 70 |
| Figure 27 – The example of WIA-FA devices multi-channel communication..... | 70 |
| Figure 28 – An example of beacon communication based on multiple ADs..... | 71 |
| Figure 29 – Process of one-way time synchronization..... | 72 |
| Figure 30 – Process of two-way time synchronization | 73 |
| Figure 31 – Aggregation frame payload format..... | 74 |
| Figure 32 – Example of NACK-based retransmission mode..... | 75 |
| Figure 33 – Example of multi-unicast retransmission mode | 76 |
| Figure 34 – Example of multi-broadcast retransmission mode..... | 76 |
| Figure 35 – Example of GACK-based timeslot backoff mode..... | 77 |
| Figure 36 – Time sequence of period data service from FD to GW | 79 |
| Figure 37 – Time sequence of other data service from FD to GW..... | 80 |
| Figure 38 – Time sequence of data service from GW to FD..... | 80 |
| Figure 39 – Network discovery process..... | 82 |
| Figure 40 – Time synchronization process | 85 |
| Figure 41 – Device join process | 88 |
| Figure 42 – Device status report process | 90 |
| Figure 43 – Channel condition report process | 91 |
| Figure 44 – Remote attribute get process | 96 |
| Figure 45 – Remote attribute set process..... | 100 |
| Figure 46 – Device leave process | 101 |
| Figure 47 – General frame format | 102 |
| Figure 48 – DLL frame header | 102 |
| Figure 49 – DLL frame control format..... | 102 |

| | |
|---|-----|
| Figure 50 – DLL Date frame format..... | 103 |
| Figure 51 – DLL Aggregation frame format | 104 |
| Figure 52 – NACK frame format..... | 104 |
| Figure 53 – NACK information | 104 |
| Figure 54 – GACK frame format..... | 104 |
| Figure 55 – GACK_Struct Structure | 104 |
| Figure 56 – DLL Beacon frame format..... | 105 |
| Figure 57 – Shared timeslot count | 105 |
| Figure 58 – DLL join request frame format..... | 106 |
| Figure 59 – DLL join request frame format..... | 106 |
| Figure 60 – DLL leave request frame format | 106 |
| Figure 61 – DLL leave response frame format..... | 106 |
| Figure 62 – DLL Device status report frame format..... | 106 |
| Figure 63 – DLL Channel condition report frame format | 107 |
| Figure 64 – DLL time synchronization request frame format..... | 107 |
| Figure 65 – DLL time synchronization response frame format | 107 |
| Figure 66 – DLL Remote attribute get request frame format | 108 |
| Figure 67 – DLL remote attribute get response frame format..... | 108 |
| Figure 68 – DLL Remote attribute set request frame format | 109 |
| Figure 69 – DLL remote attribute set response frame format..... | 109 |
| Figure 70 – DLL state machine of access device..... | 110 |
| Figure 71 – DLL state machine of field device..... | 118 |
| Figure 72 – General frame format between GW and AD..... | 124 |
| Figure 73 – AL within the protocol architecture of WIA-FA | 128 |
| Figure 74 – The relationships between UAPs and DAPs | 132 |
| Figure 75 – User application objects in a field device..... | 132 |
| Figure 76 – Example of IO data images on the gateway device..... | 133 |
| Figure 77 – C/S VCR relationships between GW and FDs..... | 136 |
| Figure 78 – P/S VCR relationships between GW and FDs..... | 137 |
| Figure 79 – R/S VCR relationships between GW and FDs..... | 138 |
| Figure 80 – Application configuration procedure for a field device..... | 139 |
| Figure 81 – Example of UAO data aggregation and disaggregation process..... | 140 |
| Figure 82 – Read request message format..... | 141 |
| Figure 83 – Read positive response message format | 142 |
| Figure 84 – Read negative response message format..... | 142 |
| Figure 85 – Read service process..... | 143 |
| Figure 86 – Write request message format..... | 143 |
| Figure 87 – Write negative response message format..... | 143 |
| Figure 88 – Write service process..... | 144 |
| Figure 89 – Publish request message format | 145 |
| Figure 90 – Publish process from FD to GW | 145 |
| Figure 91 – Publish process from GW to FD | 145 |
| Figure 92 – Report request message format | 145 |

| | |
|--|-----|
| Figure 93 – Report service process..... | 146 |
| Figure 94 – Report ACK request message format | 146 |
| Figure 95 – Report ACK positive response message format | 146 |
| Figure 96 – Report ACK negative response message format..... | 147 |
| Figure 97 – Report ACK service process..... | 147 |
| Figure 98 – Start service process..... | 148 |
| Figure 99 – Stop service process | 149 |
| Figure 100 – ASL general message format | 153 |
| Figure 101 – Format of Message control field | 153 |
| Figure 102 – Confirmed application service primitives among layers | 155 |
| Figure 103 – Unconfirmed application service primitives among layers | 156 |
| Figure 104 – ASL management service primitives between ASL and UAP..... | 156 |
| Figure 105 – State transition diagram of AMCL | 157 |
| Figure 106 – State transition diagram of AMSV | 159 |
| Figure 107 – State transition diagram of AMPB | 162 |
| Figure 108 – State transitions diagram of AMSB | 165 |
| Figure 109 – State transitions diagram of AMRS | 168 |
| Figure 110 – State transitions diagram of AMRK | 169 |
| Figure 111 – Security management architecture | 173 |
| Figure 112 – Life cycle of keys..... | 175 |
| Figure 113 – Format of NONCE | 176 |
| Figure 114 – Time sequence of key establishment..... | 178 |
| Figure 115 – Time sequence of key updating | 180 |
| Figure 116 – SecAlarmt_Struct structure..... | 180 |
| Figure 117 – Time sequence of security alarm | 181 |
| Figure 118 – Secure join process of field device | 183 |
| Figure 119 – Key establish process for field device..... | 184 |
| Figure 120 – Key update state machine for FD | 185 |
| Figure 121 – General secure DLL frame format..... | 187 |
| Figure 122 – Secure aggregation frame format | 188 |
| Figure 123 – Key establish request frame format | 189 |
| Figure 124 – Key establish response frame format..... | 189 |
| Figure 125 – Key update request frame format | 189 |
| Figure 126 – Key update response frame format..... | 189 |
| Figure 127 – Security alarm request frame format..... | 190 |
| Figure B.1 – Timeslot timing template | 194 |
| Table 1 – Conventions used for state transitions | 20 |
| Table 2 – Integer16 coding | 21 |
| Table 3 – Unsigned16 coding..... | 22 |
| Table 4 – Octetstring coding | 23 |
| Table 5 – Coding of BitField8 data with one octet | 24 |
| Table 6 – Coding of BitField16 data with two octets | 24 |

| | |
|--|----|
| Table 7 – Coding of BitField24 data with three octets..... | 24 |
| Table 8 – Bitstring coding | 24 |
| Table 9 – Network management functions..... | 31 |
| Table 10 – Security management functions..... | 31 |
| Table 11 – DMAP state transition of gateway device..... | 33 |
| Table 12 – DMAP sub-state transition of gateway device for each field device | 34 |
| Table 13 – DMAP state transition of a field device | 37 |
| Table 14 – DMAP state transition of an access device | 40 |
| Table 15 – Functions used in DMAP state machines..... | 43 |
| Table 16 – Unstructured attributes | 51 |
| Table 17 – Structured attributes..... | 54 |
| Table 18 – Superframe_StructStructure | 54 |
| Table 19 – Link_Struct Structure..... | 55 |
| Table 20 – ChanCon_Struct Structure..... | 56 |
| Table 21 – Device_Struct Structure..... | 56 |
| Table 22 – Key_Struct Structure | 57 |
| Table 23 – VcrEP_StructStructure | 58 |
| Table 24 – UAOCClassDesc_Struct Structure | 59 |
| Table 25 – ProDataDesc_Struct Structure..... | 60 |
| Table 26 – UAOWInstDesc_Struct Structure | 61 |
| Table 27 – DMAP-MIB-GET.request parameters | 62 |
| Table 28 – DMAP-MIB-GET.confirm parameters..... | 62 |
| Table 29 – DMAP-MIB-SET.request parameters | 63 |
| Table 30 – DMAP-MIB-SET.confirm parameters..... | 64 |
| Table 31 – PHY protocol selection | 64 |
| Table 32 – Coding of Modulation modes | 66 |
| Table 33 – Channel indices..... | 66 |
| Table 34 – Data rate | 67 |
| Table 35 – Parameters of timeslot template | 69 |
| Table 36 – DLDE-DATA.request primitive parameters..... | 78 |
| Table 37 – DLDE-DATA.indication primitive parameters..... | 79 |
| Table 38 – Management services..... | 81 |
| Table 39 – DLME-DISCOVERY.request parameters..... | 81 |
| Table 40 – DLME-DISCOVERY.confirm parameters..... | 82 |
| Table 41 – BeaconDescription_Struct parameters..... | 82 |
| Table 42 – DLME-TIME-SYN.indication parameters | 83 |
| Table 43 – DLME-TIME-SYN.response parameters..... | 84 |
| Table 44 – DLME-TIME-SYN.confirm parameters | 84 |
| Table 45 – DLME-JOIN.request parameters..... | 86 |
| Table 46 – DLME-JOIN.indication parameters..... | 86 |
| Table 47 – DLME-JOIN.response parameters | 87 |
| Table 48 – DLME-JOIN.confirm parameters | 87 |
| Table 49 – DLME-DEVICE-STATUS.request parameters | 89 |

| | |
|--|-----|
| Table 50 – DLME-DEVICE -STATUS.indication parameters | 89 |
| Table 51 – DLME-DEVICE -STATUS.confirm parameters | 89 |
| Table 52 – DLME-CHANNEL-CONDITION.request parameters | 90 |
| Table 53 – DLME-CHANNEL-CONDITION.indication parameters | 91 |
| Table 54 – DLME-CHANNEL-CONDITION.confirm parameters | 91 |
| Table 55 – DLME-INFO-GET.request parameters | 92 |
| Table 56 – DLME-INFO-GET.indication parameters | 93 |
| Table 57 – DLME-INFO-GET.response parameters | 94 |
| Table 58 – DLME-INFO-GET.confirm parameters | 95 |
| Table 59 – DLME-INFO-SET.request parameters | 97 |
| Table 60 – DLME-INFO-SET.indication parameters | 98 |
| Table 61 – DLME-INFO-SET.response parameters | 98 |
| Table 62 – DLME-INFO-SET.confirm parameters | 99 |
| Table 63 – DLME-LEAVE.request parameters | 100 |
| Table 64 – DLME-LEAVE.confirm parameters | 101 |
| Table 65 – Frame type coding | 103 |
| Table 66 – Addressing mode subfields | 103 |
| Table 67 – DLL state transition of access device | 110 |
| Table 68 – DLL state transition of field device | 118 |
| Table 69 – Functions used in DLL state machines | 124 |
| Table 70 – Frames between GW and AD | 125 |
| Table 71 – Payload of AD join request frame | 126 |
| Table 72 – Payload of AD join response frame | 126 |
| Table 73 – Payload of GW requesting AD to send GACK | 127 |
| Table 74 – Definition of GACKInfo_Struct | 127 |
| Table 75 – Payload of GW requesting AD to send NACK | 127 |
| Table 76 – Communication models between gateway device and field devices | 129 |
| Table 77 –EventData definition | 130 |
| Table 78 – UAO events definitions | 131 |
| Table 79 – VCR attribute configuration for a field device | 135 |
| Table 80 – Application services used by UAPs | 141 |
| Table 81 – Error code definition for Read negative response message | 142 |
| Table 82 – Error code definition for Write negative response message | 144 |
| Table 83 – Error code definition for Report ACK negative response | 147 |
| Table 84 – ASLDE-DATA.request primitive parameter definitions | 150 |
| Table 85 – ASLDE-DATA.indication primitive parameter definitions | 150 |
| Table 86 – ASLDE-DATA.response primitive parameter definitions | 151 |
| Table 87 – ASLDE-DATA.confirm primitive parameter definitions | 151 |
| Table 88 – ASLME-VcrActive.request primitive parameter definitions | 152 |
| Table 89 – ASLME-VcrDeactive.request primitive parameter definitions | 152 |
| Table 90 – ASLME-SignalEvent.request primitive parameter definitions | 153 |
| Table 91 – Service Identifier subfield definition | 154 |
| Table 92 – Message Type subfield definition | 154 |

| | |
|---|-----|
| Table 93 – Confirmed service primitives exchanged between ASL and other layers | 155 |
| Table 94 – Unconfirmed service primitives exchanged between ASL and other layers..... | 156 |
| Table 95 – ASL management service primitives between ASL and UAP | 157 |
| Table 96 – State transition table of AMCL | 158 |
| Table 97 – State transition table of AMSV | 160 |
| Table 98 – State transition table of AMPB | 162 |
| Table 99 – State transitions table of AMSB | 166 |
| Table 100 – State transitions table of AMRS | 169 |
| Table 101 – State transitions table of AMRK | 170 |
| Table 102 – All Functions used in ASLM | 171 |
| Table 103 – Parameters for KEY-ESTABLISH.request | 176 |
| Table 104 – KeyMaterial_Struct structure | 176 |
| Table 105 – Parameters for KEY-ESTABLISH.indication | 177 |
| Table 106 – Parameters for KEY-ESTABLISH.response | 177 |
| Table 107 – Parameters for KEY-ESTABLISH.confirm | 177 |
| Table 108 – Parameters for KEY-UPDATE.request | 178 |
| Table 109 – Parameters for KEY-UPDATE.indication | 179 |
| Table 110 – Parameters for KEY-UPDATE.response | 179 |
| Table 111 – Parameters for KEY-UPDATE.confirm | 179 |
| Table 112 – Parameters for SEC-ALARM.request | 180 |
| Table 113 – Parameters for SEC-ALARM.indication | 181 |
| Table 114 – Key update states..... | 184 |
| Table 115 – Key update state transition | 185 |
| Table 116 – Keys used in DLL secure communication..... | 186 |
| Table 117 – Available security levels for DLL..... | 188 |
| Table A.1 – Security grades for WIA-FA network..... | 192 |
| Table B.1 – Applicable EN 300 440-2 requirements list..... | 193 |
| Table B.2 – Applicable EN 300 328 requirements list | 194 |
| Table B.3 – Timeslot timing definitions and calculations..... | 195 |
| Table B.4 – TxMaxPHYPacket of FHSS | 195 |
| Table B.5 – TxMaxPHYPacket of DSSS/HR-DSSS..... | 195 |
| Table B.6 – TxMaxMPDU of OFDM | 196 |