

This document is a preview generated by EVS

Maritime navigation and radiocommunication equipment and systems - Class B shipborne equipment of the automatic identification system (AIS) - Part 2: Self-organising time division multiple access (SOTDMA) techniques

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 62287-2:2017 sisaldab Euroopa standardi EN 62287-2:2017 ingliskeelset teksti.	This Estonian standard EVS-EN 62287-2:2017 consists of the English text of the European standard EN 62287-2:2017.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 12.05.2017.	Date of Availability of the European standard is 12.05.2017.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 47.020.70

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

English Version

Maritime navigation and radiocommunication equipment and systems - Class B shipborne equipment of the automatic identification system (AIS) - Part 2: Self-organising time division multiple access (SOTDMA) techniques
(IEC 62287-2:2017)

Matériels et systèmes de navigation et de radiocommunications maritimes - Transpondeur embarqué du système d'identification automatique (AIS) de classe B - Partie 2: Technique d'accès multiple par répartition dans le temps auto-adaptatif (SOTDMA)
(IEC 62287-2:2017)

Navigations- und Funkkommunikationsgeräte und -systeme für die Seeschifffahrt - Geräte der Klasse B des automatischen Identifikationssystems (AIS) für Schiffe - Teil 2: Sich selbst abstimme Zeitmultiplex-Vielfachzugriffstechniken (SOTDMA)
(IEC 62287-2:2017)

This European Standard was approved by CENELEC on 2017-03-14. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

European foreword

The text of document 80/827/FDIS, future edition 2 of IEC 62287-2, prepared by IEC/TC 80 "Maritime navigation and radiocommunication equipment and systems" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62287-2:2017.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2017-12-14
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2020-03-14

This document supersedes EN 62287-2:2013.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 62287-2:2017 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 61162-3:2008	NOTE	Harmonized as EN 61162-3:2008.
IEC 61162-3:2008/AMD1:2010	NOTE	Harmonized as EN 61162-3:2008/A1:2010.
IEC 61162-3:2008/AMD2:2014	NOTE	Harmonized as EN 61162-3:2008/A2:2014.
IEC 61924-2:2012	NOTE	Harmonized as EN 61924-2:2012.
IEC 62287-1	NOTE	Harmonized as EN 62287-1.
ISO 9000 (Series)	NOTE	Harmonized as EN ISO 9000 (Series).

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60945	2002	Maritime navigation and radiocommunication equipment and systems - General requirements - Methods of testing and required test results	EN 60945	2002
IEC 61108	series	Maritime navigation and radiocommunication equipment and systems - Global navigation satellite systems (GNSS)	EN 61108	series
IEC 61108-4	-	Maritime navigation and radiocommunication equipment and systems - Global navigation satellite systems (GNSS) - Part 4: Shipborne DGPS and DGLONASS maritime radio beacon receiver equipment - Performance requirements, methods of testing and required test results	EN 61108-4	-
IEC 61162-1	-	Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 1: Single talker and multiple listeners	EN 61162-1	-
IEC 61993-2	-	Maritime navigation and radiocommunication equipment and systems - Automatic Identification Systems (AIS) - Part 2: Class A shipborne equipment of the automatic identification system (AIS) - Operational and performance requirements, methods of test and required test results	EN 61993-2	-
ITU Radio regulations, Vol 1	-	Radio Regulations - Volume 1: Articles	-	-
ITU-R Recommendation M.1084-5	-	Interim solutions for improved efficiency in the use of the band 156-174 MHz by stations in the maritime mobile service	-	-
ITU-R Recommendation M.1371-5	-	Technical characteristics for an automatic identification system using time-division multiple access in the VHF maritime mobile band	-	-
ITU-R Recommendation M.825-3	-	Characteristics of a transponder system using digital selective calling techniques for use with vessel traffic services and ship-to-ship identification	-	-

CONTENTS

FOREWORD.....	8
1 Scope.....	10
2 Normative references	10
3 Terms, definitions and abbreviated terms	11
3.1 Terms and definitions.....	11
3.2 Abbreviated terms.....	11
4 General requirements	12
4.1 General.....	12
4.1.1 Capabilities of the Class B "SO" AIS.....	12
4.1.2 Quality assurance.....	12
4.1.3 Safety of operation	13
4.1.4 Additional features.....	13
4.1.5 Functionality.....	13
4.2 Manuals	13
4.3 Marking and identification	13
5 Environmental, power supply, interference and safety requirements	13
6 Performance requirements.....	14
6.1 Internal processes	14
6.2 Operating frequency channels.....	15
6.3 Internal GNSS receiver for position reporting	15
6.4 Identification	15
6.5 AIS Information.....	15
6.5.1 Information content.....	15
6.5.2 Information reporting intervals	16
6.5.3 Short safety-related messages	17
6.5.4 Permissible initialisation period.....	17
6.6 Alarms and indications, fall-back arrangements	17
6.6.1 Built-in integrity tests (BIIT)	17
6.6.2 Transmitter shutdown procedure.....	18
6.6.3 Position sensor fallback conditions	19
6.7 User interface	19
6.7.1 Indication and display.....	19
6.7.2 Static data input	20
6.7.3 External interfaces.....	20
6.8 Protection from invalid control commands	20
7 Technical requirements	20
7.1 General.....	20
7.2 Physical layer	21
7.2.1 General	21
7.2.2 Receiver characteristics.....	21
7.2.3 Other characteristics.....	22
7.2.4 Transmitter requirements.....	23
7.3 Link layer	24
7.3.1 General	24
7.3.2 Link sub-layer 1: medium access control (MAC).....	24
7.3.3 Link sub-layer 2: data link service (DLS).....	26

7.3.4	Link sub-layer 3: link management entity (LME).....	26
7.4	Network layer.....	30
7.4.1	General	30
7.4.2	Management of regional operating settings.....	30
7.4.3	Multi-channel operation	31
7.5	Transport layer	31
7.6	Presentation interface	32
7.7	DSC receive capability	32
7.8	Long-range application by broadcast.....	32
8	Test conditions	32
8.1	General.....	32
8.2	Normal test conditions	32
8.2.1	Temperature and humidity	32
8.2.2	Power supply.....	33
8.3	Extreme test conditions.....	33
8.4	Test signals	33
8.4.1	Standard test signal number 1	33
8.4.2	Standard test signal number 2	33
8.4.3	Standard test signal number 3	33
8.4.4	Standard test signal number 4	33
8.5	Standard test environment	34
8.5.1	Test setup	34
8.5.2	Sensor test input	35
8.5.3	Synchronisation.....	35
8.5.4	Test signals applied to the receiver input.....	35
8.5.5	Waiver for receivers.....	35
8.5.6	Artificial antenna (dummy load)	35
8.5.7	Modes of operation of the transmitter.....	35
8.5.8	Common test conditions for protection from invalid controls.....	35
8.5.9	Measurement uncertainties.....	35
9	Power supply, environmental and EMC tests	36
9.1	Test summary	36
9.2	Vibration	37
9.2.1	Purpose.....	37
9.2.2	Method of measurement	37
9.2.3	Required results	38
9.3	Shock	38
9.3.1	Purpose.....	38
9.3.2	Method of measurement	38
9.3.3	Required result	38
9.4	Performance tests/checks	38
9.5	Under voltage test (brown out).....	38
9.5.1	Purpose.....	38
9.5.2	Method of test.....	38
9.5.3	Required result	39
9.6	Under voltage test (short term)	39
9.6.1	Purpose.....	39
9.6.2	Method of test.....	39
9.6.3	Required result.....	39

10	Operational tests	39
10.1	General.....	39
10.1.1	Tests by inspection.....	39
10.1.2	Safety of operation	39
10.1.3	Additional features.....	40
10.2	Modes of operation	40
10.2.1	Autonomous mode.....	40
10.2.2	Single messages	42
10.2.3	Polled mode and interrogation response	45
10.3	Channel selection	45
10.3.1	Valid channels.....	46
10.3.2	Invalid channels.....	46
10.4	Internal GNSS receiver	46
10.5	AIS information.....	46
10.5.1	Information content.....	46
10.5.2	Information update intervals	47
10.6	Initialisation period.....	49
10.6.1	Purpose.....	49
10.6.2	Method of measurement	49
10.6.3	Required results	49
10.7	Alarms and indications, fall-back arrangements	49
10.7.1	Built in integrity test.....	49
10.7.2	Transceiver protection	50
10.7.3	Transmitter shutdown procedure.....	50
10.7.4	Position sensor fallback conditions	50
10.8	User interface	51
10.8.1	Status indication.....	51
10.8.2	Message display.....	51
10.8.3	Static data input	52
11	Physical tests	53
11.1	TDMA transmitter.....	53
11.1.1	Frequency error.....	53
11.1.2	Carrier power.....	53
11.1.3	Transmission spectrum.....	54
11.1.4	Modulation accuracy.....	55
11.1.5	Transmitter output power versus time function	56
11.2	TDMA receivers	57
11.2.1	Sensitivity.....	57
11.2.2	Error behaviour at high input levels.....	58
11.2.3	Co-channel rejection.....	58
11.2.4	Adjacent channel selectivity.....	59
11.2.5	Spurious response rejection	60
11.2.6	Intermodulation response rejection	62
11.2.7	Blocking or desensitisation	63
11.3	Conducted spurious emissions.....	64
11.3.1	Spurious emissions from the receiver	64
11.3.2	Spurious emissions from the transmitter	64
12	Specific tests of link layer	65
12.1	TDMA synchronisation	65

12.1.1	Synchronisation test using UTC direct and indirect	65
12.1.2	Synchronisation test without UTC, EUT receiving semaphore	66
12.2	Time division (frame format)	66
12.2.1	Purpose	66
12.2.2	Method of measurement	66
12.2.3	Required results	66
12.3	Synchronisation jitter	66
12.3.1	Definition	66
12.3.2	Purpose	67
12.3.3	Method of measurement	67
12.3.4	Required results	67
12.4	Data encoding (bit stuffing)	67
12.4.1	Purpose	67
12.4.2	Method of measurement	67
12.4.3	Required results	67
12.5	Frame check sequence	67
12.5.1	Purpose	67
12.5.2	Method of measurement	67
12.5.3	Required results	67
12.6	Slot allocation (channel access protocols)	68
12.6.1	Network entry	68
12.6.2	Autonomous scheduled transmissions (SOTDMA)	68
12.6.3	Autonomous scheduled transmissions (ITDMA)	68
12.6.4	Transmission of Messages 24A and 24B (ITDMA)	68
12.6.5	Assigned operation	69
12.6.6	Group assignment	71
12.6.7	Base station reservations	75
12.7	Message formats	75
12.7.1	Received messages	75
12.7.2	Transmitted messages	75
13	Specific tests of network layer	76
13.1	Regional area designation by VDL Message	76
13.1.1	Purpose	76
13.1.2	Method of measurement	76
13.1.3	Required results	77
13.2	Channel management by addressed Message 22	78
13.2.1	Purpose	78
13.2.2	Method of measurement	78
13.2.3	Required results	78
13.3	Invalid regional operating areas	78
13.3.1	Purpose	78
13.3.2	Method of measurement	78
13.3.3	Required results	78
13.4	Continuation of autonomous mode reporting interval	78
13.4.1	Purpose	78
13.4.2	Method of test	79
13.4.3	Required result	79
13.5	Slot reuse and FATDMA reservations	79
13.5.1	Method of measurement	79

13.5.2	Required results	79
13.6	Long-range application by broadcast.....	79
13.6.1	Long-range broadcast.....	79
13.6.2	Multiple assignment operation	80
13.7	Other features.....	81
Annex A	(normative) DSC channel management.....	82
A.1	DSC functionality	82
A.2	DSC time sharing.....	82
A.3	DSC test signals	83
A.3.1	DSC test signal number 1	83
A.3.2	DSC test signal number 2	83
A.3.3	DSC test signal number 3	83
A.3.4	DSC test signal number 4	83
A.4	DSC functionality tests.....	83
A.4.1	General	83
A.4.2	Method of measurement	83
A.4.3	Required results	84
A.4.4	Regional area designation	84
A.4.5	Scheduling	84
A.4.6	DSC flag in Message 18	84
A.4.7	DSC monitoring time plan.....	85
A.4.8	Replacement or erasure of dated or remote regional operating settings.....	85
A.4.9	Test of addressed telecommand.....	86
A.4.10	Invalid regional operating areas.....	86
A.5	DSC receiver tests.....	86
A.5.1	General	86
A.5.2	Maximum sensitivity.....	87
A.5.3	Error behaviour at high input levels.....	87
A.5.4	Co-channel rejection.....	87
A.5.5	Adjacent channel selectivity.....	88
A.5.6	Spurious response rejection	88
A.5.7	Inter-modulation response rejection.....	88
A.5.8	Blocking or desensitisation	89
Annex B	(normative) Calculation of area size.....	90
B.1	Importance of a common method for area size.....	90
B.2	Calculation of area sizes.....	90
Annex C	(informative) Digital interface sentence to parameter group number equivalence	91
Bibliography	92
Figure 1	– OSI layer model	21
Figure 2	– Power versus time mask	25
Figure 3	– Format for repeating four-packet cluster.....	33
Figure 4	– Measurement arrangement for carrier power	53
Figure 5	– Emission mask.....	55
Figure 6	– Measurement arrangement for modulation accuracy	55
Figure 7	– Measurement arrangement	57
Figure 8	– Measurement arrangement with two generators	58

Figure 9 – SINAD or PER/BER measuring equipment	61
Figure 10 – Measurement arrangement for intermodulation.....	62
Figure 11 – Regional transitional zones	77
Table 1 – Dynamic information autonomous reporting intervals for Class B "SO" AIS.....	16
Table 2 – BIIT and reaction to malfunctions	18
Table 3 – Position sensor fallback conditions	19
Table 4 – Required receiver performance	22
Table 5 – Transceiver characteristics.....	22
Table 6 – Transmitter characteristics	24
Table 7 – Definitions of timing for Figure 2.....	26
Table 8 – Use of VDL Messages by a Class B "SO" AIS	29
Table 9 – Content of first two packets	34
Table 10 – Fixed PRS data derived from ITU-T O.153.....	34
Table 11 – Test.....	37
Table 12 – Peak frequency deviation versus time.....	56
Table 13 – Frequencies for intermodulation test.....	63
Table 14 – Regional area scenario.....	77
Table 15 – Required channels in use	77
Table A.1 – DSC monitoring times	83
Table B.1 – Coordinate points.....	90
Table C.1 – Digital sentence to PGN equivalence	91

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – CLASS B SHIPBORNE EQUIPMENT OF THE AUTOMATIC IDENTIFICATION SYSTEM (AIS) –

Part 2: Self-organising time division multiple access (SOTDMA) techniques

1 Scope

This part of IEC 62287 specifies operational and performance requirements, methods of testing and required test results for Class B "SO" shipborne automatic identifications system (AIS) equipment using self-organising time division multiple access (SOTDMA) techniques as described in Recommendation ITU-R M.1371. This document takes into account other associated IEC International Standards and existing national standards, as applicable.

The main differences between Class B "CS" (IEC 62287-1) and Class B "SO" units are that the Class B "SO"

- covers all 25 kHz channels listed in Recommendation ITU-R M.1084-5,
- only uses the internal GNSS – no position sensor input is allowed,
- requires use of VDL Message 17 for correction of the internal GNSS,
- requires a presentation interface,
- has additional reporting intervals, down to 5 s,
- has two power settings, with a high level of 5 W, and
- has the capability to transmit binary messages.

This document is applicable for AIS equipment used on craft that are not covered by a mandatory carriage requirement of AIS under SOLAS Chapter V.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945:2002, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61108 (all parts), *Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS)*

IEC 61108-4, *Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS) – Part 4: Shipborne DGPS and DGLONASS maritime radio beacon receiver equipment – Performance requirements, methods of testing and required test results*

IEC 61162-1, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners*