
**Plastics — Determination of flexural
properties**

Plastiques — Détermination des propriétés en flexion



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview generated by EVS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	2
3 Terms and definitions	2
4 Principle	5
5 Test machine	5
5.1 General	5
5.2 Test speed	5
5.3 Supports and loading edge	6
5.4 Force- and deflection measuring systems	6
5.5 Equipment for measuring the width and thickness of the test specimens	7
6 Test specimens	8
6.1 Shape and dimensions	8
6.2 Anisotropic materials	9
6.3 Preparation of test specimens	9
6.4 Specimen inspection	10
6.5 Number of test specimens	10
7 Atmosphere for conditioning and testing	10
8 Procedure	10
9 Calculation and expression of results	13
9.1 Flexural stress	13
9.2 Flexural strain	13
9.3 Flexural modulus	14
9.4 Statistical parameters	14
9.5 Significant figures	14
10 Precision	15
11 Test report	15
Annex A (informative) Precision statement	16
Annex B (informative) Influence of changes in test speed on the measured values of flexural properties	18
Bibliography	19

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 178 was prepared by Technical Committee ISO/TC 61, *Plastics*, Subcommittee SC 2, *Mechanical properties*.

This fifth edition cancels and replaces the fourth edition (ISO 178:2001), which has been technically revised to harmonize it with ISO 527-2^[2] with respect to the test speeds used for the determination of the flexural modulus and for the determination of other flexural properties. This has been done by specifying two methods, method A and method B. Method A is identical to the method specified in previous editions of ISO 178, i.e. it uses the same strain rate throughout the test, whereas method B uses two different strain rates (see 1.8 for details).

It also incorporates the Amendment ISO 178:2001/Amd.1:2004.

Plastics — Determination of flexural properties

1 Scope

1.1 This International Standard specifies a method for determining the flexural properties of rigid (see 3.12) and semi-rigid plastics under defined conditions. A standard test specimen is defined, but parameters are included for alternative specimen sizes for use where appropriate. A range of test speeds is included.

1.2 The method is used to investigate the flexural behaviour of the test specimens and to determine the flexural strength, flexural modulus and other aspects of the flexural stress/strain relationship under the conditions defined. It applies to a freely supported beam, loaded at midspan (three-point loading test).

1.3 The method is suitable for use with the following range of materials:

- thermoplastic moulding, extrusion and casting materials, including filled and reinforced compounds in addition to unfilled types; rigid thermoplastics sheets;
- thermosetting moulding materials, including filled and reinforced compounds; thermosetting sheets.

In agreement with ISO 10350-1^[5] and ISO 10350-2^[6], this International Standard applies to fibre-reinforced compounds with fibre lengths $\leq 7,5$ mm prior to processing. For long-fibre-reinforced materials (laminates) with fibre lengths $> 7,5$ mm, see ISO 14125^[7].

The method is not normally suitable for use with rigid cellular materials or sandwich structures containing cellular material. In such cases, ISO 1209-1^[3] and/or ISO 1209-2^[4] can be used.

NOTE For certain types of textile-fibre-reinforced plastic, a four-point bending test is preferred. This is described in ISO 14125.

1.4 The method is performed using specimens which may be either moulded to the specified dimensions, machined from the central section of a standard multipurpose test specimen (see ISO 20753) or machined from finished or semi-finished products, such as mouldings, laminates or extruded or cast sheet.

1.5 The method specifies the preferred dimensions for the test specimen. Tests which are carried out on specimens of different dimensions, or on specimens which are prepared under different conditions, can produce results which are not comparable. Other factors, such as the test speed and the conditioning of the specimens, can also influence the results.

NOTE Especially for semi-crystalline polymers, the thickness of the oriented skin layer, which is dependent on the moulding conditions, also affects the flexural properties.

1.6 The method is not suitable for the determination of design parameters but can be used in materials testing and as a quality control test.

1.7 For materials exhibiting non-linear stress/strain behaviour, the flexural properties are only nominal. The equations given have been derived assuming linear elastic behaviour and are valid for deflections of the specimen that are small compared to its thickness. With the preferred specimen (which measures 80 mm \times 10 mm \times 4 mm) at the conventional flexural strain of 3,5 % and a span-to-thickness ratio, L/h , of 16, the deflection is $1,5h$. Flexural tests are more appropriate for stiff and brittle materials showing small deflections at break than for very soft and ductile ones.

1.8 Contrary to the previous editions of this International Standard, this edition specifies two methods, method A and method B. Method A is identical to the method in previous editions of this International Standard, i.e. it uses a strain rate of 1 %/min throughout the test. Method B uses two different strain rates: 1 %/min for the determination of the flexural modulus and 5 %/min or 50 %/min, depending on the ductility of the material, for the determination of the remainder of the flexural stress-strain curve.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 291, *Plastics — Standard atmospheres for conditioning and testing*

ISO 293, *Plastics — Compression moulding of test specimens of thermoplastic materials*

ISO 294-1:1996, *Plastics — Injection moulding of test specimens of thermoplastic materials — Part 1: General principles, and moulding of multipurpose and bar test specimens*

ISO 295, *Plastics — Compression moulding of test specimens of thermosetting materials*

ISO 2602, *Statistical interpretation of test results — Estimation of the mean — Confidence interval*

ISO 2818, *Plastics — Preparation of test specimens by machining*

ISO 7500-1, *Metallic materials — Verification of static uniaxial testing machines — Part 1: Tension/compression testing machines — Verification and calibration of the force-measuring system*

ISO 9513, *Metallic materials — Calibration of extensometers used in uniaxial testing*

ISO 10724-1, *Plastics — Injection moulding of test specimens of thermosetting powder moulding compounds (PMCs) — Part 1: General principles, and moulding of multipurpose test specimens*

ISO 16012, *Plastics — Determination of linear dimensions of test specimens*

ISO 20753, *Plastics — Test specimens*

ISO 23529, *Rubber — General procedures for preparing and conditioning test pieces for physical test methods*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1 test speed

v
rate of relative movement between the specimen supports and the loading edge

NOTE It is expressed in millimetres per minute (mm/min).

3.2 flexural stress

σ_f
nominal stress at the outer surface of the test specimen at midspan

NOTE It is calculated from the relationship given in 9.1, Equation (5), and is expressed in megapascals (MPa).