
INTERNATIONAL STANDARD



936

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Meat and meat products — Determination of ash (Reference method)

Viandes et produits à base de viande — Détermination des cendres (Méthode de référence)

First edition — 1978-12-15

UDC 637.5 + 664.9 : 620.1

Ref. No. ISO 936-1978 (E)

Descriptors : meat, meat products, chemical analysis, determination of content, ash.

Price based on 2 pages

FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO member bodies). The work of developing International Standards is carried out through ISO technical committees. Every member body interested in a subject for which a technical committee has been set up has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 936 was developed by Technical Committee ISO/TC 34, *Agricultural food products*.

It was submitted directly to the ISO Council, in accordance with clause 6.13.1 of the Directives for the technical work of ISO. It cancels and replaces ISO Recommendation R 936-1969, which had been approved by the member bodies of the following countries :

Australia	India	Romania
Bulgaria	Iran	South Africa, Rep. of
Canada	Ireland	Thailand
Colombia	Israel	Turkey
Czechoslovakia	Korea, Rep. of	United Kingdom
Egypt, Arab Rep. of	Netherlands	U.S.S.R.
France	Norway	Yugoslavia
Greece	Poland	
Hungary	Portugal	

The member bodies of the following countries had expressed disapproval of the document on technical grounds :

Germany, F.R.
New Zealand

Meat and meat products – Determination of ash (Reference method)

1 SCOPE AND FIELD OF APPLICATION

This International Standard specifies a reference method for the determination of the ash of meat and meat products.

2 REFERENCE

ISO 3100, *Meat and meat products – Sampling*.

3 DEFINITION

ash of meat and meat products: The residue obtained after incineration at a temperature of 550 to 600 °C under the conditions specified below.

4 PRINCIPLE

Addition of magnesium acetate solution to a test portion, drying, and incineration at a temperature of 550 to 600 °C. After cooling, determination of the mass of the residue, corrected for the mass of the magnesium oxide (MgO) originating from the added magnesium acetate solution.

5 REAGENT

5.1 Magnesium acetate solution, approximately 150 g/l.

Dissolve 15 g of analytical grade anhydrous magnesium acetate $[\text{Mg}(\text{COOCH}_3)_2]$ or 25 g of analytical grade magnesium acetate tetrahydrate $[\text{Mg}(\text{COOCH}_3)_2 \cdot 4\text{H}_2\text{O}]$ in distilled water and dilute to 100 ml.

Determine the magnesium oxide content of the solution by subjecting 1 ml of the solution to the treatment described for the test portion (see 8.3).

6 APPARATUS

Usual laboratory apparatus not otherwise specified, and the following items:

6.1 Mechanical meat mincer, laboratory size, fitted with a plate with holes of diameter not exceeding 4 mm.

6.2 Dish, of platinum or of other material unaffected by the conditions of the test, with a flat bottom of area about 15 cm², and inclined walls of height at least 25 mm.

6.3 One-mark pipette, capacity 1 ml.

6.4 Electrically heated muffle furnace, capable of being controlled at 550 to 600 °C.

6.5 Water bath.

6.6 Desiccator, containing an effective desiccant.

6.7 Analytical balance.

7 SAMPLE

7.1 Proceed from a representative sample of at least 200 g. See ISO 3100.

7.2 Store the sample in such a way that deterioration and change in composition are prevented.

8 PROCEDURE

8.1 Preparation of the test sample

Homogenize the sample by passing it at least twice through the meat mincer (6.1) and mixing. Keep it in a completely filled, air-tight, closed container and store it in such a way that deterioration and change in composition are prevented. Analyse the sample as soon as possible after homogenization, but always within 24 h.

8.2 Test portion

Heat the dish (6.2) for 20 min in the muffle furnace (6.4), controlled at 550 to 600 °C. Allow to cool in the desiccator (6.6) and weigh to the nearest 0,000 1 g.

Transfer about 5 g of the test sample (8.1) to the dish. Spread it out evenly and weigh to the nearest 0,000 1 g.

8.3 Determination

Add 1 ml of the magnesium acetate solution (5.1) to the dish containing the test portion (8.2) by means of the pipette (6.3) in such a way that it is distributed over the test portion as uniformly as possible.

Place the dish on the gently boiling water bath (6.5) for 30 min, then place it on an electric hot-plate or over a gas flame and heat progressively until the substance carbonizes.