

Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN IEC 55016-1-4:2019 sisaldab Euroopa standardi EN IEC 55016-1-4:2019 ingliskeelset teksti.	This Estonian standard EVS-EN IEC 55016-1-4:2019 consists of the English text of the European standard EN IEC 55016-1-4:2019.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 15.03.2019.	Date of Availability of the European standard is 15.03.2019.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 33.100.10, 33.100.20

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

English Version

Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements
(CISPR 16-1-4:2019)

Spécifications des méthodes et des appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques - Partie 1-4: Appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques - Antennes et emplacements d'essai pour les mesures des perturbations rayonnées
(CISPR 16-1-4:2019)

Anforderungen an Geräte und Einrichtungen sowie Festlegung der Verfahren zur Messung der hochfrequenten Störaussendung (Funkstörungen) und Störfestigkeit - Teil 1-4: Geräte und Einrichtungen zur Messung der hochfrequenten Störaussendung (Funkstörungen) und Störfestigkeit - Antennen und Messplätze für Messungen der gestrahlten Störaussendung
(CISPR 16-1-4:2019)

This European Standard was approved by CENELEC on 2019-02-12. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

The text of document CIS/A/1262/FDIS, future edition 4 of CISPR 16-1-4, prepared by CISPR SC A "Radio-interference measurements and statistical methods" of CISPR "International special committee on radio interference" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 55016-1-4:2019.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2019-11-12
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2022-02-12

This document supersedes EN 55016-1-4:2010.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard CISPR 16-1-4:2019 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 61169-8	NOTE	Harmonized as EN 61169-8
IEC 61000-4-20	NOTE	Harmonized as EN 61000-4-20

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
CISPR 16-1-1	-	Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring apparatus	-	-
CISPR 16-1-5	2014	Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-5: Radio disturbance and immunity measuring apparatus - Antenna calibration sites and reference test sites for 5 MHz to 18 GHz	EN 55016-1-5	2015
+ A1	2016		+ A1	2017
CISPR 16-1-6	2014	Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-6: Radio disturbance and immunity measuring apparatus - EMC antenna calibration	EN 55016-1-6	2015
+ A1	2017		+ A1	2017
CISPR 16-2-3	2016	Specification for radio disturbance and immunity measuring apparatus and methods - Part 2-3: Methods of measurement of disturbances and immunity - Radiated disturbance measurements	EN 55016-2-3	2017
CISPR TR 16-3	-	Specification for radio disturbance and immunity measuring apparatus and methods -- Part 3: CISPR technical reports	-	-
CISPR 16-4-2	-	Specification for radio disturbance and immunity measuring apparatus and methods - Part 4-2: Uncertainties, statistics and limit modelling - Measurement instrumentation uncertainty	EN 55016-4-2	-
IEC 60050-191	-	International Electrotechnical Vocabulary - Chapter 191: Dependability and quality of service	-	-

CONTENTS

FOREWORD.....	8
1 Scope.....	10
2 Normative references.....	10
3 Terms, definitions and abbreviated terms.....	11
3.1 Terms and definitions.....	11
3.2 Abbreviated terms.....	15
4 Antennas for measurement of radiated radio disturbance.....	16
4.1 General.....	16
4.2 Physical parameter (measurand) for radiated disturbance measurements.....	16
4.3 Antennas for the frequency range 9 kHz to 150 kHz.....	17
4.3.1 General.....	17
4.3.2 Magnetic field antenna.....	17
4.3.3 Shielding of loop antenna.....	17
4.4 Antennas for the frequency range 150 kHz to 30 MHz.....	17
4.4.1 Electric field antenna.....	17
4.4.2 Magnetic field antenna.....	18
4.4.3 Balance and electric field discrimination of antennas.....	18
4.5 Antennas for the frequency range 30 MHz to 1 000 MHz.....	18
4.5.1 General.....	18
4.5.2 Low-uncertainty antenna for use if there is an alleged non-compliance to the electric disturbance field strength limit.....	18
4.5.3 Antenna characteristics.....	18
4.5.4 Balance of antenna.....	20
4.5.5 Cross-polar response of antenna.....	22
4.6 Antennas for the frequency range 1 GHz to 18 GHz.....	23
4.6.1 General.....	23
4.6.2 Receive antenna.....	23
4.7 Special antenna arrangements – large-loop antenna system.....	25
5 Test sites for measurement of radio disturbance field strength for the frequency range of 9 kHz to 30 MHz.....	25
6 Test sites for measurement of radio disturbance field strength for the frequency range of 30 MHz to 1 000 MHz.....	26
6.1 General.....	26
6.2 OATS.....	26
6.2.1 General.....	26
6.2.2 Weather-protection enclosure.....	26
6.2.3 Obstruction-free area.....	26
6.2.4 Radio-frequency ambient environment of a test site.....	27
6.2.5 Ground plane.....	28
6.3 Suitability of other test sites.....	28
6.3.1 Other ground-plane test sites.....	28
6.3.2 Test sites without ground plane (FAR).....	28
6.4 Test site validations.....	29
6.4.1 General.....	29
6.4.2 Overview of test site validations.....	30
6.5 Basic parameters of the NSA method for OATS and SAC.....	30
6.5.1 General equation and table of theoretical NSA values.....	30

6.5.2	Antenna calibration	34
6.6	Reference site method for OATS and SAC	34
6.6.1	General.....	34
6.6.2	Antennas not permitted for RSM measurements	35
6.6.3	Determination of the antenna pair reference site attenuation on a REFTS.....	35
6.6.4	Determination of the antenna pair reference site attenuation using an averaging technique on a large OATS	36
6.7	Validation of an OATS by the NSA method	39
6.7.1	Discrete frequency method.....	39
6.7.2	Swept frequency method.....	40
6.8	Validation of a weather-protection-enclosed OATS or a SAC.....	41
6.9	Possible causes for exceeding site acceptability limits	43
6.10	Site validation for FARs	44
6.10.1	General.....	44
6.10.2	RSM for FAR sites	48
6.10.3	NSA method for FAR sites.....	50
6.10.4	Site validation criteria for FAR sites	52
6.11	Evaluation of set-up table and antenna tower.....	52
6.11.1	General.....	52
6.11.2	Evaluation procedure for set-up table influences.....	53
7	Test sites for measurement of radio disturbance field strength for the frequency range 1 GHz to 18 GHz.....	54
7.1	General.....	54
7.2	Reference test site	55
7.3	Test site validation	55
7.3.1	General.....	55
7.3.2	Acceptance criterion for site validation.....	56
7.4	Antenna requirements for S_{VSWR} standard test procedure.....	56
7.4.1	General.....	56
7.4.2	Transmit antenna	57
7.4.3	Antennas and test equipment for the S_{VSWR} reciprocal test procedure	59
7.5	Required positions for site validation testing	60
7.5.1	General.....	60
7.5.2	Descriptions of S_{VSWR} measurement positions in a horizontal plane (Figure 23).....	60
7.5.3	Descriptions of S_{VSWR} additional measurement positions (Figure 24).....	61
7.5.4	Summary of S_{VSWR} measurement positions	62
7.6	S_{VSWR} site validation – standard test procedure.....	65
7.7	S_{VSWR} site validation – reciprocal test procedure using an isotropic field probe	66
7.8	S_{VSWR} conditional measurement position requirements.....	67
7.9	S_{VSWR} site validation test report	68
7.10	Limitations of the S_{VSWR} site validation method	68
7.11	Alternative test sites.....	69
8	Common mode absorption devices.....	69
8.1	General.....	69
8.2	CMAD S -parameter measurements.....	69
8.3	CMAD test jig.....	69
8.4	Measurement method using the TRL calibration.....	70

8.5	Specification of ferrite clamp-type CMAD.....	72
8.6	CMAD performance (degradation) check using spectrum analyzer and tracking generator.....	73
9	Reverberating chamber for total radiated power measurement.....	75
9.1	General.....	75
9.2	Chamber.....	75
9.2.1	Chamber size and shape.....	75
9.2.2	Door, openings in walls, and mounting brackets.....	75
9.2.3	Stirrers.....	76
9.2.4	Test for the efficiency of the stirrers.....	76
9.2.5	Coupling attenuation.....	77
10	TEM cells for immunity to radiated disturbance measurement.....	78
Annex A (normative)	Parameters of antennas.....	79
A.1	General.....	79
A.2	Preferred antennas.....	79
A.2.1	General.....	79
A.2.2	Calculable antenna.....	79
A.2.3	Low-uncertainty antennas.....	79
A.3	Simple dipole antennas.....	80
A.3.1	General.....	80
A.3.2	Tuned dipole.....	81
A.3.3	Shortened dipole.....	81
A.4	Broadband antenna parameters.....	82
A.4.1	General.....	82
A.4.2	Antenna type.....	83
A.4.3	Specification of the antenna.....	83
A.4.4	Antenna calibration.....	84
A.4.5	Antenna user information.....	84
Annex B (XXX)	(Void).....	85
Annex C (normative)	Large-loop antenna system for magnetic field induced-current measurements in the frequency range of 9 kHz to 30 MHz.....	86
C.1	General.....	86
C.2	Construction of an LLAS.....	86
C.3	Construction of a large-loop antenna (LLA).....	86
C.4	Validation of an LLA.....	91
C.5	Construction of the LLAS verification dipole antenna.....	92
C.6	Conversion factors.....	93
Annex D (normative)	Construction details for open area test sites in the frequency range of 30 MHz to 1 000 MHz (see Clause 6).....	96
D.1	General.....	96
D.2	Ground plane construction.....	96
D.2.1	Material.....	96
D.2.2	Roughness.....	96
D.3	Services to EUT.....	97
D.4	Weather-protection enclosure construction.....	97
D.4.1	Materials and fasteners.....	97
D.4.2	Internal arrangements.....	98
D.4.3	Size.....	98
D.4.4	Uniformity with time and weather.....	98

D.5	Turntable and set-up table.....	98
D.6	Receive antenna mast installation	99
Annex E (xxx)	(Void)	100
Annex F (informative)	Basis for ± 4 dB site acceptability criterion (see Clause 6)	101
F.1	General.....	101
F.2	Error analysis.....	101
Annex G (informative)	Examples of uncertainty budgets for site validation of a COMTS using RSM with a calibrated antenna pair (see 6.6).....	103
G.1	Quantities to be considered for antenna pair reference site attenuation calibration using the averaging technique	103
G.2	Quantities to be considered for antenna pair reference site attenuation calibration using a REFTS	104
G.3	Quantities to be considered for COMTS validation using an antenna pair reference site attenuation	105
Bibliography	106
Figure 1	– Schematic of radiation from EUT reaching an LPDA antenna directly and via ground reflections at a 3 m site, showing the beamwidth half-angle, φ , at the reflected ray.....	19
Figure 2	– RX antenna E-plane radiation pattern example, with limit area shaded for 3 m distance and 2 m EUT width.....	24
Figure 3	– Determination of maximum useable EUT width using half-power beamwidth.....	24
Figure 4	– Determination of maximum useable EUT height using half-power beamwidth	25
Figure 5	– Obstruction-free area of a test site with a turntable (see 6.2.3).....	27
Figure 6	– Obstruction-free area with stationary EUT (see 6.2.3)	27
Figure 7	– Test point locations for 3 m and 10 m test distances	36
Figure 8	– Paired test point locations for all test distances	38
Figure 9	– Example of paired test point selection for a test distance of 10 m	38
Figure 10	– Illustration of an investigation of influence of antenna mast on A_{APR}	39
Figure 11	– Typical antenna positions for a weather-protected OATS or a SAC – vertical polarization validation measurements	42
Figure 12	– Typical antenna positions for a weather-protected OATS or a SAC – horizontal polarization validation measurements	42
Figure 13	– Typical antenna positions for a weather-protected OATS or a SAC – vertical polarization validation measurements for a smaller EUT	43
Figure 14	– Typical antenna positions for a weather-protected OATS or a SAC – horizontal polarization validation measurements for a smaller EUT	43
Figure 15	– Measurement positions for FAR site validation	46
Figure 16	– Example of one measurement position and antenna tilt for FAR site validation	48
Figure 17	– Typical quasi free-space test site reference SA measurement set-up.....	50
Figure 18	– Theoretical free-space NSA as a function of frequency for different measurement distances [see Equation (16)]	52
Figure 19	– Position of the antenna relative to the edge above a rectangle set-up table (top view).....	54
Figure 20	– Antenna position above the set-up table (side view)	54
Figure 21	– Transmit antenna E-plane radiation pattern example (this example is for informative purposes only)	58
Figure 22	– Transmit antenna H-plane radiation pattern (this example is for informative purposes only)	59

Figure 23 – S_{VSWR} measurement positions in a horizontal plane (see 7.5.2 for description)	60
Figure 24 – S_{VSWR} positions (height requirements)	62
Figure 25 – S_{VSWR} conditional measurement position requirements	68
Figure 26 – Definition of the reference planes inside the test jig	70
Figure 27 – The four configurations for the TRL calibration	72
Figure 28 – Limits for the magnitude of S_{11} , measured according to the provisions of 8.1 to 8.3	73
Figure 29 – Example of a 50Ω adaptor construction in the vertical flange of the jig	74
Figure 30 – Example of a matching adaptor with balun or transformer	74
Figure 31 – Example of a matching adaptor with resistive matching network	75
Figure 32 – Example of a typical paddle stirrer	76
Figure 33 – Range of coupling attenuation as a function of frequency for a chamber using the stirrer shown in Figure 16	77
Figure A.1 – Short dipole antenna factors for $R_L = 50 \Omega$	82
Figure C.1 – The LLAS, consisting of three mutually perpendicular large-loop antennas	88
Figure C.2 – An LLA containing two opposite slits, positioned symmetrically with respect to the current probe C	89
Figure C.3 – Construction of an LLA slit	89
Figure C.4 – Example of an LLA slit construction using a strap of printed circuit board to obtain a rigid construction	90
Figure C.5 – Construction of the metal box containing the current probe	90
Figure C.6 – Example showing the routing of several cables from an EUT to minimize capacitive coupling from the leads to the LLAS	91
Figure C.7 – The eight positions of the LLAS verification dipole during validation of an LLA ...	92
Figure C.8 – Validation factor for an LLA of 2 m diameter	92
Figure C.9 – Construction of the LLAS verification dipole antenna	93
Figure C.10 – Conversion factors C_{dA} [for conversion into $\text{dB}(\mu\text{A}/\text{m})$] and C_{dV} [for conversion into $\text{dB}(\mu\text{V}/\text{m})$] for two standard measuring distances d	95
Figure C.11 – Sensitivity S_D of a large-loop antenna with diameter D relative to a large-loop antenna having a diameter of 2 m	95
Figure D.1 – The Rayleigh criterion for roughness in the ground plane	97
Table 1 – Site validation methods applicable for OATS, OATS-based, SAC, and FAR site types	29
Table 2 – Theoretical normalized site attenuation, A_N – recommended geometries for broadband antennas	32
Table 3 – Example template for A_{APR} data sets	35
Table 4 – RSM frequency steps	35
Table 5 – Maximum dimensions of test volume versus test distance	44
Table 6 – Frequency ranges and step sizes for FAR site validation	48
Table 7 – S_{VSWR} measurement position designations	63
Table 8 – S_{VSWR} reporting requirements	68
Table D.1 – Maximum roughness for 3 m, 10 m and 30 m measurement distances	97
Table F.1 – Error budget	101

Table G.1 – Antenna pair reference site attenuation calibration using the large-OATS averaging technique	103
Table G.2 – Antenna pair reference site attenuation calibration using REFTS	104
Table G.3 – COMTS validation using an antenna pair reference site attenuation	105

This document is a preview generated by EVS

INTERNATIONAL ELECTROTECHNICAL COMMISSION
INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

**SPECIFICATION FOR RADIO DISTURBANCE AND
IMMUNITY MEASURING APPARATUS AND METHODS –**

**Part 1-4: Radio disturbance and immunity measuring apparatus –
Antennas and test sites for radiated disturbance measurements**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights

This fourth edition cancels and replaces the third edition published in 2010, Amendment 1:2012 and Amendment 2:2017. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- provisions are added to address test site validation in the frequency range from 30 MHz to 1000 MHz using the reference site method, to take into account the receive antenna radiation pattern in the frequency range from 1 GHz to 18 GHz, and further details on test site validation using the NSA method with broadband antennas in the frequency range from 30 MHz to 1 000 MHz.

International Standard CISPR 16-1-4 has been prepared by CISPR subcommittee A: Radio-interference measurements and statistical methods.

It has the status of a basic EMC publication in accordance with IEC Guide 107, *Electromagnetic compatibility – Guide to the drafting of electromagnetic compatibility publications*.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
CIS/A/1262/FDIS	CIS/A/1275/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of CISPR 16 series, under the general title *Specification for radio disturbance and immunity measuring apparatus and methods*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

SPECIFICATION FOR RADIO DISTURBANCE AND IMMUNITY MEASURING APPARATUS AND METHODS –

Part 1-4: Radio disturbance and immunity measuring apparatus – Antennas and test sites for radiated disturbance measurements

1 Scope

This part of CISPR 16 specifies the characteristics and performance of equipment for the measurement of radiated disturbances in the frequency range 9 kHz to 18 GHz. Specifications for antennas and test sites are included.

NOTE In accordance with IEC Guide 107, CISPR 16-1-4 is a basic EMC publication for use by product committees of the IEC. As stated in Guide 107, product committees are responsible for determining the applicability of the EMC standard. CISPR and its sub-committees are prepared to cooperate with product committees in the evaluation of the value of particular EMC tests for specific products.

The requirements of this publication apply at all frequencies and for all levels of radiated disturbances within the CISPR indicating range of the measuring equipment.

Methods of measurement are covered in Part 2-3, further information on radio disturbance is given in Part 3, and uncertainties, statistics and limit modelling are covered in Part 4 of CISPR 16.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

CISPR 16-1-1, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus*

CISPR 16-1-5:2014, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-5: Radio disturbance and immunity measuring apparatus – Antenna calibration sites and reference test sites for 5 MHz to 18 GHz*
CISPR 16-1-5:2014/AMD1:2016

CISPR 16-1-6:2014, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-6: Radio disturbance and immunity measuring apparatus – EMC antenna calibration*
CISPR 16-1-6:2014/AMD1:2017

CISPR 16-2-3:2016, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 2-3: Methods of measurement of disturbances and immunity – Radiated disturbance measurements*

CISPR TR 16-3, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 3: CISPR technical reports*