

**Kohtkindlad süttiva pulber-pinnakattematerjali  
elektrostaatilised pihustusseadmed. Ohutusnõuded**

Stationary electrostatic application equipment for ignitable  
coating powder - Safety requirements

This document is a preview generated by EVS

## EESTI STANDARDI EESSÕNA

## NATIONAL FOREWORD

Käesolev Eesti standard EVS-EN 50177:2009 sisaldab Euroopa standardi EN 50177:2009 ingliskeelset teksti.

Standard on kinnitatud Eesti Standardikeskuse 31.12.2009 käskkirjaga ja jõustub sellekohase teate avaldamisel EVS Teatajas.

Euroopa standardimisorganisatsioonide poolt rahvuslikele liikmetele Euroopa standardi teksti kättesaadavaks tegemise kuupäev on 16.10.2009.

Standard on kättesaadav Eesti standardiorganisatsioonist.

This Estonian standard EVS-EN 50177:2009 consists of the English text of the European standard EN 50177:2009.

This standard is ratified with the order of Estonian Centre for Standardisation dated 31.12.2009 and is endorsed with the notification published in the official bulletin of the Estonian national standardisation organisation.

Date of Availability of the European standard text 16.10.2009.

The standard is available from Estonian standardisation organisation.

ICS 87.100

### Standardite reprodutseerimis- ja levitamiseõigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonilisse süsteemi või edastamine ükskõik millises vormis või millisel teel on keelatud ilma Eesti Standardikeskuse poolt antud kirjaliku loata.

Kui Teil on küsimusi standardite autorikaitse kohta, palun võtke ühendust Eesti Standardikeskusega:  
Aru 10 Tallinn 10317 Eesti; [www.evs.ee](http://www.evs.ee); Telefon: 605 5050; E-post: [info@evs.ee](mailto:info@evs.ee)

### Right to reproduce and distribute Estonian Standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without permission in writing from Estonian Centre for Standardisation.

If you have any questions about standards copyright, please contact Estonian Centre for Standardisation:  
Aru str 10 Tallinn 10317 Estonia; [www.evs.ee](http://www.evs.ee); Phone: +372 605 5050; E-mail: [info@evs.ee](mailto:info@evs.ee)

English version

**Stationary electrostatic application equipment  
for ignitable coating powders -  
Safety requirements**

Matériels stationnaires de projection  
électrostatique de poudres  
de revêtement inflammables -  
Exigences de sécurité

Stationäre Ausrüstung  
zum elektrostatischen Beschichten  
mit entzündbaren Beschichtungspulvern -  
Sicherheitsanforderungen

This European Standard was approved by CENELEC on 2009-09-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

**CENELEC**

European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**Central Secretariat: Avenue Marnix 17, B - 1000 Brussels**

## Foreword

This European Standard was prepared by SC 31-8, Electrostatic painting and finishing equipment, of Technical Committee CENELEC TC 31, Electrical apparatus for potentially explosive atmospheres.

The text of the draft was submitted to the formal vote and was approved by CENELEC as EN 50177 on 2009-09-01.

This European Standard supersedes EN 50177:2006 + corrigendum October 2007.

The following dates were fixed:

- latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2010-09-01
- latest date by which the national standards conflicting with the EN have to be withdrawn (dow) 2012-09-01

This European Standard has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association and covers essential requirements of EC Directive 94/9/EC. See Annex ZZ.

CENELEC/TC 31 as the responsible committee has concluded that this new edition of EN 50177 does not contain substantial changes regarding the ESRs.

The State of the Art is included in Annex ZY “*Significant changes between this European Standard and EN 50177:2006*”.

---

Preview generated by EVS

## Contents

0	Introduction.....	4
0.1	Process .....	4
0.2	Explosion hazards .....	4
0.3	Electric hazards.....	4
1	Scope .....	6
2	Normative references .....	6
3	Definitions.....	7
4	General requirements.....	10
5	Requirements for the equipment.....	11
5.1	Electrostatic spraying systems.....	11
5.2	Requirements for spraying systems of category 3D .....	11
5.3	Special requirements for spraying systems of category 2D .....	13
5.4	Spraying area .....	13
5.5	High voltage supply .....	13
5.6	Electric requirements .....	14
5.7	Grounding measures.....	14
6	Testing.....	14
6.1	Tests of the high voltage cables.....	14
6.2	Tests of the stationary equipment.....	15
6.3	Specific test requirements for spraying systems of type B-P, type C-P category 2D.....	16
7	Information for use .....	17
7.1	General.....	17
7.2	Instruction manual.....	18
7.3	Marking .....	19
7.4	Warning sign .....	21
	Bibliography .....	22
	Annex ZY (informative) Significant changes between this European Standard and EN 50177:2006 .....	23
	Annex ZZ (informative) Coverage of Essential Requirements of EC Directives .....	24
<b>Figures</b>		
	Figure 1 – Test assembly according to 6.3.2.....	17
<b>Tables</b>		
	Table 1 – Electrostatic spraying systems for ignitable coating powders – Fields of application.....	11
	Table 2 – Requirements for electrostatic spraying systems of category 3D for ignitable coating powders.....	11
	Table 3 – Survey of tests .....	15
	Table 4 – Test intervals .....	19

## 0 Introduction

### 0.1 Process

During the electrostatic coating process the coating powder is transported in an air stream from a powder hopper up to an electrostatic spraying device. As the powder particles flow through the spraying device they are electrostatically charged by means of a high voltage of the order of some tens of kilovolts and ejected in the form of a cloud which is directed towards the workpiece. The charged particles of the cloud are attracted by and applied to the earthed workpiece.

Powder, that is not applied to the workpiece (overspray) is removed by a suction device or other means in the powder collection unit.

After the coating process the workpieces are introduced into an oven where the powder is melted and cured into a coherent coating.

### 0.2 Explosion hazards

An explosion could occur, if

- the concentration of coating powder in air is within the explosion limits,
- an ignition source of appropriate energy for this coating powder cloud is present.

Ignition sources could be, for instance, a hot surface, an open flame, an electric arc or a spark.

An explosion could be prevented, if one – or better both – conditions are avoided. Because it is very difficult to exclude the possibility of ignitable discharges completely, the main focus should be the prevention of ignitable concentrations of coating powder in air.

**0.2.1** Mixtures of ignitable coating powder and air could only explode within a given range of concentration, but not, if the concentration is above or below this range.

NOTE 1 If an explosive cloud of coating powder and air is trapped into a closed room, an explosion could lead to a fatal increase of pressure.

NOTE 2 The particle size distribution of coating powders is usually in the range of 5 µm to 120 µm.

**0.2.2** It is important that deposits of powder are not allowed to accumulate within the spraying areas for they may be whirled up and give rise to an explosive atmosphere. This does not apply to deposits on filter devices and accumulations of coating powder in hoppers where filters and hoppers are integrated in the spraying area and are designed to collect the coating powder. [See EN 12981:2005, 4.6].

**0.2.3** Particular attention should be paid to the prevention of electrostatic charges on different surfaces, which are in the vicinity of the powder cloud. This could apply to workpieces during the coating process or the reciprocating devices and the mounting parts of the powder spraying system etc.

### 0.3 Electric hazards

**0.3.1** Electric shock (by direct or indirect contact) could be generated, for instance, by contact with

- live parts, which are not insulated for operational reasons,
- conductive parts, which are not under dangerous voltage during normal operation, but in case of failure,
- insulated live parts whose insulation is insufficient or has been damaged due to mechanical influences.

**0.3.2** Inadequate grounding could occur, for instance, due to

- faulty connections to the protective grounding system,
- a too high resistance to ground.

**0.3.3** Hazards could occur, for instance, if hazardous malfunctions (e.g. shortcut of the electronic safety circuits, of access guards to dangerous areas or of warning devices) occur due to interferences of the high voltage equipment and the components of control and safety systems.

**0.3.4** Hazardous electrostatic discharges could be generated, for instance, by non-earthed conductive components or by large insulating surfaces, especially if they are backed with conductive material.

This document is a preview generated by EVS

## 1 Scope

**1.1** This European Standard specifies the requirements for stationary electrostatic application equipment for ignitable coating powders to be used in explosive atmospheres generated by their own spray cloud. A distinction is made between spraying systems corresponding to EN 50050:2001 and spraying systems designed for higher discharge energies and/or currents. The charging of ignitable coating powder can be achieved by applying high voltage or triboelectrically.

This European Standard also specifies the design-related requirements for a safe operation of the stationary equipment including its electrical installation.

**1.2** This European Standard considers three types of electrostatic spraying systems; see 5.1 for more details.

**1.3** This European Standard deals with all hazards significant for the electrostatic spraying of coating materials, which could also contain small quantities of added metal particles, if the work is carried out under conditions recommended by the manufacturer. In particular, this includes ignition hazards resulting from the generated explosive atmosphere, and the protection of persons from electric shocks.

**1.4** This stationary equipment is classified as equipment of group II, category 2D or category 3D for use in potentially explosive areas of zone 21 or 22, respectively.

NOTE For other safety aspects like

- zone classification of the areas in and around spray booths, see EN 12981:2005, 5.6.2.3;
- zone classification of other areas with explosive atmosphere, see EN 60079-10-2;
- selection, erection and application of other electrical and non electrical equipment in areas with explosion hazard, see EN 60079-14 and EN 12981:2005, 5.6.2.4;
- health protection (for instance, noise) see also EN 12981:2005, 5.4 and EN 14462;
- cleaning of spraying areas, see instruction manual of the spraying equipment;
- fire prevention and protection (for instance fire hazards due to other sources) see also EN 12981:2005, 5.6;
- explosion protection system, see EN 12981:2005, 5.6.2.5;
- dust hazards, see EN 12981:2005, 5.5.

Design-related measures for reducing the generation of noise of the stationary equipment for electrostatic coating are given in EN ISO 11688-1. See also EN 14462.

## 2 Normative references

The following referenced documents are incorporated for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1081, *Resilient floor coverings – Determination of the electrical resistance*

EN 1127-1, *Explosive atmospheres – Explosion prevention and protection – Part 1: Basic concepts and methodology*

EN 1149-5, *Protective clothing – Electrostatic properties – Part 5: Material performance and design requirements*

EN 12981:2005, *Coating plants - Spray booths for application of organic powder coating material - Safety requirements*

EN 13463-1, *Non-electrical equipment for use in potentially explosive atmospheres – Part 1: Basic method and requirements*

EN 13478:2001, *Safety of machinery – Fire prevention and protection*

EN 50050:2001, *Electrical apparatus for potentially explosive atmospheres – Electrostatic hand-held spraying equipment*

EN 60079-0, *Electrical apparatus for explosive gas atmospheres – Part 0: General requirements* (IEC 60079-0)

EN 60204-1, *Safety of machinery – Electrical equipment of machines – Part 1: General requirements* (IEC 60204-1)

EN 60529:1991, *Degrees of protection provided by enclosures (IP code)* (IEC 60529:1989)

EN 61340-4-1, *Electrostatics – Part 4-1: Standard test methods for specific applications – Electrical resistance of floor coverings and installed floors* (IEC 61340-4-1)

EN 62061, *Safety of machinery – Functional safety of safety-related electrical, electronic and programmable electronic control systems* (IEC 62061)

EN ISO 13849-1, *Safety of machinery – Safety-related parts of control systems – General principles for design* (ISO 13849-1)

EN ISO 20344, *Personal protective equipment – Test method for footwear* (ISO 20344)

### 3 Definitions

For the purposes of this document, the following terms and definitions apply.

#### 3.1

##### **stationary electrostatic application equipment for ignitable coating powders**

equipment in which the electrostatic spraying equipment is either fixed stationary (e.g. on supports) and is operated automatically or is guided by reciprocators (e.g. robots).

In general, the equipment comprises the following:

- powder spray booth;
- spraying area;
- spraying system;
- dosing device;
- fixtures for workpieces;
- conveyors;
- grounding system;
- forced ventilation;
- fire prevention and protection equipment

#### 3.2

##### **spraying system**

devices for application of coating powder by means of electrostatic charge.

In general, the spraying system consists of the following components:

- device for the supply of coating material;
- high voltage electrode;
- high voltage supply system;
- spraying device

#### 3.3

##### **high voltage supply system**

system consisting in general of the following components:

- low voltage section with devices for switching on and off the unit and for adjustment, control, regulation, limitation and monitoring of current and voltage, as well as the required connecting cables;
- high voltage generator;
- high voltage switching device;
- high voltage cable;
- high voltage plug-and-socket connector