

**High-pressure decorative laminates (HPL) - Sheets based on thermosetting resins (usually called laminates) - Part 2: Determination of properties**

**EESTI STANDARDI EESSÕNA****NATIONAL FOREWORD**

See Eesti standard EVS-EN 438-2:2016+A1:2018 sisaldab Euroopa standardi EVS-EN 438-2:2016+A1:2018 ingliskeelset teksti.	This Estonian standard EVS-EN 438-2:2016+A1:2018 consists of the English text of the European standard EVS-EN 438-2:2016+A1:2018.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 19.12.2018.	Date of Availability of the European standard is 19.12.2018.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile [standardiosakond@evs.ee](mailto:standardiosakond@evs.ee).

ICS 83.140.20

**Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele**

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:  
Koduleht [www.evs.ee](http://www.evs.ee); telefon 605 5050; e-post [info@evs.ee](mailto:info@evs.ee)

**The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation**

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage [www.evs.ee](http://www.evs.ee); phone +372 605 5050; e-mail [info@evs.ee](mailto:info@evs.ee)

ICS 83.140.20

English Version

## High-pressure decorative laminates (HPL) - Sheets based on thermosetting resins (usually called laminates) - Part 2: Determination of properties

Stratifiés décoratifs haute pression (HPL) - Plaques à base de résines thermodurcissables (communément appelées stratifiés) - Partie 2: Détermination des propriétés

Dekorative Hochdruck-Schichtpressstoffplatten (HPL) - Platten auf Basis härtpbarer Harze (Schichtpressstoffe) - Teil 2: Bestimmung der Eigenschaften

This amendment A1 modifies the European Standard EN 438-2:2016; it was approved by CEN on 5 October 2018.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for inclusion of this amendment into the relevant national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This amendment exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

<b>Contents</b>		<b>Page</b>
<b>European foreword</b> .....		<b>10</b>
<b>1</b>	<b>Scope</b> .....	<b>11</b>
<b>2</b>	<b>Normative references</b> .....	<b>11</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>12</b>
<b>4</b>	<b>Assessment of appearance</b> .....	<b>12</b>
<b>4.1</b>	<b>Principle</b> .....	<b>12</b>
<b>4.2</b>	<b>Apparatus</b> .....	<b>12</b>
<b>4.3</b>	<b>Test specimen</b> .....	<b>12</b>
<b>4.4</b>	<b>Procedure</b> .....	<b>12</b>
<b>4.5</b>	<b>Test report</b> .....	<b>13</b>
<b>5</b>	<b>Determination of thickness</b> .....	<b>13</b>
<b>5.1</b>	<b>Principle</b> .....	<b>13</b>
<b>5.2</b>	<b>Apparatus</b> .....	<b>13</b>
<b>5.3</b>	<b>Test specimen</b> .....	<b>13</b>
<b>5.4</b>	<b>Procedure</b> .....	<b>13</b>
<b>5.5</b>	<b>Test report</b> .....	<b>14</b>
<b>6</b>	<b>Determination of length and width</b> .....	<b>14</b>
<b>6.1</b>	<b>Principle</b> .....	<b>14</b>
<b>6.2</b>	<b>Apparatus</b> .....	<b>14</b>
<b>6.3</b>	<b>Test specimen</b> .....	<b>14</b>
<b>6.4</b>	<b>Procedure</b> .....	<b>14</b>
<b>6.5</b>	<b>Expression of results</b> .....	<b>14</b>
<b>6.6</b>	<b>Test report</b> .....	<b>14</b>
<b>7</b>	<b>Determination of edge straightness</b> .....	<b>15</b>
<b>7.1</b>	<b>Principle</b> .....	<b>15</b>
<b>7.2</b>	<b>Apparatus</b> .....	<b>15</b>
<b>7.3</b>	<b>Test specimen</b> .....	<b>15</b>
<b>7.4</b>	<b>Procedure</b> .....	<b>15</b>
<b>7.5</b>	<b>Expression of results</b> .....	<b>15</b>
<b>7.6</b>	<b>Test report</b> .....	<b>16</b>
<b>8</b>	<b>Determination of edge squareness</b> .....	<b>16</b>
<b>8.1</b>	<b>Principle</b> .....	<b>16</b>
<b>8.2</b>	<b>Apparatus</b> .....	<b>16</b>

8.3	Test specimen.....	16
8.4	Procedure .....	16
8.5	Expression of results.....	17
8.6	Test report.....	17
9	Determination of flatness .....	17
9.1	Principle .....	17
9.2	Apparatus.....	17
9.3	Test specimens.....	18
9.4	Procedure .....	18
9.5	Expression of results.....	18
9.6	Test report.....	18
10	Resistance to surface wear .....	18
10.1	Principle .....	18
10.2	Materials.....	18
10.3	Apparatus.....	19
10.3.1	Abrasion resistance testing machine.....	19
10.4	Test specimens.....	21
10.5	Preparation of specimens and abrasive paper.....	21
10.6	Procedure .....	21
10.6.1	Preparation of abrasive wheels.....	21
10.6.2	Calibration of abrasive paper .....	21
10.6.3	Abrasion of specimen .....	21
10.7	Expression of results.....	22
10.8	Test report.....	22
11	Resistance to abrasion (flooring grade laminates) .....	23
12	Resistance to immersion in boiling water .....	23
12.1	Principle .....	23
12.2	Apparatus.....	23
12.3	Test specimens.....	23
12.4	Procedure .....	24
12.5	Expression of results.....	24
12.5.1	Calculation.....	24
12.5.2	Surface rating scale .....	25
12.5.3	Edge rating scale.....	25
12.6	Test report.....	25
13	Substrate protection against water vapour.....	25

<b>13.1</b>	<b>Principle</b> .....	<b>25</b>
<b>13.2</b>	<b>Apparatus</b> .....	<b>26</b>
<b>13.3</b>	<b>Test specimens</b> .....	<b>26</b>
<b>13.4</b>	<b>Procedure</b> .....	<b>26</b>
<b>13.5</b>	<b>Expression of results</b> .....	<b>27</b>
<b>13.6</b>	<b>Test report</b> .....	<b>27</b>
<b>14</b>	<b>Resistance to water vapour</b> .....	<b>27</b>
<b>14.1</b>	<b>Principle</b> .....	<b>27</b>
<b>14.2</b>	<b>Apparatus</b> .....	<b>28</b>
<b>14.3</b>	<b>Test specimen</b> .....	<b>28</b>
<b>14.4</b>	<b>Procedure</b> .....	<b>28</b>
<b>14.5</b>	<b>Expression of results</b> .....	<b>28</b>
<b>14.6</b>	<b>Test report</b> .....	<b>28</b>
<b>15</b>	<b>Resistance to wet conditions (Exterior grade laminates)</b> .....	<b>30</b>
<b>15.1</b>	<b>Principle</b> .....	<b>30</b>
<b>15.2</b>	<b>Apparatus</b> .....	<b>30</b>
<b>15.3</b>	<b>Test specimens</b> .....	<b>30</b>
<b>15.4</b>	<b>Procedure</b> .....	<b>30</b>
<b>15.5</b>	<b>Expression of results</b> .....	<b>30</b>
<b>15.5.1</b>	<b>Calculation</b> .....	<b>30</b>
<b>15.5.2</b>	<b>Visual examination</b> .....	<b>31</b>
<b>15.6</b>	<b>Test report</b> .....	<b>31</b>
<b>16</b>	<b>Resistance to dry heat</b> .....	<b>32</b>
<b>16.1</b>	<b>Principle</b> .....	<b>32</b>
<b>16.2</b>	<b>Apparatus and materials</b> .....	<b>32</b>
<b>16.3</b>	<b>Test specimen</b> .....	<b>34</b>
<b>16.4</b>	<b>Test procedure</b> .....	<b>34</b>
<b>16.5</b>	<b>Examination of the test specimen</b> .....	<b>34</b>
<b>16.6</b>	<b>Expression of results</b> .....	<b>34</b>
<b>16.7</b>	<b>Test report</b> .....	<b>35</b>
<b>17</b>	<b>Dimensional stability at elevated temperature</b> .....	<b>35</b>
<b>17.1</b>	<b>Principle</b> .....	<b>35</b>
<b>17.2</b>	<b>Apparatus</b> .....	<b>35</b>
<b>17.3</b>	<b>Test specimens</b> .....	<b>36</b>
<b>17.4</b>	<b>Procedure</b> .....	<b>36</b>
<b>17.5</b>	<b>Expression of results</b> .....	<b>36</b>

17.6	Test report.....	37
18	Resistance to wet heat.....	37
18.1	Principle .....	37
18.2	Apparatus and materials.....	38
18.3	Test specimens.....	38
18.4	Procedure .....	39
18.5	Expression of results.....	39
18.6	Test report.....	40
19	Resistance to climatic shock (exterior grade laminates) .....	40
19.1	Principle .....	40
19.2	Apparatus.....	40
19.3	Test specimens.....	41
19.4	Procedure .....	41
19.5	Expression of results.....	42
19.5.1	Flexural strength and modulus of elasticity in flexure .....	42
19.5.2	Appearance .....	42
19.6	Test report.....	42
20	Resistance to impact by small-diameter ball.....	42
20.1	Principle .....	42
20.2	Materials.....	43
20.3	Apparatus.....	43
20.4	Test specimens.....	46
20.5	Calibration of the impact tester .....	46
20.6	Procedure .....	47
20.7	Expression of results.....	48
20.8	Test report.....	48
21	Resistance to impact by large diameter ball .....	48
21.1	Principle .....	48
21.2	Materials.....	49
21.3	Apparatus.....	49
21.4	Test specimens.....	49
21.5	Procedure .....	49
21.6	Expression of results.....	51
21.7	Test report.....	52
22	Resistance to impact by large diameter ball (flooring grade laminates) .....	52
22.1	Principle .....	52

22.2	Materials .....	52
22.3	Apparatus .....	52
22.4	Test specimens.....	53
22.5	Procedure .....	53
22.6	Expression of results .....	53
22.7	Test report.....	53
23	Resistance to cracking under stress (laminates $\leq 2$ mm thick) .....	54
23.1	Principle.....	54
23.2	Apparatus .....	54
23.3	Test specimens.....	54
23.4	Procedure .....	56
23.5	Expression of results .....	56
23.6	Test report.....	57
24	Resistance to crazing (Compact laminates) .....	58
24.1	Principle.....	58
24.2	Apparatus .....	58
24.3	Test specimens.....	58
24.4	Procedure .....	58
24.5	Expression of results .....	58
24.6	Test report.....	59
25	Resistance to scratching.....	60
25.1	Principle.....	60
25.2	Materials .....	60
25.3	Apparatus .....	60
25.4	Calibration of apparatus.....	62
25.5	Test specimen.....	62
25.6	Procedure .....	62
25.7	Expression of results .....	66
25.8	Test report.....	66
26	Resistance to staining.....	66
26.1	Principle.....	66
26.2	Staining agents.....	66
26.3	Apparatus and Materials.....	68
26.3.1	Discs.....	68
26.3.2	Glass Petri dish .....	68
26.3.3	Tweezers.....	68

26.3.4	Absorbent paper or tissue .....	68
26.3.5	Cleaning cloth .....	68
26.3.6	Diffuse light source .....	68
26.4	Test specimens .....	69
26.5	Test procedure .....	69
26.6	Examination of the test panel .....	70
26.7	Assessment of results .....	70
26.8	Test report .....	71
27	Light fastness (Xenon arc) .....	71
27.1	Principle .....	71
27.2	Apparatus .....	71
27.3	Test specimen .....	72
27.4	Procedure .....	72
27.5	Assessment and expression of results .....	73
27.6	Test report .....	73
28	Resistance to UV light (Exterior grade laminates) .....	73
28.1	Principle .....	73
28.2	Apparatus .....	73
28.3	Test specimens .....	73
28.4	Procedure .....	74
28.5	Evaluation and expression of results .....	74
28.5.1	General .....	74
28.5.2	Contrast .....	74
28.5.3	Appearance .....	74
28.6	Test report .....	74
29	Resistance to artificial weathering (Exterior grade laminates) .....	75
29.1	Principle .....	75
29.2	Apparatus .....	75
29.3	Test specimens .....	76
29.4	Procedure .....	76
29.5	Examination and expression of results .....	76
29.5.1	General .....	76
29.5.2	Contrast .....	77
29.5.3	Appearance .....	77
29.6	Test report .....	77
30	Determination of the microscratch resistance .....	77

<b>30.1</b>	<b>Principle</b> .....	<b>77</b>
<b>30.2</b>	<b>Terms and definitions</b> .....	<b>77</b>
<b>30.3</b>	<b>Apparatus and materials</b> .....	<b>78</b>
<b>30.3.1</b>	<b>Martindale tester</b> .....	<b>78</b>
<b>30.3.2</b>	<b>Holder for scrub material</b> .....	<b>78</b>
<b>30.3.3</b>	<b>Diffuse light source</b> .....	<b>78</b>
<b>30.3.4</b>	<b>Reflectometer</b> .....	<b>78</b>
<b>30.3.5</b>	<b>Positioning device</b> .....	<b>79</b>
<b>30.4</b>	<b>Assembly and maintenance of the Martindale tester</b> .....	<b>80</b>
<b>30.5</b>	<b>Method for checking the Lissajous figure</b> .....	<b>80</b>
<b>30.6</b>	<b>Preparation and conditioning</b> .....	<b>81</b>
<b>30.6.1</b>	<b>Preparation</b> .....	<b>81</b>
<b>30.6.2</b>	<b>Test surface</b> .....	<b>81</b>
<b>30.7</b>	<b>Test procedure</b> .....	<b>81</b>
<b>30.7.1</b>	<b>General</b> .....	<b>81</b>
<b>30.7.2</b>	<b>Testing</b> .....	<b>81</b>
<b>30.8</b>	<b>Classification of the image after scratching according to procedure B</b> .....	<b>83</b>
<b>30.9</b>	<b>Test report</b> .....	<b>84</b>
<b>31</b>	<b>Formability (Method A)</b> .....	<b>84</b>
<b>31.1</b>	<b>Principle</b> .....	<b>84</b>
<b>31.2</b>	<b>Apparatus</b> .....	<b>84</b>
<b>31.3</b>	<b>Test specimens</b> .....	<b>85</b>
<b>31.4</b>	<b>Procedure</b> .....	<b>85</b>
<b>31.4.1</b>	<b>Calibration of test apparatus</b> .....	<b>85</b>
<b>31.4.2</b>	<b>Test procedure</b> .....	<b>86</b>
<b>31.5</b>	<b>Test report</b> .....	<b>87</b>
<b>32</b>	<b>Formability (Method B)</b> .....	<b>87</b>
<b>32.1</b>	<b>Principle</b> .....	<b>87</b>
<b>32.2</b>	<b>Apparatus</b> .....	<b>88</b>
<b>32.3</b>	<b>Test specimens</b> .....	<b>88</b>
<b>32.4</b>	<b>Procedure</b> .....	<b>89</b>
<b>32.5</b>	<b>Test report</b> .....	<b>90</b>
<b>33</b>	<b>Resistance to blistering (Method A)</b> .....	<b>91</b>
<b>33.1</b>	<b>Principle</b> .....	<b>91</b>
<b>33.2</b>	<b>Apparatus</b> .....	<b>91</b>
<b>33.3</b>	<b>Test specimens</b> .....	<b>91</b>

<b>33.4</b>	<b>Procedure .....</b>	<b>91</b>
<b>33.4.1</b>	<b>Calibration of test apparatus .....</b>	<b>91</b>
<b>33.4.2</b>	<b>Test procedure.....</b>	<b>91</b>
<b>33.5</b>	<b>Test report.....</b>	<b>91</b>
<b>34</b>	<b>Resistance to blistering (Method B).....</b>	<b>92</b>
<b>34.1</b>	<b>Principle.....</b>	<b>92</b>
<b>34.2</b>	<b>Apparatus.....</b>	<b>92</b>
<b>34.3</b>	<b>Test specimens.....</b>	<b>92</b>
<b>34.4</b>	<b>Procedure .....</b>	<b>92</b>
<b>34.4.1</b>	<b>General.....</b>	<b>92</b>
<b>34.4.2</b>	<b>Calibration of test apparatus .....</b>	<b>92</b>
<b>34.4.3</b>	<b>Test procedure.....</b>	<b>92</b>
<b>34.5</b>	<b>Test report.....</b>	<b>92</b>
<b>Annex A (informative) Surface finish and colour influence on surface evaluations .....</b>		<b>94</b>
<b>Annex B (informative) Calibration and maintenance of abrasion equipment .....</b>		<b>95</b>
<b>Annex C (normative) Measurement of shore A hardness.....</b>		<b>99</b>

## European foreword

This document (EN 438-2:2016+A1:2018) has been prepared by Technical Committee CEN/TC 249 "Plastics", the secretariat of which is held by NBN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2019, and conflicting national standards shall be withdrawn at the latest by June 2019.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document includes Amendment 1 approved by CEN on 28 August 2018.

This document supersedes A1 EN 438-2:2016. A1

The start and finish of text introduced or altered by amendment is indicated in the text by tags A1 A1.

EN 438, *High-pressure decorative laminates (HPL) — Sheets based on thermosetting resins (usually called laminates)*, consists of the following parts:

- *Part 1: Introduction and general information*
- *Part 2: Determination of properties*
- *Part 3: Classification and specifications for laminates less than 2 mm thick intended for bonding to supporting substrates*
- *Part 4: Classification and specifications for Compact laminates of thickness 2 mm and greater*
- *Part 5: Classification and specifications for flooring grade laminates less than 2 mm thick intended for bonding to supporting substrates*
- *Part 6: Classification and specifications for Exterior-grade Compact laminates of thickness 2 mm and greater*
- *Part 7: Compact laminate and HPL composite panels for internal and external wall and ceiling finishes*
- *Part 8: Classification and specifications for design laminates*
- *Part 9: Classification and specifications for alternative core laminates*

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

## 1 Scope

This document specifies the methods of test for determination of the properties of high-pressure decorative laminates as defined in Clause 3. These methods are primarily intended for testing the sheets specified in EN 438-3, EN 438-4, EN 438-5, EN 438-6, EN 438-8, and EN 438-9.

The precision of the test methods, specified in this European Standard, is not known because inter-laboratory data are not yet available. When inter-laboratory data will be obtained, precision statements will be added to the test method at the following revision. For those test methods having an end point determination based on subjective judgement, it is not meaningful to make a statement of precision.

## 2 Normative references

**[A1]** The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies. **[A1]**

EN 204, *Classification of thermoplastic wood adhesives for non-structural applications*

EN 312, *Particleboards — Specifications*

EN 316, *Wood fibre boards — Definition, classification and symbols*

EN 438-1, *High-pressure decorative laminates (HPL) — Sheets based on thermosetting resins (usually called laminates) — Part 1: Introduction and general information*

EN ISO 62, *Plastics — Determination of water absorption (ISO 62)*

EN ISO 178, *Plastics — Determination of flexural properties (ISO 178)*

EN ISO 291, *Plastics — Standard atmospheres for conditioning and testing (ISO 291)*

EN ISO 2813, *Paints and varnishes — Determination of gloss value at 20°, 60° and 85° (ISO 2813)*

EN ISO 3668, *Paints and varnishes — Visual comparison of the colour of paints (ISO 3668)*

EN ISO 4287, *Geometrical product specifications (GPS) — Surface texture: Profile method — Terms, definitions and surface texture parameters (ISO 4287)*

EN ISO 4288, *Geometrical product specifications (GPS) — Surface texture: Profile method — Rules and procedures for the assessment of surface texture (ISO 4288)*

EN ISO 4892-1, *Plastics — Methods of exposure to laboratory light sources — Part 1: General guidance (ISO 4892-1)*

EN ISO 4892-2:2013, *Plastics — Methods of exposure to laboratory light sources — Part 2: Xenon-arc lamps (ISO 4892-2:2013)*

EN ISO 4892-3, *Plastics — Methods of exposure to laboratory light sources — Part 3: Fluorescent UV lamps (ISO 4892-3)*

EN ISO 6506-1, *Metallic materials — Brinell hardness test — Part 1: Test method (ISO 6506-1)*

EN ISO 12945-2, *Textiles — Determination of fabric propensity to surface fuzzing and to pilling — Part 2: Modified Martindale method (ISO 12945-2)*

EN ISO 12947-1, *Textiles — Determination of the abrasion resistance of fabrics by the Martindale method — Part 1: Martindale abrasion testing apparatus (ISO 12947-1)*

ISO 48, *Rubber, vulcanized or thermoplastic — Determination of hardness (hardness between 10 IRHD and 100 IRHD)*

ISO 105-A02, *Textiles — Tests for colour fastness — Part A02: Grey scale for assessing change in colour*

ISO 209:2007, *Aluminium and aluminium alloys — Chemical composition*

ISO 1770, *Solid-stem general purpose thermometers*

ISO 7267-2, *Rubber-covered rollers — Determination of apparent hardness — Part 2: Shore-type durometer method*

ISO 9370, *Plastics — Instrumental determination of radiant exposure in weathering tests — General guidance and basic test method*

CIE 85:1989, *Solar Spectral Irradiance*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 438-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

### 4 Assessment of appearance

#### 4.1 Principle

Laminates shall be inspected for surface appearance under standardised conditions of lighting and viewing.

#### 4.2 Apparatus

**4.2.1** Horizontal inspection table, of height approximately 700 mm and large enough to accommodate the largest sheets to be inspected.

**4.2.2** The light source shall provide a diffused illumination of  $(1200 \pm 400)$  lx over the whole area of the largest sheets to be inspected. This may be either diffused daylight or diffused artificial daylight.

**A1** Deleted text. **A1** When artificial daylight is used, it shall have a correlated colour temperature of 5000 K to 6500 K. Both of them shall be in accordance with EN ISO 3668.

A convenient distance of the lights from the inspection table is approximately 1,5 m.

#### 4.3 Test specimen

The specimen shall be the laminate under test, as supplied by the manufacturer.

#### 4.4 Procedure

Place the laminate, decorative face uppermost, on the inspection table. Wipe it free of any loose contamination with a soft cloth, using a suitable cleaning agent if necessary. Inspect it from the distance required by the relevant part of EN 438 for defects such as smudges, smears, fingerprints, scratches,