

INTERNATIONAL STANDARD

ISO
9382

First edition
1990-11-01

Shipborne barges, all series — Classification and main requirements

*Barges de toutes séries embarcables à bord des navires — Classification
et exigences principales*



Reference number
ISO 9382:1990(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 9382 was prepared by Technical Committee ISO/TC 8, *Shipbuilding and marine structures*.

Annexes A and B of this International Standard are for information only.

© ISO 1990

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Shipborne barges, all series — Classification and main requirements

1 Scope

This International Standard specifies the dimensions, displacement and maximum deadweight of all series of shipborne barges.

2 Definition

For the purposes of this International Standard, the following definition applies.

shipborne barge: Unpropelled, unmanned barge designed to be loaded, secured and carried on board

and discharged from a barge-carrying vessel equipped for this purpose. It is also designed to be pushed or towed, individually or in trains, on inland waterways and other appropriate water zones.

3 Classification

Shipborne barges of series 1, 2, 3 and 4 (see annex B) shall have the dimensions, displacement and maximum deadweight as specified in table 1.

Additional data for general cargo barges of each series are given in annex A.

Table 1

Series of barge	Main dimensions				Maximum draft in fresh water T_{max} mm	Maximum displacement in fresh water D t	Maximum air draft in lightship condition T_A mm	Maximum deadweight d.w. t
	Length overall L mm	Width overall B mm	Height					
			Depth moulded to deck H mm	Depth over all projections G mm				
1	18 745	9 500	3 658	4 394	2 730	463	3 745	370
2	29 718	10 706	3 810	5 282	3 336	1 024	4 742	847
3	38 250	11 000	3 900	5 460	3 460	1 300	4 880	1 070
4	18 745	4 750	2 850	3 587	2 777	236	3 117	194