
**Photography — Digital still cameras —
Measuring shooting time lag, shutter
release time lag, shooting rate, and
start-up time lag**

*Photographie — Caméras numériques — Décalage dans le temps du
mesurage de la prise, décalage dans le temps de l'ouverture de
l'objectif, cadence de prise et temps de démarrage*

This document is a preview generated by EMS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Test conditions	3
4.1 Illumination of the test scene.....	3
4.2 The chart and positioning of the digital still camera.....	4
4.3 Battery status.....	5
4.4 Memory card.....	5
4.5 Flash.....	5
4.6 Image stabilization.....	5
4.7 Other camera settings.....	5
5 Measurements	6
5.1 Definition of measurement.....	6
5.1.1 General.....	6
5.1.2 Measurement with external controls.....	7
5.1.3 Measurement with internal controls.....	7
5.2 Measurement method.....	8
5.2.1 Start-up time.....	8
5.2.2 Shooting time lag.....	9
5.2.3 Shutter release time lag.....	10
5.2.4 Shooting rate.....	10
6 Reporting the results	11
Annex A (informative) Test results of methods to start the timing device	13
Annex B (informative) Timing device	15
Annex C (informative) Measurement with internal controls	21
Annex D (informative) Examples of reporting the result	28
Annex E (informative) Estimation of the measurement accuracy	30
Annex F (informative) Example setup for measuring the shooting time lag for cameras with continuous autofocus	32
Bibliography	36

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee 42, *Photography*.

This third edition cancels and replaces the second edition (ISO 15781:2015), which has been technically revised.

The main changes compared to the previous edition are as follows:

- Current scope includes digital still cameras that continuously shoot images into the buffer and select an image depending on the moment the exposure button is pressed.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Taking pictures of a moving target was nearly impossible in the early days of digital photography. After pressing the exposure button it took a significant amount of time to capture the image and the chance to preserve the desired moment was gone.

Part of the time between pressing the exposure button and the exposed picture is needed to focus, another part is needed to adjust the exposure, etc. This unwelcome but unavoidable period of time is called shooting time lag. This is often mixed with the term shutter release time lag, which is also defined in this document. Optimized systems are nowadays able to decrease these time lags.

Capturing the different stages of a fast moving object is sometimes very important especially in areas like sports or people photography. This high shooting rate requires fast image processing within the digital still camera that can be measured according to the method described in this document.

When a photographer decides to capture an image of a changing scene, if his or her digital still camera takes a long time to be ready to shoot once it is turned on, the opportunity to capture the image is lost. This time named start-up time lag is therefore another important value, which can be determined using this document.

Photography — Digital still cameras — Measuring shooting time lag, shutter release time lag, shooting rate, and start-up time lag

1 Scope

This document specifies how to measure and report the shooting time lag, shutter release time lag, shooting rate and start-up time lag for digital still cameras, including camera modules in phones and tablet computers. It includes a method that uses control signals inside the digital still camera and a method that determines the timing values without requiring access to the inside of the digital still camera.

This document does not address the measurement either of auto focus speed below recommended illumination level or auto focus accuracy.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 7589, *Photography — Illuminants for sensitometry — Specifications for daylight, incandescent tungsten and printer*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

digital still camera

device which incorporates an image sensor and produces a digital signal representing a still picture (1)

Note 1 to entry: A digital still camera is typically a portable, hand-held device. The digital signal is usually recorded on a removable memory, such as a solid-state memory card or magnetic disk.

[SOURCE: ISO 12231, 3.40, modified — Note 2 to entry has been deleted.]

3.2

shooting time lag

t_{SL}

time elapsed from stand-by state to reaching capture point on a digital still camera or a module built into a mobile device and the beginning of the exposure

Note 1 to entry: This period of time includes all measurements and adjustments (e.g. auto focus and exposure control) a digital still camera needs to make prior to the beginning of the exposure.

Note 2 to entry: When the exposure button of a digital still camera is pressed it performs a number of time-consuming measurements and adjustments, e.g. determination of the exposure and focus adjustment. The time needed for these procedures is part of the shooting time lag.