

MADALPINGELISED LÜLITUSAPARAADID. OSA 5-2:  
JUHTIMISAHELAAPARAADID JA LÜLITUSELEMENDID.  
LÄHEDUSLÜLITID

Low-voltage switchgear and controlgear - Part 5-2:  
Control circuit devices and switching elements -  
Proximity switches

## EESTI STANDARDI EESSÕNA

## NATIONAL FOREWORD

See Eesti standard EVS-EN IEC 60947-5-2:2020 sisaldab Euroopa standardi EN IEC 60947-5-2:2020 ingliskeelset teksti.	This Estonian standard EVS-EN IEC 60947-5-2:2020 consists of the English text of the European standard EN IEC 60947-5-2:2020.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 27.03.2020.	Date of Availability of the European standard is 27.03.2020.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile [standardiosakond@evs.ee](mailto:standardiosakond@evs.ee).

ICS 29.120.40, 29.130.20

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:  
Koduleht [www.evs.ee](http://www.evs.ee); telefon 605 5050; e-post [info@evs.ee](mailto:info@evs.ee)

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage [www.evs.ee](http://www.evs.ee); phone +372 605 5050; e-mail [info@evs.ee](mailto:info@evs.ee)

EUROPEAN STANDARD

**EN IEC 60947-5-2**

NORME EUROPÉENNE

EUROPÄISCHE NORM

March 2020

ICS 29.120.40; 29.130.20

Supersedes EN 60947-5-2:2007 and all of its  
amendments and corrigenda (if any)

English Version

**Low-voltage switchgear and controlgear - Part 5-2: Control  
circuit devices and switching elements - Proximity switches  
(IEC 60947-5-2:2019)**

Appareillage à basse tension - Partie 5-2: Appareils et  
éléments de commutation pour circuits de commande -  
DéTECTEURS DE PROXIMITÉ  
(IEC 60947-5-2:2019)

Niederspannungsschaltgeräte - Teil 5-2: Steuergeräte und  
Schaltelemente - Näherungsschalter  
(IEC 60947-5-2:2019)

This European Standard was approved by CENELEC on 2019-11-22. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels**

## European foreword

The text of document 121A/313/FDIS, future edition 4 of IEC 60947-5-2, prepared by SC 121A "Low-voltage switchgear and controlgear" of IEC/TC 121 "Switchgear and controlgear and their assemblies for low voltage" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 60947-5-2:2020.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2020-09-27
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2023-03-27

This document supersedes EN 60947-5-2:2007 and all of its amendments and corrigenda (if any).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For the relationship with EU Directives see informative Annexes ZZA and ZZB, which are an integral part of this document.

### Endorsement notice

The text of the International Standard IEC 60947-5-2:2019 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60825 (series)	NOTE	Harmonized as EN 60825 (series)
IEC 61000-3-2:2018	NOTE	Harmonized as EN IEC 61000-3-2:2019 (not modified)
IEC 61000-3-3:2013	NOTE	Harmonized as EN 61000-3-3:2013 (not modified)
IEC 61000-3-3:2013/A1:2017	NOTE	Harmonized as EN 61000-3-3:2013/A1:2019 (not modified)
IEC 61076-2-101	NOTE	Harmonized as EN 61076-2-101
IEC 61076-2-104	NOTE	Harmonized as EN 61076-2-104
IEC 61076-2-105	NOTE	Harmonized as EN 61076-2-105
IEC 62471:2006	NOTE	Harmonized as EN 62471:2008 (modified)
IEC 62683-1:2017	NOTE	Harmonized as EN 62683-1:2017 (not modified)
ISO 7010	NOTE	Harmonized as EN ISO 7010

## Annex ZA (normative)

### Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: [www.cenelec.eu](http://www.cenelec.eu).

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60068-2-6	2007	Environmental testing – Part 2-6: Tests – Test Fc: Vibration (sinusoidal)	EN 60068-2-6	2008
IEC 60068-2-14	2009	Environmental testing – Part 2-14: Tests – Test N: Change of temperature	EN 60068-2-14	2009
IEC 60068-2-27	2008	Environmental testing – Part 2-27: Tests – Test Ea and guidance: Shock	EN 60068-2-27	2009
IEC 60068-2-30	2005	Environmental testing - Part 2-30: Tests - Test Db: Damp heat, cyclic (12 h + 12 h cycle)	EN 60068-2-30	2005
IEC 60364	series	Low-voltage electrical installations	HD 60364	series
IEC 60445	2017	Basic and safety principles for man-machine interface, marking and identification – Identification of equipment terminals, conductor terminations and conductors	EN 60445	2017
IEC 60695-2-10	2013	Fire hazard testing - Part 2-10: Glowing/hot-wire based test methods - Glow-wire apparatus and common test procedure	EN 60695-2-10	2013
IEC 60695-2-11	2014	Fire hazard testing - Part 2-11: Glowing/hot-wire based test methods - Glow-wire flammability test method for end-products (GWEPT)	EN 60695-2-11	2014
IEC 60695-2-12	2010	Fire hazard testing - Part 2-12: Glowing/hot-wire based test methods - Glow-wire flammability index (GWFI) test method for materials	EN 60695-2-12	2010
+ A1	2014		+ A1	2014

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60825-1	2014	Safety of laser products - Part 1: Equipment classification and requirements	EN 60825-1	2014
			+ AC	2017
IEC 60947-1	2007	Low-voltage switchgear and controlgear - Part 1: General rules	EN 60947-1	2007
+ A1	2010		+ A1	2011
+ A2	2014		+ A2	2014
IEC 61000-4-2	2008	Electromagnetic compatibility (EMC) - Part 4-2: Testing and measurement techniques - Electrostatic discharge immunity test	EN 61000-4-2	2009
IEC 61000-4-3	2006	Electromagnetic compatibility (EMC) - Part 4-3: Testing and measurement techniques - Radiated, radio-frequency, electromagnetic field immunity test	EN 61000-4-3	2006
+ A1	2007		+ A1	2008
+ A2	2010		+ A2	2010
IEC 61000-4-4	2012	Electromagnetic compatibility (EMC) - Part 4-4: Testing and measurement techniques - Electrical fast transient/burst immunity test	EN 61000-4-4	2012
IEC 61000-4-6	2013	Electromagnetic compatibility (EMC) - Part 4-6: Testing and measurement techniques - Immunity to conducted disturbances, induced by radio- frequency fields	EN 61000-4-6	2014
			+ AC	2015
IEC 61000-4-8	2009	Electromagnetic compatibility (EMC) - Part 4-8: Testing and measurement techniques - Power frequency magnetic field immunity test	EC 61000-4-8	2010
IEC 61000-4-11	2004	Electromagnetic compatibility (EMC) - Part 4-11: Testing and measurement techniques - Voltage dips, short interruptions and voltage variations immunity tests	EN 61000-4-11	2004
+ A1	2017		+ A1	2017
IEC 61000-4-13	2002	Electromagnetic compatibility (EMC) - Part 4-13: Testing and measurement techniques - Harmonics and interharmonics including mains signalling at a.c. power port, low frequency immunity tests	EN 61000-4-13	2002
+ A1	2009		+ A1	2009
+ A2	2015		+ A2	2016
IEC 61076-2	series	Connectors for electronic equipment – Product requirements – Part 2: Circular connectors	EN 61076-2	series
IEC 61140	-	Protection against electric shock - Common aspects for installation and equipment	EN 61140	2016

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 62443	series	Security for industrial automation and control systems	EN 62443	series
IEC 62471	series	Photobiological safety of lamps and lamp systems	EN 62471	series
IEC TR 62471-2	2009	Photobiological safety of lamps and lamp systems - Part 2: Guidance on manufacturing requirements relating to non-laser optical radiation safety	-	-
CISPR 11 (mod)	2015	Industrial, scientific and medical equipment – Radio-frequency disturbance characteristics – Limits and methods of measurement	EN 55011	2016
+ A1	2016		+ A1	2017
IEC Guide 117	2010	Electrotechnical equipment - Temperatures of touchable hot surfaces	CLC Guide 29	2007

## Annex ZZA (informative)

### Relationship between this European standard and the essential requirements of Directive 2014/30/EU [2014 OJ L96] aimed to be covered

This European standard has been prepared under the European Commission standardisation request C(2016) 7641 final of 30.11.2016<sup>1</sup>, ('M/552'), as regards harmonised standards in support of Directive 2014/30/EU relating to electromagnetic compatibility, to provide one voluntary means of conforming to essential requirements of Directive 2014/30/EU of the European Parliament and of the Council of 26 February 2014 on the harmonisation of the laws of the Member States relating to electromagnetic compatibility [2014 OJ L96].

Once this standard is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of this standard given in Table ZZA.1 confers, within the limits of the scope of this standard, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

**Table ZZA.1 — Correspondence between this European standard and the Essential Requirements set out in Directive 2014/30/EU [2014 OJ L96]**

Essential requirements of Directive 2014/30/EU	Clause(s) / sub-clause(s) of this EN	Remarks / Notes
Annex I. 1(a) Electromagnetic disturbances	8.2.6.1, 8.2.6.3, 9.6.1, 9.6.3	
Annex I. 1(b) Electromagnetic immunity	8.2.6.1, 8.2.6.2, 9.6.1, 9.6.2	Full coverage of requirements for conducted and radiated disturbances in the range 150 kHz to 6 GHz

**WARNING 1:** Presumption of conformity stays valid only as long as a reference to this European standard is maintained in the list published in the Official Journal of the European Union. Users of this standard should consult frequently the latest list published in the Official Journal of the European Union.

**WARNING 2:** Other Union legislation may be applicable to the product(s) falling within the scope of this standard.

---

<sup>1</sup> COMMISSION IMPLEMENTING DECISION C(2016) 7641 final of 30.11.2016 on a standardisation request to the European Committee for Standardisation, to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards harmonised standards in support of Directive 2014/30/EU of the European Parliament and of the Council of 26 February 2014 on the harmonisation of the laws of the Member States relating to electromagnetic compatibility.

## Annex ZZB (informative)

### Relationship between this European standard and the safety objectives of Directive 2014/35/EU [2014 OJ L96] aimed to be covered

This European standard has been prepared under a Commission's standardisation request relating to harmonised standards in the field of the Low Voltage Directive, M/511, to provide one voluntary means of conforming to safety objectives of Directive 2014/35/EU of the European Parliament and of the Council of 26 February 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of electrical equipment designed for use within certain voltage limits [2014 OJ L96].

Once this standard is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of this standard given in Table ZZB.1 confers, within the limits of the scope of this standard, a presumption of conformity with the corresponding safety objectives of that Directive, and associated EFTA regulations.

**Table ZZB.1 — Correspondence between this European standard and Annex I of Directive 2014/35/EU [2014 OJ L96]**

Safety objectives of Directive 2014/35/EU	Clause(s) / sub-clause(s) of this EN	Remarks/note
1 a)	1, 2, 3, 4, 5.3, 5.4, 6.1, 6.2, 6.3, 6.4, 7.1, 8.1, 8.2, 9.1, 9.2, 9.3, ANNEX B	
1 b)	1, 2, 3, 4, 5, 6.1, 6.2, 6.3, 7, 8.1, 8.2 ANNEX B	
1 c)	1, 2, 3, 4, 5, 6, 7, 8 Also refer to 2 a) to 2 d) and 3 a) to 3 c) in this table	
2 a)	1, 2, 3, 4, 5.3, 6.1, 8.1, 8.2, 8.4, 9.1, 9.2, 9.3, ANNEX B, ANNEX C	
2 b)	1, 2, 3, 4, 5.3, 5.4, 6.1, 6.3, 7.1, 8.1, 8.2, 9.2, 9.3	This document does not deal with any specific requirement on acoustic noise. Photobiological radiation risk (8.1) is covered by using the standard informed (EN 60825- 1/EN 62471 (all parts)).
2 c)	1, 2, 3, 4, 5, 6.4, 7, 8.1, 8.4, 9.1, ANNEX B, ANNEX C	

Safety objectives of Directive 2014/35/EU	Clause(s) / sub-clause(s) of this EN	Remarks/note
2 d)	1, 2, 3, 4, 5.3, 5.4, 6.1 7, 8.1, 8.2, 9.1, 9.2, 9.3, ANNEX B	
3 a)	1, 2, 3, 4, 5, 7, 8.4, 9.1, ANNEX B, ANNEX C	
3 b)	1, 2, 3, 4, 5, 8.1	In reference to the scope of this document the risk about biological/chemical effects and chemical stress (8.1) is not recognized and therefore not covered.
3 c)	1, 2, 3, 4, 5, 7.1, 8.1, 8.2, 9.3	

**WARNING 1:** Presumption of conformity stays valid only as long as a reference to this European standard is maintained in the list published in the Official Journal of the European Union. Users of this standard should consult frequently the latest list published in the Official Journal of the European Union.

**WARNING 2:** Other Union legislation may be applicable to the product(s) falling within the scope of this standard.

## CONTENTS

FOREWORD .....	9
1 Scope .....	12
2 Normative references .....	13
3 Terms and definitions .....	14
3.1 Basic terms and definitions .....	17
3.2 Parts of a proximity switch .....	18
3.3 Operation of a proximity switch .....	20
3.4 Switching element characteristics .....	22
4 Classification .....	24
4.1 General .....	24
4.2 Classification according to sensing means .....	26
4.3 Classification according to the mechanical installation .....	26
4.4 Classification according to the construction form and size .....	26
4.5 Classification according to switching element function .....	26
4.6 Classification according to type of output .....	26
4.7 Classification according to method of connection .....	26
5 Characteristics .....	26
5.1 General .....	26
5.1.1 Summary of characteristics .....	26
5.1.2 Operation of an inductive or capacitive proximity switch .....	26
5.1.3 Operation of an ultrasonic proximity switch .....	27
5.1.4 Operation of a photoelectric proximity switch .....	27
5.1.5 Operation of a magnetic proximity switch .....	27
5.2 Operating conditions .....	27
5.2.1 Operating conditions of inductive and capacitive proximity switches .....	27
5.2.2 Operating distance (s) of an ultrasonic proximity switch .....	28
5.2.3 Operating distance (s) of a photoelectric proximity switch .....	29
5.3 Rated and limiting values for the proximity switch and switching element(s) .....	31
5.3.1 Voltages .....	31
5.3.2 Currents .....	31
5.3.3 Rated supply frequency .....	32
5.3.4 Frequency of operating cycles ( $f$ ) .....	32
5.3.5 Normal load and abnormal load characteristics .....	32
5.3.6 Short-circuit characteristics .....	32
5.4 Utilization categories for the switching element .....	32
6 Product information .....	33
6.1 Nature of information – Identification .....	33
6.2 Marking .....	34
6.2.1 General .....	34
6.2.2 Terminal identification and marking .....	34
6.2.3 Functional markings .....	34
6.3 Instructions for installation, operation and maintenance .....	34
6.4 Environmental information .....	35
6.4.1 Environmentally conscious design process (ECD process) .....	35

6.4.2	Procedure to establish material declaration .....	35
7	Normal service, mounting and transport conditions .....	35
7.1	Normal service conditions .....	35
7.1.1	General .....	35
7.1.2	Ambient air temperature .....	35
7.1.3	Altitude .....	36
7.1.4	Climatic conditions .....	36
7.2	Conditions during transport and storage .....	36
7.3	Mounting .....	36
8	Constructional and performance requirements .....	36
8.1	Constructional requirements .....	36
8.1.1	Materials .....	36
8.1.2	Current-carrying parts and their connections .....	37
8.1.3	Clearances and creepage distances .....	38
8.1.4	Actuation .....	38
8.1.5	Void .....	38
8.1.6	Void .....	38
8.1.7	Terminals .....	38
8.1.8	Void .....	40
8.1.9	Provisions for protective earthing .....	40
8.1.10	Degree of protection .....	40
8.1.11	Requirements for proximity switches with integrally connected cables .....	40
8.1.12	Class II proximity switches .....	41
8.1.13	Chemical stress .....	41
8.1.14	Equipment design .....	41
8.1.15	Protection against artificial optical radiation .....	41
8.1.16	Biological and chemical effects .....	42
8.1.17	Unattended operation .....	42
8.1.18	Safety related security .....	42
8.1.19	Requirements for embedded software .....	42
8.2	Performance requirements .....	42
8.2.1	Operating conditions .....	42
8.2.2	Temperature-rise .....	46
8.2.3	Dielectric properties .....	47
8.2.4	Ability to make and break under normal load and abnormal load conditions .....	48
8.2.5	Conditional short-circuit current .....	49
8.2.6	Electromagnetic compatibility (EMC) .....	49
8.3	Physical dimensions .....	53
8.4	Shock and vibration and special environmental conditions .....	53
8.4.1	Shock .....	53
8.4.2	Vibration .....	53
8.4.3	Results to be obtained .....	53
8.4.4	Special environmental conditions – damp heat, salt mist, vibration and shock .....	54
9	Tests .....	54
9.1	Kinds of tests .....	54
9.1.1	General .....	54
9.1.2	Type tests .....	54

9.1.3	Routine tests .....	54
9.1.4	Sampling tests .....	54
9.1.5	Special tests .....	54
9.2	Compliance with constructional requirements .....	55
9.2.1	General .....	55
9.2.2	Materials .....	55
9.3	Performances .....	55
9.3.1	Test sequences .....	55
9.3.2	General test conditions .....	56
9.3.3	Performance under no load, normal load and abnormal load condition .....	58
9.3.4	Performance under short-circuit current conditions .....	64
9.4	Testing of operating distances .....	65
9.4.1	Inductive, capacitive, non-mechanical magnetic and ultrasonic proximity switches .....	65
9.4.2	Photoelectric proximity switches .....	66
9.5	Testing for the frequency of operating cycles .....	69
9.5.1	General .....	69
9.5.2	Method for measuring the frequency of operating cycles .....	70
9.5.3	Results to be obtained .....	72
9.5.4	Photoelectric proximity switches .....	72
9.6	Verification of the electromagnetic compatibility .....	74
9.6.1	General .....	74
9.6.2	Immunity .....	74
9.6.3	Emission .....	75
9.7	Test results and test report .....	75
Annex A (informative)	Typical dimensions and operating distances of proximity switches .....	76
A.1	MODEL IA, IB – INDUCTIVE CYLINDRICAL PROXIMITY SWITCHES WITH THREADED BARREL (IA) OR SMOOTH BARREL (IB) WITH CABLE OR CONNECTOR .....	76
A.1.1	(IA, IB) Dimensions .....	76
A.1.2	(IA, IB) Rated operating distances .....	79
A.1.3	(IA, IB) Installation (mounting) threaded barrel (IA) and smooth barrel (IB) .....	80
A.1.4	(IA, IB) Frequency of operating cycles ( <i>f</i> ) .....	80
A.2	MODEL IC – INDUCTIVE RECTANGULAR PROXIMITY SWITCHES WITH SQUARE CROSS-SECTION .....	81
A.2.1	(IC) Dimensions .....	81
A.2.2	(IC) Rated operating distance .....	83
A.2.3	(IC) Installation (mounting) .....	84
A.2.4	(IC) Frequency of operating cycles ( <i>f</i> ) .....	85
A.3	MODEL ID – INDUCTIVE RECTANGULAR PROXIMITY SWITCHES WITH RECTANGULAR CROSS-SECTION .....	86
A.3.1	(ID) Dimensions .....	86
A.3.2	(ID) Installation (mounting) .....	87
A.3.3	(IC) Frequency of operating cycles ( <i>f</i> ) .....	88
A.4	MODEL IX (IN, IS, FLATPACK, CUBICAL INDUCTIVE RECTANGULAR AND CUBICAL PROXIMITY SWITCHES WITH SMALL SIZES) .....	88

A.4.1	(IX) Dimensions .....	88
A.4.2	(Flatpack) Dimensions .....	89
A.4.3	(Cubical) Dimensions .....	90
A.4.4	(IX) Rated operating distance .....	92
A.4.5	(IX) Installation (mounting) .....	92
A.4.6	(IX) Frequency of operating cycles ( $f$ ) .....	92
A.5	MODEL CA – CAPACITIVE CYLINDRICAL PROXIMITY SWITCHES WITH THREADED BARREL .....	93
A.5.1	(CA) Dimensions .....	93
A.5.2	(CA) Rated operating distance ( $s_n$ ) .....	94
A.5.3	(CA) Installation (mounting) .....	94
A.5.4	(CA) Frequency of operating cycles ( $f$ ) .....	95
A.6	MODEL CB – CAPACITIVE PROXIMITY SWITCHES WITH SMOOTH BARREL .....	95
A.7	MODEL CC – CAPACITIVE RECTANGULAR PROXIMITY SWITCHES WITH SQUARE CROSS-SECTION .....	95
A.7.1	(CC) Dimensions .....	95
A.7.2	(CC) Rated operating distances ( $s_n$ ) .....	96
A.7.3	(CC) Installation (mounting) .....	97
A.7.4	(CC) Frequency of operating cycles ( $f$ ) .....	97
A.8	MODEL CD – CAPACITIVE RECTANGULAR PROXIMITY SWITCHES WITH RECTANGULAR CROSS-SECTION .....	98
A.8.1	(CD) Dimensions .....	98
A.8.2	(CD) Rated operating distance ( $s_n$ ) .....	98
A.8.3	(CD) Installation (mounting) .....	98
A.8.4	(CD) Frequency of operating cycles ( $f$ ) .....	99
A.9	MODEL CX – CAPACITIVE PROXIMITY SWITCHES WITH OTHER FORMS, DIMENSIONS AND SMALL SIZES .....	99
A.10	MODEL UA – THREADED BARREL ULTRASONIC CYLINDRICAL PROXIMITY SWITCHES .....	99
A.10.1	(UA) Dimensions .....	99
A.10.2	(UA) Sensing range .....	100
A.10.3	(UA) Installation (mounting) .....	100
A.10.4	(UA) Frequency of operating cycles ( $f$ ) .....	100
A.11	MODEL UD – ULTRASONIC RECTANGULAR PROXIMITY SWITCHES WITH RECTANGULAR CROSS-SECTION .....	101
A.11.1	(UD) Dimensions .....	101
A.11.2	(UD) Sensing range .....	101
A.11.3	(UD) Installation (mounting) .....	101
A.11.4	(UD) Frequency of operating cycles ( $f$ ) .....	101
Annex B (normative)	Class II proximity switches insulated by encapsulation – Requirements and tests .....	102
B.1	General .....	102
B.2	Terms and definitions .....	102
B.6	Marking .....	102
B.8	Constructional and functional requirements .....	103
B.9	Tests .....	103
Annex C (normative)	Additional requirements for proximity switches with integrally connected cables .....	106
C.1	General .....	106

C.2	Terms and definitions.....	106
C.8	Constructional and performance requirements .....	106
C.9	Tests .....	107
Annex D	(normative) Integral connectors for plug-in proximity switches .....	111
Annex E	(normative) Additional requirements for proximity switches suitable for use in strong magnetic fields .....	119
E.1	Preamble .....	119
E.3	Terms and definitions.....	119
E.4	Classification .....	119
E.8	Construction and performance requirements .....	120
E.9	Tests .....	121
Annex F	(informative) Symbols for proximity switches .....	124
F.1	General.....	124
F.2	Standard symbols for proximity switches .....	124
F.3	Additional symbols for photoelectric proximity switches.....	126
F.3.1	Sensor principles .....	126
F.3.2	Optical actuation means .....	126
F.3.3	Functional symbol definitions .....	126
Bibliography	.....	128
Figure 1	– Relationship between operating distances of inductive and capacitive proximity switches (see 8.2.1.3 and 9.4.1) .....	28
Figure 2	– Ultrasonic proximity switch operating distances.....	28
Figure 3	– Relationship between operating distances of ultrasonic proximity switches (see 8.2.1.3 and 9.4.1).....	29
Figure 4	– Sensing range and operating range of photoelectric proximity switches (see 8.2.1.3 and 9.4) .....	30
Figure 5	– Relationship between $U_e$ and $U_B$ .....	31
Figure 6	– Method of measuring the operating distance (see 9.3.2.1 and 9.4.1) .....	57
Figure 7	– Test circuit for the verification of time delay before availability (see 8.2.1.7 and 9.3.3.2.1) .....	59
Figure 8	– Signal output across load in Figure 7 (see 9.3.3.2.1).....	60
Figure 9	– Test circuit for the verification of minimum operational current OFF-state current, voltage drop and independent action (see 9.3.3.2.2, 9.3.3.2.3, 9.3.3.2.4 and 9.3.3.2.5) .....	61
Figure 10	– Test circuit for the verification of making and breaking capability (see 9.3.3.5) .....	64
Figure 11	– Short-circuit testing (see 9.3.4.2) .....	65
Figure 12	– Testing of the sensing range (see 9.4.2) .....	68
Figure 13	– Methods for measuring the frequency of operating cycle of inductive, capacitive and non-mechanical magnetic proximity switches (if applicable).....	70
Figure 14	– Methods for measuring the frequency of operating cycles ( $f$ ), ultrasonic proximity switch .....	71
Figure 15	– Output signal of direct current proximity switch during the measurement of frequency of operating cycles ( $f$ ) .....	71
Figure 16	– Measurement means for turn-on time $t_{ON}$ and turn-off time $t_{OFF}$ .....	72
Figure 17	– Turn-on time $t_{ON}$ measurement.....	73

Figure 18 – Turn-off time $t_{off}$ measurement .....	73
Figure A.1 – (IA) – Dimensions for threaded barrel – cable type .....	76
Figure A.2 – (IB) – Dimensions for smooth barrel – cable type .....	77
Figure A.3 – Type A dimensions – Body M5x0,5, M8x1, Ø 4, Ø 6,5 with connector M5/M8 .....	78
Figure A.4 – Type B dimensions – Body M5x0,5, M8x1, Ø 4, Ø 6,5 with connector M8/M12 .....	78
Figure A.5 – Type C dimensions – Body M12x1, M18x1, M30x1,5 with connector M12 .....	79
Figure A.6 – (IA, IB) – Installation (mounting) <sup>a</sup> .....	80
Figure A.7 – Dimensions of Type I1C26 (in millimetres) .....	82
Figure A.8 – Dimensions of Types I2C40 and I1C40 (in millimetres) .....	82
Figure A.9 – Dimensions of Types I2IMC and I1IMC (IMC) 40 x 40 (cube) .....	83
Figure A.10 – Installation of a I1C proximity switch in damping material.....	84
Figure A.11 – (IC) Installation of I2C in damping material <sup>a</sup> .....	85
Figure A.12 – (ID) Dimensions .....	86
Figure A.13 – (IDC) Dimensions.....	87
Figure A.14 – (ID) Installation in damping material.....	88
Figure A.15 – (IN) with cable or connector M8 entry.....	89
Figure A.16 – (IS) with cable or connector M8 entry.....	89
Figure A.17 – (Flatpack) with cable or connector M8 entry .....	90
Figure A.18 – (5 mm x 5 mm) Cubical with cable.....	91
Figure A.19 – (8 mm x 8 mm) Cubical with cable.....	91
Figure A.20 – (8 mm x 8 mm) Cubical with M8 connector.....	92
Figure A.21 – (CA) Dimensions.....	93
Figure A.22 – (CA) Installation (mounting) .....	95
Figure A.23 – Model CC Dimensions.....	96
Figure A.24 – (CC) Installation (mounting) .....	97
Figure A.25 – (CD) Dimensions in millimetres .....	98
Figure A.26 – (CD) Installation (mounting) .....	99
Figure A.27 – (UA) Dimensions.....	100
Figure A.28 – (UD) Dimensions of Type D80.....	101
Figure B.1 – Encapsulated device.....	103
Figure B.2 – Test device .....	105
Figure D.1 – M12 thread 3-pin integral connector for AC proximity switches .....	111
Figure D.2 – M12 thread 5-pin integral connector for DC proximity switches .....	112
Figure D.3 – 8 mm thread 3-pin integral connector for DC proximity switches .....	113
Figure D.4 – 8 mm thread 4-pin integral connector for DC proximity switches .....	114
Figure D.5 – M12 thread 4-pin integral connector for AC proximity switches .....	115
Figure D.6 – M12 thread 5-pin integral connector for AC proximity switches .....	116
Figure D.7 – M12 thread 6-pin integral connector for AC proximity switches .....	117
Figure D.8 – M5 thread 4-pin/3-pin integral connector for DC proximity switches .....	118
Figure E.1 – Examples of test configuration for verification of the immunity to an alternating field.....	122

Figure E.2 – Example of test configuration for verification of the immunity in a constant magnetic field .....	123
Figure F.1 – Examples of symbols for proximity switches .....	125
Figure F.2 – Examples of symbols for proximity switches .....	127
Table 1 – Classification of proximity switches .....	25
Table 2 – Cross reference between active optical signal and output function .....	27
Table 3 – Utilization categories for switching elements .....	33
Table 4 – Test conditions for glow-wire test .....	37
Table 5 – Connection and wiring identification .....	39
Table 6 – Burn threshold .....	47
Table 7 – Verification of making and breaking capacities of switching elements under normal conditions corresponding to the utilization categories <sup>a</sup> .....	48
Table 8 – Verification of making and breaking capacities of switching elements under abnormal conditions corresponding to the utilization categories <sup>a</sup> .....	49
Table 9 – Acceptance criteria .....	50
Table 10 – Immunity tests (1 of 2) .....	51
Table 11 – Target sizes of ultrasonic proximity switches .....	57
Table 12 – Test voltages .....	63
Table A.1 – (IA, IB) – Preferred and secondary series smooth and threaded barrel cable types .....	77
Table A.2 – (IA) – Dimensions of nuts .....	77
Table A.3 – (Types A, B, C) – Preferred and secondary series, smooth and threaded barrel connector types .....	79
Table A.4 – (IA, IB) – Rated operating distances .....	80
Table A.5 – (IA, IB) – Frequency of operating cycles ( <i>f</i> ) in operating cycles per second – Minimum requirements .....	81
Table A.6 – (IC) – Rated operating distance .....	84
Table A.7 – (IC) – Frequency of operating cycles ( <i>f</i> ) in operating cycles per second – Minimum requirements .....	85
Table A.8 – (ID) – Dimensions .....	86
Table A.9 – (IC) – Frequency of operating cycles ( <i>f</i> ) in operating cycles per second – Minimum requirements .....	88
Table A.10 – (IX) – Rated operating distances IN, IS, flatpack, cubical .....	92
Table A.11 – (IX) – Frequency of operating cycles IN, IS, flatpack and cubical ( <i>f</i> ) in operating cycles per second .....	93
Table A.12 – (CA) – Dimensions .....	94
Table A.13 – (CA) – Rated operating distances .....	94
Table A.14 – (CC) – Rated operational distance .....	97
Table A.15 – (UA) – Dimensions .....	100
Table C.1 – Material characteristics .....	107
Table C.2 – Examples of standard cable types .....	108
Table C.3 – Tensile forces .....	109