

**RAADIOHÄIRINGUTE JA HÄIRINGUTALUVUSE  
MÕÕTESEADMED JA -MEETODID. OSA 2-1: HÄIRINGUTE  
JA HÄIRINGUTALUVUSE MÕÕTEMEETODID.  
JUHTIVUSLIKULT LEVIVATE HÄIRINGUTE MÕÕTMINE**

**Specification for radio disturbance and immunity  
measuring apparatus and methods - Part 2-1: Methods  
of measurement of disturbances and immunity -  
Conducted disturbance measurements**

**EESTI STANDARDI EESSÕNA****NATIONAL FOREWORD**

See Eesti standard EVS-EN 55016-2-1:2014 sisaldab Euroopa standardi EN 55016-2-1:2014 ingliskeelset teksti.	This Estonian standard EVS-EN 55016-2-1:2014 consists of the English text of the European standard EN 55016-2-1:2014.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 11.07.2014.	Date of Availability of the European standard is 11.07.2014.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile [standardiosakond@evs.ee](mailto:standardiosakond@evs.ee).

ICS 33.100.10, 33.100.20

**Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele**

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:  
Koduleht [www.evs.ee](http://www.evs.ee); telefon 605 5050; e-post [info@evs.ee](mailto:info@evs.ee)

**The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation**

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage [www.evs.ee](http://www.evs.ee); phone +372 605 5050; e-mail [info@evs.ee](mailto:info@evs.ee)

English Version

Specification for radio disturbance and immunity measuring apparatus and methods - Part 2-1: Methods of measurement of disturbances and immunity - Conducted disturbance measurements  
(CISPR 16-2-1:2014)

Spécifications des méthodes et des appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques - Partie 2-1: Méthodes de mesure des perturbations et de l'immunité - Mesures des perturbations conduites  
(CISPR 16-2-1:2014)

Anforderungen an Geräte und Einrichtungen sowie Festlegung der Verfahren zur Messung der hochfrequenten Störaussendung (Funkstörungen) und Störfestigkeit - Teil 2-1: Verfahren zur Messung der hochfrequenten Störaussendung (Funkstörungen) und Störfestigkeit - Messung der leitungsgeführten Störaussendung  
(CISPR 16-2-1:2014)

This European Standard was approved by CENELEC on 2014-04-02. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

## Foreword

The text of document CISPR/A/1053/FDIS, future edition 3 of CISPR 16-2-1, prepared by SC A "Radio-interference measurements and statistical methods" of IEC/TC CISPR "International special committee on radio interference" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 55016-2-1:2014.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2015-01-11
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2017-04-02

This document supersedes EN 55016-2-1:2009.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

## Endorsement notice

The text of the International Standard CISPR 16-2-1:2014 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

CISPR 11:2003 + A1:2004	NOTE	Harmonized as EN 55011:2007 <sup>1)</sup> (modified).
CISPR 16-1-4:2010	NOTE	Harmonized as EN 55016-1-4:2010 (not modified).
CISPR 16-2-3:2010	NOTE	Harmonized as EN 55016-2-3:2010 (not modified).
IEC 60364-4 Series	NOTE	Harmonized as HD 60364-4 Series (modified).
IEC 61000-4-6:2008	NOTE	Harmonized as EN 61000-4-6:2009 (modified).
IEC 61010-1:2001	NOTE	Harmonized as EN 61010-1:2001 (modified).

<sup>1)</sup> Superseded by EN 55011:2009 (CISPR 11:2009, mod.)

## Annex ZA (normative)

### Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: [www.cenelec.eu](http://www.cenelec.eu)

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
CISPR 14-1	-	Electromagnetic compatibility - Requirements for household appliances, electric tools and similar apparatus - Part 1: Emission	EN 55014-1	-
CISPR 16-1-1	2010	Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring apparatus	EN 55016-1-1	2010
CISPR 16-1-2	2014	Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-2: Radio disturbance and immunity measuring apparatus - Coupling devices for conducted disturbance measurements	EN 55016-1-2	2014
CISPR 16-4-2	-	Specification for radio disturbance and immunity measuring apparatus and methods - Part 4-2: Uncertainties, statistics and limit modelling - Measurement instrumentation uncertainty	EN 55016-4-2	-
IEC 60050	Series	International Electrotechnical Vocabulary	-	-

## CONTENTS

FOREWORD.....	8
1 Scope.....	10
2 Normative references.....	10
3 Terms, definitions and abbreviations.....	11
3.1 Terms and definitions.....	11
3.2 Abbreviations.....	16
4 Types of disturbance to be measured.....	17
4.1 General.....	17
4.2 Types of disturbance.....	17
4.3 Detector functions.....	17
5 Connection of measuring equipment.....	18
5.1 General.....	18
5.2 Connection of ancillary equipment.....	18
5.3 Connections to RF reference ground.....	18
5.4 Connection between the EUT and the artificial mains network.....	19
6 General measurement requirements and conditions.....	20
6.1 General.....	20
6.2 Disturbance not produced by the equipment under test.....	20
6.2.1 General.....	20
6.2.2 Compliance testing.....	20
6.3 Measurement of continuous disturbance.....	20
6.3.1 Narrowband continuous disturbance.....	20
6.3.2 Broadband continuous disturbance.....	20
6.3.3 Use of spectrum analyzers and scanning receivers.....	21
6.4 EUT arrangement and measurement conditions.....	21
6.4.1 EUT arrangement.....	21
6.4.2 Normal load conditions.....	23
6.4.3 Duration of operation.....	23
6.4.4 Running-in/warm-up time.....	23
6.4.5 Supply.....	24
6.4.6 Mode of operation.....	24
6.4.7 Operation of multifunction equipment.....	24
6.4.8 Determination of EUT arrangement(s) that maximize(s) emissions.....	24
6.4.9 Recording of measurement results.....	24
6.5 Interpretation of measuring results.....	24
6.5.1 Continuous disturbance.....	24
6.5.2 Discontinuous disturbance.....	25
6.5.3 Measurement of the duration of disturbances.....	25
6.6 Measurement times and scan rates for continuous disturbance.....	25
6.6.1 General.....	25
6.6.2 Minimum measurement times.....	25
6.6.3 Scan rates for scanning receivers and spectrum analyzers.....	26
6.6.4 Scan times for stepping receivers.....	27
6.6.5 Strategies for obtaining a spectrum overview using the peak detector.....	28

	6.6.6	Timing considerations using FFT-based instruments.....	31
7		Measurement of disturbances conducted along leads, 9 kHz to 30 MHz .....	33
	7.1	General.....	33
	7.2	Measuring equipment (receivers, etc.) .....	33
	7.2.1	General .....	33
	7.2.2	Use of detectors for conducted disturbance measurements .....	33
	7.3	Ancillary measuring equipment .....	34
	7.3.1	General .....	34
	7.3.2	Artificial networks (ANs) .....	34
	7.3.3	Voltage probes .....	34
	7.3.4	Current probes .....	35
	7.4	Equipment under test configuration.....	35
	7.4.1	Arrangement of the EUT and its connection to the AN .....	35
	7.4.2	Procedure for the measurement of unsymmetric disturbance voltages with V-networks (AMNs) .....	40
	7.4.3	Measurement of common mode voltages at differential mode signal terminals .....	47
	7.4.4	Measurements using voltage probes.....	48
	7.4.5	Measurement using a capacitive voltage probe (CVP) .....	51
	7.4.6	Measurements using current probes .....	51
	7.5	System test configuration for conducted emissions measurements .....	51
	7.5.1	General approach to system measurements .....	51
	7.5.2	System configuration .....	52
	7.5.3	Measurements of interconnecting lines .....	54
	7.5.4	Decoupling of system components.....	55
	7.6	In situ measurements.....	55
	7.6.1	General .....	55
	7.6.2	Reference ground .....	55
	7.6.3	Measurement with voltage probes.....	56
	7.6.4	Selection of measuring points.....	56
8		Automated measurement of disturbances .....	56
	8.1	Precautions for automating measurements.....	56
	8.2	Generic measurement procedure .....	57
	8.3	Prescan measurements .....	57
	8.4	Data reduction .....	58
	8.5	Disturbance maximization and final measurement.....	58
	8.6	Post processing and reporting.....	59
	8.7	Disturbance measurement strategies with FFT-based measuring instruments .....	59
9		Test set-up and measurement procedure using the CDNE in the frequency range 30 MHz to 300 MHz .....	59
	9.1	General.....	59
	9.2	Test set-up .....	60
	9.3	Measurement procedure .....	62
Annex A (informative) Guidelines for connection of electrical equipment to the artificial mains network .....			63
	A.1	General.....	63
	A.2	Classification of the possible cases.....	63
	A.2.1	Well-shielded but poorly filtered EUT (Figures A.1 and A.2).....	63

A.2.2	Well-filtered but incompletely shielded EUT (Figures A.3 and A.4) .....	64
A.2.3	Practical general case .....	64
A.3	Method of grounding .....	66
A.4	Conditions of grounding .....	66
A.4.1	General .....	66
A.4.2	Classification of typical testing conditions .....	67
A.5	Connection of the AMN as a voltage probe .....	68
Annex B (informative)	Use of spectrum analyzers and scanning receivers .....	70
B.1	General.....	70
B.2	Overload.....	70
B.3	Linearity test.....	70
B.4	Selectivity.....	70
B.5	Normal response to pulses.....	70
B.6	Peak detection.....	70
B.7	Frequency scan rate .....	71
B.8	Signal interception.....	71
B.9	Average detection.....	71
B.10	Sensitivity .....	71
B.11	Amplitude accuracy.....	72
Annex C (informative)	Decision tree for use of detectors for conducted disturbance measurements .....	73
Annex D (informative)	Scan rates and measurement times for use with the average detector .....	75
D.1	General.....	75
D.2	Suppression of impulsive disturbance .....	75
D.2.1	General .....	75
D.2.2	Suppression of impulsive disturbance by digital averaging.....	76
D.3	Suppression of amplitude modulation.....	76
D.4	Measurement of slowly intermittent, unsteady or drifting narrowband disturbances .....	76
D.5	Recommended procedure for automated or semi-automated measurements .....	78
Annex E (informative)	Guidelines for the improvement of the test set-up with ANs .....	79
E.1	In situ verification of the AN impedance and voltage division factor.....	79
E.2	PE chokes and sheath current absorbers for the suppression of ground loops.....	82
Annex F (normative)	Determination of suitability of spectrum analyzers for compliance tests .....	84
Annex G (informative)	Basic guidance for measurements on telecommunications ports .....	85
G.1	Limits.....	85
G.2	Combination of current probe and capacitive voltage probe (CVP).....	86
G.3	Basic ideas of the capacitive voltage probe.....	86
G.4	Combination of current limit and voltage limit.....	87
G.5	Adjusting the TCM impedance with ferrites .....	89
G.6	Ferrite specifications for use with methods of Annex H .....	89
Annex H (normative)	Specific guidance for conducted disturbance measurements on telecommunication ports .....	92
H.1	General.....	92

H.2	Characteristics of AANs .....	93
H.3	Characteristics of current probe .....	94
H.4	Characteristics of capacitive voltage probe .....	94
H.5	Procedures for common mode measurements .....	94
H.5.1	General .....	94
H.5.2	Measurement procedure using AANs .....	94
H.5.3	Measurement procedure using a 150 Ω load connected to the outside surface of the cable screen .....	95
H.5.4	Measurement procedure using a combination of current probe and capacitive voltage probe .....	96
H.5.5	Measurement of cable, ferrite and AE common mode impedance .....	97
Annex I (informative)	Examples of AANs and ANs for screened cables .....	99
Bibliography	.....	108
Figure 1	– Example of a recommended test set-up with PE chokes with three AMNs and a sheath current absorber on the RF cable.....	19
Figure 2	– Measurement of a combination of a CW signal (“NB”) and an impulsive signal (“BB”) using multiple sweeps with maximum hold.....	28
Figure 3	– Example of a timing analysis.....	29
Figure 4	– A broadband spectrum measured with a stepped receiver.....	30
Figure 5	– Intermittent narrowband disturbances measured using fast short repetitive sweeps with maximum hold function to obtain an overview of the disturbance spectrum .....	30
Figure 6	– FFT scan in segments.....	32
Figure 7	– Frequency resolution enhanced by FFT-based measuring instrument .....	32
Figure 8	– Illustration of current $I_{CCM}$ .....	35
Figure 9	– Test configuration: table-top equipment for conducted disturbance measurements on power mains.....	37
Figure 10	– Arrangement of EUT and AMN at 40 cm distance, with a) vertical RGP and b) horizontal RGP .....	38
Figure 11	– Optional example test configuration for an EUT with only a power cord attached .....	38
Figure 12	– Test configuration: floor-standing equipment (see 7.4.1 and 7.5.2.3).....	39
Figure 13	– Example test configuration: floor-standing and table-top equipment (see 7.4.1 and 7.5.2.3) .....	40
Figure 14	– Schematic of disturbance voltage measurement configuration (see also 7.5.2.3).....	42
Figure 15	– Equivalent circuit for measurement of unsymmetric disturbance voltage for safety-class I (grounded) EUT.....	43
Figure 16	– Equivalent circuit for measurement of unsymmetric disturbance voltage for safety-class II (ungrounded) EUT .....	44
Figure 17	– RC element for artificial hand .....	46
Figure 18	– Portable electric drill with artificial hand .....	46
Figure 19	– Portable electric saw with artificial hand.....	46
Figure 20	– Measuring example for voltage probes .....	49
Figure 21	– Measurement arrangement for two-terminal regulating controls.....	50
Figure 22	– Generic process to help reduce measurement time .....	57
Figure 23	– Test set-up for measurement of an EUT with one cable.....	61

Figure 24 – Test set-up for measurement of an EUT with two cables connected adjacent surfaces of the EUT .....	61
Figure 25 – Test set-up for measurement of an EUT with two cables connected on the same surface of the EUT .....	62
Figure A.1 – Basic schematic of well-shielded but poorly filtered EUT .....	63
Figure A.2 – Detail of well-shielded but poorly filtered EUT .....	64
Figure A.3 – Well-filtered but incompletely shielded EUT .....	64
Figure A.4 – Well-filtered but incompletely shielded EUT, with $U_2$ reduced to zero .....	64
Figure A.5 – Disturbance supply through shielded conductors .....	65
Figure A.6 – Disturbance supply through unshielded but filtered conductors .....	65
Figure A.7 – Disturbance supply through ordinary conductors .....	66
Figure A.8 – AMN configurations .....	68
Figure C.1 – Decision tree for optimizing speed of conducted disturbance measurements with peak, quasi-peak and average detectors .....	73
Figure D.1 – Weighting function of a 10 ms pulse for peak (“PK”) and average detections with (“CISPR AV”) and without (“AV”) peak reading; meter time constant 160 ms .....	77
Figure D.2 – Weighting functions of a 10 ms pulse for peak (“PK”) and average detections with (“CISPR AV”) and without (“AV”) peak reading; meter time constant 100 ms .....	77
Figure D.3 – Example of weighting functions (of a 1 Hz pulse) for peak (“PK”) and average detections as a function of pulse width; meter time constant 160 ms .....	78
Figure D.4 – Example of weighting functions (of a 1 Hz pulse) for peak (“PK”) and average detections as a function of pulse width; meter time constant 100 ms .....	78
Figure E.1 – Parallel resonance of enclosure capacitance and ground strap inductance .....	79
Figure E.2 – Connection of an AMN to RGP using a wide grounding sheet for low inductance grounding .....	80
Figure E.3 – Impedance measured with the arrangement of Figure E.2 both with reference to the front panel ground and to the grounding sheet .....	80
Figure E.4 – VDF in the configuration of Figure E.2 measured with reference to the front panel ground and to the grounding sheet .....	80
Figure E.5 – Arrangement showing the measurement grounding sheet (shown with dotted lines) when measuring the impedance with reference to RGP .....	81
Figure E.6 – Impedance measured with the arrangement of Figure E.5 with reference to the RGP .....	81
Figure E.7 – VDF measured with parallel resonances in the AMN grounding .....	81
Figure E.8 – Attenuation of a sheath current absorber measured in a 150 $\Omega$ test arrangement .....	82
Figure E.9 – Arrangement for the measurement of attenuation due to PE chokes and sheath current absorbers .....	83
Figure G.1 – Basic circuit for considering the limits with a defined TCM impedance of 150 $\Omega$ .....	88
Figure G.2 – Basic circuit for the measurement with unknown TCM impedance .....	88
Figure G.3 – Impedance layout of the components used in Figure H.2 .....	90
Figure G.4 – Basic test set-up to measure combined impedance of the 150 $\Omega$ and ferrites .....	91
Figure H.1 – Measurement set-up using an AAN .....	95

Figure H.2 – Measurement set-up using a 150 $\Omega$ load to the outside surface of the shield.....	96
Figure H.3 – Measurement set-up using current and capacitive voltage probes.....	97
Figure H.4 – Characterization set-up.....	98
Figure I.1 – Example AAN for use with unscreened single balanced pairs.....	99
Figure I.2 – Example AAN with high LCL for use with either one or two unscreened balanced pairs.....	100
Figure I.3 – Example AAN with high LCL for use with one, two, three, or four unscreened balanced pairs.....	101
Figure I.4 – Example AAN, including a 50 $\Omega$ source matching network at the voltage measuring port, for use with two unscreened balanced pairs.....	102
Figure I.5 – Example AAN for use with two unscreened balanced pairs.....	103
Figure I.6 – Example AAN, including a 50 $\Omega$ source matching network at the voltage measuring port, for use with four unscreened balanced pairs.....	104
Figure I.7 – Example AAN for use with four unscreened balanced pairs.....	105
Figure I.8 – Example AN for use with coaxial cables, employing an internal common mode choke created by bifilar winding an insulated centre-conductor wire and an insulated screen-conductor wire on a common magnetic core (for example, a ferrite toroid).....	106
Figure I.9 – Example AN for use with coaxial cables, employing an internal common mode choke created by miniature coaxial cable (miniature semi-rigid solid copper screen or miniature double-braided screen coaxial cable) wound on ferrite toroids.....	106
Figure I.10 – Example AN for use with multi-conductor screened cables, employing an internal common mode choke created by bifilar winding multiple insulated signal wires and an insulated screen-conductor wire on a common magnetic core (for example, a ferrite toroid).....	107
Figure I.11 – Example AN for use with multi-conductor screened cables, employing an internal common mode choke created by winding a multi-conductor screened cable on ferrite toroids.....	107
Table 1 – Minimum scan times for the three CISPR bands with peak and quasi-peak detectors.....	26
Table 2 – Minimum measurement times for the four CISPR bands.....	26
Table A.2 – Testing conditions for types of EUTs – Screened cable.....	69
Table B.1 – Sweep time/frequency or fastest scan rate.....	71
Table D.1 – Pulse suppression factors and scan rates for a 100 Hz video bandwidth.....	76
Table D.2 – Meter time constants and the corresponding video bandwidths and maximum scan rates.....	77
Table F.1 – Maximum amplitude difference between peak and quasi-peak detected signals.....	84
Table G.1 – Summary of advantages and disadvantages of the methods described in the specific subclauses of Annex H.....	86
Table H.1 – Telecommunication port disturbance measurement procedure selection.....	92
Table H.2 – $a_{LCL}$ values.....	93