

**Kõrghoonetes kasutatavad tuletõrjeteenistuste teleskooppäästeseadmed. Kombineeritud liikumisega pöördredelid. Ohutus- ja toimivusnõuded ja katsemeetodid**

**High rise aerial appliances for fire and rescue service use - Turntable ladders with combined movements - Safety and performance requirements and test methods**

## EESTI STANDARDI EESSÕNA

## NATIONAL FOREWORD

See Eesti standard EVS-EN 14043:2014 sisaldab Euroopa standardi EN 14043:2014 inglisekeelset teksti.	This Estonian standard EVS-EN 14043:2014 consists of the English text of the European standard EN 14043:2014.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 15.01.2014.	Date of Availability of the European standard is 15.01.2014.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile [standardiosakond@evs.ee](mailto:standardiosakond@evs.ee).

ICS 13.220.10

### **Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele**

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:  
Aru 10, 10317 Tallinn, Eesti; [www.evs.ee](http://www.evs.ee); telefon 605 5050; e-post [info@evs.ee](mailto:info@evs.ee)

### **The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation**

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:  
Aru 10, 10317 Tallinn, Estonia; [www.evs.ee](http://www.evs.ee); phone 605 5050; e-mail [info@evs.ee](mailto:info@evs.ee)

English Version

## High rise aerial appliances for fire and rescue service use - Turntable ladders with combined movements - Safety and performance requirements and test methods

Moyens élévateurs aériens à l'usage des services de secours et de lutte contre l'incendie - Echelles pivotantes à mouvements combinés - Prescriptions de sécurité et de performance et méthodes d'essais

Hubrettungsfahrzeuge für die Feuerwehr - Drehleitern mit kombinierten Bewegungen (Automatik-Drehleitern) - Sicherheits- und Leistungsanforderungen sowie Prüfverfahren

This European Standard was approved by CEN on 26 October 2013.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels**

<b>Contents</b>	<b>Page</b>
Foreword.....	4
Introduction .....	7
<b>1 Scope .....</b>	<b>8</b>
<b>2 Normative references .....</b>	<b>8</b>
<b>3 Terms and definitions, symbols and abbreviated terms .....</b>	<b>9</b>
<b>4 List of significant hazards .....</b>	<b>17</b>
<b>5 Requirements .....</b>	<b>25</b>
5.1 Safety requirements and/or measures .....	25
5.1.1 General.....	25
5.1.2 Requirements in respect of stability.....	26
5.1.3 Requirements relating to the strength of the turntable ladder .....	38
5.1.4 Verification of vehicle performance by functional testing .....	39
5.1.5 Requirements relating to function .....	41
5.1.6 Requirements relating to noise .....	68
5.2 Performance requirements .....	69
5.2.1 Operational requirements .....	69
5.2.2 Requirements demanded by national regulations .....	70
5.2.3 Overall maximum dimensions.....	70
5.2.4 Maximum gross laden mass.....	71
5.2.5 Radio interference .....	71
<b>6 Designation .....</b>	<b>72</b>
<b>7 Information for use .....</b>	<b>72</b>
7.1 General.....	72
7.2 Instruction handbook .....	73
7.2.1 General.....	73
7.2.2 Operating instruction .....	73
7.2.3 Transport, handling and storage information.....	74
7.2.4 Information on commissioning .....	75
7.2.5 Machine details .....	75
7.2.6 Maximum loads in the rescue cage and/or on the ladder set .....	75
7.2.7 Maintenance information for use by trained personnel.....	75
7.2.8 Special working methods or conditions .....	76
7.2.9 Periodical examinations and tests.....	76
7.3 Marking .....	76
<b>Annex A (informative) Example of table recording the stability tests .....</b>	<b>79</b>
<b>Annex B (normative) Operating time.....</b>	<b>80</b>
<b>Annex C (informative) List of nominal reaches in several European countries applicable to turntable ladders.....</b>	<b>81</b>
<b>Annex D (informative) Verification and reception tests .....</b>	<b>83</b>
<b>Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2006/42/EC .....</b>	<b>87</b>
<b>Bibliography.....</b>	<b>88</b>

## Figures

Figure 1 — Example of boundary .....	13
Figure 2 — Jacking width .....	14
Figure 3 — Designation of ladder set sections .....	16
Figure 4 — Example of forces acting on turntable ladder .....	27
Figure 5 — Resulting force of the working load.....	28
Figure 6 — Surface exposed to the wind .....	29
Figure 7 — Minimum required residual force related to jacking width.....	31
Figure 8 — Maximum and minimum jacking width.....	32
Figure 11 — Static tilt angle $\delta$ for turntable ladders .....	45
Figure 12 — Maximum angle of elevation.....	47
Figure 13 — Relative positions of hand and guard-rails.....	49
Figure 14 — Impact simulation on the rescue cage .....	53
Figure 15 — Rung alignment.....	60
Figure 16 — Minimum dimensions of ladder sections .....	63
Figure 17 — Rung spacing dimensions.....	63
Figure 18 — Winding diameter.....	67
Figure 19 — Diagram of minimum unaffected zones .....	72
Figure 20 — Example of a warning label for the number of person permissible in the rescue cage.....	77
<b>Tables</b>	
Table 1 — List of significant hazards .....	17
Table 2 — Safety factors for load calculations .....	29
Table 3 — Test cases for verification method 2.....	34
Table 4 — Functional Safety and Performance Level.....	53
Table 5 — Functional requirements for ladder set main control console .....	55
Table 6 — Dimensions .....	62
Table 7 — Determination of factor $c$ .....	65
Table 8 — Determination of factor $h_1$ for the following construction unit.....	66
Table 9 — Determination of factor $h_2$ for the following construction unit.....	67
Table 10 — Nominal reaches.....	70
Table 11 — Overall maximum dimensions in travel position .....	70
Table 12 — Maximum gross laden mass .....	71
Table 13 — Masses taken into consideration in the calculation of gross laden mass .....	71
Table A.1 — Example of table recording the stability tests .....	79
Table B.1 — Determination of the operating time.....	80
Table C.1 — Nominal reaches of turntable ladders in several European countries.....	81
Table D.1— Verifications and reception tests .....	83

## Foreword

This document (EN 14043:2014) has been prepared by Technical Committee CEN/TC 192 "Fire and rescue service equipment", the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by July 2014, and conflicting national standards shall be withdrawn at the latest by July 2014.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 14043:2005+A1:2009.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EU Directive(s), see informative Annex ZA, which is an integral part of this document.

The significant changes with respect to the previous edition of EN 14043 are listed below:

- a) ladder class > 30 to 56 added;
- b) terms and definitions for turntable ladder with combined movements, rescue height, supported boundary, jacking width and load per person reworded, for dead man's device, working position and boundary added and for special boundary of use deleted;
- c) calculation of the working load and of diverse force revised;
- d) fatigue stress analysis completely revised;
- e) static stability revised and depends on the jacking width with defined residual forces;
- f) verification of static stability and dynamic stability revised;
- g) functional requirements revised;
- h) requirement for audible alarm at low battery voltage added;
- i) verification relating to the strength of the turntable ladder at the boundary of free-standing use with  $\alpha_{\max}$  revised;
- j) verification relating to the strength of the turntable ladder at the boundary of free-standing use (without or with rescue cage) deleted;
- k) verification relating to turntable ladders constructed to be operated only with the rear axle suspension fully or partially locked revised;
- l) requirement that loaded ladder shall maintain its position for 10 min with a variation less than 150 mm added;
- m) at least 100 mm difference at relative positions for the suspension locking device added;
- n) static tilt angle added;

- o) requirements on hand and guard-rails of the rescue cage revised and a requirement relating to aperture size added;
- p) requirements for anchoring points in the rescue cage for personal protective equipment against falling added;
- q) requirements relating to access doors and door locking devices in the rescue cage fully revised;
- r) requirements and verification revised relating to attachment systems for turntable ladders with a removable rescue cage;
- s) working light requirements revised;
- t) safety related parts of the control system according to category 1 or 2 of EN 954-1 changed to performance level (PL) according to EN ISO 13849-1;
- u) general normative reference to CEN/TS 15989 for the symbols on the control console added and all figures and tables with symbols deleted;
- v) requirements for the main control console added, that movement via the control lever of the rescue cage control console shall only take place after unlocking the emergency stop control in the rescue cage;
- w) indicator (e. g. display) to show the actual values of ladder length, ladder extension and elevation angle together with the maximum achievable values added;
- x) requirement revised relating to access from the ground to the ladder set (either directly (e.g. access ladder) or indirectly (e.g. deck));
- y) voice communication revised;
- z) rung alignment revised;
- aa) requirement revised relating to transmission systems (safety factors) and cable drums (grooves or devices preventing the cable running off the drum);
- bb) safety requirements related to electromagnetic phenomena and requirements relating to noise revised;
- cc) recommendation to use dependability management systems added;
- dd) precision of designation;
- ee) instruction handbook revised;
- ff) list of all known nominal reaches in several European countries applicable to turntable ladders in Annex C added;
- gg) list of verification and reception tests in Annex D with short description of requirement/test added;
- hh) Annex ZA deleted relating to the relationship between this European Standard and the Essential Requirements of the replaced EU Directive 98/37/EC;
- ii) Normative references revised: withdrawn standards EN 418, EN 457, EN 954-1, EN 982, EN 1050, EN ISO 12100-1:2003, EN ISO 12100-2:2003 have been deleted; CEN/TS 15989, EN ISO 4413, EN ISO 7731, EN ISO 12100:2010, EN ISO 13849-1, EN ISO 13850 have been added, and EN 1846 (all parts) as well as EN 60204-1 have been updated regarding dated reference;
- jj) Bibliography revised;

kk) content of standard editorially revised.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

This document is a preview generated by EVS

## Introduction

This European Standard is a type C standard as stated in EN ISO 12100.

The machinery concerned and the extent to which hazards, hazardous situations and events are covered are indicated in the scope of this European Standard.

When provisions of this type C standard are different from those which are stated in type A or B standards, the provisions of this type C standard take precedence over the provisions of the other standards, for machines that have been designed and built according to the provisions of this type C standard.

This document is a preview generated by EVS

## 1 Scope

**1.1** This European Standard specifies the safety and performance requirements and test methods applicable to turntable ladders with combined movements of classes 18, 24, 30 and > 30 to 56, as defined in 3.13, under the control of fire-fighters and intended for fire fighting and rescuing people.

NOTE This European Standard is intended to be used in conjunction with EN 1846–1, EN 1846–2 and EN 1846–3.

Turntable ladder vehicles comprise a chassis, bodywork and a powered extending structure unit in the form of a ladder with or without a rescue cage.

Turntable ladder vehicles covered by this European Standard have a self-propelled chassis, the motor of which supplies the power necessary for the operation of the ladder and permits all of the operational movements to be made simultaneously, with no restriction on the angle of the slewing movement.

**1.2** This European Standard deals with the technical safety requirements to minimize the hazards listed in Clause 4 which can arise during commissioning, operational use, routine checking and maintenance of turntable ladders when carried out in accordance with the specifications given by the manufacturer or the manufacturer's authorized representative.

**1.3** This European Standard deals with the use of turntable ladder vehicles within an ambient temperature range from  $-15\text{ °C}$  to  $+35\text{ °C}$  and with a wind velocity on the ladder set  $\leq 12,5\text{ m/s}$ . Additional measures can be necessary for use outside this range. Special designs for use under special climatic conditions should be agreed between the manufacturer and the purchaser. Any additional requirements are outside the scope of the standard.

**1.4** This European Standard does not deal with the design of a standard automotive chassis with regard to hazards resulting from or due to use as a road vehicle.

**1.5** This European Standard is not applicable to turntable ladder vehicles with combined movements which are manufactured before the date of publication of this European Standard by CEN.

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1846-1, *Firefighting and rescue service vehicles - Part 1: Nomenclature and designation*

EN 1846-2:2009+A1:2013, *Firefighting and rescue service vehicles - Part 2: Common requirements - Safety and performance*

EN 1846-3, *Firefighting and rescue service vehicles - Part 3: Permanently installed equipment - Safety and performance*

CEN/TS 15989, *Firefighting vehicles and equipment - Symbols for operator controls and other displays*

EN 60204-1:2006, *Safety of machinery - Electrical equipment of machines - Part 1: General requirements (IEC 60204-1:2005, modified)*

EN 60529, *Degrees of protection provided by enclosures (IP Code) (IEC 60529)*

EN 61310-1, *Safety of machinery - Indication, marking and actuation - Part 1: Requirements for visual, acoustic and tactile signals (IEC 61310-1)*

EN ISO 4413, *Hydraulic fluid power - General rules and safety requirements for systems and their components (ISO 4413)*

EN ISO 7731, *Ergonomics - Danger signals for public and work areas - Auditory danger signals (ISO 7731)*

EN ISO 12100:2010, *Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)*

EN ISO 13849-1, *Safety of machinery - Safety-related parts of control systems - Part 1: General principles for design (ISO 13849-1)*

EN ISO 13850:2008, *Safety of machinery - Emergency stop - Principles for design (ISO 13850:2006)*

### 3 Terms and definitions, symbols and abbreviated terms

For the purposes of this document, the terms and definitions given in EN ISO 12100, EN 1846-1, EN 1846-2 and the following apply.

#### 3.1

##### **turntable ladder with combined movements**

machine with an extending structure in the form of a ladder set mounted on a self-propelled chassis with no restriction on the angle of the slewing movement, where the chassis engine supplies the power necessary for operation and where at least the raising/lowering, extending/retracting and the slewing right/left are simultaneously feasible under the continuous control of the operator

#### 3.2

##### **turntable ladder equipment**

entire assembly of the mobile components mounted on the chassis which can carry at its upper extent, fixed or removable rescue equipment

Note 1 to entry: The jacking system is part of the turntable ladder equipment.

#### 3.3

##### **ladder set**

part of turntable ladder comprising several ladder sections which are connected together so as to extend telescopically

#### 3.4

##### **extended ladder set length**

$L$

distance between the extreme points of the extended ladder

Note 1 to entry: The length is expressed in metres.

#### 3.5

##### **rescue cage**

fixed or removable complementary device principally used for firefighting, rescuing people and other operational services

#### 3.6

##### **angle of elevation**

$\alpha$

angle between the longitudinal axis of the last (downmost) ladder section and the horizontal

Note 1 to entry: The angle is expressed in degrees.