

Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-6: Radio disturbance and immunity measuring apparatus - EMC antenna calibration

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 55016-1-6:2015 sisaldab Euroopa standardi EN 55016-1-6:2015 ingliskeelset teksti.	This Estonian standard EVS-EN 55016-1-6:2015 consists of the English text of the European standard EN 55016-1-6:2015.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 06.02.2015.	Date of Availability of the European standard is 06.02.2015.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 33.100.10, 33.100.20

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:

Aru 10, 10317 Tallinn, Eesti; koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Aru 10, 10317 Tallinn, Estonia; homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

ICS 33.100.10; 33.100.20

English Version

Specification for radio disturbance and immunity measuring
apparatus and methods -
Part 1-6: Radio disturbance and immunity measuring apparatus -
EMC antenna calibration
(CISPR 16-1-6:2014)

Spécifications des méthodes et des appareils de mesure
des perturbations radioélectriques et de l'immunité aux
perturbations radioélectriques -
Partie 1-6: Appareils de mesure des perturbations
radioélectriques et de l'immunité aux perturbations
radioélectriques - Étalonnage des antennes CEM
(CISPR 16-1-6:2014)

Anforderungen an Geräte und Einrichtungen sowie
Festlegung der Verfahren zur Messung der hochfrequenten
Störaussendung (Funkstörungen) und Störfestigkeit -
Teil 1-6: Geräte und Einrichtungen zur Messung der
hochfrequenten Störaussendung (Funkstörungen) und
Störfestigkeit - Kalibrierung von Antennen für EMV-
Messungen
(CISPR 16-1-6:2014)

This European Standard was approved by CENELEC on 2015-01-21. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword

The text of document CISPR/A/1087/FDIS, future edition 1 of CISPR 16-1-6, prepared by CISPR SC A "Radiointerference measurements and statistical methods" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 55016-1-6:2015.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2015-10-21
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2018-01-21

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard CISPR 16-1-6:2014 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

CISPR 16-1-1:2010	NOTE	Harmonized as EN 55016-1-1:2010 (not modified).
CISPR 16-2-3:2010	NOTE	Harmonized as EN 55016-2-3:2010 (not modified).
CISPR 16-4-2:2011	NOTE	Harmonized as EN 55016-4-2:2011 (not modified).
CISPR 25:2008	NOTE	Harmonized as EN 55025:2008 (not modified).
IEC 61000-4-22:2010	NOTE	Harmonized as EN 61000-4-22:2010 (not modified).
IEC 61169-16:2006	NOTE	Harmonized as EN 61169-16:2007 (not modified).
ISO/IEC 17043:2010	NOTE	Harmonized as EN ISO/IEC 17043:2010 (not modified).

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
CISPR 16-1-4	2010	Specification for radio disturbance and immunity measuring apparatus and methods -	EN 55016-1-4	2010
+A1	2012	Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements	+A1	2012
CISPR 16-1-5	2014	Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-5: Radio disturbance and immunity measuring apparatus - Antenna calibration sites and reference test sites for 5 MHz to 18 GHz	EN 55016-1-5	2015
IEC 60050-161	-	International Electrotechnical Vocabulary (IEV) - Chapter 161: Electromagnetic compatibility	-	-
ISO/IEC Guide 98-3 2008		Uncertainty of measurement - Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)	-	-

CONTENTS

FOREWORD.....	10
1 Scope.....	12
2 Normative references	12
3 Terms, definitions and abbreviations	13
3.1 Terms and definitions.....	13
3.1.1 Antenna terms	13
3.1.2 Antenna factor terms	16
3.1.3 Measurement site terms	17
3.1.4 Other terms	18
3.2 Abbreviations.....	19
4 Fundamental concepts.....	20
4.1 General.....	20
4.2 The concept of antenna factor.....	20
4.3 Calibration methods for 30 MHz and above.....	21
4.3.1 General	21
4.3.2 Antenna minimum separation distances	21
4.3.3 General considerations for the TAM.....	21
4.3.4 General considerations for the SSM.....	21
4.3.5 General considerations for the SAM.....	22
4.4 Measurement uncertainties for antenna calibration measurement results	22
4.5 Summary of methods of measurement to obtain AF	23
5 Calibration methods for the frequency range 9 kHz to 30 MHz.....	25
5.1 Calibration of monopole antennas.....	25
5.1.1 General	25
5.1.2 Calibration by the ECSM.....	26
5.2 Calibration of loop antennas	32
5.2.1 General	32
5.2.2 TEM (Crawford) cell method	32
6 Frequencies, equipment and functional checks for calibrations at or above 30 MHz.....	35
6.1 Calibration frequencies	35
6.1.1 Calibration frequency ranges and increments	35
6.1.2 Transition frequency for hybrid antennas	36
6.2 Measurement instrumentation requirements for antenna calibrations	37
6.2.1 Equipment types.....	37
6.2.2 Mismatch.....	38
6.2.3 Dynamic range and reproducibility of SIL measurement.....	40
6.2.4 Signal-to-noise ratio	40
6.2.5 Antenna masts and cables.....	41
6.3 Functional checks of an AUC	41
6.3.1 General	41
6.3.2 Balance of an antenna.....	41
6.3.3 Cross-polar performance of an antenna.....	41
6.3.4 Radiation patterns of an antenna	42
7 Basic parameters and equations common to antenna calibration methods for frequencies above 30 MHz	43
7.1 Summary of methods for measurements to obtain AF	43

7.2	Site insertion loss measurements.....	43
7.2.1	General	43
7.2.2	SIL and SA measurement procedure.....	43
7.2.3	Common uncertainty components of a SIL measurement.....	44
7.3	Basic equations for the calculation of AF from SIL and SA measurements	46
7.3.1	Antenna factor from SIL measurements	46
7.3.2	Relationship of AF and SIL for a free-space calibration site	46
7.3.3	Relationship of AF and SIL for a calibration site with a metal ground plane	47
7.4	Equations for AF and measurement uncertainties using the TAM, SSM, and SAM.....	48
7.4.1	TAM	48
7.4.2	SSM	53
7.4.3	SAM	55
7.5	Parameters for specifying antenna phase centre and position	57
7.5.1	General	57
7.5.2	Reference position and phase centres of LPDA and hybrid antennas.....	58
7.5.3	Phase centres of horn antennas	61
8	Details for TAM, SAM, and SSM calibration methods for frequencies of 30 MHz and above	63
8.1	General.....	63
8.2	Considerations for F_a calibrations using TAM	63
8.2.1	General considerations	63
8.2.2	Calibration site and antenna set-up considerations for use with the TAM	63
8.2.3	Antenna parameters for a free-space environment or a ground plane site	65
8.2.4	Validation of calibration method.....	66
8.3	Considerations for F_a calibrations using the SAM	66
8.3.1	General considerations and calibration site for use of the SAM.....	66
8.3.2	Calibration procedures and antenna set-ups for F_a by the SAM.....	67
8.3.3	Parameters of the STA	67
8.4	SSM calibrations at a ground-plane site, 30 MHz to 1 GHz	68
8.4.1	General considerations and calibration site for SSM	68
8.4.2	Calibration procedure for SSM.....	69
8.4.3	Calculation of F_a	69
8.4.4	Uncertainties of F_a obtained using SSM	70
9	Calibration procedures for specific antenna types for frequencies of 30 MHz and above	71
9.1	General.....	71
9.2	Calibrations for biconical and hybrid antennas in a free-space environment for 30 MHz to 300 MHz, and tuned dipoles for 60 MHz to 1 000 MHz	71
9.2.1	General considerations and calibration site requirements	71
9.2.2	Calibration procedure and antenna set-up for use with the SAM	71
9.2.3	Uncertainties of F_a determined by the SAM	72
9.2.4	Antenna set-up for use with the TAM (alternative)	74
9.3	Calibration of biconical (30 MHz to 300 MHz) and hybrid antennas, using the SAM and VP at a ground plane site.....	74
9.3.1	General considerations and calibration site requirements	74
9.3.2	Calibration procedure and antenna set-up	75
9.3.3	Uncertainties of F_a determined with the SAM.....	76

9.4	Calibration of LPDA, hybrid, and horn antennas in a free-space environment, 200 MHz to 18 GHz.....	77
9.4.1	General considerations and calibration site for a free-space environment.....	77
9.4.2	Calibrations using the TAM.....	79
9.4.3	Antenna set-up for use with the SAM.....	80
9.4.4	Alternative antenna set-up for site with absorber on the ground.....	80
9.5	Calibration of horn and LPDA antennas in a FAR, 1 GHz to 18 GHz.....	81
9.5.1	Calibration using the TAM.....	81
9.5.2	Calibration and antenna set-up for the SAM.....	84
Annex A (informative) Background information and rationale for the methods of antenna calibration.....		85
A.1	Rationale for the need for several calibration methods and for use of a ground plane site.....	85
A.2	Special measures for calibration of omnidirectional antennas.....	86
A.2.1	General.....	86
A.2.2	Difficulties with calibration of omnidirectional antennas.....	87
A.2.3	Minimizing reflections from antenna supports and radiation from cables.....	87
A.2.4	Field taper and monocone set-up for VP biconical calibration.....	88
A.2.5	Use of HP or VP in a FAR.....	89
A.2.6	Substitution where the STA is the same model as the AUC.....	89
A.3	Calibrations using broadband calculable dipole antennas.....	89
A.3.1	Disadvantages of tuned dipole antennas.....	89
A.3.2	Advantages of broadband calculable dipole antennas.....	90
A.3.3	Disadvantages of calculable dipole antennas.....	90
A.4	Rationale for F_a and biconical/LPDA antenna cross-over frequency.....	90
A.4.1	Rationale for F_a	90
A.4.2	Cross-over frequency from biconical to LPDA antennas.....	91
A.4.3	Biconical element designs.....	91
A.5	Sources of increased uncertainty in measurement of F_a by the SSM.....	92
A.6	Calibration of LPDA antennas using smaller separation distances.....	94
A.6.1	Calibration of LPDA antennas using smaller separation distances.....	94
A.6.2	Correction of electric field strength to account for phase centre of LPDA antennas.....	95
A.7	Cross-polar discrimination of LPDA antennas.....	96
A.8	Tips for measurement instrumentation.....	97
A.8.1	Signal-to-noise ratio.....	97
A.8.2	Connector pin depth.....	99
A.8.3	Effect of added adaptor in a “cable-through” measurement.....	99
A.8.4	Compression level.....	100
A.8.5	Source power slope function above 6 GHz.....	100
A.8.6	Frequency increment for detection of resonances.....	100
A.8.7	Return loss or VSWR.....	100
A.9	Uncertainty considerations.....	101
A.9.1	General.....	101
A.9.2	Achievable uncertainties for F_a	101
A.9.3	Uncertainties of dipoles above a ground plane.....	101
A.9.4	Verification of uncertainty by comparison of methods.....	102
Annex B (normative) Calibration of biconical antennas and tuned dipole antennas above a ground plane using the TAM and the SAM.....		103

B.1	General.....	103
B.2	Characteristics of biconical antennas and dipole antennas.....	103
B.3	Frequencies.....	103
B.4	Measurement of $F_a(h,p)$ of biconical and tuned dipole antennas and derivation of F_a by averaging $F_a(h,p)$, 30 MHz to 300 MHz.....	104
B.4.1	General.....	104
B.4.2	Measurement of $F_a(h,H)$ by the SAM and derivation of F_a	104
B.4.3	Measurement of $F_a(h,H)$ by the TAM and derivation of F_a	107
B.5	Measurement of F_a of tuned dipoles placed high above a ground plane in the frequency range 30 MHz to 1 000 MHz.....	109
B.5.1	General.....	109
B.5.2	Measurement of F_a by the SAM.....	109
B.5.3	Measurement of F_a by the TAM.....	111
Annex C (informative) Rationale for the equations used in antenna calibration and relevant information about antenna characteristics for uncertainty analysis in the frequency range 30 MHz to 1 GHz.....		113
C.1	General.....	113
C.2	Antenna factor and antenna gain.....	113
C.2.1	Relationship between AF and gain for antennas in a free-space environment.....	113
C.2.2	Relationship between AF and gain for monopole antennas on a large ground plane.....	115
C.3	Equations for the insertion loss between antennas.....	115
C.3.1	Site insertion loss measured at a free-space calibration site.....	115
C.3.2	Site insertion loss measured at a metal ground plane site.....	117
C.3.3	Site attenuation measured at a metal ground plane site.....	119
C.4	Uncertainty contribution caused by near-field effects.....	120
C.5	Uncertainty contribution due to the antenna proximity coupling.....	121
C.6	Uncertainty contribution due to the ground plane reflection.....	123
C.6.1	Coupling to image in ground plane.....	123
C.6.2	Correction factors $\Delta F_{a,SSM}$ for F_a of biconical antenna.....	127
C.7	Uncertainty contribution due to the antenna radiation pattern.....	128
C.7.1	General.....	128
C.7.2	Biconical antennas.....	129
C.7.3	LPDA antennas.....	129
C.7.4	Hybrid antennas.....	130
C.7.5	Horn and LPDA antennas from 1 GHz to 18 GHz.....	131
Annex D (informative) Background information and rationale for calibration of antennas at frequencies above 1 GHz.....		134
D.1	Mismatch uncertainty.....	134
D.2	Mutual coupling between antennas and chamber reflection.....	134
D.3	Antenna separation distance and phase centre.....	134
D.4	Example gain of DRH at 1 m distance.....	136
Annex E (informative) Notes for measurement uncertainty budgets.....		138
E.1	General.....	138
E.2	Notes for measurement uncertainty budgets.....	138
Annex F (informative) Mismatch uncertainties from a two-port device connected between a transmit port and a receive port.....		147
Annex G (informative) Verification method for calibration of monopole antennas and uncertainty analysis of the ECSM.....		149

G.1	Verification method for calibration of monopole antennas by the plane wave method from 5 MHz to 30 MHz.....	149
G.1.1	Calibration procedure	149
G.1.2	Uncertainty evaluation for the calibration of monopole antennas by the plane wave method.....	150
G.2	Uncertainty analysis of the ECSM	150
G.2.1	Effect of rod length longer than $\lambda/8$	150
G.2.2	Effect on AF of monopole antenna mounted on a tripod	152
G.2.3	Monopole antenna receiving an electric field	153
G.2.4	Equivalent capacitance substitution method (ECSM)	153
G.2.5	Uncertainties associated with the ECSM.....	155
G.2.6	An alternative to the dummy antenna, for which $F_{ac} = V_D - V_L$	157
Annex H (informative)	Helmholtz coil method for calibration of loop antennas up to 150 kHz	158
H.1	Measurement procedure	158
H.2	Uncertainties.....	160
Bibliography	162
Figure 1	– Set-up for AF determination using a network analyzer.....	29
Figure 2	– Set-up for AF determination using a measuring receiver and signal generator	29
Figure 3	– Example of mounting a capacitor in the dummy antenna	30
Figure 4	– Block diagram of TEM cell set-up for passive loop antennas	34
Figure 5	– Block diagram of TEM cell set-up for active loop antennas	34
Figure 6	– Example of resonant spike due to poor biconical element connections, using 2 MHz increment.....	36
Figure 7	– Antenna set-up for SIL measurement at a free-space calibration site	44
Figure 8	– Antenna set-up for SIL and SA measurement at a ground-plane calibration site ..	44
Figure 9	– Antenna set-up for the TAM at a free-space calibration site	49
Figure 10	– Antenna set-up for the TAM at a calibration site with a metal ground plane	52
Figure 11	– Antenna set-up for the SSM	54
Figure 12	– Antenna set-up for the SAM at a calibration site with a metal ground plane	56
Figure 13	– Separation distance relative to the phase centre of an LPDA antenna	59
Figure 14	– LPDA antenna with a tapered curved geometry	61
Figure 15	– Separation distance with respect to the phase centre of horn antennas (see [49] for details).....	62
Figure 16	– Schematic of a DRH showing relative locations of field point and phase centre of the DRH	63
Figure 17	– Biconical antenna set-up for SAM using vertical polarization, showing the paired monocone antenna and an example collapsible-element biconical AUC	76
Figure 18	– Test set-up for the calibration of LPDA and hybrid antennas positioned at a large height.....	79
Figure 19	– Set-up for LPDA antennas above absorber.....	81
Figure 20	– Set-up for transmission measurements using a network analyzer	82
Figure A.1	– Illustration of the angles of the electromagnetic rays subtended from the scanned LPDA antenna to the fixed height LPDA antenna and to the ground plane	93
Figure A.2	– F_a of biconical antenna with 200 Ω balun measured by the VP method of 9.3, and by the SSM method of 8.4 without correction.....	94

Figure A.3 – F_a of biconical antenna with 200 Ω balun measured by the VP method of 9.3, and by the SSM method of 8.4 with correction	94
Figure A.4 – Separation distance relative to the phase centre of an LPDA antenna.....	96
Figure A.5 – Statistical properties of multiple S_{21} sweeps (minimum, maximum, and mean value).....	98
Figure A.6 – Standard deviation of S_{21}	98
Figure A.7 – Normalized standard deviation of S_{21}	99
Figure C.1 – Simplified model of a receive antenna	114
Figure C.2 – Insertion loss measurement for antenna calibration at a free-space calibration site	116
Figure C.3 – Insertion loss measurement for antenna calibration at a calibration site with a metal ground plane.....	118
Figure C.4 – Comparison of field strength given by Equation (C.17) versus in near-field region given by Equation (C.31).....	121
Figure C.5 – Theoretical calculations of proximity coupling effects on the AF from the TAM (free-space conditions)	123
Figure C.6 – Deviation of AF from free-space value, F_a , caused by mutual coupling to the image in a metal ground plane (theoretical results).....	124
Figure C.7 – Variation of $F_a(h,H)$ of biconical antenna with 50 Ω balun, 30 MHz to 320 MHz at heights every 0,5 m above a ground plane from 1 m to 4 m.....	125
Figure C.8 – AF of Figure C.7 normalized to free-space AF	125
Figure C.9 – Variation of $F_a(h,H)$ of biconical antenna with 200 Ω balun, 30 MHz to 320 MHz at heights every 0,5 m above a ground plane from 1 m to 4 m.....	126
Figure C.10 – Diagram of one triangular section of a biconical antenna element.....	128
Figure C.11 – Examples of radiation patterns (relative realized gain) of two example biconical antennas compared to ideal half-wave tuned dipole antenna.....	129
Figure C.12 – Examples of radiation patterns (relative realized gain) of three example LPDA antennas, compared to ideal half-wave tuned dipole antenna.....	130
Figure C.13 – Examples of radiation patterns (relative realized gain) of an example hybrid antenna, compared to ideal half-wave tuned dipole antenna.....	131
Figure C.14 – Example radiation patterns for classical DRH antenna.....	132
Figure C.15 – Example radiation patterns for novel DRH antenna.....	132
Figure C.16 – Example radiation patterns for classical LPDA antenna	133
Figure C.17 – Example radiation patterns for V-type LPDA antenna.....	133
Figure D.1 – Relative phase centres of a DRH antenna and an LPDA antenna	135
Figure D.2 – A transmission system between a horn antenna and an LPDA antenna	136
Figure D.3 – Measured AFs of a DRH antenna at 4,5 GHz.....	136
Figure D.4 – Graph showing the realized gain at 1 m for a DRH antenna	137
Figure E.1 – Comparison of measured and predicted SIL for calculable dipole antenna – 60 MHz element.....	141
Figure E.2 – Comparison of measured and predicted SIL for calculable dipole antenna – 180 MHz element.....	141
Figure E.3 – Reflectivity of chamber absorbing materials	145
Figure E.4 – Laser alignment system	146
Figure F.1 – Flow graph representation of a two-port device between a transmit port and a receiver port.....	147
Figure F.2 – Signal flow reduction.....	147

Figure G.1 – Diagram showing how the brass rod connects to the type N male bulkhead connector.....	150
Figure G.2 – Graph of the magnitude of the tan(...) ratio term in Equation (4) of 5.1.2.2	151
Figure G.3 – Graphical presentation of Equation (4) of 5.1.2.2 self-capacitance C_a of a 1 m monopole	151
Figure G.4 – Graphical presentation of Equation (5) of 5.1.2.2 height correction factor L_h ..	152
Figure G.5 – Calibration set-up consisting of a biconical and a loop antenna, and an elevated monopole antenna with vertical feed wires.....	153
Figure G.6 – Equivalent circuit representation for a monopole antenna system	153
Figure G.7 – Monopole antenna calibration using the ECSM.....	154
Figure G.8 – Equivalent circuit representation for the ECSM	154
Figure G.9 – Simplified circuit representation for Figure G.8	155
Figure G.10 – Circuit for dummy antenna simulating the effects of the antenna effective height, h_e	157
Figure H.1 – Diagram of Helmholtz coil method set-up.....	158
Figure H.2 – Variation of H/I across the central plane between the coils	160
Table 1 – Summary of calibration methods above 30 MHz for F_a	24
Table 2 – Calibration methods above 30 MHz by subclause number	25
Table 3 – Frequency increments for monopole antenna calibration	26
Table 4 – Example measurement uncertainty budget for F_{ac} of a monopole antenna calibrated by the ECSM using Equation (9)	32
Table 5 –Example measurement uncertainty budget for F_{aH} of a loop antenna measured in a TEM cell	35
Table 6 – Frequency increments for broadband antenna calibration.....	35
Table 7 – Example measurement uncertainty budget for common components of a SIL measurement result evaluated from Equation (20)	46
Table 8 – Parameters used to determine phase centres of segments A and B.....	61
Table 9 – Example measurement uncertainty budget for F_a of a horizontally-polarized biconical antenna measured by the SSM.....	70
Table 10 – Example measurement uncertainty budget for F_a of a biconical antenna measured by the SAM in a FAR over the frequency range 30 MHz to 300 MHz	73
Table 11 – Example measurement uncertainty budget for F_a of a tuned dipole antenna obtained by the SAM in a FAR at a free-space calibration site, using a calculable tuned dipole as the STA in the frequency range above 60 MHz	74
Table 12 – Example measurement uncertainty budget for F_a of a biconical antenna measured using the SAM for vertical polarization over the frequency range 30 MHz to 300 MHz	77
Table 13 – Example measurement uncertainty budget for F_a of LPDA and hybrid antennas measured by the TAM at 4 m height for the frequency range 200 MHz to 3 GHz	80
Table 14 – Example measurement uncertainty budget for F_a of a horn antenna measured by the TAM above 1 GHz for 3 m separation in free space.....	84
Table A.1 – Example type N male and female connector pin depths and tolerances using a type N pin-depth gauge	99
Table A.2 – Typical type N adaptor characteristics.....	100
Table B.1 – Antenna set-up for the SAM for tuned dipole antennas with averaging of $F_a(h,H)$	104

Table B.2 – Antenna set-up for the SAM for biconical antennas with averaging of $F_a(h,H)$	105
Table B.3 – Example measurement uncertainty budget for $F_a(h,H)$ of a biconical antenna measured by the SAM over the frequency range 30 MHz to 300 MHz	105
Table B.4 – Example measurement uncertainty budget for F_a of a biconical antenna obtained by the SAM with averaging of $F_a(h,H)$ in the frequency range below 300 MHz	107
Table B.5 – Example measurement uncertainty budget for $F_a(h,H)$ of a biconical antenna obtained by the TAM with the antenna set-up specified in Table B.2.....	108
Table B.6 – Example measurement uncertainty budget for F_a of a biconical antenna obtained by the TAM with averaging of $F_a(h,H)$ in the frequency range below 300 MHz	108
Table B.7 – Antenna set-ups for the SAM for determining F_a of tuned dipole antennas at specific frequencies in the range 30 MHz to 1 000 MHz	110
Table B.8 – Example measurement uncertainty budget for F_a of a tuned dipole antenna obtained by the SAM using the antenna set-ups specified in Table B.7	111
Table B.9 – Example measurement uncertainty budget for F_a of a tuned dipole antenna obtained by the TAM using the antenna set-ups specified in Table B.7	112
Table C.1 – Examples of the antenna height range h for horizontal polarization for an error $\leq 0,3$ dB	126
Table C.2 – Correction factors $\Delta F_{a,SSM}$ to convert AF measured by SSM to F_a	127
Table C.3 – Mechanical dimensions for the biconical antenna [52].....	128
Table G.1 – Example measurement uncertainty budget for F_a of a monopole antenna measured by the SAM.....	150
Table H.1 – Example measurement uncertainty budget for F_{aH} of a loop antenna measured by the Helmholtz coil method for the frequency range 50 kHz to 150 kHz	161

view generated by EVS