

INTERNATIONAL
STANDARD

ISO
11786

First edition
1995-06-01

**Agricultural tractors and machinery —
Tractor-mounted sensor interface —
Specifications**

Tracteurs et matériels agricoles — Interface des capteurs montés sur le tracteur — Spécifications



Reference number
ISO 11786:1995(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 11786 was prepared by Technical Committee ISO/TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 19, *Agricultural electronics*.

This document is a preview generated by EVS

© ISO 1995

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Agricultural tractors and machinery — Tractor-mounted sensor interface — Specifications

1 Scope

This International Standard specifies an electrical connector and its pin layout for mounting on an agricultural tractor with a nominal 12-volt battery supply for the purpose of providing an interface between tractor-mounted sensors and equipment requiring signals from those sensors. The connector also provides access to a low-current power source to provide power primarily to instrumentation.

This International Standard therefore provides a short-term solution to data communication between a restricted set of tractor-mounted sensors and other equipment such as monitors, actuators and control systems on agricultural tractors and attached machinery, in anticipation of the availability of a standardized digital data bus system.

It allows limited data communication facilities for lower specification tractors not fitted with a digital data bus system.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

DIN 405-1:1975, *Knuckle thread: profiles, basic sizes, general plan.*

DIN 405-2:1981, *Knuckle thread: deviations and tolerances.*

3 Definitions

For the purposes of this International Standard, the following definitions apply.

3.1 ground speed signal: Actual forward speed of the tractor.

3.2 theoretical ground speed signal: Product of tractor drive wheel rotational speed and the rolling wheel circumference.

NOTE 1 This is the true ground speed where there is no wheel slip. The rolling circumference is defined in ISO 11785, *Agricultural tractor drive wheel tyres — Methods of measuring tyre rolling circumference.*

3.3 linkage position signal: Position of the tractor three-point linkage in the vertical plane between its lowest and highest points.

3.4 in-work/out-of-work signal: Binary status signal indicating that the three-point linkage is situated below (in-work) or above (out-of-work) an adjustable switching threshold.

3.5 CMOS: Complementary Metal-Oxide Semiconductor.

4 Connector

4.1 Dimensions

The connector shall have the dimensions shown in figure 1.