
Aircraft — Hydraulic tubing joints and fittings — Rotary flexure test

Aéronautique — Joints et raccords pour tubes hydrauliques — Essai de flexion rotative

This document is a preview generated by EMS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Requirements	1
2.1 Flexure test device.....	1
2.2 Flexure test specimen.....	1
2.3 Specimen length and deflection requirements.....	7
2.3.1 Specimen length.....	7
2.3.2 Stress determination.....	7
2.3.3 Deflection.....	7
2.4 Method of classification of fittings according to <i>S/N</i> flexure performance.....	7
2.5 Method of determining deflection/fatigue strength.....	7
3 Procedure	8
3.1 Preparation for test.....	8
3.1.1 Instrumentation, strain gauges.....	8
3.1.2 Rotary flexure test set-up centring.....	8
3.1.3 Flexure stress measurement.....	9
3.1.4 Flexure deflection measurement.....	9
3.1.5 Operating pressure.....	9
3.2 <i>S/N</i> testing.....	9
3.3 Deflection/fatigue testing.....	10
4 Formula	10
5 Equipment	10
Bibliography	12

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/TC 20, *Aircraft and space vehicles*, Subcommittee SC 10, *Aerospace fluid systems and components*.

This second edition cancels and replaces the first edition (ISO 7257:1983), which has been technically revised to add imperial unit equivalents, three DN sizes, and for additional clarifications.

Introduction

This International Standard describes a flexure fatigue test procedure which allows evaluation of various tube fitting designs or material combinations. This evaluation is performed by fatigue testing the tube joints over a spectrum of bending stresses and then plotting the cycles to failure. Other test methods may be used as long as they develop the same data as the rotary flexure test.

Aircraft — Hydraulic tubing joints and fittings — Rotary flexure test

1 Scope

This International Standard specifies a flexure test procedure to determine and classify the fatigue strengths of reconnectable or permanent hydraulic tube joints.

The procedure is intended for conducting flexure tests of fittings and joints with high-strength hydraulic tubes of various alloys such as corrosion resistant steel, Nimonic^{TM1)}, titanium and aluminium alloy hydraulic tube for use on commercial and military aircraft.

A mean stress is applied by holding system pressure in the specimens and then flexing in a rotary bending test machine.

2 Requirements

2.1 Flexure test device

The test device should be capable of testing in-line or bulkhead union test specimens and other configurations such as elbows and tees.

The rotary flexure test device should be similar to that shown in [Figure 1](#). Each rotary flexure test device should be capable of testing one specimen, but several specimens may be mounted on one plate.

The device should be capable of constantly maintaining the required operating pressure during the test. The test fluid shall be water or system fluid (working fluid) unless otherwise specified by the responsible authorities. A typical pressurization and automatic shutdown system is shown in [Figure 2](#). The shut-down should be automatic in the event of failure or pressure drop. The device should be capable of testing at controlled constant temperature, if specified by the procuring agency. The tailstock of the test device should be designed to permit alignment during initial installation and specimen mounting, and to serve as a pressure manifold. The rotating headstock should have a low-friction, self-aligning bearing and should be designed to permit total deflections of up to 25 mm/1 inch, and a constant rotational frequency within the range of 1 500 min⁻¹ to 3 600 min⁻¹. The base should be of rigid construction.

2.2 Flexure test specimen

The test specimen should be consisting of an adapter fitting (headstock end), a section of straight tubing, and a test fitting at the tailstock end. Typical test specimens are shown in [Figure 3](#). The tubing shall be of a size and wall thickness as specified by the user or procuring agency.

1) NimonicTM is the trademark of a product supplied by Special Metals Corporation. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO of the product named. Equivalent products can be used if they can be shown to lead to the same results.