

INTERNATIONAL STANDARD

ISO
366-2

First edition
1988-11-15



INTERNATIONAL ORGANIZATION FOR STANDARDIZATION
ORGANISATION INTERNATIONALE DE NORMALISATION
МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ

Textile machinery and accessories — Reeds —

Part 2 :

Metal reeds with plate baulk — Dimensions and designation

Matériel pour l'industrie textile — Peignes —

Partie 2: Peignes métalliques soudés à bandes — Dimensions et désignation

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 366-2 was prepared by Technical Committee ISO/TC 72, *Textile machinery and allied machinery and accessories*.

This first edition of ISO 366-2 cancels and replaces ISO 367 : 1976, of which it constitutes a technical revision.

Users should note that all International Standards undergo revision from time to time and that any reference made herein to any other International Standard implies its latest edition, unless otherwise stated.

Textile machinery and accessories — Reeds —

Part 2 : Metal reeds with plate baulk — Dimensions and designation

0 Introduction

ISO 366 on reeds for use in the textile industry comprises the following three parts:

Part 1: Pitch bound reeds — Dimensions.

Part 2: Metal reeds with plate baulk — Dimensions and designation. (This part of ISO 366.)

Part 3: Metal reeds with double-spring baulk — Dimensions and designation.

1 Scope and field of application

This part of ISO 366 specifies the dimensions and designation of metal reeds with plate baulk for use in the textile industry.

The strip steel used in the manufacture of dents of reeds is the subject of ISO 9473.

2 Reference

ISO 9473, *Textile machinery and accessories — Strip steel for dents of reeds.*

3 Dimensions

The dimensions of metal reeds with plate baulk are shown on the figure and are given in the table.

4 Designation

The designation of a metal reed with plate baulk shall include the following information in the order given:

- a) "Metal reed with plate baulk";
- b) reference to this part of ISO 366, i.e. ISO 366-2;
- c) the overall depth of the reed (h);
- d) the thickness of the reed baulk (d);
- e) the width of the dents of the reed (b);
- f) the type of steel used for the dents of the reed, in accordance with ISO 9473, i.e. plain or stainless.

Example:

A metal reed with plate baulk of overall depth $h = 150$ mm, of thickness of reed baulk $d = 8$ mm and having dents of width $b = 4$ mm, made of stainless steel, shall be designated as follows:

**Metal reed with plate baulk ISO 366-2
150 × 8 × 4 stainless**