

VÄIKELAEVAD. STABIILSUSE JA UJUVUSE HINDAMINE JA
KLASSIFITSEERIMINE. OSA 2: PURJELAEVAD, MILLE
KERE PIKKUS ON 6 MEETRIT VÕI ROHKEM

Small craft - Stability and buoyancy assessment and
categorization - Part 2: Sailing boats of hull length
greater than or equal to 6 m (ISO 12217-2:2015)

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN ISO 12217-2:2017 sisaldab Euroopa standardi EN ISO 12217-2:2017 ingliskeelset teksti.	This Estonian standard EVS-EN ISO 12217-2:2017 consists of the English text of the European standard EN ISO 12217-2:2017.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 27.09.2017.	Date of Availability of the European standard is 27.09.2017.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 47.080

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

EUROPEAN STANDARD

EN ISO 12217-2

NORME EUROPÉENNE

EUROPÄISCHE NORM

September 2017

ICS 47.080

Supersedes EN ISO 12217-2:2015

English Version

Small craft - Stability and buoyancy assessment and categorization - Part 2: Sailing boats of hull length greater than or equal to 6 m (ISO 12217-2:2015)

Petits navires - Évaluation et catégorisation de la stabilité et de la flottabilité - Partie 2: Bateaux à voiles d'une longueur de coque supérieure ou égale à 6 m (ISO 12217-2:2015)

Kleine Wasserfahrzeuge - Stabilitäts- und Auftriebsbewertung und Kategorisierung - Teil 2: Segelboote ab 6 m Rumpflänge (ISO 12217-2:2015)

This European Standard was approved by CEN on 23 July 2017.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

European foreword

The text of ISO 12217-2:2015 has been prepared by Technical Committee ISO/TC 188 "Small craft" of the International Organization for Standardization (ISO) and has been taken over as EN ISO 12217-2:2017.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by March 2018, and conflicting national standards shall be withdrawn at the latest by March 2018.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 12217-2:2015.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EU Directive(s), see informative Annex ZA, which is an integral part of this document.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 12217-2:2015 has been approved by CEN as EN ISO 12217-2:2017 without any modification.

Contents

	Page
Foreword	v
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
3.1 Primary.....	2
3.2 Hazards.....	4
3.3 Downflooding.....	4
3.4 Dimensions, areas and angles.....	5
3.5 Condition, mass and volume.....	6
3.6 Other terms and definitions.....	9
4 Symbols	12
5 Procedure	13
5.1 Maximum load.....	13
5.2 Sailing or non-sailing.....	13
5.3 Tests, calculations and requirements to be applied.....	14
5.4 Variation in input parameters.....	14
6 Requirements for monohull boats	14
6.1 Requirements to be applied.....	14
6.2 Downflooding.....	15
6.2.1 Downflooding openings.....	15
6.2.2 Downflooding height.....	18
6.2.3 Downflooding angle.....	19
6.3 Recess size.....	19
6.3.1 Application.....	19
6.3.2 Simplified methods.....	20
6.3.3 Direct calculation method.....	22
6.4 Minimum righting energy.....	22
6.5 Angle of vanishing stability.....	22
6.5.1 Normal requirement.....	23
6.5.2 Alternative requirement for design category B.....	23
6.6 Stability index (STIX).....	24
6.6.1 Method.....	24
6.6.2 Dynamic stability factor (FDS).....	25
6.6.3 Inversion recovery factor (FIR).....	25
6.6.4 Knockdown recovery factor (FKR).....	25
6.6.5 Displacement-length factor (FDL).....	26
6.6.6 Beam-displacement factor (FBD).....	26
6.6.7 Wind moment factor (FWM).....	26
6.6.8 Downflooding factor (FDF).....	27
6.6.9 Calculation of the stability index (STIX).....	27
6.7 Knockdown-recovery test.....	28
6.8 Wind stiffness test.....	29
6.8.1 General.....	29
6.8.2 Practical test.....	29
6.8.3 Compliance by calculation.....	30
6.8.4 Requirements.....	30
6.9 Flotation requirements.....	31
6.10 Capsize-recovery test.....	32
6.11 Detection and removal of water.....	33
7 Requirements for catamarans, trimarans and form-stable monohulls	34
7.1 Requirements to be applied.....	34

7.2	Downflooding openings.....	34
7.3	Downflooding height.....	34
7.4	Recess size.....	34
7.5	Stability information.....	35
7.6	Safety signs.....	36
7.7	Bare poles factor.....	37
7.8	Rolling in breaking waves.....	37
7.9	Pitchpoling.....	37
7.10	Diagonal stability.....	38
7.11	Habitable multihull boats.....	38
7.12	Buoyancy when inverted.....	39
7.13	Escape after inversion.....	40
8	Safety signs.....	41
9	Application.....	42
9.1	Deciding the design category.....	42
9.2	Meaning of the design categories.....	42
	Annex A (normative) Full method for required downflooding height.....	44
	Annex B (normative) Methods for calculating downflooding angle.....	47
	Annex C (normative) Determining the curve of righting moments.....	50
	Annex D (normative) Method for calculating reserve of buoyancy after inversion or swamping.....	53
	Annex E (normative) Flotation material and elements.....	55
	Annex F (normative) Information for owner's manual.....	57
	Annex G (normative) Determination of safe wind speed information.....	61
	Annex H (normative) Determination of longitudinal righting characteristics.....	64
	Annex I (informative) Summary of requirements.....	67
	Annex J (informative) Worksheets.....	70
	Annex K (informative) Illustration of recess retention level.....	89
	Bibliography.....	90

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#).

The committee responsible for this document is ISO/TC 188, *Small craft*.

This third edition cancels and replaces the second edition (ISO 12217-2:2013), of which it constitutes a minor revision. It incorporates the following modifications:

- Introduction: the reference to the European Directive has been updated (2013/53/EU);
- [Clause 1](#), [6.2.1.6 d\) 3\)](#), [7.6](#), [7.11](#), [7.12](#), [7.13](#), [Annex I](#), [Table I.2](#), and [Annex J](#), Worksheets 2, 12, 14 and 16: vulnerable has been replaced with susceptible;
- [Clause 3](#): definitions [3.1.1](#), [3.5.5](#), [3.5.6](#) and [3.6.11](#) have been amended;
- [Subclause 6.3.1](#): second item in the list has been inserted;
- [Subclauses 6.3.2.3](#) and [6.3.2.4](#): formulae coefficients have been corrected;
- [Subclause 6.6.2](#): exponent '0,3' has been deleted;
- [Subclause 6.6.7](#): symbols have been corrected;
- [Subclause 6.6.8](#): a note has been added to explain the phrase "fully flooded with water";
- [Clause 9.2](#): the text and [Table 11](#) have been amended;
- [Subclause H.3.2 c\)](#): the coefficient in the formula has been corrected;
- [Annex J](#): worksheets 1, 2, 5, 7, 12 and 16 have been corrected to align with corrections listed above;
- [Annex K](#) has been added;
- Bibliography: reference to ISO 7010 has been added;
- Editorial and cross-referencing corrections have been made to [Table 1](#), [Annex J](#), worksheets 1, 5, 7, 12, 14 and 16, and to [subclauses 6.3.1](#), [6.3.2.2](#) and [6.3.2.3](#).

ISO 12217 consists of the following parts, under the general title *Small craft — Stability and buoyancy assessment and categorization*:

- *Part 1: Non-sailing boats of hull length greater than or equal to 6 m*
- *Part 2: Sailing boats of hull length greater than or equal to 6 m*
- *Part 3: Boats of hull length less than 6 m*

This document is a preview generated by EVS

Introduction

This part of ISO 12217 enables the determination of limiting environmental conditions for which an individual boat has been designed.

It enables the boat to be assigned to a design category appropriate to its design and maximum load. The design categories used align with those in the Recreational Craft Directive of the European Union, EU Directive 2013/53/EU.

[Annex J](#) provides worksheets to assist in the systematic assessment of a boat according to this part of ISO 12217.

Small craft — Stability and buoyancy assessment and categorization —

Part 2:

Sailing boats of hull length greater than or equal to 6 m

CAUTION — Compliance with this part of ISO 12217 does not guarantee total safety or total freedom of risk from capsize or sinking.

IMPORTANT — The electronic file of this document contains colours which are considered to be useful for the correct understanding of the document. Users should therefore consider printing this document using a colour printer.0

1 Scope

This part of ISO 12217 specifies methods for evaluating the stability and buoyancy of intact (i.e. undamaged) boats. The flotation characteristics of boats susceptible to swamping are also encompassed.

The evaluation of stability and buoyancy properties using this part of ISO 12217 will enable the boat to be assigned to a design category (A, B, C or D) appropriate to its design and maximum load.

This part of ISO 12217 is principally applicable to boats propelled primarily by sail (even if fitted with an auxiliary engine) of 6 m up to and including 24 m hull length. However, it can also be applied to boats less than 6 m if they are habitable multihulls or may be applied if they do not attain the desired design category specified in ISO 12217-3 and they are decked and have quick-draining recesses which comply with ISO 11812.

In relation to habitable multihulls, this part of ISO 12217 includes assessment of susceptibility to inversion, definition of viable means of escape and requirements for inverted flotation.

This part of ISO 12217 excludes:

- inflatable and rigid-inflatable boats covered by ISO 6185, except for references made in ISO 6185 to specific clauses of ISO 12217;
- gondolas and pedalos;
- surfboards including sailing surfboards; and
- hydrofoils and foil stabilized boats when not operating in the displacement mode.

NOTE Displacement mode means that the boat is only supported by hydrostatic forces.

It does not include or evaluate the effects on stability of towing, fishing, dredging or lifting operations, which need to be separately considered if appropriate.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2896:2001, *Rigid cellular plastics — Determination of water absorption*

ISO 3864-1, *Graphical symbols — Safety colours and safety signs — Part 1: Design principles for safety signs and safety markings*

ISO 8666, *Small craft — Principal data*

ISO 9093-1, *Small craft — Seacocks and through-hull fittings — Part 1: Metallic*

ISO 9093-2, *Small craft — Seacocks and through-hull fittings — Part 2: Non-metallic*

ISO 9094 (all parts), *Small craft — Fire protection*

ISO 10240, *Small craft — Owner's manual*

ISO 11812, *Small craft — Watertight cockpits and quick-draining cockpits*

ISO 12216, *Small craft — Windows, portlights, hatches, deadlights and doors — Strength and watertightness requirements*

ISO 12217-1:2015, *Small craft — Stability and buoyancy assessment and categorization — Part 1: Non-sailing boats of hull length greater than or equal to 6 m*

ISO 12217-3:2015, *Small craft — Stability and buoyancy assessment and categorization — Part 3: Boats of hull length less than 6 m*

ISO 14946, *Small craft — Maximum load capacity*

ISO 15083, *Small craft — Bilge-pumping systems*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

NOTE The meanings of certain symbols used in the definitions are given in [Clause 4](#).

3.1 Primary

3.1.1

design category

description of the sea and wind conditions for which a boat is assessed to be suitable

Note 1 to entry: See also [9.2](#).

3.1.2

sailing boat

boat for which the primary means of propulsion is by wind power, having reference sail area ([3.4.8](#))
 $A_S \geq 0,07(m_{LDC})^{2/3}$

Note 1 to entry: m_{LDC} is the mass of the boat in the maximum load condition, expressed in kilograms.

3.1.3

catamaran

boat with two main load-bearing hulls

EXAMPLE Boats with a centreline or bridge-deck nacelle which supports less than 30 % of the mass in the maximum load condition are considered to be catamarans. Proas are asymmetric catamarans.

3.1.4

trimaran

boat with a centre main hull and two sidehulls in which the centre hull, when the boat is upright, supports 30 % or more of the mass in the maximum load condition