

RAUDTEEALASED RAKENDUSED. RAUDTEEVEEREMI
SÕIDUOMADUSTE HEAKSKIIDUKATSETUSED JA
SIMULATSIOON. SÕIDU- JA SEISUKATSETUSED

Railway applications - Testing and Simulation for the
acceptance of running characteristics of railway
vehicles - Running Behaviour and stationary tests

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 14363:2016+A1:2018 sisaldab Euroopa standardi EN 14363:2016+A1:2018 ingliskeelset teksti.	This Estonian standard EVS-EN 14363:2016+A1:2018 consists of the English text of the European standard EN 14363:2016+A1:2018.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 19.12.2018.	Date of Availability of the European standard is 19.12.2018.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 45.060.01

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:

Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

English Version

Railway applications - Testing and Simulation for the acceptance of running characteristics of railway vehicles - Running Behaviour and stationary tests

Applications ferroviaires - Essais et simulations en vue de l'homologation des caractéristiques dynamiques des véhicules ferroviaires - Comportement dynamique et essais stationnaires

Bahnanwendungen - Versuche und Simulationen für die Zulassung der fahrtechnischen Eigenschaften von Eisenbahnfahrzeugen - Fahrverhalten und stationäre Versuche

This European Standard was approved by CEN on 19 September 2015 and includes Amendment 1 approved by CEN on 15 July 2018.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents	Page
European foreword.....	6
Introduction.....	7
1 Scope.....	9
2 Normative references.....	11
3 Terms and definitions.....	12
4 Deviations from requirements.....	14
5 Test requirements.....	14
5.1 Measuring uncertainty.....	14
5.2 Test extent.....	15
5.2.1 General.....	15
5.2.2 Fault modes.....	15
5.3 Test vehicle.....	15
5.3.1 Selection and status of the vehicle.....	15
5.3.2 Loading conditions.....	16
5.3.3 Distribution of static wheel forces.....	17
5.4 Assessment of test result.....	17
5.5 Documentation of test.....	17
6 First stages assessment.....	19
6.1 Safety against derailment on twisted track.....	19
6.1.1 General.....	19
6.1.2 Signal processing.....	20
6.1.3 Rail test conditions.....	20
6.1.4 Vehicle test conditions.....	21
6.1.5 Test methods.....	23
6.2 Safety against derailment under longitudinal compressive forces in S-shaped curves.....	37
6.3 Evaluation of the torsional coefficient of a vehicle body.....	37
6.4 Determination of displacement characteristics.....	38
6.5 Loading of the diverging branch of a switch.....	38
6.6 Running safety in curved crossings for vehicles with small wheels.....	38
7 Second stage – dynamic performance assessment.....	38
7.1 General.....	38
7.2 Choice of measuring method.....	39
7.2.1 General.....	39
7.2.2 Base conditions for the use of the simplified measuring method and measurement of axle box forces.....	41
7.2.3 Simplifications for separate stability testing.....	41
7.3 Performing on-track tests.....	42
7.3.1 General.....	42
7.3.2 Test zones and track sections.....	47
7.3.3 Extent of tests.....	48
7.3.4 Test operation.....	49
7.4 Measured quantities and measuring points.....	49
7.5 Assessment quantities and limit values.....	51
7.5.1 General.....	51
7.5.2 Running safety.....	56
7.5.3 Track loading.....	57

7.5.4	Ride characteristics	57
7.6	Test evaluation	57
7.6.1	Overview	57
7.6.2	Recording the measuring signals.....	58
7.6.3	Statistical evaluation in test zones	59
7.6.4	Evaluation of test results in transition curves	66
7.6.5	Verification of stability	66
7.7	Documentation	66
7.7.1	General	66
7.7.2	Description of the vehicle design and status of the tested vehicle	67
7.7.3	Additional information for future extension of acceptance.....	67
7.7.4	Description of the test routes.....	67
7.7.5	Description of data capture	67
7.7.6	Description of evaluation	67
7.7.7	Test results (including additional information for model validation)	68
7.7.8	Deficiencies in reaching the target test conditions	69
7.7.9	Infrastructure conditions more severe than the target test conditions.....	69
Annex A (informative) Information on safety against derailment		70
A.1	Factors influencing the safety against derailment of vehicles running on twisted track.....	70
A.2	Evaluation and limit value for safety against derailment.....	71
A.3	Friction conditions during testing on special track	72
A.4	Special conditions for vehicles with air springs.....	74
A.5	Test twist conditions for articulated vehicles	76
A.6	Test twist conditions for vehicles with more than two suspension levels.....	81
A.7	Calculation of the shim sizes (test method 1).....	82
A.8	Performing and evaluating a twist test for a two-axle vehicle (test method 2).....	83
A.9	Performing and evaluation of a twist test for a vehicle with two bogies with two axles (test method 2).....	86
Annex B (informative) Computer simulations designed to examine whether the vehicle has an acceptable resistance to flange climbing derailment at low speed		94
B.1	General requirement.....	94
B.2	Computer output.....	94
B.3	Track input.....	94
B.4	Body-bogie yaw torque.....	95
B.5	Performance requirement	95
Annex C (informative) Tests for determination of the torsional coefficient of a vehicle body		97
C.1	Force-deflection measurement directly at the vehicle body	97
C.2	Force-deflection measurement at the contact points between wheel and rail after blocking of the suspension(s) between wheelset (bogie frame) and vehicle body	98
Annex D (informative) Determination of displacement characteristics for application with EN 15273		99
D.1	Introduction.....	99

D.2	Determination of displacement characteristics	99
Annex E (informative) Assessment of the behaviour of vehicles with small wheels in curved crossings.....		
E.1	Purpose.....	105
E.2	Area of application.....	105
E.3	Description of the crossing geometry.....	105
E.4	Test conditions.....	108
Annex F (informative) Test specification for assessment of vehicle behaviour in switches and crossings		
F.1	Introduction	111
F.2	Definitions	111
F.3	Test conditions.....	111
F.4	Assessment of the test results	112
F.5	Documentation.....	112
Annex G (normative) Coordinate system for measured quantities		
Annex H (informative) Operational parameters		
Annex I (informative) Position of the different wheelsets during test.....		
Annex J (informative) Additional track loading assessment quantities		
J.1	General.....	119
J.2	Maximum lateral force.....	119
J.3	Combination of lateral and vertical forces.....	119
Annex K (informative) Evaluation and background of the rail surface damage quantity		
Annex L (informative) Typical maximum estimated values of ride characteristics.....		
Annex M (normative) Track geometric quality – Selection of test tracks.....		
M.1	Basis of evaluation	124
M.2	Assessment quantities for track geometric quality.....	124
M.3	Different measuring systems	125
M.4	Target test conditions.....	126
M.5	Reporting	128
Annex N (informative) Background of track quality description		
Annex O (normative) Rail profile measurement		
O.1	General.....	130
O.2	Manual measurements.....	130
O.3	Automatic measurements.....	130
Annex P (normative) Requirements for evaluation of equivalent conicity		
Annex Q (informative) Radial steering index		
Q.1	Introduction	132

Q.2	Calculation of radial steering index.....	133
Annex R (normative) Statistical evaluation		136
R.1	Objectives and principles of statistical analysis.....	136
R.2	Determination of the percentiles for each track section.....	137
R.3	Preparation of the random samples	138
R.4	One-dimensional analysis for estimated maximum values	138
R.5	Two-dimensional analysis for estimated values.....	138
R.6	Multiple regression analysis for estimated values.....	139
R.7	Statistical evaluation for the overturning criterion.....	141
R.8	Regression assumptions	142
Annex S (informative) Running behaviour of special vehicles.....		145
S.1	General	145
S.2	Vehicle design and classification	145
S.3	Use of the simplified measuring method	146
S.4	Test conditions	146
S.5	Specific limit value	146
Annex T (informative) Simulation of on-track tests		147
T.1	Introduction.....	147
T.2	Fields of application.....	147
T.3	Validation	149
T.4	Input	163
T.5	Output.....	167
T.6	Documentation	167
T.7	Examples for model validation according to Method 1	168
Annex U (informative) Extension of acceptance.....		175
U.1	General	175
U.2	Determination of the safety factor	181
U.3	Dispensation.....	181
U.4	[A1] Use of the simplified method [A1]	182
U.5	Requirements depending on the initial approval.....	182
Annex V (normative) Symbols.....		184
Annex W (informative) List with the main technical changes compared to EN 14363:2005, EN 15686:2010 and EN 15687:2010.....		188
Annex X (informative) A-deviations.....		191
Annex ZA (informative) [A1] Relationship between this European Standard and the Essential Requirements of EU Directive 2008/57/EC aimed to be covered [A1]		193
Bibliography		196

European foreword

This document (EN 14363:2016+A1:2018) has been prepared by Technical Committee CEN/TC 256 "Railway applications", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2019, and conflicting national standards shall be withdrawn at the latest by June 2019.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document includes Amendment 1 approved by CEN on 2018-07-15.

This document supersedes A1 EN 14363:2016 A1.

The start and finish of text introduced or altered by amendment is indicated in the text by tags A1 A1.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EU Directive(s), see informative Annex ZA, which is an integral part of this document.

It is not necessary to require further assessment of vehicles which have been already assessed under the conditions of previous standards in this field. Test results achieved under the conditions of the previous standards remain valid and can be used for the extension of acceptance of a vehicle or vehicle design according to this standard.

Prior to the first issue of this standard, national procedures were applied for vehicle acceptance, for example in Germany or UK. The underlying principles that were applied in these earlier standards are also incorporated in this standard. The fundamentals have not been changed but the formulation of the requirements has been made consistent. Therefore it is considered that also vehicles that were previously approved utilizing these earlier requirements have an equal status compared to vehicles that are approved according to this standard. This applies to the infrastructure and operating conditions that were considered in the earlier approval. This includes also a use as reference vehicle for extension of acceptance.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

Acceptable running characteristics of a railway vehicle (hereafter called vehicle) are essential for a safe and economic operation of a railway system. They are related to:

- the vehicle,
- the operating conditions,
- the characteristics of the infrastructure (track layout design and track quality) and
- the contact conditions of the wheel/rail interface.

The objective is to quantify the vehicle's performance under known representative conditions of operation and infrastructure.

This standard describes methods to assess the vehicle performance in the following areas:

- safety against derailment on twisted track (see 6.1);
- running safety under longitudinal compressive forces in s-shaped curves (see 6.2);
- evaluation of the torsional coefficient (see 6.3);
- determination of displacement characteristics (see 6.4);
- loading of the diverging branch of a switch (see 6.5);
- running safety in curved crossings (see 6.6);
- running safety, track loading and ride characteristics (see Clause 7).

The vehicle performance is assessed in two stages. Usually in the first stage the basic characteristics and low speed behaviour are investigated before first runs on the line under controlled operating conditions. In the second stage the running behaviour is assessed. The assessment of a vehicle according to the elements listed above can be performed either by physical testing, numerical simulation, calculation or comparison with a known solution (dispensation). Details about the requirements relating to the choice of the appropriate assessment method are given in this document.

The operational envelope (speed and cant deficiency) that the vehicle has been assessed for needs to be documented.

The establishment of this document was based on existing rules, practices and procedures. The following principles were applied:

- the railway system requires comprehensive technical rules in order to ensure an acceptable interaction of vehicle and track;
- the performance of new railway vehicles has to be evaluated and assessed before putting them into service;
- it is of particular importance that the existing level of safety and reliability is not compromised even when changes in design or operating conditions are demanded, e.g. by the introduction of higher speeds, higher vertical wheel forces, modification of the suspension, etc.
- it is possible to demonstrate compliance with the requirements of this standard by comparison of relevant parameters or by simulation if changes are made to the design or to the operating conditions;
- as the combination of all the target test conditions described is not always achievable, the compliance against the missing target test conditions can be demonstrated by other means.

Requirements on running safety under longitudinal compressive forces in S-shaped curves of certain vehicles are given in EN 15839, while EN 16235 specifies a method to get dispensation from on-track

testing for A_1 vehicles equipped with established or standardised running gear A_1 , if certain conditions are fulfilled.

The informative Annexes A, B, C, D, E, F; Q, S, T and U contain requirements that have to be fulfilled when the annex is applied.

This document is a preview generated by EVS

1 Scope

This European Standard defines the process for assessment of the running characteristics of railway vehicles for the European network of standard gauge tracks (nominally 1 435 mm).

In addition to the assessment of the running characteristics of vehicles for acceptance processes, this standard also defines quantities and dependencies that are not directly used for acceptance purposes. This information is for example intended for the validation of simulation models. It can also be used to define operating conditions outside the reference conditions to be used for the approval.

The assessment of running characteristics applies to vehicles which:

- are newly developed;
- have had relevant design modifications; or
- have changes in their operating conditions.

The assessment process is based on specified target test conditions (see 3.1) given in this document.

Experience over many years has demonstrated that vehicles complying with this standard can be operated safely on infrastructure with conditions more severe than the target test conditions, if the current general operating rules are applied. As an example it is generally current practice to restrict cant deficiency in curves below a certain radius. It may be necessary to adapt these operating rules, if a deterioration of the infrastructure conditions is observed. These operating rules are defined on a national basis. The procedure to evaluate these operating rules is out of the scope of this standard.

NOTE 1 There are margins included in the specified limit values and the statistical evaluation. They cannot be quantified, but they explain why vehicles can also be operated at full speed and cant deficiency in many cases outside of the target test conditions.

This standard also enables the demonstration of compliance against the target test conditions for the case that their combination is not achievable during tests. It is also possible to carry out the assessment of a vehicle for limited test conditions such as test zones 1 and 2 or reduced speed or reduced cant deficiency. In this case the approval of the vehicle shall be restricted accordingly.

NOTE 2 National regulations sometimes allow the increase or decrease of the values for speed, curve radius and cant deficiency for local operation based on safety considerations taking into account the local characteristics of the infrastructure (track layout, track structure, track geometrical quality and contact conditions). These local characteristics can be different from those included in the assessment for the vehicle acceptance.

NOTE 3 The methods of this standard can also be applied to gather information about the compatibility between the vehicle and infrastructure with conditions more severe than the target test conditions. The results of such investigations can be used to determine safe operating rules for such infrastructure conditions.

Where testing the vehicle demonstrates that the performance of a vehicle complies with the requirements of this standard when operating at maximum speed and maximum cant deficiency under infrastructure conditions that are more severe than the target test conditions, the obtained results are accepted and there is no need to carry out additional tests to fulfil the requirements defined in this standard.

This standard addresses four aspects:

1) Vehicles

The assessment of the running characteristics applies principally to all railway vehicles. The document contains acceptance criteria for all types of vehicles with nominal static vertical wheelset forces up to 225 kN (of the highest loaded wheelset of the vehicle in the assessed load configuration specified in 5.3.2). In addition for freight vehicles with nominal static vertical wheelset forces up to 250 kN the acceptance criteria are defined. The acceptance criteria given in this document apply to vehicles designed to operate on standard gauge tracks.

2) Infrastructure

In the acceptance process the range of curve radii is defined, for which the vehicle is assessed. A vehicle accepted according to the requirements of this standard is able to be operated on all standard gauge tracks complying with EN 13803-1 and EN 13803-2.

EN 14363 also gives guidance about the handling of geometric track quality associated with the assessment.

3) Conditions of the wheel rail interface

This standard contains requirements relating to the necessary range of equivalent conicity to be included in the assessment as target test conditions.

In some national systems, either parts or all, equivalent conicities are significantly higher than the target test conditions of this standard. These cases are outside the scope of this standard. Nevertheless the methodology defined in this standard for the proof of running stability can also be used for higher equivalent conicities.

NOTE 4 In these cases running safety is demonstrated by application of existing national requirements for high equivalent conicities during stability testing. Experience shows, that it is not necessary to include the maximum occurring values of equivalent conicity in such national requirements.

4) Operating conditions

The document requires the specification of the combination of admissible speed and admissible cant deficiency as well as the loading conditions for each type of vehicle.

NOTE 5 Recommended values of cant deficiencies for broad international approval are given in informative Annex H.

This standard is not directly applicable to:

- railways with different track layout, e.g. tramways, metros and underground railways;
- railways with non-standard gauge tracks;

but assessment can be conducted by analogy with this document, e.g. the test procedures described in this standard can be applied also to vehicles operated in networks with other track gauges (e.g. 1 524 mm and 1 668 mm). The related limit values and test conditions could be different. They are specified nationally taking into account track design and operating conditions.

The strength of the vehicle and mounted parts, passengers and train crew vibration exposure, comfort, load security and effects of cross wind are out of the scope of this standard.

This document includes the assessment of track loading quantities, the quantification of track deterioration or track fatigue is out of the scope of this standard.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 13803-1, *Railway applications — Track — Track alignment design parameters — Track gauges 1435 mm and wider — Part 1: Plain line*

EN 13803-2, *Railway applications — Track alignment design parameters — Track gauges 1 435 mm and wider — Part 2: Switches and crossings and comparable alignment design situations with abrupt changes of curvature*

EN 13848-1, *Railway applications — Track — Track geometry quality — Part 1: Characterisation of track geometry*

EN 13848-2, *Railway applications — Track — Track geometry quality — Part 2: Measuring systems — Track recording vehicles*

EN 13848-5:2008+A1:2010, *Railway applications — Track — Track geometry quality — Part 5: Geometric quality levels — Plain line*

EN 14033-1, *Railway applications — Track — Railbound construction and maintenance machines — Part 1: Technical requirements for running*

EN 15273-1, *Railway applications — Gauges — Part 1: General — Common rules for infrastructure and rolling stock*

EN 15273-2, *Railway applications — Gauges — Part 2: Rolling stock gauge*

EN 15302:2008+A1:2010, *Railway applications — Method for determining the equivalent conicity*

EN 15663:2009, *Railway applications — Definition of vehicle reference masses*

EN 15746-1, *Railway applications — Track — Road-rail machines and associated equipment — Part 1: Technical requirements for running and working*

EN 15839, *Railway applications — Testing for the acceptance of running characteristics of railway vehicles — Freight wagons — Testing of running safety under longitudinal compressive forces*

EN 15954-1, *Railway applications — Track — Trailers and associated equipment — Part 1: Technical requirements for running and working*

EN 15955-1, *Railway applications — Track — Demountable machines and associated equipment — Part 1: Technical requirements for running and working*

EN 16235, *Railway application — Testing for the acceptance of running characteristics of railway vehicles — Freight wagons — Conditions for dispensation of freight wagons with defined characteristics from on-track tests according to EN 14363*