

INTERNATIONAL
STANDARD

ISO
7046-2

First edition
1990-10-15

**Cross recessed countersunk flat head screws
(common head style) — Grade A —**

Part 2 :

Steel of property class 8.8, stainless steel and non-ferrous metals

Vis à métaux à tête fraisée à empreinte cruciforme — Grade A —

Partie 2 : Acier de classe de qualité 8.8, acier inoxydable et métaux non ferreux



Reference number
ISO 7046-2 : 1990 (E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 7046-2 was prepared by Technical Committee ISO/TC 2, *Fasteners*.

ISO 7046 consists of the following parts, under the general title *Cross recessed countersunk flat head screws (common head style) — Grade A*:

- *Part 1: Steel of property class 4.8* (future revision of ISO 7046 : 1983)
- *Part 2: Steel of property class 8.8, stainless steel and non-ferrous metals*

© ISO 1990

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Introduction

Penetration depths of cross recesses for countersunk flat head screws

The penetration depth of cross recesses for countersunk flat head screws has to satisfy two requirements which act in opposite directions for a given head dimension.

First, there is the requirement for sufficient head strength to attain the proof and breaking loads of the respective property class. A shallow cross recess increases the head strength. On the other hand, the wrenchability of the screw should be satisfactory; this can only be achieved by a sufficiently deep cross recess.

ISO 7721-2 was developed in order to find a compromise which, as far as possible, would meet both requirements.

ISO 7721-2 specifies deep cross recesses for countersunk head screws of low strength: a good wrenchability is achieved and the head strength is still sufficient. This execution will be used in ISO 7046-1 (see the foreword).

For screws of higher strength, sufficient head strength can only be attained by a shallower penetration depth of the cross recesses. If such screws also require good wrenchability, then, under the conditions of the common head style, a shoulder has to be provided under the head, in addition to the larger penetration depth, in order to guarantee sufficient head strength. This part of ISO 7046 covers both possibilities.

This compromise, which unfortunately results in different, but interchangeable, types of cross recessed flat countersunk head screws, is at the moment the only way of reaching an agreement at the international level.

This document is a preview generated by EVS

This page intentionally left blank

Cross recessed countersunk flat head screws (common head style) — Grade A —

Part 2 :

Steel of property class 8.8, stainless steel and non-ferrous metals

1 Scope

This part of ISO 7046 specifies the characteristics of recessed countersunk flat head screws with threads M2 up to and including M10, of grade A and of property class 8.8 for steel, A2-70 for stainless steel and CU2 and CU3 for non-ferrous metals.

If, in special cases, specifications other than those listed in this International Standard are required, they shall be selected from existing International Standards, for example ISO 261, ISO 888, ISO 898-1, ISO 965-2, ISO 3506, ISO 4759-1, ISO 8839.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 7046. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 7046 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 225 : 1983, *Fasteners — Bolts, screws, studs and nuts — Symbols and designations of dimensions.*

ISO 261 : 1973, *ISO general purpose metric screw threads — General plan.*

ISO 888 : 1976, *Bolts, screws and studs — Nominal lengths, and thread lengths for general purpose bolts.*

ISO 898-1 : 1988, *Mechanical properties of fasteners — Part 1: Bolts, screws and studs.*

ISO 965-2 : 1980, *ISO general purpose metric screw threads — Tolerances — Part 2: Limits of sizes for general purpose bolt and nut threads — Medium quality.*

ISO 3269 : 1988, *Fasteners — Acceptance inspection.*

ISO 3506 : 1979, *Corrosion-resistant stainless steel fasteners — Specifications.*

ISO 4042 : 1989, *Threaded components — Electroplated coatings.*

ISO 4757 : 1983, *Cross recesses for screws.*

ISO 4759-1 : 1978, *Tolerances for fasteners — Part 1: Bolts, screws and nuts with thread diameters $\geq 1,6$ and ≤ 150 mm and product grades A, B and C.*

ISO 6157-1 : 1988, *Fasteners — Surface discontinuities — Part 1: Bolts, screws and studs for general requirements.*

ISO 6157-3 : 1988, *Fasteners — Surface discontinuities — Part 3: Bolts, screws and studs for special requirements.*

ISO 7721 : 1983, *Countersunk head screws — Head configuration and gauging.*

ISO 7721-2 : 1990, *Countersunk flat head screws — Part 2: Penetration depth of cross recesses.*

ISO 8839 : 1986, *Mechanical properties of fasteners — Bolts, screws, studs and nuts made of non-ferrous metals.*